

Page 1/12

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 10.03.2024 Version number 28 (replaces version 27) Revision: 10.03.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

Trade name MC-DUR 2211 MB - Komponente A

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance

/ the mixture Construction chemicals

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier: MC-Bauchemie Müller GmbH & Co. KG

Am Kruppwald 1-8 D-46238 Bottrop Tel.: +49(0)2041-101-0 Fax.: +49(0)2041-101-400 E-Mail: info@mc-bauchemie.de

MC-Bauchemie AG Hagackerstr. 10 CH-8953 Dietikon Tel.: +44-7400510 Fax: +44-7400533

· Informing department:

msds@mc-bauchemie.de

· 1.4 Emergency telephone

number:

Tel.: +49 / (0)700 24112112 (MCR)

Tel.: +1 872 5888271 (MCR)

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

Skin Sens. 1 H317 May cause an allergic skin reaction.
Repr. 1A H360D May damage the unborn child.

Aquatic Chronic 1 H410 Very toxic to aquatic life with long lasting effects.

· 2.2 Label elements

· Labelling according to

Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP

regulation.

· Hazard pictograms







GHS07 GHS08 GHS09

· Signal word Danger

· Hazard-determining

components of labelling: 6-methyl-2,4-bis(methylthio)phenylene-1,3-diamine

2-Ethylhexanacid

(Contd. on page 2)



Page 2/12

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 10.03.2024 Version number 28 (replaces version 27) Revision: 10.03.2024

Trade name MC-DUR 2211 MB - Komponente A

(Contd. of page 1)

· **Hazard statements** H317 May cause an allergic skin reaction.

H360D May damage the unborn child.

H410 Very toxic to aquatic life with long lasting effects.

• **Precautionary statements** P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye

protection/face protection/hearing protection.

P308+P313 IF exposed or concerned: Get medical advice/

attention.

P333+P313 If skin irritation or rash occurs: Get medical advice/

attention.

P405 Store locked up.

· 2.3 Other hazards

Results of PBT and vPvB assessment
PBT: Not applicable.
vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

• **Description:** Mixture consisting of the following components.

· Dangerous components:		
CAS: 106264-79-3	6-methyl-2,4-bis(methylthio)phenylene-1,3-diamine	≥10-<25%
ELINCS: 403-240-8	Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Acute Tox. 4, H302; Skin Sens. 1, H317	
CAS: 14808-60-7	crystalline silica	<10%
	STOT RE 1, H372	
CAS: 149-57-5	2-Ethylhexanacid	≥0.3-<2.5%
Reg.nr.: 01-2119488942-23	Repr. 1A, H360D; Acute Tox. 4, H302	
CAS: 68479-98-1	diethylmethylbenzenediamine	≥0.25-<2.5%
EINECS: 270-877-4	STOT RE 2, H373; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Acute Tox. 4, H302; Acute Tox. 4, H312; Eye Irrit. 2, H319	
CAS: 25550-51-0 EINECS: 247-094-1	hexahydromethylphthalic anhydride	<1%

·SVHC

CAS: 25550-51-0 hexahydromethylphthalic anhydride

Additional information For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

General information Remove, decontaminate and dispose of soiled, soaked clothing

and shoes immediately.

· After inhalation Remove person to fresh air, keep warm, allow to rest; if breathing

is difficult, seek medical attention.

(Contd. on page 3)



Page 3/12

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 10.03.2024 Version number 28 (replaces version 27) Revision: 10.03.2024

Trade name MC-DUR 2211 MB - Komponente A

(Contd. of page 2)

· After skin contact In case of contact with skin, preferably wash with polyethylene

glycol-based cleaner or clean with plenty of warm water and soap.

Consult a doctor in case of skin reactions.

· After eye contact Rinse the eyes with open eyelids for a sufficiently long time (at

least 10 minutes) with water that is as lukewarm as possible.

Consult an ophthalmologist.

· After swallowing Do NOT induce vomiting. Rinse mouth with water. Medical

attention required.

· 4.2 Most important symptoms and effects, both acute and

delayed

Information for the doctor: The product irritates the respiratory tract and is a potential trigger for skin and respiratory sensitisation. Treatment of acute irritation or bronchial constriction is primarily symptomatic. Depending on the extent of exposure and the symptoms, prolonged medical treatment may be necessary.

4.3 Indication of any immediate medical attention

and special treatment needed No information available.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

· Suitable extinguishing agents Use fire fighting measures that suit the environment.

 5.2 Special hazards arising from the substance or

mixture No further relevant information available.

· 5.3 Advice for firefighters

· **Protective equipment:** No special measures required.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and

emergency procedures Not required.

· 6.2 Environmental precautions:

Prevent material from reaching sewage system, holes and cellars.

6.3 Methods and material for

containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders,

universal binders, sawdust).

· 6.4 Reference to other

sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

GB



Page 4/12

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Revision: 10.03.2024 Printing date 10.03.2024 Version number 28 (replaces version 27)

Trade name MC-DUR 2211 MB - Komponente A

(Contd. of page 3)

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure sufficient air exchange and/or extraction in the work areas.

Air extraction is required for spray application.

For solid products: Avoid dust formation and dust deposits. Air limit values mentioned in section 8 must be monitored.

At workplaces where isocyanate aerosols and/or vapours can occur in higher concentrations, targeted air extraction must be used to prevent the occupational hygiene limit value from being

exceeded. The air must be moved away from people.

For products containing solvents: Explosion protection required. The personal protective measures described in section 8 must be observed. The protective measures required when handling isocyanates must be observed. Avoid contact with skin and eyes and inhalation of vapours.

Keep away from food and beverages. Wash hands before breaks and at the end of work and apply skin protection ointment. Store work clothes separately. Remove soiled, soaked clothing

immediately.

· 7.2 Conditions for safe storage, including any incompatibilities

Keep container dry and tightly closed. Further information on the storage conditions that must be observed for quality assurance

reasons can be found in our technical data sheet.

· Storage

· Requirements to be met by

storerooms and containers: Store only in the original container.

· Further information about

storage conditions: None. · Storage class 6.1C

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

Components with critical values that require

monitoring at the workplace: The product does not contain any relevant quantities of materials

with critical values that have to be monitored at the workplace.

DNELs

CAS: 68479-98-1 diethylmethylbenzenediamine

DNEL 1 mg/kg bw/day (ArL) Dermal Inhalative DNEL 0.13 mg/m³ (ArL)

(Contd. on page 5)



Page 5/12

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 10.03.2024 Version number 28 (replaces version 27) Revision: 10.03.2024

Trade name MC-DUR 2211 MB - Komponente A

(Contd. of page 4)

· PNECs

CAS: 68479-98-1 diethylmethylbenzenediamine

PNEC aqua 0.05 µg/l (Mew)

0.5 μg/l (Freshwater)

PNEC 17 mg/l (Kla)

PNEC 0.0029 mg/kg dwt (Marine water sediment)

0.029 mg/kg dwt (Fresh water sediment)

• Additional information: The lists that were valid during the compilation were used as basis.

8.2 Exposure controls
Appropriate engineering

controls No further data; see section 7.

· Individual protection measures, such as personal protective equipment

· General protective and

hygienic measures Keep away from food, drink and animal feed.

Remove soiled, soaked clothing immediately.
Wash hands before breaks and at the end of work.

Avoid contact with eyes and skin.

· Breathing equipment: Respiratory protection required at insufficiently ventilated

workplaces and when working with splashes. Fresh air masks or combination filters A2-P2 (EN529) are recommended for short-

term work.

If applicable, further recommendations for respiratory protection

can be found in the appendix.

In case of hypersensitivity of the respiratory tract (asthma, chronic

bronchitis), handling of the product is not recommended.

· Hand protection Suitable materials for protective gloves; EN 374:

Butyl rubber, nitrile rubber, chloroprene rubber (neoprene).

Note: suitable materials that provide sufficient protection for industrial cleaning with aprotic polar solvents (according to IUPAC

definition): butyl rubber.

In case of prolonged or frequently repeated contact, a glove with a protection class of 5 or higher is recommended (breakthrough time greater than 240 minutes according to EN374). For short-term contact, a glove with a protection class of 3 or higher is recommended (breakthrough time greater than 60 minutes

according to EN374).

The thickness of the material is not the only criterion for the level of protection of a glove against a chemical substance. The protective effect also depends to a large extent on the type of glove material. Depending on the type and material, the thickness must be more than 0.35 mm to ensure adequate protection in the event of prolonged and frequent contact. Exceptions to this rule are multilayer gloves, which guarantee sufficient protection even with a thickness of less than 0.35 mm during prolonged wear. Other glove materials with a thickness of less than 0.35 mm only provide

sufficient protection for short periods of wear.

For solvent-free products:

Example:

(Contd. on page 6)



Page 6/12

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 10.03.2024 Version number 28 (replaces version 27) Revision: 10.03.2024

Trade name MC-DUR 2211 MB - Komponente A

(Contd. of page 5)

Polychloroprene - CR: thickness ≥0.5mm; breakthrough time

<u>≥</u>480min.

Nitrile rubber - NBR: thickness ≥0.35mm; breakthrough time

≥480min.

Butyl rubber - IIR: thickness ≥0.5mm; breakthrough time ≥480min. Fluoro rubber - FKM: thickness ≥0.4mm; breakthrough time

>480min

Recommendation: Dispose of contaminated gloves.

Material of gloves Polychloroprene - CR

Nitrile rubber - NBR Butyl rubber - IIR Fluoro rubber - FKM

· Penetration time of glove

material Polychloroprene - CR: thickness ≥0.5mm; breakthrough time

≥480min.

Nitrile rubber - NBR: thickness ≥0.35mm; breakthrough time

≥480min.

Butyl rubber - IIR: thickness ≥0.5mm; breakthrough time ≥480min. Fluoro rubber - FKM: Thickness ≥0.4mm; Breakthrough time

*≥*480min.

• Eye/face protection Safety goggles with side protection in accordance with EN 166.

· **Body protection:** Use chemical-resistant protective clothing.

In case of hypersensitivity of the skin, handling the product is not

recommended.

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Colour: Grey

Smell: Product specificMelting point/freezing point: Not determined

· Boiling point or initial boiling point and

boiling range
Not determined
>Flash point:
>100 °C

pH Viscosity:

Not determined.

• Kinematic viscosity Not determined. • dynamic at 20 °C: 800 mPas

· Solubility

· Water: Not miscible or difficult to mix

· Steam pressure at 20 °C: 0.1 hPa

· Density and/or relative density

Density at 20 °C 1.53 g/cm³

(Contd. on page 7)



Page 7/12

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Revision: 10.03.2024 Printing date 10.03.2024 Version number 28 (replaces version 27)

Trade name MC-DUR 2211 MB - Komponente A

(Contd. of page 6)

· 9.2 Other information

· Appearance:

Fluid · Form:

· Important information on protection of health

and environment, and on safety.

· Self-inflammability: Product is not selfigniting. · Explosive properties: Product is not explosive.

· Information with regard to physical hazard

classes

· Explosives Void · Flammable gases Void Void · Aerosols · Oxidising gases Void

· Gases under pressure Void Flammable liquids Void · Flammable solids Void · Self-reactive substances and mixtures Void

· Pyrophoric liquids Void · Pyrophoric solids Void · Self-heating substances and mixtures Void

· Substances and mixtures, which emit flammable gases in contact with water Void · Oxidising liquids Void Oxidising solids Void Void · Organic peroxides Void · Corrosive to metals

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability Thermal decomposition /

· Desensitised explosives

conditions to be avoided: No decomposition if used according to specifications.

Void

· 10.3 Possibility of hazardous

reactions No dangerous reactions known

· 10.4 Conditions to avoid No further relevant information available. · 10.5 Incompatible materials: No further relevant information available.

· 10.6 Hazardous

decomposition products: No dangerous decomposition products known

(Contd. on page 8)



Page 8/12

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 10.03.2024 Version number 28 (replaces version 27) Revision: 10.03.2024

Trade name MC-DUR 2211 MB - Komponente A

(Contd. of page 7)

SECTION 11: Toxicological information

· 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

• Acute toxicity Based on available data, the classification criteria are not met.

 LD/LC50 values that are relevant for classification:

 CAS: 149-57-5 2-Ethylhexanacid

 Oral
 LD50
 1260 mg/kg (rabbit)

 3000 mg/kg (rat)
 3000 mg/kg (rat)

 CAS: 68479-98-1 diethylmethylbenzenediamine

 Oral
 LD50
 738 mg/kg (rat)

 Dermal
 LD50
 >2000 mg/kg (rabbit)

 >2000 mg/kg (rat)
 >2000 mg/kg (rat)

CAS: 25550-51-0 hexahydromethylphthalic anhydride

Inhalative LC50/4 h 563 mg/l (rat)

• Skin corrosion/irritation Based on available data, the classification criteria are not met.

· Respiratory or skin

sensitisation May cause an allergic skin reaction.

• Germ cell mutagenicity
• Carcinogenicity

Based on available data, the classification criteria are not met.

Based on available data, the classification criteria are not met.

Reproductive toxicity May damage the unborn child.

STOT-single exposure
STOT-repeated exposure
Aspiration hazard

Based on available data, the classification criteria are not met.
Based on available data, the classification criteria are not met.
Based on available data, the classification criteria are not met.

11.2 Information on other hazards

· Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

CAS: 68479-98-1 diethylmethylbenzenediamine

EC50/24h | 170 mg/l (Pseudomonas putida)

EC50/72h 104 mg/l (algae) LC50/96h >104 mg/l (fish)

LC50/48h 0.5 mg/l (Daphnien)

200 mg/l (fish)

EC50/48h 5.8 mg/l (Daphnien)

· 12.2 Persistence and

degradability · 12.3 Bioaccumulative

potential No further relevant information available.

itv No further relevant information available.

(Contd. on page 9)



Page 9/12

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 10.03.2024 Version number 28 (replaces version 27) Revision: 10.03.2024

Trade name MC-DUR 2211 MB - Komponente A

(Contd. of page 8)

• **12.4 Mobility in soil** No further relevant information available.

12.5 Results of PBT and vPvB assessment
 PBT: Not applicable.
 vPvB: Not applicable.

· 12.6 Endocrine disrupting

properties The product does not contain substances with endocrine disrupting

properties.

· 12.7 Other adverse effects

· Additional ecological information:

• General notes: Danger to drinking water if even extremely small quantities leak

into soil.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

• Recommendation Must not be disposed of together with household garbage. Do not

allow product to reach sewage system.

· Uncleaned packagings:

• Recommendation: Empty contaminated packagings thoroughly. They can be recycled

after thorough and proper cleaning.

14.1 UN number or ID number ADR, IMDG, IATA	UN3082	
14.2 UN proper shipping name ADR, IATA IMDG	ENVIRONMENTALLY HAZARDOU SUBSTANCE, LIQUID, N.O.S. (6-methyl-2, bis(methylthio)phenylene-1,3-diamin diethylmethylbenzenediamine) ENVIRONMENTALLY HAZARDOU SUBSTANCE, LIQUID, N.O.S. (6-methyl-2, bis(methylthio)phenylene-1,3-diamin diethylmethylbenzenediamine), MARIN POLLUTANT	
14.3 Transport hazard class(es)		
ADR		
Class	9 (M6) Miscellaneous dangerous substances at articles.	
Label	9	
IMDG, IATA		
Class	9 Miscellaneous dangerous substances au articles.	

(Contd. on page 10)





Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 10.03.2024 Version number 28 (replaces version 27) Revision: 10.03.2024

Trade name MC-DUR 2211 MB - Komponente A

Label	(Contd. of page
	9
14.4 Packing group ADR, IMDG, IATA	III
14.5 Environmental hazards:	
Marine pollutant:	Yes
marme ponatant.	Symbol (fish and tree)
Special marking (ADR):	Symbol (fish and tree)
Special marking (IATA):	Symbol (fish and tree)
14.6 Special precautions for user	Warning: Miscellaneous dangerous substances ar
14.0 Special precautions for user	articles.
Kemler Number:	90
EMS Number:	F-A,S-F
Stowage Category	A
Transport/Additional information: ADR Limited quantities (LQ)	5L
Limited quantities (LQ) Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 100
Transport autorom.	ml 3
Transport category Tunnel restriction code	3 (-)
	1/
IMDG	51
Limited quantities (LQ)	5L Code: E1
Excepted quantities (EQ)	
	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 100 ml
UN "Model Regulation":	UN 3082 ENVIRONMENTALLY HAZARDOU SUBSTANCE, LIQUID, N.O.S. (6-METHYL-2, BIS(METHYLTHIO)PHENYLENE-1,3-DIAMIN

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Poisons Act

· Regulated explosives precursors

None of the ingredients is listed.

(Contd. on page 11)



Page 11/12

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 10.03.2024 Version number 28 (replaces version 27) Revision: 10.03.2024

Trade name MC-DUR 2211 MB - Komponente A

(Contd. of page 10)

Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors

None of the ingredients is listed.

· Reportable poisons

None of the ingredients is listed.

- Directive 2012/18/EU
- Qualifying quantity (tonnes) for the application of lower-

tier requirements 200 t

Qualifying quantity (tonnes) for the application of upper-

tier requirements 500 t

- · National regulations
- · Substances of very high concern (SVHC) according to UK REACH

CAS: 25550-51-0 hexahydromethylphthalic anhydride

· 15.2 Chemical safety

assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases H302 Harmful if swallowed.

H312 Harmful in contact with skin.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H360D May damage the unborn child.

H372 Causes damage to organs through prolonged or repeated

exposure.

H373 May cause damage to organs through prolonged or

repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

· Department issuing data

specification sheet: Environme

Environment protection department.

· Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises

dangereuses par chemin de fer (Regulations Concerning the International

Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous

Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals (Contd. on page 12)



Page 12/12

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 10.03.2024 Version number 28 (replaces version 27) Revision: 10.03.2024

Trade name MC-DUR 2211 MB - Komponente A

(Contd. of page 11)

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (UK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Acute Tox. 4: Acute toxicity – Category 4

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

Skin Sens. 1: Skin sensitisation – Category 1 Repr. 1A: Reproductive toxicity – Category 1A

STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard –

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic

hazard - Category 1

GB

^{*} Data compared to the previous version altered.