

Page 1/12

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 02.12.2023 Version number 26 (replaces version 25) Revision: 02.12.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

Trade name MC-POWERPRO HCR - Komponente B

· Article number: 3162

1.2 Relevant identified uses of the substance or mixture

and uses advised against No further relevant information available.

· Application of the substance

/ the mixture Epoxy coating

Hardening agent/ Curing agent

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier: MC-Bauchemie Müller GmbH & Co. KG

Am Kruppwald 1-8 D-46238 Bottrop Tel.: +49(0)2041-101-0 Fax.: +49(0)2041-101-400 E-Mail: info@mc-bauchemie.de

MC-Bauchemie AG Hagackerstr. 10 CH-8953 Dietikon Tel.: +44-7400510 Fax: +44-7400533

· Informing department:

number:

1.4 Emergency telephone

Tel.: +49 / (0)700 24112112 (MCR)

Tel.: +48612864565

msds@mc-bauchemie.de

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

Acute Tox. 4 H302 Harmful if swallowed.

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.
Skin Sens. 1 H317 May cause an allergic skin reaction.

Aguatic Chronic 3 H412 Harmful to aguatic life with long lasting effects.

· 2.2 Label elements

Labelling according to

Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms



GHS05 GHS07





Safety data sheet according to 1907/2006/EC, Article 31

Printing date 02.12.2023 Version number 26 (replaces version 25) Revision: 02.12.2023

Trade name MC-POWERPRO HCR - Komponente B

(Contd. of page 1)

· Signal word

Danger

· Hazard-determining

components of labelling:

Benzyl alcohol Isophorone diamine polymer amine terminated Tetraethylenepentamine

Amine polymer

Kohlenwasserstoffe, C9-ungesättigt, polymerisiert

m-phenylenebis(methylamine)

2,4,6-Tris-(1-Phenyl-Ethyl) carbolic acid

Triethylenetetramine

· **Hazard statements** H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

• Precautionary statements P260 Do not breathe dusts or mists.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all

contaminated clothing. Rinse skin with water [or

shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for

several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P321 Specific treatment (see on this label).

P362+P364 Take off contaminated clothing and wash it

before reuse.

· Additional information: To avoid risks to human health and the environment, comply with

the instructions for use.

· 2.3 Other hazards

Results of PBT and vPvB assessment
 PBT: Not applicable.
 vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

• **Description:** Binding agent with colouring agents.

Mixture consisting of the following components.

CAS: 100-51-6	Benzyl alcohol	30-60%
	Acute Tox. 4, H302; Acute Tox. 4, H332; Eye Irrit. 2, H319	
CAS: 2855-13-2 EINECS: 220-666-8 Reg.nr.: 01-2119514687-32	Isophorone diamine Skin Corr. 1B, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1, H317; Aquatic Chronic 3, H412	≥10-<25%



Page 3/12

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 02.12.2023 Version number 26 (replaces version 25) Revision: 02.12.2023

Trade name MC-POWERPRO HCR - Komponente B

	polymer amine terminated	(Contd. of page 2 10-30%
	Eye Dam. 1, H318; Skin Irrit. 2, H315; Skin Sens. 1B, H317	
EC number: 948-369-5	Amine polymer Eye Dam. 1, H318; Skin Irrit. 2, H315; Skin Sens. 1B, H317	10-30%
CAS: 90640-66-7 EINECS: 292-587-7 Reg.nr.: 01-2119487290-37	Tetraethylenepentamine Skin Corr. 1B, H314; Aquatic Chronic 2, H411; Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1, H317	≥5-<10%
CAS: 1477-55-0 EINECS: 216-032-5 Reg.nr.: 01-2119480150-50	Onin Con. 1D, Horn, Modic Tox. 1, Hooz, Modic Tox. 1,	
CAS: 69-72-7 EINECS: 200-712-3	salicylic acid Repr. 2, H361d; Eye Dam. 1, H318; Acute Tox. 4, H302	≥1-<1.5%
CAS: 71302-83-5 EC number: 701-299-7	Kohlenwasserstoffe, C9-ungesättigt, polymerisiert Asp. Tox. 1, H304; Skin Sens. 1A, H317; Aquatic Chronic 3, H412	≥0.1-<1%
CAS: 61788-44-1 2,4,6-Tris-(1-Phenyl-Ethyl) carbolic acid EINECS: 262-975-0 Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Skin Sens. 1, H317		≥0.25-<0.5%
CAS: 90640-67-8 EINECS: 292-588-2 Skin Corr. 1B, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1, H317; Aquatic Chronic 3, H412		≥0.1-<0.5%

• Additional information For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

• General information Seek medical treatment.

Instantly remove any clothing soiled by the product.

Supply fresh air; consult doctor in case of symptoms.

Instantly wash with water and soap and rinse thoroughly.

After eye contact

Rinse opened eye for several minutes under running water.

Seek medical treatment.

· After swallowing Drink copious amounts of water and provide fresh air. Instantly call

for doctor.

· 4.2 Most important symptoms and effects, both acute and

delayed No further relevant information available.

(Contd. on page 4)



Page 4/12

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 02.12.2023 Version number 26 (replaces version 25) Revision: 02.12.2023

Trade name MC-POWERPRO HCR - Komponente B

(Contd. of page 3)

 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

· Suitable extinguishing agents Use fire fighting measures that suit the environment.

 5.2 Special hazards arising from the substance or

mixture No further relevant information available.

· 5.3 Advice for firefighters

· Protective equipment: Put on breathing apparatus.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and

emergency procedures Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:

Prevent material from reaching sewage system, holes and cellars.

· 6.3 Methods and material for

containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders,

universal binders, sawdust). Use neutralising agent.

Dispose of contaminated material as waste according to item 13.

Ensure adequate ventilation.

· 6.4 Reference to other

sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

SECTION 7: Handling and storage

· 7.1 Precautions for safe

handling Store in cool, dry place in tightly closed containers.

Open and handle container with care.

 Information about protection against explosions and fires: No special measures required.

7.2 Conditions for safe storage, including any incompatibilities

· Storage

· Requirements to be met by

storerooms and containers: No special requirements.

Information about storage in

one common storage facility: Not required.

· Further information about

storage conditions: Keep container tightly sealed.

(Contd. on page 5)



Page 5/12

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 02.12.2023 Version number 26 (replaces version 25) Revision: 02.12.2023

Trade name MC-POWERPRO HCR - Komponente B

(Contd. of page 4)

· Storage class

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

Components with critical

values that require

monitoring at the workplace: The product does not contain any relevant quantities of materials

with critical values that have to be monitored at the workplace.

DNELS	5	
CAS: 1	100-51-6 B	Benzyl alcohol
Oral	DNEL	4 mg/kg bw/Tag (ArL)
		20 mg/kg bw/Tag (Ark)
Derma	I DNEL	8 mg/kg bw/day (ArL)
		40 mg/kg bw/day (Ark)
Inhalat	ive DNEL	22 mg/m³ (ArL)
		110 mg/m³ (Ark)
CAS: 2	2855-13-2	Isophorone diamine
Oral	DNEL	0.526 mg/kg bw/Tag (ArL)
Inhalat	ive DNEL	20.1 mg/m³ (ArL)
CAS: 1	1477-55-0	m-phenylenebis(methylamine)
Derma	I DNEL	0.33 mg/kg bw/day (Workers)
Inhalat	alative DNEL 1.2 mg/m³ (Workers)	
PNEC	s	
CAS: 1	100-51-6 B	Benzyl alcohol
PNEC	0.527 mg/	/I (Marine water sediment)
	0.1 mg/l (l	Mew)
	1 mg/l (Fr	resh water sediment)
PNEC	0.456 mg/	/kg dwt (Bod)
	5.27 mg/k	kg dwt (Fresh water sediment)
CAS: 2	2855-13-2	Isophorone diamine
PNEC	IEC 0.006 mg/l (Mew)	
	0.06 mg/l	(Freshwater)
PNEC	0.578 mg/	/kg dwt (Sediment)
	5.784 mg/	/kg dwt (Fresh water sediment)
CAS: 1	1477-55-0	m-phenylenebis(methylamine)
PNEC	10 mg/l (k	(la)
	0.009 mg/	/I (Mew)
	0.094 mg/	/l (Freshwater)

(Contd. on page 6)



Page 6/12

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 02.12.2023 Version number 26 (replaces version 25) Revision: 02.12.2023

Trade name MC-POWERPRO HCR - Komponente B

(Contd. of page 5)

PNEC 0.045 mg/kg dwt (Bod)

0.43 mg/kg dwt (Marine water sediment) 0.43 mg/kg dwt (Fresh water sediment)

· Additional information: The lists that were valid during the compilation were used as basis.

8.2 Exposure controls
Appropriate engineering

controls No further data; see section 7.

· Individual protection measures, such as personal protective equipment

General protective and

hygienic measures Keep away from foodstuffs, beverages and food.

Instantly remove any soiled and impregnated garments. Wash hands during breaks and at the end of the work.

Avoid contact with the eyes and skin.

· Breathing equipment: For spray application, type A2P2 combination filters should be

used.

· Hand protection Protective gloves.

Selection of the glove material on consideration of the penetration

times, rates of diffusion and the degradation

After use of gloves apply skin-cleaning agents and skin cosmetics. The selection of the suitable gloves does not only depend on the

material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the

application.

· Penetration time of glove

Material of gloves

material The exact breakthrough time must be obtained from the protective

glove manufacturer and must be observed.

• Eye/face protection Safety glasses

Tightly sealed safety glasses.

· **Body protection:** Protective work clothing.

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

Colour: Transparent
 Smell: Amine-like
 Melting point/freezing point: Not determined

Boiling point or initial boiling point and

boiling range 205 °C

· Lower and upper explosion limit

Lower: 1.3 Vol %
Upper: 13 Vol %
Flash point: 101 °C
Auto-ignition temperature: 380 °C

(Contd. on page 7)



Page 7/12

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 02.12.2023 Version number 26 (replaces version 25) Revision: 02.12.2023

Trade name MC-POWERPRO HCR - Komponente B

(Contd. of page 6)

· pH Not determined.

· Viscosity:

· Kinematic viscosity Not determined. · dynamic at 20 °C: 150 mPas

· Solubility

· Water: Not miscible or difficult to mix

· Steam pressure at 20 °C: 0.1 hPa

· Density and/or relative density

· Density at 20 °C 1.06 g/cm3

· 9.2 Other information

· Appearance:

· Form: Fluid

· Important information on protection of health

and environment, and on safety.

· Self-inflammability: Product is not selfigniting. Explosive properties: Product is not explosive.

· Information with regard to physical hazard

classes

· Explosives Void · Flammable gases Void · Aerosols Void · Oxidising gases Void · Gases under pressure Void · Flammable liquids Void Flammable solids Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void · Pyrophoric solids Void Self-heating substances and mixtures Void · Substances and mixtures, which emit flammable gases in contact with water Void

· Oxidising liquids Void · Oxidising solids Void · Organic peroxides Void Corrosive to metals Void · Desensitised explosives Void

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

10.2 Chemical stability Thermal decomposition /

conditions to be avoided:

No decomposition if used according to specifications.

· 10.3 Possibility of hazardous

No dangerous reactions known reactions

· 10.4 Conditions to avoid No further relevant information available.

(Contd. on page 8)



Page 8/12

Safety data sheet according to 1907/2006/EC, Article 31

Revision: 02.12.2023 Printing date 02.12.2023 Version number 26 (replaces version 25)

Trade name MC-POWERPRO HCR - Komponente B

(Contd. of page 7)

· 10.5 Incompatible materials: No further relevant information available.

· 10.6 Hazardous

decomposition products: No dangerous decomposition products known

SECTION 11: Toxicological information

· 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

· Acute toxicity Harmful if swallowed.

CAS: 100	-51-6 Benzyl alcohol	
Oral	LD50	1230 mg/kg (rat)
	NOAEL 2nd year study	200 mg/kg (mouse)
		200 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rabbit)
Inhalative	LC50/4 h	>4178 mg/l (rat)
CAS: 285	5-13-2 Isophorone dian	nine
Oral	LD50	1030 mg/kg (ATE)
		1030 mg/kg (rat)
	NOAEL	250 mg/kg (rat)
Dermal	LD50	1840 mg/kg (rabbit)
		>2000 mg/kg (rat)
CAS: 147	7-55-0 m-phenylenebis	(methylamine)
Oral	LD50	1180 mg/kg (mouse)
		930 mg/kg (rat)
Dermal	LD50	>3100 mg/kg (rabbit)
CAS: 69-7	72-7 salicylic acid	
Oral	LD50	891 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rat)
CAS: 906	40-67-8 Triethylenetetra	amine
Oral	LD50	1716 mg/kg (rat)
Dermal	LD50	1465 mg/kg (rat)

Causes severe skin burns and eye damage. · Skin corrosion/irritation

· Serious eye damage/irritation Causes serious eye damage.

· Respiratory or skin

sensitisation May cause an allergic skin reaction.

· Germ cell mutagenicity Based on available data, the classification criteria are not met. · Carcinogenicity Based on available data, the classification criteria are not met. · Reproductive toxicity Based on available data, the classification criteria are not met. STOT-single exposure Based on available data, the classification criteria are not met. · STOT-repeated exposure Based on available data, the classification criteria are not met. · Aspiration hazard Based on available data, the classification criteria are not met.

(Contd. on page 9)



Page 9/12

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 02.12.2023 Version number 26 (replaces version 25) Revision: 02.12.2023

Trade name MC-POWERPRO HCR - Komponente B

· 11.2 Information	on other hazards	(Contd. of page 8)
· Endocrine disru	oting properties	
CAS: 69-72-7	salicylic acid	List II; III
CAS: 61788-44-1	2,4,6-Tris-(1-Phenyl-Ethyl) carbolic acid	List II

SECTION 12: Ecological information

· 12.1 Toxicity

	•
· Aquatic to	xicity:
CAS: 100-	51-6 Benzyl alcohol
IC50/72h	700 mg/l (algae)
LC50/96h	460 mg/l (Pimephales promelas)
	10 mg/l (Lepomis macrochirus)
CAS: 2855	-13-2 Isophorone diamine
LC50/96h	110 mg/l (Leucidus idus)
EC50	1120 mg/l (Pseudomonas putida)
EC50/48h	23 mg/l (Daphnia magna)
NOEC	1.5 mg/l (Desmodesmus subspicatus)
	3 mg/l (Daphnia magna)
ErC50/72h	>50 mg/l (Desmodesmus subspicatus)
CAS: 1477	-55-0 m-phenylenebis(methylamine)
IC50/72h	12 mg/l (algae)
EC50/72h	12 mg/l (Scenedesmus subspicatus)
LC50/96h	>100 mg/l (Oncorhynchus mykiss)
	87.6 mg/l (Ory)
EC50/48h	15.2 mg/l (Daphnia magna)

12.2 Persistence and

degradability No further relevant information available.

12.3 Bioaccumulative

potential
No further relevant information available.

12.4 Mobility in soil
No further relevant information available.

· 12.5 Results of PBT and vPvB assessment · PBT: Not applicable. · vPvB: Not applicable.

· 12.6 Endocrine disrupting

properties For information on endocrine disrupting properties see section 11.

12.7 Other adverse effects

· Additional ecological information:

General notes: Do not allow product to reach ground water, water bodies or

sewage system.

(Contd. on page 10)



Page 10/12

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 02.12.2023 Version number 26 (replaces version 25) Revision: 02.12.2023

Trade name MC-POWERPRO HCR - Komponente B

(Contd. of page 9)

Danger to drinking water if even small quantities leak into soil.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

• Recommendation Must not be disposed of together with household garbage. Do not

allow product to reach sewage system.

· Uncleaned packagings:

• Recommendation: Empty contaminated packagings thoroughly. They can be recycled

after thorough and proper cleaning.

14.1 UN number or ID number ADR, IMDG, IATA	UN2735
14.2 UN proper shipping name ADR, IMDG, IATA	AMINES, LIQUID, CORROSIVE, N.C (Isophorone diamine, Tetraethylenepentamine)
14.3 Transport hazard class(es)	
ADR Class Label	8 (C7) Corrosive substances. 8
IMDG, IATA Class Label	8 Corrosive substances. 8
14.4 Packing group ADR, IMDG, IATA	II
14.5 Environmental hazards: Marine pollutant:	No
14.6 Special precautions for user Kemler Number: EMS Number: Segregation groups Stowage Category Segregation Code	Warning: Corrosive substances. 80 F-A,S-B (SGG18) Alkalis A SG35 Stow "separated from" SGG1-acids

(Contd. on page 11)



Page 11/12

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 02.12.2023 Version number 26 (replaces version 25) Revision: 02.12.2023

Trade name MC-POWERPRO HCR - Komponente B

(Contd. of page 10)

· Transport/Additional information:

· ADR

· Limited quantities (LQ) 1L

· Excepted quantities (EQ) Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

· Transport category 2 · Tunnel restriction code E

· Remarks:

· Limited quantities (LQ)

1L Codo: F

Excepted quantities (EQ) Code: E2

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml

cont.: diaminomenthane, isophoronediamine

· UN "Model Regulation": UN 2735 AMINES, LIQUID, CORROSIVE, N.O.S.

(ISOPHORONE DIAMINE

TETRAETHYLENEPENTAMINE), 8, II

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/ legislation specific for the

substance or mixture No further relevant information available.

· Poisons Act

· Regulated explosives precursors

None of the ingredients is listed.

· Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors

None of the ingredients is listed.

· Reportable poisons

None of the ingredients is listed.

15.2 Chemical safety

assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

(Contd. on page 12)



Page 12/12

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 02.12.2023

Version number 26 (replaces version 25)

Trade name MC-POWERPRO HCR - Komponente B

(Contd. of page 11)

Revision: 02.12.2023

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H361d Suspected of damaging the unborn child.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

Department issuing data specification sheet:

Environment protection department.

· Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International

Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (ÚK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

Acute Tox. 4: Acute toxicity - Category 4

Skin Corr. 1B: Skin corrosion/irritation - Category 1B

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation - Category 1

Skin Sens. 1A: Skin sensitisation - Category 1A Skin Sens. 1B: Skin sensitisation - Category 1B

Repr. 2: Reproductive toxicity - Category 2

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic

hazard - Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic

hazard - Category 3

* * Data compared to the previous version altered.