

PRODUCT PROPERTIES

- Permanently elastic and tear-resistant
- Impermeable to water
- Quick and easy application
- Resistant to ageing
- High chemical resistant
- Suitable for terraces, balconies and damp rooms
- Particularly suitable in the system with MC-Proof and Nafuflex products

AREAS OF APPLICATION

- Sealing connection joints
- Producing wall-floor connections
- Use in internal and external corners

APPLICATION ADVICE

Substrate preparation: Loose parts, old coats, dust, dirt, etc. must be completely removed. The substrate must be frost-free, load-bearing and free of adhesion-reducing components. Burrs and sharp-edged unevenness must be removed.

Application: MC-FastTape is embedded in the first layer of the waterproofing. The second layer can then be applied. If a wall-floor connection is desired, we recommend laying a first layer of two-component waterproofing products. If joints are to be made, these should be made with a two-component waterproofing material. For this purpose, the material is applied over the entire surface of the part of the tape to be overlapped (min. 100 mm)

Note: MC-FastTape has been tested by the building authorities in combination with MC-Proof eco and MC-Proof one.

You will find illustrated instructions in our MC-FastTape flyer

TECHNICAL VALUES & PRODUCT CHARACTERISTICS

Characteristic	Unit	Value	Comments
Thickness	mm	0.7	
Width	mm	120	
Weight	g/m	44	
Thermal resistance	°C	> -30 < 90	
Water impermeability	bar	> 1.5	EN 1928
Fire behaviour		B2 E	DIN 4102-1 DIN 13501-1
Elongation at fracture (lengthways)	%	50	EN ISO 527-3
Elongation at fracture (transverse)	%	200	EN ISO 527-3

All technical values are laboratory results determined at 21°C ±2°C and 50% relative humidity.

Delivery form	MC-FastTape - 50 m roll MC-FastTape IE - 10 Inner corners / package MC-FastTape AE - 10 Outer corners / package
Colour	blue

Safety instructions

Please note the safety information and advice given on the packaging labels and safety data sheets.

Note: The information contained in this data sheet is based on our experience and is correct to the best of our knowledge. It is, however, not binding. It will need to be adapted to the requirements of the individual structure, to the specific application and to non-standard local conditions. Application-specific conditions must be checked in advance by the planning engineer/specifier and, where different from the standard conditions indicated, will require individual approval. Technical advice provided by MC's specialist consultants does not replace the need for a planning review by the client or its agents in respect of the history of the building or structure. Subject to this prerequisite, we are liable for the correctness of this information within the framework of our terms and conditions of sale and delivery. Recommendations of our employees deviating from the information given in our data sheets are only binding for us if they are confirmed in writing. In all cases, the generally accepted rules and practices reflecting the current state of the art must be observed. The information given in this technical data sheet is valid for the product supplied by the country company listed in the footer. It should be noted that data in other countries may differ. The product data sheets valid for the relevant foreign country must be observed. The latest technical data sheet shall apply to the exclusion of previous, duly superseded versions; the date of issue in the footer must be observed. The latest version is available from us on request or may be downloaded from our website. [2300018567]