Acessory Guide for Wind Power Grout Emcekrete WP 108

Machine	S 5 EVTM	FP-V5
Manufacturer	Putzmeister	b&m GmbH
Product	Spiral pump S5 EVTM with integrated compulsory mixer	Spiral pump FP-V5 with integrated compulsory mixer GM 100
Product	Emcekrete WP 108	

integrated	integrated
2L6	2L54
7–40 l/min	5 – 50 l/min
25 bar	40 bar
5.5 kW	5.5 kW
2.2 kW	2.2 kW
80	80
100 l	100
2,505 x 680 x 1,150	2,550 x 680 x 1,170
400	195 + 210
NW 50 (Ø 67 external diameter)	NW 50 (Ø 67 external diameter)
	2L6 7–40 l/min 25 bar 5.5 kW 2.2 kW 80 l 100 l 2,505 x 680 x 1,150 400

Mixing process	Emcekrete WP 108	
Grain size	0 – 8 mm	0 – 8 mm
Water / 25 kg	1.8 – 2.0 l	1.8 – 2.0 l
Material quantity per mixture	5 bags (per 25 kg)	5 bags (per 25 kg)
Mixing time	5 min	5 min

* The pumping quantity depends on the pump type. Depending on the used pump, the quantity may vary.

** Mortar tubes have to be pre-slurried with cement slurry in honey-like consistency.

The machinery and accessories have been tested with the MC-mentioned products. Machinery and equipment from other manufacturers may also be suitable. However, appropriate preliminary tests are carried out by specialist companies. If necessary, please ask for our technical advice.





Acessory Guide for Wind Power Grout Emcekrete WP 108

PFT ZP 3 XL	WM Variojet FU
PFT	Werner Mader
Spiral pump PFT ZP 3 XL with compulsory mixer PFT MULTIMIX	Spiral pump WM Variojet FU with compulsory mixer WM Jetmix
	PFT

Product	Emcekrete WP 108	
Compulsory mixer	PFT MULTIMIX	WM Jetmix 125
Spiral	PFT ZP 3 XL	WM Variojet FU
Flowrate*	27 l/min	0.2–2.2 m ³ /h
Pump pressure	30 bar	25 bar
Motor	7.5 kW	5.5 kW
Mixer drive	2.5 kW	2.2 kW
Mixer volume	80	125
Funnel volume	130	40
Dimension in mm	2,255 x 725 x 745	1,600 x 480 x 525
Weight in kg	238 + 148	200 + 200
Mortar tube**	NW 50 (Ø 67 external diameter)	NW 50 (Ø 67 external diameter)

Mixing process	Emcekrete WP 108	
Grain size	0 – 8 mm	0 – 8 mm
Water / 25 kg	1.8 – 2.0 l	1.8 – 2.0 l
Material quantity per mixture	5 bags (per 25 kg)	3 bags (per 25 kg)
Mixing time	5 min	5 min

* The pumping quantity depends on the pump type. Depending on the used pump, the quantity may vary.

** Mortar tubes have to be pre-slurried with cement slurry in honey-like consistency.

The machinery and accessories have been tested with the MC-mentioned products. Machinery and equipment from other manufacturers may also be suitable. However, appropriate preliminary tests are carried out by specialist companies. If necessary, please ask for our technical advice.



