

Centrament Stabi M 15

Reference number of the Declaration of Performance: 1460004

1. Unique ID code of the product type	Centrament Stabi M 15
2. Application(s)	Stabiliser per EN 934-2: T 4
3. Manufacturer	MC-Bauchemie Müller GmbH & Co. KG Am Kruppwald 1-8 46238 Bottrop / Germany
4. Authorized representative	-
5. System of AVCP	System 2+ (for uses in buildings and civil engineering works)
6. Harmonised standard	EN 934-2: 2009+A1: 2012
7. Notified body	Institut für Massivbau und Baustofftechnologie Universität Karlsruhe (TH) ID code 0754 EN 934-2 T4

8. Declared performances


Essential characteristic	Performance	harmonised technical specification
Chloride content	max. 0.10% by mass	EN 934-1
Alkaline content	max. 1.0 % by mass	
Corrosion behaviour	Contains components only from EN 934-1 : 2008, Annex A.1	
Compressive strength	after 28 days: Test mixture \geq 85 % of the control mixture	EN 934-2: 2009 + A1: 2012
Air void content	Test mixture \leq 2 % by volume above the control mixture	
Water secretion (bleeding)	Test mixture \leq 50 % of the control mixture	
Hazardous substances	Regulation (EC) No. 1907/2006, see safety data sheet	EGVO

The performance of the product identified above is in conformity with the set of declared performance/s. This Declaration of Performance is issued in accordance with Regulation (EU) No 305/2011 (amended by Commissions delegated Regulation (EU) No 574/2014), under the soleresponsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

van Diemen
Head of research and development and quality control

Bottrop, 20.07.2022
(place and date of issue)



(Unterschrift)

Annex

According to Art. 6 (5) of the Regulation (EU) No. 305/2011 a Safety Data sheet according Regulation (EU) No. 1907/2006(REACH), Annex II is attached to this Declaration of Performance.