Declaration of Performance



Elegant MRP

Reference number of the Declaration of Performance: IN4189000

1.	Unique ID code of the product type	Elegant MRP	
2.	Application(s)	Normal plastering mortar (in- and outdoor) for sustainable moisture regulation of we and salt-loaded surfaces	
3.	Manufacturer	MC-Bauchemie Müller GmbH & Co. KG Am Kruppwald 1-8	
		46238 Bottrop / Germany	
4.	Authorized representative	MC-Bauchemie Müller GmbH & Co. KG	
		Am Kruppwald 1-8	
		46238 Bottrop / Germany	
5.	System of AVCP	System 4	
6.	Harmonised standard	DIN EN 988-1: 2010	
7.	Notified body	<u>-</u>	


8. Declared performances

Essential characteristic	Performance	AVCP	harmonised technical specification
Water absorption	W0	System 4	DIN EN 998-1: 2010
Tensile strength	≥ 0.43 N/mm² Fracture appearance A/B		
Thermal conductivity	0.33 W/m x K (Tabular value)		
Durability (frost resistance)	Evaluation dependant on the determinations at the intended production site of the render.		
Fire behaviour	A1		

The performance of the product identified above is in conformity with the set of declared performance/s. This Declaration of Performance is issued in accordance with Regulation (EU) No 305/2011 (amended by Commissions delegated Regulation (EU) No 574/2014), under the soleresponsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

John van Diemen Head of Research & Development and Quality



Bottrop, 21.11.2023 (place and date of issue)

Annex

According to Art. 6 (5) of the Regulation (EU) No. 305/2011 a Safety Data sheet according Regulation (EU) No. 1907/2006(REACH), Annex II is attached to this Declaration of Performance.