

MC-DUR 2095 G

Reference number of the Declaration of Performance: IN5439005

1.	Unique ID code of the product type	MC-DUR 2095 G
2.	Application(s)	Surface protection product coating Protection against ingress (1.3) Moisture control (2.2) Physical resistance (5.1) Increasing resistivity (8.2)
3.	Manufacturer	MC-Bauchemie Müller GmbH & Co. KG Am Kruppwald 1-8 46238 Bottrop / Germany
4.	Authorized representative	-
5.	System of AVCP	System 2+ (for uses in buildings and civil engineering works)
6.	Harmonised standard	EN 1504-2: 2004
7.	Notified body	Institut für Massivbau und Baustofftechnologie Universität Karlsruhe (TH) ID code 0754

8. Declared performances

Essential characteristic	Performance	harmonised technical specification
Wear resistance	< 3000 mg	
CO ₂ permeability	Sd > 50 m	
Water vapour permeability	class I S _D < 5 m	
Capillary water absorption	< 0.1 kg/m ² ·h ^{0.5}	
Impact strength	class I: ≥ 4 Nm	EN 1504-2: 2004
Tear-off test to determine adhesive strength	≥ 1.0 (0.7) N/mm²	
Behaviour after artificial weathering	no visible defects	
Fire behaviour	E _{fl}	
Hazardous substances	EN 1504-2, pt. 5.3	

The performance of the product identified above is in conformity with the set of declared performance/s. This Declaration of Performance is issued in accordance with Regulation (EU) No 305/2011 (amended by Commissions delegated Regulation (EU) No 574/2014), under the soleresponsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

John van Diemen Head of Research & Development and Quality

FRKLÄR (signature)

Bottrop, 13.10.2023 (place and date of issue)

Annex

According to Art. 6 (5) of the Regulation (EU) No. 305/2011 a Safety Data sheet according Regulation (EU) No. 1907/2006(REACH), Annex II is attached to this Declaration of Performance.