

## MC-Estribond MB

Reference number of the Declaration of Performance: CC18500

1. Unique ID code of the product type	MC-Estribond MB
2. Application(s)	Product for non-structural repair for concrete Manual mortar application (3.1)
3. Manufacturer	MC-Bauchemie Müller GmbH & Co. KG Am Kruppwald 1-8 46238 Bottrop / Germany
4. Authorized representative	-
5. System of AVCP	System 2+ (for uses in buildings and civil engineering works)
6. Harmonised standard	-
7. Notified body	Institut für Massivbau und Baustofftechnologie Universität Karlsruhe (TH) ID code 0754

8. Declared performances


Essential characteristic	Performance	harmonised technical specification
Compressive strength	class R4	EN 1504-3: 2005
Chloride ion content	≤ 0.05%	
Thermal shock tolerance Part 1	≥ 2.0 MPa	
Capillary water absorption	≤ 0.5 kg/m <sup>2</sup> h <sup>0.5</sup>	
Fire behaviour	A1	

The performance of the product identified above is in conformity with the set of declared performance/s. This Declaration of Performance is issued in accordance with Regulation (EU) No 305/2011 (amended by Commissions delegated Regulation (EU) No 574/2014), under the soleresponsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

John van Diemen  
Head of Research & Development and Quality

Bottrop, 13.10.2023  
(place and date of issue)

  
 (signature)

Annex

According to Art. 6 (5) of the Regulation (EU) No. 305/2011 a Safety Data sheet according Regulation (EU) No. 1907/2006(REACH), Annex II is attached to this Declaration of Performance.