

Declaration of Performance



MC-FLEX 2097

Reference number of the Declaration of Performance: IN5499001

1. Unique ID code of the product type	MC-FLEX 2097
2. Application(s)	Surface protection products – Coating Protection against ingress (1.3) Moisture control (2.2) Physical resistance (5.1) Resistance to chemicals (6.1) Increasing resistivity (8.2)
3. Manufacturer	MC-Bauchemie Müller GmbH & Co. KG Am Kruppwald 1-8 46238 Bottrop / Germany
4. Authorized representative	-
5. System of AVCP	System 2+ (for uses in buildings and civil engineering works)
6. Harmonised standard	EN 1504-2: 2004
7. Notified body	Institut für Massivbau und Baustofftechnologie Universität Karlsruhe (TH) ID code 0754

8. Declared performances


Essential characteristic	Performance	harmonised technical specification
Wear resistance	< 3000 mg	EN 1504-2: 2004
CO2 permeability	sD > 50 m	
Water vapour permeability	class III sD > 50 m	
Capillary water absorption	w < 0.1 kg/m ² x h ^{0.5}	
Resistance to chemicals	< 50%	
Resistance to strong chemical attack	Reduction in hardness of less than 50%	
Crack-bridging capacity	A4	
Impact strength	class II (≥ 10 Nm)	
Tear-off test to determine adhesive strength	≥ 1.5 (1.0)	
Fire behaviour	E _{fl}	
Hazardous substances	EN 1504-2, Pt. 5.3	

The performance of the product identified above is in conformity with the set of declared performance/s. This Declaration of Performance is issued in accordance with Regulation (EU) No 305/2011 (amended by Commissions delegated Regulation (EU) No 574/2014), under the soleresponsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

van Diemen
Head of research and development and quality control

Bottrop, 19.11.2021
(place and date of issue)



(Unterschrift)

Annex

According to Art. 6 (5) of the Regulation (EU) No. 305/2011 a Safety Data sheet according Regulation (EU) No. 1907/2006(REACH), Annex II is attached to this Declaration of Performance.