

MC-Fastpack 2300 top

Reference number of the Declaration of Performance: 5507000

1. Unique ID code of the product type	MC-Fastpack 2300 top
2. Application(s)	Concrete injection for ductile filling of cracks, voids and interstices (D), U (D2) W (1) (1/2/3/4) (5/40)
3. Manufacturer	MC-Bauchemie Müller GmbH & Co. KG Am Kruppwald 1-8 46238 Bottrop / Germany
4. Authorized representative	MC-Bauchemie Müller GmbH & Co. KG Am Kruppwald 1-8 46238 Bottrop / Germany
5. System of AVCP	System 2+ (for uses in buildings and civil engineering works)
6. Harmonised standard	EN 1504-5: 2004
7. Notified body	Institut für Massivbau und Baustofftechnologie Universität Karlsruhe (TH) ID code 0754

8. Declared performances


Essential characteristic	Performance	AVCP	harmonised technical specification
Adhesion	0.46 - 1.31 N/mm ²	System 2+	EN 1504-5: 2004
Ductility	> 10 %		
Water impermeability	D2 (7 bar)		
Glass transition temperature	- 34 °C		
Injectability with dry medium	class 1 (0.1 mm)		
Durability: Compatibility with concrete	no failure in compressive test, loss of deformation capacity < 20%		
Hazardous substances	Accordance with 5.4		

The performance of the product identified above is in conformity with the set of declared performance/s. This Declaration of Performance is issued in accordance with Regulation (EU) No 305/2011 (amended by Commissions delegated Regulation (EU) No 574/2014), under the soleresponsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

John van Diemen
Head of Research & Development and Quality

Bottrop, 13.10.2023
(place and date of issue)


 (signature)

Annex

According to Art. 6 (5) of the Regulation (EU) No. 305/2011 a Safety Data sheet according Regulation (EU) No. 1907/2006(REACH), Annex II is attached to this Declaration of Performance.