

MC-Injekt 2700 L

Reference number of the Declaration of Performance: IN 5527001

1. Unique ID code of the product type	MC-Injekt 2700 L
2. Application(s)	Concrete injection for ductile filling of cracks, voids and interstices (D), U (F1) W (2) (1) (5/40) (0)
3. Manufacturer	MC-Bauchemie Müller GmbH & Co. KG Am Kruppwald 1-8 46238 Bottrop / Germany
4. Authorized representative	MC-Bauchemie Müller GmbH & Co. KG Am Kruppwald 1-8 46238 Bottrop / Germany
5. System of AVCP	System 4
6. Harmonised standard	EN 1504-5: 2004
7. Notified body	-

8. Declared performances


Essential characteristic	Performance	AVCP	harmonised technical specification
Volumetric shrinkage	< 3 %	System 4	EN 1504-5: 2004
Glass transition temperature	> 40 °C		
Injectability with dry medium	class 2 (0.2 mm)		
Adhesion through adhesive tensile strength	> 3 N/mm ²		
Hazardous substances	Accordance with 5.4		

The performance of the product identified above is in conformity with the set of declared performance/s. This Declaration of Performance is issued in accordance with Regulation (EU) No 305/2011 (amended by Commissions delegated Regulation (EU) No 574/2014), under the soleresponsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

John van Diemen
Head of Research & Development and Quality

Bottrop, 13.10.2023
(place and date of issue)



(signature)

The image shows a blue ink signature over a circular stamp. The stamp contains the text 'LEISTUNGSERKLÄRUNG' at the top, 'MC' on the left and right sides, and 'DECLARATION OF PERFORMANCE' at the bottom. In the center of the stamp is a CE mark.

Annex

According to Art. 6 (5) of the Regulation (EU) No. 305/2011 a Safety Data sheet according Regulation (EU) No. 1907/2006(REACH), Annex II is attached to this Declaration of Performance.