

Declaration of Performance



MC-Injekt 2700 L

Reference number of the Declaration of Performance: IN 5527001

1. Unique ID code of the product type	MC-Injekt 2700 L
2. Application(s)	Concrete injection for ductile filling of cracks, voids and interstices (D), U (F1) W (2) (1) (5/40) (0)
3. Manufacturer	MC-Bauchemie Müller GmbH & Co. KG Am Kruppwald 1-8 46238 Bottrop / Germany
4. Authorized representative	MC-Bauchemie Müller GmbH & Co. KG Am Kruppwald 1-8 46238 Bottrop / Germany
5. System of AVCP	System 4
6. Harmonised standard	EN 1504-5: 2004
7. Notified body	-

8. Declared performances


Essential characteristic	Performance	AVCP	harmonised technical specification
Adhesion through adhesive tensile strength	> 3 N/mm ²	System 4	EN 1504-5: 2004
Volumetric shrinkage	< 3 %		
Glass transition temperature	> 40 °C		
Injectability with dry medium	0,2 mm		
Hazardous substances	Compliance with 5.4		

The performance of the product identified above is in conformity with the set of declared performance/s. This Declaration of Performance is issued in accordance with Regulation (EU) No 305/2011 (amended by Commissions delegated Regulation (EU) No 574/2014), under the soleresponsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

van Diemen
Head of research and development and quality control

Bottrop, 28.05.2021
(place and date of issue)



The image shows a blue circular stamp with the text 'LEISTUNGSERKLÄRUNG' at the top, 'MC' on the left, 'CE' in the center, and 'MC' on the right. Below the stamp, the word 'DECLARATION OF PERFORMANCE' is written. A blue ink signature is written over the stamp. Below the signature, the word '(Unterschrift)' is printed.

Annex

According to Art. 6 (5) of the Regulation (EU) No. 305/2011 a Safety Data sheet according Regulation (EU) No. 1907/2006(REACH), Annex II is attached to this Declaration of Performance.