

## MC-Montan Grout 01

Reference number of the Declaration of Performance: 1548100

1. Unique ID code of the product type	MC-Montan Grout 01
2. Application(s)	Additive(s) / Admixture(s) for shotcrete – EN 934-5: T2
3. Manufacturer	MC-Bauchemie Müller GmbH & Co. KG Am Kruppwald 1-8 46238 Bottrop / Germany
4. Authorized representative	-
5. System of AVCP	System 2+ (for uses in buildings and civil engineering works)
6. Harmonised standard	EN 934-5 T2
7. Notified body	Institut für Massivbau und Baustofftechnologie Universität Karlsruhe (TH) ID code 0754

8. Declared performances


Essential characteristic	Performance	harmonised technical specification
Chloride content	max. 0.10% by mass	EN 934-1
Alkaline content	max. 12.0 % by mass	
Corrosion behaviour	Contains components only from EN 934-1 : 2008, Annex A.1	
Compressive strength	at 28 days: Test mix $\geq$ 75 % control mix at 90 days: Test mix $\geq$ test mix at 28 days	EN 934-5 Table 2
Hardening time	Start of hardening $\leq$ 10 min. End of hardening $\leq$ 60 min.	
Hazardous substances	Regulation (EC) No. 1907/2006, see safety data sheet	EGVO

The performance of the product identified above is in conformity with the set of declared performance/s. This Declaration of Performance is issued in accordance with Regulation (EU) No 305/2011 (amended by Commissions delegated Regulation (EU) No 574/2014), under the soleresponsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

John van Diemen  
Head of Research & Development and Quality

Bottrop, 13.10.2023  
(place and date of issue)

  
 (signature)

Annex

According to Art. 6 (5) of the Regulation (EU) No. 305/2011 a Safety Data sheet according Regulation (EU) No. 1907/2006(REACH), Annex II is attached to this Declaration of Performance.