## **Declaration of Performance**



## MC-PowerFlow 5105

Reference number of the Declaration of Performance: 1322000

| Unique ID code of the product type | MC-PowerFlow 5105                                                                                                |  |  |
|------------------------------------|------------------------------------------------------------------------------------------------------------------|--|--|
| Application(s)                     | High range water reducing admixtures/superplasticizing admixture for concrete - EN 934-2:T 3.1/3.2; EN 934-2: T2 |  |  |
| Manufacturer                       | MC-Bauchemie Müller GmbH & Co. KG<br>Am Kruppwald 1-8<br>46238 Bottrop / Germany                                 |  |  |
| Authorized representative          | -                                                                                                                |  |  |
| System of AVCP                     | System 2+ (for uses in buildings and civil engineering works)                                                    |  |  |
| Harmonised standard                | EN 934-2: 2009+A1: 2012                                                                                          |  |  |
| Notified body                      | Institut für Massivbau und Baustofftechnologie Universität Karlsruhe (TH) ID code 0754 EN 934-2 T3.1, T3.2; T2   |  |  |
|                                    | Application(s)  Manufacturer  Authorized representative  System of AVCP  Harmonised standard                     |  |  |

## Declared performances

| Essential characteristic                                              | Performance                                                                                                                            | AVCP        | harmonised technical specification         |
|-----------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------|-------------|--------------------------------------------|
| Chloride content                                                      | max. 0.10% by mass                                                                                                                     | - System 2+ | EN 934-1                                   |
| Alkaline content                                                      | max. 2.0 % by mass                                                                                                                     |             |                                            |
| Corrosion behaviour                                                   | Contains components only from EN 934-1 : 2008, Annex A.1                                                                               |             |                                            |
| Compressive strength                                                  | after 7 and 28 days: Test mix-<br>ture ≥ 110 % of the control<br>mixture                                                               | System 2+   | EN 934-2: 2009 + A1: 2012<br>Table 2       |
| Reduction in water requirement                                        | with test mixture ≥ 5 % in comparison with control mixture                                                                             |             |                                            |
| Air content of the fresh concrete with reduction in water requirement | Test mixture ≤ 2% by volume above the control mixture                                                                                  | System 2+   | EN 934-2: 2009 + A1: 2012<br>Table 2 + 3.1 |
| Compressive strength with reduction in water requirement              | at 1 day: ≥ 140 % of control mix at 28 days: test mix ≥ 115 % of control mix                                                           | System 2+   | EN 934-2: 2009 + A1: 2012<br>Table 3.1     |
| Reduction in water requirement                                        | with test mixture ≥ 12 % in comparison with control mixture                                                                            |             |                                            |
| Retention of consistency                                              | 30 min after the addition the consistence of the test mix shall not fall below the value of the initial consistence of the control mix | System 2+   | EN 934-2: 2009 + A1: 2012<br>Table 3.2     |
| Compressive strength with enhancement of consistency                  | after 28 days: Test mixture ≥ 85 % of the control mixture                                                                              |             |                                            |
| Enhancement of consistency                                            | Increase in flow ≥ 160 mm from initial (350 ± 20) mm                                                                                   |             |                                            |
| Air content of the fresh concrete with enhancement of consistency     | Test mixture ≤ 2 % by volume above the control mixture                                                                                 |             |                                            |
| Hazardous substances                                                  | Regulation (EC) No.<br>1907/2006, see safety data<br>sheet                                                                             | System 2+   | EGVO                                       |

The performance of the product identified above is in conformity with the set of declared performance/s. This Declaration of Performance is issued in accordance with Regulation (EU) No 305/2011 (amended by Commissions delegated Regulation (EU) No 574/2014), under the soleresponsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

John van Diemen Head of Research & Development and Quality



Bottrop, 13.10.2023 (place and date of issue)

Annex

According to Art. 6 (5) of the Regulation (EU) No. 305/2011 a Safety Data sheet according Regulation (EU) No. 1907/2006(REACH), Annex II is attached to this Declaration of Performance.