

MC-PowerFlow 5300

Reference number of the Declaration of Performance: 1317000

I believe ID and a of the sum doubt to me		
Unique ID code of the product type	MC-PowerFlow 5300	
Application(s)	High range water reducing admixtures/superplasticizing admixture for concrete - EN	
	934-2:T 3.1/3.2; EN 934-2: T2	
Manufacturer	MC-Bauchemie Müller GmbH & Co. KG	
	Am Kruppwald 1-8	
	46238 Bottrop / Germany	
Authorized representative	-	
System of AVCP	System 2+ (for uses in buildings and civil engineering works)	
	· · · · · · · · · · · · · · · · · · ·	
Harmonised standard	EN 934-2: 2009+A1: 2012	
	Institut für Massinkerungel Deusteffteskuslagis	
7. Notified body	Institut für Massivbau und Baustofftechnologie	
	Universität Karlsruhe (TH)	
	ID code 0754	
	EN 934-2 T3.1, T3.2; T2	
	Manufacturer Authorized representative System of AVCP	

8. Declared performances

Essential characteristic	Performance	AVCP	harmonised technical specification
Chloride content	max. 0.10% by mass	- System 2+	EN 934-1
Alkaline content	max. 2.0 % by mass		
Corrosion behaviour	Contains components only from EN 934-1 : 2008, Annex A.1		
Compressive strength	after 7 and 28 days: Test mix- ture \ge 110 % of the control mixture	System 2+	EN 934-2: 2009 + A1: 2012 Table 2
Reduction in water requirement	with test mixture ≥ 5 % in com- parison with control mixture		
Air content of the fresh concrete with reduction in water requirement	Test mixture ≤ 2% by volume above the control mixture	System 2+	EN 934-2: 2009 + A1: 2012 Table 2 + 3.1
Compressive strength with reduction in water requirement	at 1 day: ≥ 140 % of control mix at 28 days: test mix ≥ 115 % of control mix	System 2+	EN 934-2: 2009 + A1: 2012 Table 3.1
Reduction in water requirement	with test mixture ≥ 12 % in comparison with control mix- ture		
Retention of consistency	30 min after the addition the consistence of the test mix shall not fall below the value of the initial consistence of the control mix	System 2+	EN 934-2: 2009 + A1: 2012 Table 3.2
Compressive strength with enhancement of consistency	after 28 days: Test mixture ≥ 85 % of the control mixture		
Enhancement of consistency	Increase in flow ≥ 160 mm from initial (350 ± 20) mm		
Air content of the fresh concrete with enhance- ment of consistency	Test mixture $\leq 2 \%$ by volume above the control mixture		
Hazardous substances	Regulation (EC) No. 1907/2006, see safety data sheet	System 2+	EGVO

The performance of the product identified above is in conformity with the set of declared performance/s. This Declaration of Performance is issued in accordance with Regulation (EU) No 305/2011 (amended by Commissions delegated Regulation (EU) No 574/2014), under the soleresponsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

John van Diemen Head of Research & Development and Quality



Bottrop, 13.10.2023 (place and date of issue)

Annex

According to Art. 6 (5) of the Regulation (EU) No. 305/2011 a Safety Data sheet according Regulation (EU) No. 1907/2006(REACH), Annex II is attached to this Declaration of Performance.