

Mycoflex 450 VE

Reference number of the Declaration of Performance: IN9255090

| 1. | Unique ID code of the product type | Mycoflex 450 VE | |
|----|------------------------------------|---|--|
| 2. | Application(s) | Sealant for facade for interior and exterior application (intended for use in cold climates) Sealant for movement joints in floors for interior and exterior application (intended for use in cold climates) | |
| 3. | Manufacturer | MC-Bauchemie Müller GmbH & Co. KG Am Kruppwald 1-8 46238 Bottrop / Germany | |
| 4. | Authorized representative | - | |
| 5. | System of AVCP | System 3 System 3 (for fire behaviour only) | |
| 6. | Harmonised standard | DIN EN 15651-1: 2012 DIN EN 15651-4: 2012 | |
| 7. | Notified body | Institut für Massivbau und Baustofftechnologie Universität Karlsruhe (TH) ID code 0754 | |

8. Declared performances

| Essential characteristic | Performance | harmonised technical specification | |
|--|---|------------------------------------|--|
| Stability | not required | | |
| Loss of volume | ≤ 10 % | DIN EN 15651-1: 2012 | |
| Tensile behaviour for non-bearing sealants with high modulus | not required | | |
| Tensile behaviour (i.e. under preload) | passed | | |
| Tensile behaviour (i.e. elongation behaviour) after prestressing after immersion in water | passed | | |
| Durability | passed | _ | |
| Release of chemicals dangerous to the envi- ronment and health | not required | | |
| Fire behaviour | E | | |
| Tensile behaviour (i.e. under preload) | passed | - | |
| Loss of volume | ≤ 10 % | | |
| Ultimate fracture strength | passed | | |
| Adhesion/stretching behaviour under preload after 28-day water storage | passed | - | |
| Adhesion/stretching behaviour under preload after 28-day salt water storage | passed | | |
| Tensile properties (i.e. secant modulus) at -30°C | (i.e. secant modulus) at passed DIN EN 15651-4: | | |
| Tensile behaviour under preload at -30°C | passed | | |
| Durability | passed | | |
| Release of chemicals dangerous to the envi- ronment and health | not required | - | |
| Fire behaviour | E | | |

The performance of the product identified above is in conformity with the set of declared performance/s. This Declaration of Performance is issued in accordance with Regulation (EU) No 305/2011 (amended by Commissions delegated Regulation (EU) No 574/2014), under the soleresponsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

John van Diemen Head of Research & Development and Quality



Bottrop, 13.10.2023 (place and date of issue)

Annex

According to Art. 6 (5) of the Regulation (EU) No. 305/2011 a Safety Data sheet according Regulation (EU) No. 1907/2006(REACH), Annex II is attached to this Declaration of Performance.