

Nafuflex Easy Tech 1

Reference number of the Declaration of Performance: CC3354091

1. Unique ID code of the product type	Nafuflex 2K-05
2. Application(s)	-
3. Manufacturer	MC-Bauchemie Müller GmbH & Co. KG Am Kruppwald 1-8 46238 Bottrop / Germany
4. Authorized representative	-
5. System of AVCP	System 3 (for fire behaviour only)
6. Harmonised standard	EN 15814: 2012
7. Notified body	MPA NRW ID code 0432

8. Declared performances


Essential characteristic	Performance	harmonised technical specification
Water impermeability	class W2A	EN 15814: 2012
Crack-bridging capacity	CB2	
Resistance to water	no colouration of the water, no debonding from inlay	
Flexibility at low temperatures	no cracks	
Dimensional stability at high temperatures	no sliding or draining down	
Compressive strength	C2A	
Durability of watertightness and reaction to fire	passed	
Fire behaviour	E	

The performance of the product identified above is in conformity with the set of declared performance/s. This Declaration of Performance is issued in accordance with Regulation (EU) No 305/2011 (amended by Commissions delegated Regulation (EU) No 574/2014), under the soleresponsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

John van Diemen
Head of Research & Development and Quality

Bottrop, 13.10.2023
(place and date of issue)



(signature)

Annex

According to Art. 6 (5) of the Regulation (EU) No. 305/2011 a Safety Data sheet according Regulation (EU) No. 1907/2006(REACH), Annex II is attached to this Declaration of Performance.