

Oxal VSM WTA

Reference number of the Declaration of Performance: IN0076420

1. Unique ID code of the product type	Oxal VSM WTA
2. Application(s)	WTA-spatter coat according to WTA restoration render system
3. Manufacturer	MC-Bauchemie Müller GmbH & Co. KG Am Kruppwald 1-8 46238 Bottrop / Germany
4. Authorized representative	MC-Bauchemie Müller GmbH & Co. KG Am Kruppwald 1-8 46238 Bottrop / Germany
5. System of AVCP	System 4
6. Harmonised standard	DIN EN 988-1: 2010
7. Notified body	-

8. Declared performances


Essential characteristic	Performance	AVCP	harmonised technical specification
Water absorption	W0	System 4	DIN EN 998-1: 2010
Water vapour permeability	$\mu = 15/35$		
Tensile strength	$\geq 0.08 \text{ N/mm}^2$ Fracture appearance A, B or C		
Thermal conductivity	$< 1.11 \text{ W/m} \times \text{K}$ for P=50 % $\leq 1.21 \text{ W/m} \times \text{K}$ for P=90 % (tabular value to EN 1745)		
Fire behaviour	A1		

The performance of the product identified above is in conformity with the set of declared performance/s. This Declaration of Performance is issued in accordance with Regulation (EU) No 305/2011 (amended by Commissions delegated Regulation (EU) No 574/2014), under the soleresponsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

John van Diemen
Head of Research & Development and Quality

Bottrop, 13.10.2023
(place and date of issue)



 (signature)



Annex

According to Art. 6 (5) of the Regulation (EU) No. 305/2011 a Safety Data sheet according Regulation (EU) No. 1907/2006(REACH), Annex II is attached to this Declaration of Performance.