

Declaration of Performance



Oxal WPw WTA

Reference number of the Declaration of Performance: IN0076419

1. Unique ID code of the product type	Oxal WPw WTA
2. Application(s)	Part 1: Cladding joint sealants (suitable for use in cold climates) Resistance to chemicals (6.1)
3. Manufacturer	MC-Bauchemie Müller GmbH & Co. KG Am Kruppwald 1-8 46238 Bottrop / Germany
4. Authorized representative	MC-Bauchemie Müller GmbH & Co. KG Am Kruppwald 1-8 46238 Bottrop / Germany
5. System of AVCP	System 4
6. Harmonised standard	DIN EN 988-1: 2010
7. Notified body	-

8. Declared performances


Essential characteristic	Performance	AVCP	harmonised technical specification
Water absorption	0.3 kg/m ² after 24 h	System 4	DIN EN 998-1: 2010
Water vapour permeability	$\mu \leq 15$		
Water penetration after water absorption test	≥ 5 mm		
Tensile strength	≥ 0.08 N/mm ² Fracture appearance A, B or C		
Thermal conductivity	≤ 0.33 W/m x K for P=50 % ≤ 0.36 W/m x K for P=90 % (tabular value to EN 1745)		
Fire behaviour	A1		

The performance of the product identified above is in conformity with the set of declared performance/s. This Declaration of Performance is issued in accordance with Regulation (EU) No 305/2011 (amended by Commissions delegated Regulation (EU) No 574/2014), under the soleresponsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

John van Diemen
Head of Research & Development and Quality

Bottrop, 13.10.2023
(place and date of issue)



(signature)



Annex

According to Art. 6 (5) of the Regulation (EU) No. 305/2011 a Safety Data sheet according Regulation (EU) No. 1907/2006(REACH), Annex II is attached to this Declaration of Performance.