

## MC-DUR VS PUR

Reference number of the Declaration of Performance: IN5431732

1. Unique ID code of the product type	MC-DUR VS PUR
2. Application(s)	Surface protection products – Coating Protection against ingress (1.3) Moisture control (2.2) Increasing resistivity (8.2) Synthetic resin screed for internal uses
3. Manufacturer	MC-Bauchemie Müller GmbH & Co. KG Am Kruppwald 1-8 46238 Bottrop / Germany
4. Authorized representative	-
5. System of AVCP	System 2+ (for uses in buildings and civil engineering works) System 4
6. Harmonised standard	EN 13813: 2002 EN 1504-2: 2004
7. Notified body	Institut für Massivbau und Baustofftechnologie Universität Karlsruhe (TH) ID code 0754

8. Declared performances


Essential characteristic	Performance	harmonised technical specification
CO2 permeability	sD > 50 m	EN 1504-2: 2004
Water vapour permeability	class II	
Capillary water absorption	w < 0,1 kg/m <sup>2</sup> x h <sup>0,5</sup>	
Tear-off test to determine adhesive strength	≥ 1,0 (0,7) 1) N/mm <sup>2</sup>	
Fire behaviour	class E <sub>fl</sub>	
Hazardous substances	EN 1504-2, Pkt. 5.3	
Fire behaviour	E <sub>fl</sub> a)	EN 13813: 2017-03
Release of corrosive substances	SR	
Impact strength	IR4	
Tensile strength	B1,5	
Wear resistance	AR1	

The performance of the product identified above is in conformity with the set of declared performance/s. This Declaration of Performance is issued in accordance with Regulation (EU) No 305/2011 (amended by Commissions delegated Regulation (EU) No 574/2014), under the soleresponsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

van Diemen  
Head of research and development and quality control

Bottrop, 10.07.2021  
(place and date of issue)



(Unterschrift)

Annex

According to Art. 6 (5) of the Regulation (EU) No. 305/2011 a Safety Data sheet according Regulation (EU) No. 1907/2006(REACH), Annex II is attached to this Declaration of Performance.