

MC-Estribond MB

Reference number of the Declaration of Performance: CC18500

1. Unique ID code of the product type	MC-Estribond MB
2. Application(s)	
3. Manufacturer	MC-Bauchemie Müller GmbH & Co. KG Am Kruppwald 1-8 46238 Bottrop / Germany
4. Authorized representative	-
5. System of AVCP	System 2+ (for uses in buildings and civil engineering works)
6. Harmonised standard	-
7. Notified body	Institut für Massivbau und Baustofftechnologie Universität Karlsruhe (TH) ID code 0754

8. Declared performances


Essential characteristic	Performance	harmonised technical specification
Compressive strength	≥ 15 MPa	EN 1504-3: 2005
Thermal shock tolerance Part 1	$\geq 0,8$ MPa	
Capillary water absorption	$\leq 0,5$ kg · m ⁻² · h ^{-0,5}	
Fire behaviour	Class A1	

The performance of the product identified above is in conformity with the set of declared performance/s. This Declaration of Performance is issued in accordance with Regulation (EU) No 305/2011 (amended by Commissions delegated Regulation (EU) No 574/2014), under the soleresponsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

van Diemen
Head of research and development and quality control

Bottrop, 28.05.2021
(place and date of issue)



(Unterschrift)

Annex

According to Art. 6 (5) of the Regulation (EU) No. 305/2011 a Safety Data sheet according Regulation (EU) No. 1907/2006(REACH), Annex II is attached to this Declaration of Performance.