

DECLARATION OF PERFORMANCE

according Annex III of the Regulation (EU) No 305/2011
amended by Commissions delegated Regulation (EU) No 574/2014

**Reference number of the
declaration of performance:** IN4445000

Unique identification code of the product-type: Nafufill SF

Intended use: **Product for non-structural repair for concrete**
Applying mortar by hand (3.1)
Spraying concrete or mortar (3.3)

Manufacturer: MC-Bauchemie Müller GmbH & Co.KG
Am Kruppwald 1-8
46238 Bottrop

System of AVCP: System 2+ (for uses in buildings and civil engineering works)

Harmonised standard: EN 1504-3:2005

Notified body: Institut für Massivbau und Baustofftechnologie
Universität Karlsruhe (TH)
Identification no: 0754

Declared performances:

Essential characteristics	Performance	System of assessment and verification of constancy of performance	Harmonised Technical specification
Compressive strength	class R1	System 2+	EN 1504-3:2005
Chloride ion content	≤ 0.05 %		
Adhesive bond	≥ 0.8 MPa		
Restrained shrinkage/expansion	≥ 0.8 MPa		
Carbonation resistance ¹⁾	NPD		
Reaction to fire	class A1		
Dangerous substances	EN 1504-3, Pkt. 5.4		

¹⁾ Not required if the repair product includes a surface protection system with proven protection against carbonation (EN 1504-2) or is a PC mortar

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Dr. Hans-Günter Seltmann
Head of research and development and quality control



Bottrop, 29.03.2016
(place and date of issue)

.....
(signature)

Annex

According to Art. 6 (5) of the Regulation (EU) No. 305/2011 a Safety Data sheet according Regulation (EU) No. 1907/2006 (REACH), Annex II is attached to this Declaration of Performance.