

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 29.12.2022

Version number 14 (replaces version 13)

Revision: 29.12.2022

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

· **1.1 Product identifier**

· **Trade name** **Colusal SP - Komponente A**

· **Article number:** 2888

· **1.2 Relevant identified uses of the substance or mixture and uses advised against**

No further relevant information available.

· **Application of the substance / the mixture**

Coating  
Epoxy coating

· **1.3 Details of the supplier of the safety data sheet**

· **Informing department:** msds@mc-bauchemie.de

· **1.4 Emergency telephone number:**

Tel.: +49 / (0)700 24112112 (MCR)  
Tel.: +48612864565

### SECTION 2: Hazards identification

· **2.1 Classification of the substance or mixture**

· **Classification according to Regulation (EC) No 1272/2008**

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

· **2.2 Label elements**

· **Labelling according to**

**Regulation (EC) No 1272/2008** The product is classified and labelled according to the GB CLP regulation.

· **Hazard pictograms**



GHS07 GHS09

· **Signal word**

Warning

· **Hazard-determining components of labelling:**

epoxide derivates  
2,2'-[methylenebis(p-phenyleneoxymethylene)]bisoxirane polymers and homologues, molecular weight < 700  
1,6-hexene-diglycidylether  
N,N'-ethane-1,2-diylbis(12-hydroxyoctadecan-1-amide)

· **Hazard statements**

H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H317 May cause an allergic skin reaction.  
H411 Toxic to aquatic life with long lasting effects.

· **Precautionary statements**

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.  
P273 Avoid release to the environment.  
P280 Wear protective gloves / eye protection / face protection.  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.  
P337+P313 If eye irritation persists: Get medical advice/attention.

(Contd. on page 2)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 29.12.2022

Version number 14 (replaces version 13)

Revision: 29.12.2022

### Trade name Colusal SP - Komponente A

(Contd. of page 1)

- **Additional information:** Contains epoxy constituents. May produce an allergic reaction.  
Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

## SECTION 3: Composition/information on ingredients

- **3.2 Mixtures**
- **Description:** Resin mixture with colouring agents.  
Mixture consisting of the following components.

- **Dangerous components:**

CAS: 1675-54-3 EINECS: 216-823-5	epoxide derivates Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	≥10-<25%
CAS: 9003-36-5 NLP: 500-006-8	2,2'-[methylenebis(p-phenyleneoxymethylene)]bisoxirane polymers and homologues, molecular weight < 700 Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317, EUH205	≥10-<25%
CAS: 16096-31-4 EINECS: 240-260-4	1,6-hexene-diglycidylether Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; Aquatic Chronic 3, H412, EUH205	≥2.5-<10%
CAS: 13463-67-7 EINECS: 236-675-5	titanium dioxide Carc. 2, H351	≥0.1-<5%
CAS: 64742-94-5 EINECS: 265-198-5	Solvent naphtha (petroleum), heavy arom. Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H336	≥2.5-<5%
CAS: 107-98-2 EINECS: 203-539-1	1-methoxypropan-2-ol Flam. Liq. 3, H226; STOT SE 3, H336	<3%
CAS: 1633-05-2 EINECS: 216-643-7	strontium carbonate Eye Irrit. 2, H319	<2.5%
CAS: 100-51-6 EINECS: 202-859-9	Benzyl alcohol Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332	<2.5%
CAS: 2530-83-8 EINECS: 219-784-2	[3-(2,3-epoxypropoxy)propyl]trimethoxysilane Eye Dam. 1, H318	≥1-<1.5%
CAS: 123-26-2	N,N'-ethane-1,2-diylbis(12-hydroxyoctadecan-1-amide) Skin Sens. 1, H317; Aquatic Chronic 3, H412	≥0.1-<0.5%

- **Additional information** For the wording of the listed hazard phrases refer to section 16.

## SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **After inhalation** Supply fresh air.
- **After skin contact** Instantly wash with water and soap and rinse thoroughly.
- **After eye contact** Rinse opened eye for several minutes under running water.  
Seek medical treatment.
- **After swallowing** Rinse out mouth and then drink plenty of water.  
Seek medical treatment.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.

(Contd. on page 3)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 29.12.2022

Version number 14 (replaces version 13)

Revision: 29.12.2022

Trade name Colusal SP - Komponente A

(Contd. of page 2)

- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

### SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents** Use fire fighting measures that suit the environment.
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** No special measures required.

### SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures** Not required.
- **6.2 Environmental precautions:** Prevent material from reaching sewage system, holes and cellars.
- **6.3 Methods and material for containment and cleaning up:** Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
- **6.4 Reference to other sections** See Section 7 for information on safe handling  
See Section 8 for information on personal protection equipment.  
See Section 13 for information on disposal.

### SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Store in cool, dry place in tightly closed containers.  
Open and handle container with care.
- **Information about protection against explosions and fires:** No special measures required.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage**
- **Requirements to be met by storerooms and containers:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep container tightly sealed.
- **7.3 Specific end use(s)** No further relevant information available.

### SECTION 8: Exposure controls/personal protection

- **8.1 Control parameters**

- **Components with critical values that require monitoring at the workplace:**

107-98-2 1-methoxypropan-2-ol

WEL	Short-term value: 560 mg/m <sup>3</sup> , 150 ppm
	Long-term value: 375 mg/m <sup>3</sup> , 100 ppm
Sk	

(Contd. on page 4)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 29.12.2022

Version number 14 (replaces version 13)

Revision: 29.12.2022

### Trade name Colusal SP - Komponente A

(Contd. of page 3)

#### · DNELs

##### 16096-31-4 1,6-hexene-diglycidylether

Dermal DNEL 2.8 mg/kg bw/day (ArL)

Inhalative DNEL 4.9 mg/m<sup>3</sup> (ArL)

##### 107-98-2 1-methoxypropan-2-ol

Oral DNEL 3.3 mg/kg bw/Tag (ArL)

Dermal DNEL 50.6 mg/kg bw/day (ArL)

Inhalative DNEL 369 mg/m<sup>3</sup> (ArL)

##### 100-51-6 Benzyl alcohol

Oral DNEL 4 mg/kg bw/Tag (ArL)

20 mg/kg bw/Tag (Ark)

Dermal DNEL 8 mg/kg bw/day (ArL)

40 mg/kg bw/day (Ark)

Inhalative DNEL 22 mg/m<sup>3</sup> (ArL)110 mg/m<sup>3</sup> (Ark)

#### · PNECs

##### 16096-31-4 1,6-hexene-diglycidylether

PNEC 0.0115 mg/l (Fresh water)

0.00115 mg/l (Mew)

PNEC 0.223 mg/kg dwt (Bod)

0.0283 mg/kg dwt (Sediment)

0.283 mg/kg dwt (Fresh water sediment)

##### 100-51-6 Benzyl alcohol

PNEC 0.527 mg/l (Marine water sediment)

0.1 mg/l (Mew)

1 mg/l (Fresh water sediment)

PNEC 0.456 mg/kg dwt (Bod)

5.27 mg/kg dwt (Fresh water sediment)

· **Additional information:** The lists that were valid during the compilation were used as basis.

#### · 8.2 Exposure controls

##### · Appropriate engineering controls

No further data; see item 7.

##### · Individual protection measures, such as personal protective equipment

##### · General protective and hygienic measures

Keep away from foodstuffs, beverages and food.  
Instantly remove any soiled and impregnated garments.  
Wash hands during breaks and at the end of the work.  
Avoid contact with the eyes and skin.

##### · Hand protection

Protective gloves.  
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

##### · Material of gloves

After use of gloves apply skin-cleaning agents and skin cosmetics.  
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

##### · Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 29.12.2022

Version number 14 (replaces version 13)

Revision: 29.12.2022

**Trade name Colusal SP - Komponente A**

(Contd. of page 4)

- **Eye/face protection**                  Safety glasses
- **Body protection:**                      Tightly sealed safety glasses.
- Protective work clothing.

### SECTION 9: Physical and chemical properties

#### · 9.1 Information on basic physical and chemical properties

##### · General Information

- |   |                                  |
|---|----------------------------------|
| · <b>Colour:</b>  | Pigmented                        |
| · <b>Smell:</b>   | Characteristic                   |
| · <b>Melting point/freezing point:</b>                            | Not determined                   |
| · <b>Boiling point or initial boiling point and boiling range</b> | 200 °C                           |
| · <b>Flash point:</b>   | 120 °C                           |
| · <b>Ignition temperature:</b>                                    | 184 °C                           |
| · <b>Viscosity:</b>   |                                  |
| · <b>dynamic at 20 °C:</b>  | 9000 mPas                        |
| · <b>Solubility</b>   |                                  |
| · <b>Water:</b>   | Not miscible or difficult to mix |
| · <b>Steam pressure at 20 °C:</b>                                 | 0.1 hPa                          |
| · <b>Density and/or relative density</b>                          |                                  |
| · <b>Density at 20 °C</b>   | 1.5 g/cm <sup>3</sup>            |

#### · 9.2 Other information

- **Appearance:**
- **Form:** Fluid
- **Important information on protection of health and environment, and on safety.**
- **Self-inflammability:** Product is not selfigniting.
- **Explosive properties:** Product is not explosive.

#### · Information with regard to physical hazard classes

- |  |      |
|--|------|
| · <b>Explosives</b>  | Void |
| · <b>Flammable gases</b>   | Void |
| · <b>Aerosols</b>  | Void |
| · <b>Oxidising gases</b>   | Void |
| · <b>Gases under pressure</b>  | Void |
| · <b>Flammable liquids</b>   | Void |
| · <b>Flammable solids</b>  | Void |
| · <b>Self-reactive substances and mixtures</b>                                     | Void |
| · <b>Pyrophoric liquids</b>  | Void |
| · <b>Pyrophoric solids</b>   | Void |
| · <b>Self-heating substances and mixtures</b>                                      | Void |
| · <b>Substances and mixtures, which emit flammable gases in contact with water</b> | Void |
| · <b>Oxidising liquids</b>   | Void |
| · <b>Oxidising solids</b>  | Void |
| · <b>Organic peroxides</b>   | Void |
| · <b>Corrosive to metals</b>   | Void |
| · <b>Desensitised explosives</b>   | Void |

GB

(Contd. on page 6)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 29.12.2022

Version number 14 (replaces version 13)

Revision: 29.12.2022

Trade name Colusal SP - Komponente A

(Contd. of page 5)

### SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known

### SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

- **LD/LC50 values that are relevant for classification:**

#### 1675-54-3 epoxide derivates

Dermal	LD50	23000 mg/kg (rabbit)
--------	------	----------------------

#### 9003-36-5 2,2'-[methylenebis(p-phenyleneoxymethylene)]bisoxirane polymers and homologues, molecular weight < 700

Oral	LD50	>2000 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rabbit)

#### 16096-31-4 1,6-hexene-diglycidylether

Oral	LD50	>8500 mg/kg (rat)
Dermal	LD50	>4900 mg/kg (rat)

#### 13463-67-7 titanium dioxide

Oral	LD50	>10000 mg/kg (rat)
Dermal	LD50	>10000 mg/kg (rabbit)
Inhalative	LC50/4 h	>6.8 mg/l (rat)

#### 64742-94-5 Solvent naphtha (petroleum), heavy arom.

Oral	LD50	>5000 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rabbit)
Inhalative	LC50/4 h	>4688 mg/l (rat)

#### 107-98-2 1-methoxypropan-2-ol

Oral	LD50	4016 mg/kg (rat)
Dermal	LD50	13000 mg/kg (rbt)
Inhalative	LC50/4 h	54.6 mg/l (rat)

#### 100-51-6 Benzyl alcohol

Oral	LD50	1230 mg/kg (rat)
	NOAEL 2nd year study	200 mg/kg (mouse)
		200 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rabbit)
Inhalative	LC50/4 h	>4178 mg/l (rat)

#### 2530-83-8 [3-(2,3-epoxypropoxy)propyl]trimethoxysilane

Oral	LD50	8030 mg/kg (rat)
Dermal	LD50	4248 mg/kg (rabbit)

- **Skin corrosion/irritation** Causes skin irritation.
- **Serious eye damage/irritation** Causes serious eye irritation.

(Contd. on page 7)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 29.12.2022

Version number 14 (replaces version 13)

Revision: 29.12.2022

### Trade name Colusal SP - Komponente A

(Contd. of page 6)

- **Respiratory or skin sensitisation** *May cause an allergic skin reaction.*
- **Germ cell mutagenicity** *Based on available data, the classification criteria are not met.*
- **Carcinogenicity** *Based on available data, the classification criteria are not met.*
- **Reproductive toxicity** *Based on available data, the classification criteria are not met.*
- **STOT-single exposure** *Based on available data, the classification criteria are not met.*
- **STOT-repeated exposure** *Based on available data, the classification criteria are not met.*
- **Aspiration hazard** *Based on available data, the classification criteria are not met.*
- **11.2 Information on other hazards**

- **Endocrine disrupting properties**

128-37-0 Butylated hydroxytoluene

List II

## SECTION 12: Ecological information

- **12.1 Toxicity**

- **Aquatic toxicity:**

#### 1675-54-3 epoxide derivates

IC50	>42.6 mg/l (Bak)
LC50/96h	2 mg/l (Oncorhynchus mykiss)
EC50/48h	1.8 mg/l (Daphnia magna)
ErC50/72h	11 mg/l (Selenastrum capricornutum)

#### 9003-36-5 2,2'-[methylenebis(p-phenyleneoxymethylene)]bisoxirane polymers and homologues, molecular weight < 700

LC50/96h	>100 mg/l (Daphnia magna)
EC50/96h	>100 mg/l (Leucidus idus)

#### 16096-31-4 1,6-hexene-diglycidylether

LC50/96h	30 mg/l (Leucidus idus)
EC50/48h	47 mg/l (Daphnia magna)

#### 107-98-2 1-methoxypropan-2-ol

IC50	1000 mg/l (BEL)
LC50/96h	6812 mg/l (Leucidus idus)
LC50/48h	23300 mg/l (Daphnia magna)
EC50/48h	23300 mg/l (Daphnia magna)

#### 100-51-6 Benzyl alcohol

IC50/72h	700 mg/l (algae)
LC50/96h	460 mg/l (Pimephales promelas)
	10 mg/l (Lepomis macrochirus)

#### 2530-83-8 [3-(2,3-epoxypropoxy)propyl]trimethoxysilane

LC50/96h	55 mg/l (Cyp)
EC50/48h	473 mg/l (Daphnia magna)
ErC50/72h	255 mg/l (Scenedesmus subspicatus)

- **12.2 Persistence and degradability**

*No further relevant information available.*

- **12.3 Bioaccumulative potential**

*No further relevant information available.*

- **12.4 Mobility in soil**

*No further relevant information available.*

- **12.5 Results of PBT and vPvB assessment**

- **PBT:**

*Not applicable.*

- **vPvB:**

*Not applicable.*

- **12.6 Endocrine disrupting properties**

*For information on endocrine disrupting properties see section 11.*

(Contd. on page 8)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 29.12.2022

Version number 14 (replaces version 13)

Revision: 29.12.2022

Trade name Colusal SP - Komponente A

(Contd. of page 7)

- **12.7 Other adverse effects**
- **Additional ecological information:**
- **General notes:** Do not allow product to reach ground water, water bodies or sewage system.  
Danger to drinking water if even small quantities leak into soil.

### SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation** Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Empty contaminated packagings thoroughly. They can be recycled after thorough and proper cleaning.

### SECTION 14: Transport information

- |   |   |
|---|---|
| <ul style="list-style-type: none"> <li>· <b>14.1 UN number or ID number</b></li> <li>· <b>ADR, IMDG, IATA</b></li> </ul>  | UN3082  |
| <ul style="list-style-type: none"> <li>· <b>14.2 UN proper shipping name</b></li> <li>· <b>ADR, IATA</b></li> <li>· <b>IMDG</b></li> </ul>  | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (epoxide derivates)<br>ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (epoxide derivates),<br>MARINE POLLUTANT |
| <ul style="list-style-type: none"> <li>· <b>14.3 Transport hazard class(es)</b></li> <li>· <b>ADR</b></li> <li>· <b>Class</b></li> <li>· <b>Label</b></li> </ul>  | 9 (M6) Miscellaneous dangerous substances and articles.<br>9  |
| <ul style="list-style-type: none"> <li>· <b>IMDG, IATA</b></li> <li>· <b>Class</b></li> <li>· <b>Label</b></li> </ul>   | 9 Miscellaneous dangerous substances and articles.<br>9   |
| <ul style="list-style-type: none"> <li>· <b>14.4 Packing group</b></li> <li>· <b>ADR, IMDG, IATA</b></li> </ul>   | III   |
| <ul style="list-style-type: none"> <li>· <b>14.5 Environmental hazards:</b></li> <li>· <b>Marine pollutant:</b></li> <li>· <b>Special marking (ADR):</b></li> <li>· <b>Special marking (IATA):</b></li> </ul> | Product contains environmentally hazardous substances: epoxide derivates<br>Yes<br>Symbol (fish and tree)<br>Symbol (fish and tree)<br>Symbol (fish and tree)           |
| <ul style="list-style-type: none"> <li>· <b>14.6 Special precautions for user</b></li> <li>· <b>Kemler Number:</b></li> <li>· <b>EMS Number:</b></li> <li>· <b>Stowage Category</b></li> </ul>                | Warning: Miscellaneous dangerous substances and articles.<br>90<br>F-A, S-F<br>A  |
| <ul style="list-style-type: none"> <li>· <b>14.7 Maritime transport in bulk according to IMO instruments</b></li> </ul>   | Not applicable.   |

(Contd. on page 9)



# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 29.12.2022

Version number 14 (replaces version 13)

Revision: 29.12.2022

Trade name Colusal SP - Komponente A

(Contd. of page 8)

· **Transport/Additional information:**

· **ADR**

- Limited quantities (LQ)
- Excepted quantities (EQ)

5L

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

- Transport category

3

- Tunnel restriction code

(-)

· **IMDG**

- Limited quantities (LQ)
- Excepted quantities (EQ)

5L

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

- **UN "Model Regulation":**

UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXIDE DERIVATES), 9, III

### SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

- Directive 2012/18/EU

- Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t

- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t

- **15.2 Chemical safety assessment:**

A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H336 May cause drowsiness or dizziness.

H351 Suspected of causing cancer.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

EUH205 Contains epoxy constituents. May produce an allergic reaction.

- **Department issuing data specification sheet:**

Environment protection department.

(Contd. on page 10)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 29.12.2022

Version number 14 (replaces version 13)

Revision: 29.12.2022

### Trade name Colusal SP - Komponente A

(Contd. of page 9)

- Abbreviations and acronyms:** RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)  
 ICAO: International Civil Aviation Organisation  
 ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)  
 IMDG: International Maritime Code for Dangerous Goods  
 IATA: International Air Transport Association  
 GHS: Globally Harmonised System of Classification and Labelling of Chemicals  
 EINECS: European Inventory of Existing Commercial Chemical Substances  
 ELINCS: European List of Notified Chemical Substances  
 CAS: Chemical Abstracts Service (division of the American Chemical Society)  
 DNEL: Derived No-Effect Level (UK REACH)  
 PNEC: Predicted No-Effect Concentration (UK REACH)  
 LC50: Lethal concentration, 50 percent  
 LD50: Lethal dose, 50 percent  
 PBT: Persistent, Bioaccumulative and Toxic  
 vPvB: very Persistent and very Bioaccumulative  
 Flam. Liq. 3: Flammable liquids – Category 3  
 Acute Tox. 4: Acute toxicity – Category 4  
 Skin Irrit. 2: Skin corrosion/irritation – Category 2  
 Eye Dam. 1: Serious eye damage/eye irritation – Category 1  
 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2  
 Skin Sens. 1: Skin sensitisation – Category 1  
 Carc. 2: Carcinogenicity – Category 2  
 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3  
 Asp. Tox. 1: Aspiration hazard – Category 1  
 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2  
 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

- \* Data compared to the previous version altered.**