



BE SURE. BUILD SURE.

Page 1/14

Safety data sheet according to UK REACH

Printing date 10.12.2024

Version number 44 (replaces version 43)

Revision: 07.12.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· **1.1 Product identifier**

· **Trade name** Konudur 160 PL-XL - Komponente B

· **Article number:** 912

· **1.2 Relevant identified uses of the substance or mixture and uses advised against**

No further relevant information available.

· **Application of the substance / the mixture**

Epoxy sealing
Hardening agent/ Curing agent

· **1.3 Details of the supplier of the safety data sheet**

· **Manufacturer/Supplier:** MC-Bauchemie Müller GmbH & Co. KG
Am Kruppwald 1-8
D-46238 Bottrop
Tel.: +49(0)2041-101-0
Fax.: +49(0)2041-101-400
E-Mail: info@mc-bauchemie.de

MC-Bauchemie AG
Hagackerstr. 10
CH-8953 Dietikon
Tel.: +44-7400510
Fax : +44-7400533

· **Informing department:** msds@mc-bauchemie.de

· **1.4 Emergency telephone number:**

Tel.: +49 / (0)700 24112112 (MCR)
Tel.: +1 872 5888271 (MCR)

SECTION 2: Hazards identification

· **2.1 Classification of the substance or mixture**

· **Classification according to Regulation (EC) No 1272/2008**

Acute Tox. 4 H302 Harmful if swallowed.
Skin Corr. 1A H314 Causes severe skin burns and eye damage.
Eye Dam. 1 H318 Causes serious eye damage.
Skin Sens. 1 H317 May cause an allergic skin reaction.
Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

· **2.2 Label elements**

· **Labelling according to**

Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation.

· **Hazard pictograms**



GHS05 GHS07 GHS09

(Contd. on page 2)

GB



BE SURE. BUILD SURE.

Safety data sheet according to UK REACH

Printing date 10.12.2024

Version number 44 (replaces version 43)

Revision: 07.12.2024

Trade name Konudur 160 PL-XL - Komponente B

(Contd. of page 1)

- **Signal word** Danger
- **Hazard-determining components of labelling:** *Isophorone diamine
polymer amine terminated
Fettsäuren, Tallöl-, Reaktionsprodukte mit Triethylentetramin
Polyoxypropylene triamine
Hydrocarbons, C9-unsaturated, polymerised
2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine
Triethylenetetramine
2,4,6-Tris-(1-Phenyl-Ethyl) carboic acid*
- **Hazard statements** *H302 Harmful if swallowed.
H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.
H411 Toxic to aquatic life with long lasting effects.*
- **Precautionary statements** *P260 Do not breathe dusts or mists.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a POISON CENTER/doctor.
P321 Specific treatment (see on this label).
P362+P364 Take off contaminated clothing and wash it before reuse.*
- **Additional information:** *EUH401 To avoid risks to human health and the environment, comply with the instructions for use.*
- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** *Not applicable.*
- **vPvB:** *Not applicable.*

SECTION 3: Composition/information on ingredients

- **3.2 Mixtures**
- **Description:** *Mixture consisting of the following components.*

· **Dangerous components:**

CAS: 2855-13-2 EINECS: 220-666-8 Reg.nr.: 01-2119514687-32	<i>Isophorone diamine</i> <i>Skin Corr. 1B, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1, H317; Aquatic Chronic 3, H412</i> <i>Specific concentration limit:</i> <i>Skin Sens. 1A; H317: C ≥0.001 %</i>	30-60%
EC number: 949-140-2	<i>polymer amine terminated</i> <i>Eye Dam. 1, H318; Skin Irrit. 2, H315; Skin Sens. 1B, H317</i>	10-30%

(Contd. on page 3)



BE SURE. BUILD SURE.

Page 3/14

Safety data sheet according to UK REACH

Printing date 10.12.2024

Version number 44 (replaces version 43)

Revision: 07.12.2024

Trade name Konudur 160 PL-XL - Komponente B

(Contd. of page 2)

CAS: 1226892-44-9 Reg.nr.: 01-2119490750-36	Fettsäuren, Tallöl-, Reaktionsprodukte mit Triethylentetramin Skin Corr. 1C, H314; Eye Dam. 1, H318; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Sens. 1, H317	≥10-<25%
CAS: 39423-51-3	Polyoxypropylene triamine Eye Dam. 1, H318; Aquatic Chronic 2, H411; Acute Tox. 4, H302; Acute Tox. 4, H312	≥10-<25%
CAS: 71302-83-5 EC number: 701-299-7	Hydrocarbons, C9-unsaturated, polymerised Asp. Tox. 1, H304; Skin Sens. 1A, H317; Aquatic Chronic 3, H412	≥2.5-<5%
CAS: 15520-10-2 EINECS: 239-556-6	2-methylpentane-1,5-diamine Skin Corr. 1A, H314; Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; STOT SE 3, H335	≥1-<5%
CAS: 25513-64-8 EINECS: 247-063-2 Reg.nr.: 01-2119560598-25-XXXX	2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine Skin Corr. 1A, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Skin Sens. 1, H317	≥3-<5%
CAS: 90640-67-8 EINECS: 292-588-2	Triethylenetetramine Skin Corr. 1B, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1, H317; Aquatic Chronic 3, H412	≥1-<1.5%
EC number: 701-443-9	Phenol, mono- und distyrolisiert Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Skin Sens. 1A, H317	≥1-<1.5%

· **Additional information**

For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· **4.1 Description of first aid measures**

- **General information** Remove contaminated clothing immediately. Consult a doctor if symptoms occur. Move affected person to fresh air.
- **After inhalation** Supply fresh air; seek medical advice if symptoms occur. If unconscious, place in recovery position and seek medical advice.
- **After skin contact** In case of contact with skin, wash carefully with plenty of soap and water. Consult a doctor in case of skin reactions.
- **After eye contact** Rinse opened eye for several minutes under running water. Call a doctor immediately
- **After swallowing** Rinse mouth with water. Never give anything by mouth to an unconscious person. DO NOT induce vomiting. If symptoms persist, consult a doctor.

(Contd. on page 4)

GB



BE SURE. BUILD SURE.

Page 4/14

Safety data sheet according to UK REACH

Printing date 10.12.2024

Version number 44 (replaces version 43)

Revision: 07.12.2024

Trade name Konudur 160 PL-XL - Komponente B

(Contd. of page 3)

- **4.2 Most important symptoms and effects, both acute and delayed**

Advice for the doctor: Elementary aid, decontamination, symptomatic treatment.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents** *Use fire fighting measures that suit the environment.*
- **5.2 Special hazards arising from the substance or mixture** *No further relevant information available.*
- **5.3 Advice for firefighters**
- **Protective equipment:** *No special measures required.*

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures** *Wear protective equipment. Keep unprotected persons away.*
- **6.2 Environmental precautions:** *Prevent material from reaching sewage system, holes and cellars.*
- **6.3 Methods and material for containment and cleaning up:** *Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Use neutralising agent.
Dispose of contaminated material as waste according to item 13.
Ensure adequate ventilation.*
- **6.4 Reference to other sections** *See Section 7 for information on safe handling
See Section 8 for information on personal protection equipment.
See Section 13 for information on disposal.*

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** *Open and handle containers with care.
Ventilation measures are required in rooms without sufficient air exchange (e.g. closed rooms), because the occupational exposure limit values (see chapter 8) could be exceeded. This must be avoided.
Wear suitable personal protective equipment (see section 8). Avoid contact with eyes, skin and clothing. Change contaminated or damaged gloves and contaminated clothing immediately and wash skin immediately. Mix slowly, partially covering the mixing container. Pour carefully and slowly when repotting. Observe the BGBau technical data sheet and practical guide for handling epoxy*

(Contd. on page 5)



BE SURE. BUILD SURE.

Safety data sheet according to UK REACH

Printing date 10.12.2024

Version number 44 (replaces version 43)

Revision: 07.12.2024

Trade name Konudur 160 PL-XL - Komponente B

(Contd. of page 4)

resins.

- **Information about protection against explosions and fires:** *Ensure sufficient air exchange and/or extraction in the working areas. Take precautionary measures to avoid electrostatic discharges.*
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage**
- **Requirements to be met by storerooms and containers:** *No special requirements.*
- **Further information about storage conditions:** *None.*
- **Storage class** *8A*

SECTION 8: Exposure controls/personal protection

- **8.1 Control parameters**
- **Components with critical values that require monitoring at the workplace:** *The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.*

· **DNELs**

CAS: 2855-13-2 Isophorone diamine

Oral	DNEL	0.526 mg/kg bw/Tag (ArL)
Inhalative	DNEL	20.1 mg/m ³ (ArL)

CAS: 39423-51-3 Polyoxypropylene triamine

Inhalative	DNEL	14 mg/m ³ (ArL)
------------	------	----------------------------

CAS: 15520-10-2 2-methylpentane-1,5-diamine

Dermal	DNEL	1.5 mg/kg bw/day (ArL)
Inhalative	DNEL	0.25 mg/m ³ (ArL)
		0.5 mg/m ³ (Ark)

· **PNECs**

CAS: 2855-13-2 Isophorone diamine

PNEC	0.006 mg/l (Mew)
	0.06 mg/l (Freshwater)
PNEC	0.578 mg/kg dwt (Sediment)
	5.784 mg/kg dwt (Fresh water sediment)

CAS: 39423-51-3 Polyoxypropylene triamine

PNEC	10 mg/l (Sewage Treatment Plant)
	0.00044 mg/l (Mew)
	0.0044 mg/l (Freshwater)
PNEC	0.002 mg/kg dwt (Bod)
	0.002 mg/kg dwt (Sediment)

(Contd. on page 6)



BE SURE. BUILD SURE.

Safety data sheet according to UK REACH

Printing date 10.12.2024

Version number 44 (replaces version 43)

Revision: 07.12.2024

Trade name Konudur 160 PL-XL - Komponente B

(Contd. of page 5)

	0.02 mg/kg dwt (Fresh water sediment)
CAS: 15520-10-2 2-methylpentane-1,5-diamine	
PNEC	0.042 mg/l (Mew) 0.42 mg/l (Freshwater)
CAS: 25513-64-8 2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine	
PNEC	72 mg/l (Sewage Treatment Plant) 0.102 mg/l (Fresh water) 0.01 mg/l (Mew)
PNEC	10 mg/kg dwt (Bod) 0.062 mg/kg dwt (Sediment) 0.622 mg/kg dwt (Fresh water sediment)

· **Additional information:** The lists that were valid during the compilation were used as basis.

· **8.2 Exposure controls**

· **Appropriate engineering controls**

No further data; see section 7.

· **Individual protection measures, such as personal protective equipment**

· **General protective and hygienic measures**

Keep away from food, drink and animal feed.
Remove soiled, soaked clothing immediately.
Wash hands before breaks and at the end of work.
Avoid contact with eyes and skin.

· **Breathing equipment:**

If workplace limit values cannot be complied with by ventilation measures or if rooms cannot be technically ventilated, respiratory protection must be worn: Use combination filter A1-P2 (brown/white) in rooms that cannot be ventilated. If oxygen deficiency is expected, use self-contained breathing apparatus. Observe wearing time limits according to §9 (3) GefStoffV in conjunction with BGR 190.

· **Hand protection**

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

You can find help with choosing gloves on the website <https://www.bgbau.de/fileadmin/Gisbau/Projekte.pdf>

For example, we recommend the Sol-vex 37-900 protective gloves from Ansell GmbH. The breakthrough time of the protective gloves can be found under point 8 "Penetration time of the glove material". The selection of a suitable glove depends not only on the material, but also on other quality features and varies from manufacturer to manufacturer. As the product

is a preparation of several substances, the resistance of glove materials cannot be calculated in advance and must therefore be checked before use.

Nitrile rubber

Recommended material thickness: ≥ 0.4 mm

· **Penetration time of glove material**

The breakthrough times of the Sol-vex 37-900 protective gloves are around 8 hours.

The following applies to all other gloves:

(Contd. on page 7)



BE SURE. BUILD SURE.

Safety data sheet according to UK REACH

Printing date 10.12.2024

Version number 44 (replaces version 43)

Revision: 07.12.2024

Trade name Konudur 160 PL-XL - Komponente B

(Contd. of page 6)

The exact breakthrough time must be obtained from the protective glove manufacturer and adhered to.

Nitrile rubber

Material thickness: ≥ 0.40 mm

Penetration time: ≥ 480 min

Butyl rubber:

Material thickness: ≥ 0.5 mm

Penetration time: ≥ 480 min

Tight-fitting safety goggles.

Safety goggles.

· **Eye/face protection**

· **Body protection:**

Protective clothing

Suitable protective clothing should be worn when working with epoxy resins. In addition to normal work clothing (long trousers, long-sleeved shirt or T-shirt), disposable overalls, aprons, overshoes, sleeve protectors etc. may be necessary depending on the activity. Uncovered areas of skin should be avoided as far as possible, even in hot weather. If the work involves kneeling, the lower leg area should be protected by protective trousers.

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· **Colour:**

Yellow

· **Smell:**

Amine-like

· **Melting point/freezing point:**

Not determined

· **Boiling point or initial boiling point and boiling range**

232 °C

· **Flash point:**

110 °C

· **Auto-ignition temperature:**

380 °C

· **pH**

Not determined.

· **Viscosity:**

· **Kinematic viscosity**

Not determined.

· **dynamic:**

Not determined.

· **Solubility**

· **Water:**

Not miscible or difficult to mix

· **Steam pressure at 20 °C:**

0.1 hPa

· **Density and/or relative density**

· **Density at 20 °C**

0.95 g/cm³

· 9.2 Other information

· **Appearance:**

· **Form:**

Fluid

· **Important information on protection of health and environment, and on safety.**

· **Self-inflammability:**

Product is not selfigniting.

(Contd. on page 8)



BE SURE. BUILD SURE.

Safety data sheet according to UK REACH

Printing date 10.12.2024

Version number 44 (replaces version 43)

Revision: 07.12.2024

Trade name Konudur 160 PL-XL - Komponente B

(Contd. of page 7)

· **Explosive properties:** Product is not explosive.

· **Information with regard to physical hazard classes**

- **Explosives** Void
- **Flammable gases** Void
- **Aerosols** Void
- **Oxidising gases** Void
- **Gases under pressure** Void
- **Flammable liquids** Void
- **Flammable solids** Void
- **Self-reactive substances and mixtures** Void
- **Pyrophoric liquids** Void
- **Pyrophoric solids** Void
- **Self-heating substances and mixtures** Void
- **Substances and mixtures, which emit flammable gases in contact with water** Void
- **Oxidising liquids** Void
- **Oxidising solids** Void
- **Organic peroxides** Void
- **Corrosive to metals** Void
- **Desensitised explosives** Void

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Harmful if swallowed.

· **LD/LC50 values that are relevant for classification:**

CAS: 2855-13-2 Isophorone diamine

Oral	LD50	1030 mg/kg (ATE) 1030 mg/kg (rat)
	NOAEL	250 mg/kg (rat)

(Contd. on page 9)



BE SURE. BUILD SURE.

Safety data sheet according to UK REACH

Printing date 10.12.2024

Version number 44 (replaces version 43)

Revision: 07.12.2024

Trade name Konudur 160 PL-XL - Komponente B

(Contd. of page 8)

Dermal	LD50	1840 mg/kg (rabbit) >2000 mg/kg (rat) 1840 mg/kg (rabbit)
CAS: 39423-51-3 Polyoxypropylene triamine		
Oral	LD50	550 mg/kg (rat)
Dermal	LD50	>1000 mg/kg (rat)
CAS: 15520-10-2 2-methylpentane-1,5-diamine		
Oral	LD50	1170 mg/kg (rat)
Dermal	LD50	1870 mg/kg (rabbit)
Inhalative	LC50/4 h	19.6 mg/l (rat)
CAS: 25513-64-8 2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine		
Oral	LD50	910 mg/kg (rat)
	NOAEL	10 mg/kg (rat)
CAS: 90640-67-8 Triethylenetetramine		
Oral	LD50	1716 mg/kg (rat)
Dermal	LD50	1465 mg/kg (rat)

- **Primary irritant effect:**
- **Skin corrosion/irritation** Causes severe skin burns and eye damage.
- **Serious eye damage/irritation** Causes serious eye damage.
- **Respiratory or skin sensitisation** May cause an allergic skin reaction.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.
- **11.2 Information on other hazards**

· **Endocrine disrupting properties**

None of the ingredients is listed.

SECTION 12: Ecological information

· **12.1 Toxicity**

· **Aquatic toxicity:**

CAS: 2855-13-2 Isophorone diamine

LC50/96h	110 mg/l (fish) 110 mg/l (<i>Leucidus idus</i>)
EC50	1120 mg/l (<i>Pseudomonas putida</i>)
EC50/48h	23 mg/l (<i>daphnia</i>) 23 mg/l (<i>Daphnia magna</i>)

(Contd. on page 10)



BE SURE. BUILD SURE.

**Safety data sheet
according to UK REACH**

Printing date 10.12.2024

Version number 44 (replaces version 43)

Revision: 07.12.2024

Trade name Konudur 160 PL-XL - Komponente B

(Contd. of page 9)

NOEC	1.5 mg/l (<i>Desmodesmus subspicatus</i>) 3 mg/l (<i>Daphnia magna</i>)
ErC50/72h	>50 mg/l (<i>Desmodesmus subspicatus</i>) >50 mg/l (algae)
CAS: 39423-51-3 Polyoxypropylene triamine	
LC50/96h	>100 mg/l (<i>Oncorhynchus mykiss</i>)
EC50/48h	13 mg/l (<i>Daphnia magna</i>)
ErC50/72h	4.4 mg/l (algae)
CAS: 15520-10-2 2-methylpentane-1,5-diamine	
EC50/72h	>100 mg/l (algae)
EC50	1825 mg/l (fish)
EC50/48h	19.8 mg/l (<i>Daphnia magna</i>)
CAS: 25513-64-8 2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine	
EC50/24h	31.5 mg/l (<i>Daphnien</i>)
EC50	89 mg/l (<i>Pseudomonas putida</i>)
LC50/48h	174 mg/l (<i>Leucidus idus</i>)
NOEC	10.9 mg/l (<i>Danio rerio</i>) 16 mg/l (<i>Pseudokirchneriella subcapitata</i>) 1.02 mg/l (<i>Daphnia magna</i>)
ErC50/72h	43.5 mg/l (<i>Pseudokirchneriella subcapitata</i>)

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties** The product does not contain substances with endocrine disrupting properties.
- **12.7 Other adverse effects**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:** Must not reach sewage water or drainage ditch undiluted or unneutralised.
Harmful to aquatic organisms
Do not allow product to reach ground water, water bodies or sewage system.
Danger to drinking water if even small quantities leak into soil.

GB

(Contd. on page 11)



BE SURE. BUILD SURE.

Safety data sheet according to UK REACH

Printing date 10.12.2024

Version number 44 (replaces version 43)

Revision: 07.12.2024

Trade name Konudur 160 PL-XL - Komponente B

(Contd. of page 10)

SECTION 13: Disposal considerations

· **13.1 Waste treatment methods**

· **Recommendation**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· **Waste disposal key number:**

55352

Bez.: aliphatische Amine

Entsorgungshinweise:

Sonderabfallverbrennung

· **Uncleaned packagings:**

· **Recommendation:**

Dispose of packaging according to regulations on the disposal of packagings.

Empty contaminated packagings thoroughly. They can be recycled after thorough and proper cleaning.

SECTION 14: Transport information

· **14.1 UN number or ID number**

· **ADR, IMDG, IATA**

UN2735

· **14.2 UN proper shipping name**

· **ADR**

AMINES, LIQUID, CORROSIVE, N.O.S.
(ISOPHORONEDIAMINE, Fettsäuren, Tallöl-,
Reaktionsprodukte mit Triethylentetramin),
ENVIRONMENTALLY HAZARDOUS

· **IMDG**

AMINES, LIQUID, CORROSIVE, N.O.S.
(ISOPHORONEDIAMINE, Fettsäuren, Tallöl-,
Reaktionsprodukte mit Triethylentetramin),
MARINE POLLUTANT

· **IATA**

AMINES, LIQUID, CORROSIVE, N.O.S.
(ISOPHORONEDIAMINE, Fettsäuren, Tallöl-,
Reaktionsprodukte mit Triethylentetramin)

· **14.3 Transport hazard class(es)**

· **ADR**

· **Class**

8 (C7) Corrosive substances.

· **Label**

8

· **IMDG, IATA**

· **Class**

8 Corrosive substances.

· **Label**

8

· **14.4 Packing group**

· **ADR, IMDG, IATA**

II

(Contd. on page 12)



BE SURE. BUILD SURE.

Safety data sheet according to UK REACH

Printing date 10.12.2024

Version number 44 (replaces version 43)

Revision: 07.12.2024

Trade name Konudur 160 PL-XL - Komponente B

(Contd. of page 11)

· 14.5 Environmental hazards:	Product contains environmentally hazardous substances: Fettsäuren, Tallöl-, Reaktionsprodukte mit Triethylentetramin
· Marine pollutant:	Yes Symbol (fish and tree)
· Special marking (ADR):	Symbol (fish and tree)
· 14.6 Special precautions for user	Warning: Corrosive substances.
· Kemler Number:	80
· EMS Number:	F-A, S-B
· Segregation groups	(SGG18) Alkalis
· Stowage Category	A
· Segregation Code	SG35 Stow "separated from" SGG1-acids
· 14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· Transport category	2
· Tunnel restriction code	E
· IMDG	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 2735 AMINES, LIQUID, CORROSIVE, N.O.S. (ISOPHORONEDIAMINE, FETTSÄUREN, TALLÖL-, REAKTIONSPRODUKTE MIT TRIETHYLENTETRAMIN), 8, II, ENVIRONMENTALLY HAZARDOUS

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Poisons Act**

· **Regulated explosives precursors**

None of the ingredients is listed.

· **Regulated poisons**

None of the ingredients is listed.

(Contd. on page 13)



BE SURE. BUILD SURE.

Safety data sheet according to UK REACH

Printing date 10.12.2024

Version number 44 (replaces version 43)

Revision: 07.12.2024

Trade name Konudur 160 PL-XL - Komponente B

(Contd. of page 12)

· Reportable explosives precursors

None of the ingredients is listed.

· Reportable poisons

None of the ingredients is listed.

· Directive 2012/18/EU

**· Qualifying quantity (tonnes)
for the application of lower-
tier requirements** 200 t

**· Qualifying quantity (tonnes)
for the application of upper-
tier requirements** 500 t

**· 15.2 Chemical safety
assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.

**· Department issuing data
specification sheet:**

Environment protection department.

· Abbreviations and acronyms:

- RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
- ICAO: International Civil Aviation Organisation
- ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- DNEL: Derived No-Effect Level (UK REACH)
- PNEC: Predicted No-Effect Concentration (UK REACH)
- LC50: Lethal concentration, 50 percent

(Contd. on page 14)



BE SURE. BUILD SURE.

Page 14/14

Safety data sheet according to UK REACH

Printing date 10.12.2024

Version number 44 (replaces version 43)

Revision: 07.12.2024

Trade name Konudur 160 PL-XL - Komponente B

(Contd. of page 13)

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Acute Tox. 4: Acute toxicity – Category 4

Skin Corr. 1A: Skin corrosion/irritation – Category 1A

Skin Corr. 1B: Skin corrosion/irritation – Category 1B

Skin Corr. 1C: Skin corrosion/irritation – Category 1C

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Skin Sens. 1: Skin sensitisation – Category 1

Skin Sens. 1A: Skin sensitisation – Category 1A

Skin Sens. 1B: Skin sensitisation – Category 1B

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

*** Data compared to the previous version altered.**

GB