

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.03.2024

Version number 30 (replaces version 29)

Revision: 09.03.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name **Konudur 160 PL-XL - Komponente B**

Article number: 912

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture

Epoxy sealing
Hardening agent/ Curing agent

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: MC-Bauchemie Müller GmbH & Co. KG
Am Kruppwald 1-8
D-46238 Bottrop
Tel.: +49(0)2041-101-0
Fax.: +49(0)2041-101-400
E-Mail: info@mc-bauchemie.de

MC-Bauchemie AG
Hagackerstr. 10
CH-8953 Dietikon
Tel.: +44-7400510
Fax : +44-7400533

Informing department: msds@mc-bauchemie.de

1.4 Emergency telephone number:

Tel.: +49 / (0)700 24112112 (MCR)
Tel.: +1 872 5888271 (MCR)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Acute Tox. 4 H302 Harmful if swallowed.
Skin Corr. 1A H314 Causes severe skin burns and eye damage.
Eye Dam. 1 H318 Causes serious eye damage.
Skin Sens. 1 H317 May cause an allergic skin reaction.
Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to

Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms



GHS05 GHS07 GHS09

(Contd. on page 2)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.03.2024

Version number 30 (replaces version 29)

Revision: 09.03.2024

Trade name Konudur 160 PL-XL - Komponente B

(Contd. of page 1)

- **Signal word** Danger
- **Hazard-determining components of labelling:** Isophorone diamine
polymer amine terminated
Fettsäuren, Tallöl-, Reaktionsprodukte mit Triethylentetramin
Polyoxypropylene triamine
Hydrocarbons, C9-unsaturated, polymerised
2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine
Triethylenetetramine
2,4,6-Tris-(1-Phenyl-Ethyl) carboic acid
- **Hazard statements** H302 Harmful if swallowed.
H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.
H411 Toxic to aquatic life with long lasting effects.
- **Precautionary statements** P260 Do not breathe dusts or mists.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a POISON CENTER/doctor.
P321 Specific treatment (see on this label).
P362+P364 Take off contaminated clothing and wash it before reuse.
- **Additional information:** EUH401 To avoid risks to human health and the environment, comply with the instructions for use.
- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- **3.2 Mixtures**
- **Description:** Mixture consisting of the following components.

· **Dangerous components:**

CAS: 2855-13-2 EINECS: 220-666-8 Reg.nr.: 01-2119514687-32	Isophorone diamine Skin Corr. 1B, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1, H317; Aquatic Chronic 3, H412	30-60%
--	--	--------

(Contd. on page 3)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.03.2024

Version number 30 (replaces version 29)

Revision: 09.03.2024

Trade name Konudur 160 PL-XL - Komponente B

(Contd. of page 2)

EC number: 949-140-2	polymer amine terminated Eye Dam. 1, H318; Skin Irrit. 2, H315; Skin Sens. 1B, H317	10-30%
CAS: 1226892-44-9 Reg.nr.: 01-2119490750-36	Fettsäuren, Tallöl-, Reaktionsprodukte mit Triethylentetramin Skin Corr. 1C, H314; Eye Dam. 1, H318; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Sens. 1, H317	≥10-<25%
CAS: 39423-51-3	Polyoxypropylene triamine Eye Dam. 1, H318; Aquatic Chronic 2, H411; Acute Tox. 4, H302; Acute Tox. 4, H312	≥10-<25%
CAS: 71302-83-5 EC number: 701-299-7	Hydrocarbons, C9-unsaturated, polymerised Asp. Tox. 1, H304; Skin Sens. 1A, H317; Aquatic Chronic 3, H412	≥2.5-<5%
CAS: 15520-10-2 EINECS: 239-556-6	2-methylpentane-1,5-diamine Skin Corr. 1A, H314; Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; STOT SE 3, H335	≥1-<5%
CAS: 25513-64-8 EINECS: 247-063-2 Reg.nr.: 01-2119560598-25-XXXX	2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine Skin Corr. 1A, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Skin Sens. 1, H317	≥3-<5%
CAS: 90640-67-8 EINECS: 292-588-2	Triethylenetetramine Skin Corr. 1B, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1, H317; Aquatic Chronic 3, H412	≥1-<1.5%
CAS: 61788-44-1 EINECS: 262-975-0	2,4,6-Tris-(1-Phenyl-Ethyl) carboic acid Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Skin Sens. 1, H317	≥1-<1.5%

· **Additional information**

For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· General information

Take affected persons into the open air.

Immediately remove any clothing contaminated with the product.

· After inhalation

Supply fresh air; consult doctor in case of symptoms.

· After skin contact

Instantly wash with water and soap and rinse thoroughly.

· After eye contact

Rinse opened eye for several minutes under running water.

Call a doctor immediately.

· After swallowing

Rinse out mouth and then drink plenty of water.

Instantly call for doctor.

GB

(Contd. on page 4)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.03.2024

Version number 30 (replaces version 29)

Revision: 09.03.2024

Trade name Konudur 160 PL-XL - Komponente B

(Contd. of page 3)

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents** Use fire fighting measures that suit the environment.
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** No special measures required.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures** Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:** Prevent material from reaching sewage system, holes and cellars.
- **6.3 Methods and material for containment and cleaning up:** Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Use neutralising agent.
Dispose of contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **6.4 Reference to other sections** See Section 7 for information on safe handling
See Section 8 for information on personal protection equipment.
See Section 13 for information on disposal.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Store in cool, dry place in tightly closed containers.
Open and handle container with care.
- **Information about protection against explosions and fires:** No special measures required.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage**
- **Requirements to be met by storerooms and containers:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep container tightly sealed.
- **Storage class** 8A

GB

(Contd. on page 5)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.03.2024

Version number 30 (replaces version 29)

Revision: 09.03.2024

Trade name Konudur 160 PL-XL - Komponente B

(Contd. of page 4)

SECTION 8: Exposure controls/personal protection

- **8.1 Control parameters**
- **Components with critical values that require**

monitoring at the workplace: *The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.*

· **DNELs**

CAS: 2855-13-2 Isophorone diamine

Oral DNEL 0.526 mg/kg bw/Tag (ArL)

Inhalative DNEL 20.1 mg/m³ (ArL)

CAS: 39423-51-3 Polyoxypropylene triamine

Inhalative DNEL 14 mg/m³ (ArL)

CAS: 15520-10-2 2-methylpentane-1,5-diamine

Dermal DNEL 1.5 mg/kg bw/day (ArL)

Inhalative DNEL 0.25 mg/m³ (ArL)

0.5 mg/m³ (Ark)

· **PNECs**

CAS: 2855-13-2 Isophorone diamine

PNEC 0.006 mg/l (Mew)

0.06 mg/l (Freshwater)

PNEC 0.578 mg/kg dwt (Sediment)

5.784 mg/kg dwt (Fresh water sediment)

CAS: 39423-51-3 Polyoxypropylene triamine

PNEC 10 mg/l (Sewage Treatment Plant)

0.00044 mg/l (Mew)

0.0044 mg/l (Freshwater)

PNEC 0.002 mg/kg dwt (Bod)

0.002 mg/kg dwt (Sediment)

0.02 mg/kg dwt (Fresh water sediment)

CAS: 15520-10-2 2-methylpentane-1,5-diamine

PNEC 0.042 mg/l (Mew)

0.42 mg/l (Freshwater)

CAS: 25513-64-8 2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine

PNEC 72 mg/l (Sewage Treatment Plant)

0.102 mg/l (Fresh water)

0.01 mg/l (Mew)

PNEC 10 mg/kg dwt (Bod)

0.062 mg/kg dwt (Sediment)

0.622 mg/kg dwt (Fresh water sediment)

(Contd. on page 6)



BE SURE. BUILD SURE.

Page 6/13

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.03.2024

Version number 30 (replaces version 29)

Revision: 09.03.2024

Trade name Konudur 160 PL-XL - Komponente B

(Contd. of page 5)

- **Additional information:** The lists that were valid during the compilation were used as basis.
- **8.2 Exposure controls**
- **Appropriate engineering controls** No further data; see section 7.
- **Individual protection measures, such as personal protective equipment**
- **General protective and hygienic measures** Keep away from foodstuffs, beverages and food.
Instantly remove any soiled and impregnated garments.
Wash hands during breaks and at the end of the work.
Avoid contact with the eyes and skin.
- **Breathing equipment:** If workplace limit values cannot be complied with by ventilation measures or if rooms cannot be technically ventilated, respiratory protection must be worn: Use combination filter A1-P2 (brown/white) in rooms that cannot be ventilated. If oxygen deficiency is expected, use self-contained breathing apparatus. Observe wearing time limits according to §9 (3) GefStoffV in conjunction with BGR 190.
- **Hand protection** Protective gloves.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
After use of gloves apply skin-cleaning agents and skin cosmetics.
- **Material of gloves** The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material** The exact breakthrough time must be obtained from the protective glove manufacturer and must be observed.
- **Eye/face protection** Not required.
- **Body protection:** Protective work clothing.

SECTION 9: Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**
- **General Information**
- **Colour:** Yellow
- **Smell:** Amine-like
- **Melting point/freezing point:** Not determined
- **Boiling point or initial boiling point and boiling range** 232 °C
- **Flash point:** 110 °C
- **Auto-ignition temperature:** 380 °C
- **pH** Not determined.
- **Viscosity:**
- **Kinematic viscosity** Not determined.

(Contd. on page 7)

GB

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.03.2024

Version number 30 (replaces version 29)

Revision: 09.03.2024

Trade name Konudur 160 PL-XL - Komponente B

(Contd. of page 6)

· dynamic:	Not determined.
· Solubility	
· Water:	Not miscible or difficult to mix
· Steam pressure at 20 °C:	0.1 hPa
· Density and/or relative density	
· Density at 20 °C	0.95 g/cm ³

· 9.2 Other information	
· Appearance:	
· Form:	Fluid
· Important information on protection of health and environment, and on safety.	
· Self-inflammability:	Product is not selfigniting.
· Explosive properties:	Product is not explosive.

· Information with regard to physical hazard classes	
· Explosives	Void
· Flammable gases	Void
· Aerosols	Void
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Void
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

SECTION 10: Stability and reactivity

· 10.1 Reactivity	No further relevant information available.
· 10.2 Chemical stability	
· Thermal decomposition / conditions to be avoided:	No decomposition if used according to specifications.
· 10.3 Possibility of hazardous reactions	No dangerous reactions known
· 10.4 Conditions to avoid	No further relevant information available.
· 10.5 Incompatible materials:	No further relevant information available.

(Contd. on page 8)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.03.2024

Version number 30 (replaces version 29)

Revision: 09.03.2024

Trade name Konudur 160 PL-XL - Komponente B

(Contd. of page 7)

· **10.6 Hazardous decomposition products:** No dangerous decomposition products known

SECTION 11: Toxicological information

· **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**

· **Acute toxicity** Harmful if swallowed.

· **LD/LC50 values that are relevant for classification:**

CAS: 2855-13-2 Isophorone diamine

Oral	LD50	1030 mg/kg (ATE)
		1030 mg/kg (rat)
Dermal	NOAEL	250 mg/kg (rat)
	LD50	1840 mg/kg (rabbit)
		>2000 mg/kg (rat)

CAS: 39423-51-3 Polyoxypropylene triamine

Oral	LD50	550 mg/kg (rat)
Dermal	LD50	>1000 mg/kg (rat)

CAS: 15520-10-2 2-methylpentane-1,5-diamine

Oral	LD50	1170 mg/kg (rat)
Dermal	LD50	1870 mg/kg (rabbit)
Inhalative	LC50/4 h	19.6 mg/l (rat)

CAS: 25513-64-8 2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine

Oral	LD50	910 mg/kg (rat)
	NOAEL	10 mg/kg (rat)

CAS: 90640-67-8 Triethylenetetramine

Oral	LD50	1716 mg/kg (rat)
Dermal	LD50	1465 mg/kg (rat)

· **Skin corrosion/irritation** Causes severe skin burns and eye damage.

· **Serious eye damage/irritation** Causes serious eye damage.

· **Respiratory or skin sensitisation** May cause an allergic skin reaction.

· **Germ cell mutagenicity** Based on available data, the classification criteria are not met.

· **Carcinogenicity** Based on available data, the classification criteria are not met.

· **Reproductive toxicity** Based on available data, the classification criteria are not met.

· **STOT-single exposure** Based on available data, the classification criteria are not met.

· **STOT-repeated exposure** Based on available data, the classification criteria are not met.

· **Aspiration hazard** Based on available data, the classification criteria are not met.

· **11.2 Information on other hazards**

· **Endocrine disrupting properties**

CAS: 61788-44-1 2,4,6-Tris-(1-Phenyl-Ethyl) carboic acid

List II

GB
(Contd. on page 9)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.03.2024

Version number 30 (replaces version 29)

Revision: 09.03.2024

Trade name Konudur 160 PL-XL - Komponente B

(Contd. of page 8)

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity:

CAS: 2855-13-2 Isophorone diamine

LC50/96h	110 mg/l (Leucidus idus)
EC50	1120 mg/l (Pseudomonas putida)
EC50/48h	23 mg/l (Daphnia magna)
NOEC	1.5 mg/l (Desmodesmus subspicatus)
	3 mg/l (Daphnia magna)
ErC50/72h	>50 mg/l (Desmodesmus subspicatus)

CAS: 39423-51-3 Polyoxypropylene triamine

LC50/96h	>100 mg/l (Oncorhynchus mykiss)
EC50/48h	13 mg/l (Daphnia magna)
ErC50/72h	4.4 mg/l (algae)

CAS: 15520-10-2 2-methylpentane-1,5-diamine

EC50/72h	>100 mg/l (algae)
EC50	1825 mg/l (fish)
EC50/48h	19.8 mg/l (Daphnia magna)

CAS: 25513-64-8 2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine

EC50/24h	31.5 mg/l (Daphnien)
EC50	89 mg/l (Pseudomonas putida)
LC50/48h	174 mg/l (Leucidus idus)
NOEC	10.9 mg/l (Danio rerio)
	16 mg/l (Pseudokirchneriella subcapitata)
	1.02 mg/l (Daphnia magna)
ErC50/72h	43.5 mg/l (Pseudokirchneriella subcapitata)

12.2 Persistence and degradability

No further relevant information available.

12.3 Bioaccumulative potential

No further relevant information available.

12.4 Mobility in soil

No further relevant information available.

12.5 Results of PBT and vPvB assessment

PBT:

Not applicable.

vPvB:

Not applicable.

12.6 Endocrine disrupting properties

For information on endocrine disrupting properties see section 11.

12.7 Other adverse effects

Remark:

Harmful to fish

Additional ecological information:

General notes:

Must not reach sewage water or drainage ditch undiluted or unneutralised.

(Contd. on page 10)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.03.2024

Version number 30 (replaces version 29)

Revision: 09.03.2024

Trade name Konudur 160 PL-XL - Komponente B

(Contd. of page 9)

*Harmful to aquatic organisms
Do not allow product to reach ground water, water bodies or
sewage system.
Danger to drinking water if even small quantities leak into soil.*

SECTION 13: Disposal considerations

· **13.1 Waste treatment methods**

· **Recommendation** *Must not be disposed of together with household garbage. Do not allow product to reach sewage system.*

· **Waste disposal key number:** 55352
*Bez.: aliphatische Amine
Entsorgungshinweise:
Sonderabfallverbrennung*

· **Uncleaned packagings:**

· **Recommendation:** *Dispose of packaging according to regulations on the disposal of packagings.
Empty contaminated packagings thoroughly. They can be recycled after thorough and proper cleaning.*

SECTION 14: Transport information

· **14.1 UN number or ID number**

· **ADR, IMDG, IATA** UN2735

· **14.2 UN proper shipping name**

· **ADR** *AMINES, LIQUID, CORROSIVE, N.O.S.
(Isophorone diamine, 2,2,4(or 2,4,4)-
trimethylhexane-1,6-diamine),
ENVIRONMENTALLY HAZARDOUS*

· **IMDG** *AMINES, LIQUID, CORROSIVE, N.O.S.
(Isophorone diamine, 2,2,4(or 2,4,4)-
trimethylhexane-1,6-diamine), MARINE
POLLUTANT*

· **IATA** *AMINES, LIQUID, CORROSIVE, N.O.S.
(Isophorone diamine, 2,2,4(or 2,4,4)-
trimethylhexane-1,6-diamine)*

· **14.3 Transport hazard class(es)**

· **ADR**

· **Class** 8 (C7) Corrosive substances.

· **Label** 8

· **IMDG, IATA**

· **Class** 8 Corrosive substances.

· **Label** 8

(Contd. on page 11)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.03.2024

Version number 30 (replaces version 29)

Revision: 09.03.2024

Trade name Konudur 160 PL-XL - Komponente B

(Contd. of page 10)

· 14.4 Packing group · ADR, IMDG, IATA	II
· 14.5 Environmental hazards: · Marine pollutant: · Special marking (ADR):	Product contains environmentally hazardous substances: Fettsäuren, Tallöl-, Reaktionsprodukte mit Triethylentetramin Yes Symbol (fish and tree) Symbol (fish and tree)
· 14.6 Special precautions for user · Kemler Number: · EMS Number: · Segregation groups · Stowage Category · Segregation Code	Warning: Corrosive substances. 80 F-A, S-B (SGG18) Alkalies A SG35 Stow "separated from" SGG1-acids
· 14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
· Transport/Additional information:	
· ADR · Limited quantities (LQ) · Excepted quantities (EQ)	1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· Transport category · Tunnel restriction code	2 E
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 2735 AMINES, LIQUID, CORROSIVE, N.O.S. (ISOPHORONE DIAMINE, 2,2,4(OR 2,4,4)-TRIMETHYLHEXANE-1,6-DIAMINE), 8, II, ENVIRONMENTALLY HAZARDOUS

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Poisons Act**

· **Regulated explosives precursors**

None of the ingredients is listed.

(Contd. on page 12)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.03.2024

Version number 30 (replaces version 29)

Revision: 09.03.2024

Trade name Konudur 160 PL-XL - Komponente B

(Contd. of page 11)

· **Regulated poisons**

None of the ingredients is listed.

· **Reportable explosives precursors**

None of the ingredients is listed.

· **Reportable poisons**

None of the ingredients is listed.

· **Directive 2012/18/EU**

· **Qualifying quantity (tonnes)
for the application of lower-
tier requirements**

200 t

· **Qualifying quantity (tonnes)
for the application of upper-
tier requirements**

500 t

· **15.2 Chemical safety
assessment:**

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H302 Harmful if swallowed.
H304 May be fatal if swallowed and enters airways.
H312 Harmful in contact with skin.
H314 Causes severe skin burns and eye damage.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.
H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.

· **Department issuing data
specification sheet:**

Environment protection department.

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
ICAO: International Civil Aviation Organisation
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)

(Contd. on page 13)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.03.2024

Version number 30 (replaces version 29)

Revision: 09.03.2024

Trade name Konudur 160 PL-XL - Komponente B

(Contd. of page 12)

DNEL: Derived No-Effect Level (UK REACH)
PNEC: Predicted No-Effect Concentration (UK REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Acute Tox. 4: Acute toxicity – Category 4
Skin Corr. 1A: Skin corrosion/irritation – Category 1A
Skin Corr. 1B: Skin corrosion/irritation – Category 1B
Skin Corr. 1C: Skin corrosion/irritation – Category 1C
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Skin Sens. 1: Skin sensitisation – Category 1
Skin Sens. 1A: Skin sensitisation – Category 1A
Skin Sens. 1B: Skin sensitisation – Category 1B
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

· * **Data compared to the previous version altered.**