



BE SURE. BUILD SURE.

Page 1/13

## Safety data sheet according to UK REACH

Printing date 11.12.2024

Version number 27 (replaces version 26)

Revision: 11.12.2024

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

· **1.1 Product identifier**

· **Trade name** Konudur 170 BT - Komponente B

· **1.2 Relevant identified uses of the substance or mixture and uses advised against**

No further relevant information available.

· **Application of the substance / the mixture**

Epoxy sealing  
Hardening agent/ Curing agent

· **1.3 Details of the supplier of the safety data sheet**

· **Manufacturer/Supplier:**

MC-Bauchemie Müller GmbH & Co. KG  
Am Kruppwald 1-8  
D-46238 Bottrop  
Tel.: +49(0)2041-101-0  
Fax.: +49(0)2041-101-400  
E-Mail: info@mc-bauchemie.de

MC-Bauchemie AG  
Hagackerstr. 10  
CH-8953 Dietikon  
Tel.: +44-7400510  
Fax : +44-7400533

· **Informing department:**

msds@mc-bauchemie.de

· **1.4 Emergency telephone number:**

Tel.: +49 / (0)700 24112112 (MCR)  
Tel.: +1 872 5888271 (MCR)

### SECTION 2: Hazards identification

· **2.1 Classification of the substance or mixture**

· **Classification according to Regulation (EC) No 1272/2008**

Acute Tox. 4 H302 Harmful if swallowed.  
Skin Corr. 1B H314 Causes severe skin burns and eye damage.  
Eye Dam. 1 H318 Causes serious eye damage.  
Skin Sens. 1 H317 May cause an allergic skin reaction.  
STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.  
Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

· **2.2 Label elements**

· **Labelling according to**

**Regulation (EC) No 1272/2008** The product is classified and labelled according to the GB CLP regulation.

· **Hazard pictograms**



GHS05 GHS07 GHS08

(Contd. on page 2)

GB



BE SURE. BUILD SURE.

## Safety data sheet according to UK REACH

Printing date 11.12.2024

Version number 27 (replaces version 26)

Revision: 11.12.2024

**Trade name Konudur 170 BT - Komponente B**

(Contd. of page 1)

- **Signal word** Danger
- **Hazard-determining components of labelling:** Isophorone diamine  
4,4'-methylenebis(cyclohexylamine)  
polymer amine terminated  
2,4,6-tris(dimethylaminomethyl)phenol  
2,4,6-Tris-(1-Phenyl-Ethyl) carboic acid
- **Hazard statements** H302 Harmful if swallowed.  
H314 Causes severe skin burns and eye damage.  
H317 May cause an allergic skin reaction.  
H373 May cause damage to organs through prolonged or repeated exposure.  
H412 Harmful to aquatic life with long lasting effects.
- **Precautionary statements** P260 Do not breathe dusts or mists.  
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P310 Immediately call a POISON CENTER/doctor.  
P321 Specific treatment (see on this label).  
P362+P364 Take off contaminated clothing and wash it before reuse.
- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

### SECTION 3: Composition/information on ingredients

- **3.2 Mixtures**
- **Description:** Mixture consisting of the following components.

· **Dangerous components:**

CAS: 2855-13-2 EINECS: 220-666-8 Reg.nr.: 01-2119514687-32	Isophorone diamine Skin Corr. 1B, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1, H317; Aquatic Chronic 3, H412 Specific concentration limit: Skin Sens. 1A; H317: C ≥ 0.001 %	30-60%
EC number: 949-140-2	polymer amine terminated Eye Dam. 1, H318; Skin Irrit. 2, H315; Skin Sens. 1B, H317	10-30%
CAS: 1761-71-3 EINECS: 217-168-8	4,4'-methylenebis(cyclohexylamine) STOT RE 2, H373; Skin Corr. 1B, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Skin Sens. 1B, H317	10-30%

(Contd. on page 3)



BE SURE. BUILD SURE.

## Safety data sheet according to UK REACH

Printing date 11.12.2024

Version number 27 (replaces version 26)

Revision: 11.12.2024

**Trade name Konudur 170 BT - Komponente B**

(Contd. of page 2)

CAS: 90-72-2 EINECS: 202-013-9 Reg.nr.: 2119560597-27	2,4,6-tris(dimethylaminomethyl)phenol Skin Corr. 1C, H314; Eye Dam. 1, H318; Acute Tox. 4, H302	≥5-<10%
CAS: 100-51-6	Benzyl alcohol Acute Tox. 4, H302; Acute Tox. 4, H332; Eye Irrit. 2, H319	<5%
EC number: 701-443-9	Phenol, mono- und distyrolisiert Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Skin Sens. 1A, H317	≥1-<2.5%
CAS: 69-72-7 EINECS: 200-712-3	salicylic acid Repr. 2, H361d; Eye Dam. 1, H318; Acute Tox. 4, H302	<1%

· **Additional information** For the wording of the listed hazard phrases refer to section 16.

### SECTION 4: First aid measures

· **4.1 Description of first aid measures**

- **General information** Remove contaminated clothing immediately. Consult a doctor if symptoms occur. Move affected person to fresh air.
- **After inhalation** Supply fresh air; seek medical advice if symptoms occur.  
If unconscious, place in recovery position and seek medical advice.
- **After skin contact** In case of contact with skin, wash carefully with plenty of soap and water. Consult a doctor in case of skin reactions.
- **After eye contact** Rinse opened eye for several minutes under running water.  
Call a doctor immediately
- **After swallowing** Rinse mouth with water. Never give anything by mouth to an unconscious person. DO NOT induce vomiting. If symptoms persist, consult a doctor.

· **4.2 Most important symptoms and effects, both acute and delayed**

Advice for the doctor: Elementary aid, decontamination, symptomatic treatment.

### SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents** Use fire fighting measures that suit the environment.
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** No special measures required.

GB

(Contd. on page 4)



BE SURE. BUILD SURE.

Page 4/13

## Safety data sheet according to UK REACH

Printing date 11.12.2024

Version number 27 (replaces version 26)

Revision: 11.12.2024

Trade name Konudur 170 BT - Komponente B

(Contd. of page 3)

### SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**  
*Wear protective equipment. Keep unprotected persons away.*
- **6.2 Environmental precautions:**  
*Inform respective authorities in case product reaches water or sewage system.*
- **6.3 Methods and material for containment and cleaning up:**  
*Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Use neutralising agent.  
Dispose of contaminated material as waste according to item 13.  
Ensure adequate ventilation.*
- **6.4 Reference to other sections**  
*See Section 7 for information on safe handling  
See Section 8 for information on personal protection equipment.  
See Section 13 for information on disposal.*

### SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**  
*Open and handle containers with care.  
Ventilation measures are required in rooms without sufficient air exchange (e.g. closed rooms), because the occupational exposure limit values (see chapter 8) could be exceeded. This must be avoided.  
Wear suitable personal protective equipment (see section 8). Avoid contact with eyes, skin and clothing. Change contaminated or damaged gloves and contaminated clothing immediately and wash skin immediately. Mix slowly, partially covering the mixing container. Pour carefully and slowly when repotting. Observe the BGBau technical data sheet and practical guide for handling epoxy resins.*
- **Information about protection against explosions and fires:**  
*Ensure sufficient air exchange and/or extraction in the working areas. Take precautionary measures to avoid electrostatic discharges.*
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage**
- **Requirements to be met by storerooms and containers:**  
*No special requirements.*
- **Further information about storage conditions:**  
*Protect from heat and direct sunlight.*
- **Storage class**  
*8A*

GB

(Contd. on page 5)



BE SURE. BUILD SURE.

**Safety data sheet  
according to UK REACH**

Printing date 11.12.2024

Version number 27 (replaces version 26)

Revision: 11.12.2024

**Trade name Konudur 170 BT - Komponente B**

(Contd. of page 4)

**SECTION 8: Exposure controls/personal protection**

- **8.1 Control parameters**
- **Components with critical values that require**

**monitoring at the workplace:** *The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.*

· **DNELs**

**CAS: 2855-13-2 Isophorone diamine**

Oral DNEL 0.526 mg/kg bw/Tag (ArL)

Inhalative DNEL 20.1 mg/m<sup>3</sup> (ArL)

**CAS: 1761-71-3 4,4'-methylenebis(cyclohexylamine)**

Oral DNEL 0.06 mg/kg bw/Tag (ArL)

Dermal DNEL 0.1 mg/kg bw/day (ArL)

Inhalative DNEL 1 mg/m<sup>3</sup> (ArL)

**CAS: 90-72-2 2,4,6-tris(dimethylaminomethyl)phenol**

Inhalative DNEL 0.31 mg/m<sup>3</sup> (ArL)

**CAS: 100-51-6 Benzyl alcohol**

Oral DNEL 4 mg/kg bw/Tag (ArL)

20 mg/kg bw/Tag (Ark)

Dermal DNEL 8 mg/kg bw/day (ArL)

40 mg/kg bw/day (Ark)

Inhalative DNEL 22 mg/m<sup>3</sup> (ArL)

110 mg/m<sup>3</sup> (Ark)

· **PNECs**

**CAS: 2855-13-2 Isophorone diamine**

PNEC 0.006 mg/l (Mew)

0.06 mg/l (Freshwater)

PNEC 0.578 mg/kg dwt (Sediment)

5.784 mg/kg dwt (Fresh water sediment)

**CAS: 1761-71-3 4,4'-methylenebis(cyclohexylamine)**

PNEC 0.08 mg/l (Fresh water)

3.2 mg/l (Kla)

13.7 mg/l (Mew)

PNEC 27.2 mg/kg dwt (Bod)

13.7 mg/kg dwt (Sediment)

137 mg/kg dwt (Fresh water sediment)

**CAS: 90-72-2 2,4,6-tris(dimethylaminomethyl)phenol**

PNEC 0.2 mg/l (Sewage Treatment Plant)

0.0084 mg/l (Mew)

(Contd. on page 6)



BE SURE. BUILD SURE.

### Safety data sheet according to UK REACH

Printing date 11.12.2024

Version number 27 (replaces version 26)

Revision: 11.12.2024

**Trade name Konudur 170 BT - Komponente B**

(Contd. of page 5)

	0.084 mg/l (Freshwater)
<b>CAS: 100-51-6 Benzyl alcohol</b>	
PNEC	0.527 mg/l (Marine water sediment)
	0.1 mg/l (Mew)
	1 mg/l (Fresh water sediment)
PNEC	0.456 mg/kg dwt (Bod)
	5.27 mg/kg dwt (Fresh water sediment)

· **Additional information:** The lists that were valid during the compilation were used as basis.

· **8.2 Exposure controls**

· **Appropriate engineering controls**

No further data; see section 7.

· **Individual protection measures, such as personal protective equipment**

· **General protective and hygienic measures**

Keep away from food, drink and animal feed.  
Remove soiled, soaked clothing immediately.  
Wash hands before breaks and at the end of work.  
Avoid contact with eyes and skin.

· **Breathing equipment:**

If workplace limit values cannot be complied with by ventilation measures or if rooms cannot be technically ventilated, respiratory protection must be worn: Use combination filter A1-P2 (brown/white) in rooms that cannot be ventilated. If oxygen deficiency is expected, use self-contained breathing apparatus. Observe wearing time limits according to §9 (3) GefStoffV in conjunction with BGR 190.

· **Hand protection**

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

You can find help with choosing gloves on the website <https://www.bgbau.de/fileadmin/Gisbau/Projekte.pdf>  
For example, we recommend the Sol-vex 37-900 protective gloves from Ansell GmbH. The breakthrough time of the protective gloves can be found under point 8 "Penetration time of the glove material". The selection of a suitable glove depends not only on the material, but also on other quality features and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of glove materials cannot be calculated in advance and must therefore be checked before use.

Nitrile rubber

Recommended material thickness: ≥ 0.4 mm

· **Penetration time of glove material**

The breakthrough times of the Sol-vex 37-900 protective gloves are around 8 hours.

The following applies to all other gloves:

The exact breakthrough time must be obtained from the protective glove manufacturer and adhered to.

Nitrile rubber

Material thickness: ≥ 0.40 mm

Penetration time: ≥ 480 min

(Contd. on page 7)



BE SURE. BUILD SURE.

### Safety data sheet according to UK REACH

Printing date 11.12.2024

Version number 27 (replaces version 26)

Revision: 11.12.2024

**Trade name Konudur 170 BT - Komponente B**

(Contd. of page 6)

· **Eye/face protection**

*Butyl rubber:*

*Material thickness: ≥ 0.5 mm*

*Penetration time: ≥ 480 min*

*Tight-fitting safety goggles.*

*Safety goggles.*

· **Body protection:**

*Protective clothing*

*Suitable protective clothing should be worn when working with epoxy resins. In addition to normal work clothing (long trousers, long-sleeved shirt or T-shirt), disposable overalls, aprons, overshoes, sleeve protectors etc. may be necessary depending on the activity. Uncovered areas of skin should be avoided as far as possible, even in hot weather. If the work involves kneeling, the lower leg area should be protected by protective trousers.*

## SECTION 9: Physical and chemical properties

### · 9.1 Information on basic physical and chemical properties

#### · General Information

· **Colour:**

*Colourless*

· **Smell:**

*Amine-like*

· **Melting point/freezing point:**

*Not determined*

· **Boiling point or initial boiling point and boiling range**

*247 °C (CAS: 2855-13-2 3-aminomethyl-3,5,5-trimethylcyclohexylamine)*

· **Flash point:**

*>100 °C*

· **Auto-ignition temperature:**

*380 °C*

· **pH at 20 °C**

*10*

· **Viscosity:**

· **Kinematic viscosity**

*Not determined.*

· **dynamic:**

*Not determined.*

· **Solubility**

· **Water:**

*Not miscible or difficult to mix*

· **Steam pressure:**

*Not determined.*

· **Density and/or relative density**

· **Density at 20 °C**

*0.98 g/cm<sup>3</sup>*

### · 9.2 Other information

· **Appearance:**

· **Form:**

*Fluid*

· **Important information on protection of health and environment, and on safety.**

· **Self-inflammability:**

*Product is not selfigniting.*

· **Explosive properties:**

*Product is not explosive.*

· **Information with regard to physical hazard classes**

· **Explosives**

*Void*

· **Flammable gases**

*Void*

(Contd. on page 8)





BE SURE. BUILD SURE.

### Safety data sheet according to UK REACH

Printing date 11.12.2024

Version number 27 (replaces version 26)

Revision: 11.12.2024

Trade name **Konudur 170 BT - Komponente B**

(Contd. of page 7)

- **Aerosols** Void
- **Oxidising gases** Void
- **Gases under pressure** Void
- **Flammable liquids** Void
- **Flammable solids** Void
- **Self-reactive substances and mixtures** Void
- **Pyrophoric liquids** Void
- **Pyrophoric solids** Void
- **Self-heating substances and mixtures** Void
- **Substances and mixtures, which emit flammable gases in contact with water** Void
- **Oxidising liquids** Void
- **Oxidising solids** Void
- **Organic peroxides** Void
- **Corrosive to metals** Void
- **Desensitised explosives** Void

#### SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known

#### SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Harmful if swallowed.

· **LD/LC50 values that are relevant for classification:**

**CAS: 2855-13-2 Isophorone diamine**

Oral	LD50	1030 mg/kg (ATE) 1030 mg/kg (rat)
	NOAEL	250 mg/kg (rat)
Dermal	LD50	1840 mg/kg (rabbit) >2000 mg/kg (rat) 1840 mg/kg (rabbit)

(Contd. on page 9)





BE SURE. BUILD SURE.

## Safety data sheet according to UK REACH

Printing date 11.12.2024

Version number 27 (replaces version 26)

Revision: 11.12.2024

**Trade name Konudur 170 BT - Komponente B**

(Contd. of page 8)

<b>CAS: 1761-71-3 4,4'-methylenebis(cyclohexylamine)</b>		
Oral	LD50	380 mg/kg (rat)
Dermal	LD50	2110 mg/kg (rat)
<b>CAS: 90-52-2 2,4,6-tris(dimethylaminomethyl)phenol</b>		
Oral	LD50	mg/kg (rat)
	NOAEL	15 mg/kg (rat)
<b>CAS: 100-51-6 Benzyl alcohol</b>		
Oral	LD50	1230 mg/kg (rat)
	NOAEL 2nd year study	200 mg/kg (mouse)
		200 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rabbit)
Inhalative	LC50/4 h	>4178 mg/l (rat)
<b>CAS: 69-72-7 salicylic acid</b>		
Oral	LD50	891 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rat)

- **Primary irritant effect:**
- **Skin corrosion/irritation** Causes severe skin burns and eye damage.
- **Serious eye damage/irritation** Causes serious eye damage.
- **Respiratory or skin sensitisation** May cause an allergic skin reaction.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** May cause damage to organs through prolonged or repeated exposure.
- **Aspiration hazard** Based on available data, the classification criteria are not met.
- **11.2 Information on other hazards**

· **Endocrine disrupting properties**

CAS: 69-72-7 salicylic acid

List II; III

### SECTION 12: Ecological information

· **12.1 Toxicity**

· **Aquatic toxicity:**

**CAS: 2855-13-2 Isophorone diamine**

LC50/96h	110 mg/l (fish)
	110 mg/l ( <i>Leucidus idus</i> )
EC50	1120 mg/l ( <i>Pseudomonas putida</i> )
EC50/48h	23 mg/l ( <i>daphnia</i> )
	23 mg/l ( <i>Daphnia magna</i> )

(Contd. on page 10)



BE SURE. BUILD SURE.

**Safety data sheet  
according to UK REACH**

Printing date 11.12.2024

Version number 27 (replaces version 26)

Revision: 11.12.2024

**Trade name Konudur 170 BT - Komponente B**

(Contd. of page 9)

NOEC	1.5 mg/l ( <i>Desmodesmus subspicatus</i> ) 3 mg/l ( <i>Daphnia magna</i> )
ErC50/72h	>50 mg/l ( <i>Desmodesmus subspicatus</i> ) >50 mg/l (algae)
<b>CAS: 1761-71-3 4,4'-methylenebis(cyclohexylamine)</b>	
LC50/96h	>100 mg/l ( <i>Leucidus idus</i> )
EC50/48h	6.84 mg/l ( <i>Daphnia magna</i> )
NOEC	4 mg/l ( <i>Daphnia magna</i> )
ErC50/72h	141.2 mg/l ( <i>Desmodesmus subspicatus</i> )
<b>CAS: 90-72-2 2,4,6-tris(dimethylaminomethyl)phenol</b>	
EC50/72h	84 mg/l ( <i>Desmodesmus subspicatus</i> )
LC50/96h	175 mg/l ( <i>Cyp</i> ) 718 mg/l ( <i>Daphnia magna</i> )
NOEC	2 mg/l (BEL) 6.25 mg/l ( <i>Desmodesmus subspicatus</i> )
<b>CAS: 100-51-6 Benzyl alcohol</b>	
IC50/72h	700 mg/l (algae)
LC50/96h	460 mg/l ( <i>Pimephales promelas</i> ) 10 mg/l ( <i>Lepomis macrochirus</i> )

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties** For information on endocrine disrupting properties see section 11.
- **12.7 Other adverse effects**
- **Remark:** Toxic for fish
- **Additional ecological information:**
- **General notes:** Also poisonous for fish and plankton in water bodies.  
Toxic for aquatic organisms  
Must not reach sewage water or drainage ditch undiluted or unneutralised.  
Do not allow product to reach ground water, water bodies or sewage system.  
Danger to drinking water if even small quantities leak into soil.

GB

(Contd. on page 11)



BE SURE. BUILD SURE.

### Safety data sheet according to UK REACH

Printing date 11.12.2024

Version number 27 (replaces version 26)

Revision: 11.12.2024

Trade name Konudur 170 BT - Komponente B

(Contd. of page 10)

#### SECTION 13: Disposal considerations

· **13.1 Waste treatment methods**

· **Recommendation**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· **Waste disposal key number:**

55352

Bez.: aliphatische Amine

Entsorgungshinweise:

Sonderabfallverbrennung

· **Uncleaned packagings:**

· **Recommendation:**

Dispose of packaging according to regulations on the disposal of packagings.

Empty contaminated packagings thoroughly. They can be recycled after thorough and proper cleaning.

#### SECTION 14: Transport information

· **14.1 UN number or ID number**

· **ADR, IMDG, IATA**

UN2735

· **14.2 UN proper shipping name**

· **ADR, IMDG, IATA**

AMINES, LIQUID, CORROSIVE, N.O.S. (4,4'-methylenebis(cyclohexylamine), ISOPHORONEDIAMINE)

· **14.3 Transport hazard class(es)**

· **ADR**

· **Class**

8 (C7) Corrosive substances.

· **Label**

8

· **IMDG, IATA**

· **Class**

8 Corrosive substances.

· **Label**

8

· **14.4 Packing group**

· **ADR, IMDG, IATA**

II

· **14.5 Environmental hazards:**

· **Marine pollutant:**

No

· **14.6 Special precautions for user**

Warning: Corrosive substances.

· **Kemler Number:**

80

· **EMS Number:**

F-A, S-B

· **Segregation groups**

(SGG18) Alkalis

· **Stowage Category**

A

· **Segregation Code**

SG35 Stow "separated from" SGG1-acids

· **14.7 Maritime transport in bulk according to IMO instruments**

Not applicable.

(Contd. on page 12)



BE SURE. BUILD SURE.

### Safety data sheet according to UK REACH

Printing date 11.12.2024

Version number 27 (replaces version 26)

Revision: 11.12.2024

**Trade name Konudur 170 BT - Komponente B**

(Contd. of page 11)

**· Transport/Additional information:**

**· ADR**

- Limited quantities (LQ)
- Excepted quantities (EQ)

1L  
Code: E2  
Maximum net quantity per inner packaging: 30 ml  
Maximum net quantity per outer packaging: 500 ml

- Transport category
- Tunnel restriction code

2  
E

**· IMDG**

- Limited quantities (LQ)
- Excepted quantities (EQ)

1L  
Code: E2  
Maximum net quantity per inner packaging: 30 ml  
Maximum net quantity per outer packaging: 500 ml

**· UN "Model Regulation":**

UN 2735 AMINES, LIQUID, CORROSIVE, N.O.S.  
(4,4'-METHYLENEBIS(CYCLOHEXYLAMINE),  
ISOPHORONEDIAMINE), 8, II

### SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/ legislation specific for the substance or mixture

No further relevant information available.

**· Poisons Act**

**· Regulated explosives precursors**

None of the ingredients is listed.

**· Regulated poisons**

None of the ingredients is listed.

**· Reportable explosives precursors**

None of the ingredients is listed.

**· Reportable poisons**

None of the ingredients is listed.

**· 15.2 Chemical safety assessment:**

A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

**· Relevant phrases**

H302 Harmful if swallowed.  
H312 Harmful in contact with skin.  
H314 Causes severe skin burns and eye damage.

(Contd. on page 13)



BE SURE. BUILD SURE.

Page 13/13

## Safety data sheet according to UK REACH

Printing date 11.12.2024

Version number 27 (replaces version 26)

Revision: 11.12.2024

**Trade name Konudur 170 BT - Komponente B**

(Contd. of page 12)

H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H318 Causes serious eye damage.  
H319 Causes serious eye irritation.  
H332 Harmful if inhaled.  
H361d Suspected of damaging the unborn child.  
H373 May cause damage to organs through prolonged or repeated exposure.  
H411 Toxic to aquatic life with long lasting effects.  
H412 Harmful to aquatic life with long lasting effects.

· **Department issuing data specification sheet:**

· **Abbreviations and acronyms:**

Environment protection department.

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (UK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Acute Tox. 4: Acute toxicity – Category 4

Skin Corr. 1B: Skin corrosion/irritation – Category 1B

Skin Corr. 1C: Skin corrosion/irritation – Category 1C

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Skin Sens. 1A: Skin sensitisation – Category 1A

Skin Sens. 1B: Skin sensitisation – Category 1B

Repr. 2: Reproductive toxicity – Category 2

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

· **\* Data compared to the previous version altered.**

GB