

Page 1/12

Safety data sheet according to UK REACH

Printing date 14.04.2025 Version number 53 (replaces version 52) Revision: 14.04.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

Trade name <u>MBC-VT 116 - Komponente A</u>

· Article number: 2431

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

Suctor of Use SU22 Professional uses: Public domain (administration,

education, entertainment, services, craftsmen)

· Application of the substance

/ the mixture Epoxy impregnation

1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier: MC-Bauchemie Müller GmbH & Co. KG

Am Kruppwald 1-8 D-46238 Bottrop Tel.: +49(0)2041-101-0 Fax.: +49(0)2041-101-400 E-Mail: info@mc-bauchemie.de

MC-Bauchemie AG Hagackerstr. 10 CH-8953 Dietikon Tel.: +44-7400510 Fax: +44-7400533

Informing department:

1.4 Emergency telephone

number:

Tel.: +49 / (0)700 24112112 (MCR)

Tel.: +1 872 5888271 (MCR)

msds@mc-bauchemie.de

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.
Skin Sens. 1 H317 May cause an allergic skin reaction.

Repr. 1B H360F May damage fertility.

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

· 2.2 Label elements

Labelling according to

Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms







HS07 GHS08 GHS

(Contd. on page 2)



Page 2/12

Safety data sheet according to UK REACH

Printing date 14.04.2025 Version number 53 (replaces version 52) Revision: 14.04.2025

Trade name MBC-VT 116 - Komponente A

(Contd. of page 1)

· Signal word

· Hazard statements

· Hazard-determining

components of labelling: 4.4'-Methylenediphenyldialycidyl ether

Danger

Oxirane, mono((C12-14-alkyloxy)methyl)derivatives

[[(2-ethylhexyl)oxy]methyl]oxirane

Reaction mass of 2.2'-[methylenebis(2.1-phenyleneoxymethylene)] bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)] bis(oxirane) and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}

methyl)oxirane

Reaction products of hexane-1,6-diol with 2-(chloromethyl)oxirane

(1:2)

Phenol, methylstyrolised H315 Causes skin irritation.

H319 Causes serious eye irritation. H317 May cause an allergic skin reaction.

H360F May damage fertility.

H411 Toxic to aquatic life with long lasting effects.

· Precautionary statements P261 Avoid breathing dust/fume/gas/mist/vapours/

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye

protection/face protection/hearing protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for

several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/

attention.

P405 Store locked up.

· Additional information: EUH205 Contains epoxy constituents. May produce an allergic

reaction.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· PBT: Not applicable. · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Mixture consisting of the following components.

Dangerous components:

CAS: 1675-54-3 4,4'-Methylenediphenyldiglycidyl ether 60-80%

Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319;

Skin Sens. 1, H317

(Contd. on page 3)



Page 3/12

Safety data sheet according to UK REACH

Printing date 14.04.2025 Version number 53 (replaces version 52) Revision: 14.04.2025

Trade name MBC-VT 116 - Komponente A

	(Co	ntd. of page 2
CAS: 2461-15-6	[[(2-ethylhexyl)oxy]methyl]oxirane	≥1-<10%
EINECS: 219-553-6	Chair irric. 2, 170 TG, Chair Corio. 1, 170 Tr	
CAS: 9003-36-5	Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane	≥2.5-<5%
	Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Skin Sens. 1, H317	
CAS: 68609-97-2	Oxirane, mono((C12-14-alkyloxy)methyl)derivatives	≥1-<5%
EINECS: 271-846-8	Repr. 1B, H360F; Skin Irrit. 2, H315; Skin Sens. 1, H317	
CAS: 933999-84-9	Reaction products of hexane-1,6-diol with 2-(chloromethyl)oxirane (1:2)	≥2.5-<5%
	Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; Aquatic Chronic 3, H412	
	Phenol, methylstyrolised	≥2.5-<3%
	Skin Irrit. 2, H315; Skin Sens. 1, H317; Aquatic Chronic 3, H412	
· Additional informa	tion For the wording of the listed hazard phrases refer to see	tion 16

SECTION 4: First aid measures

· 4.1 Description of first aid measures

General information Remove contaminated clothing immediately. Consult a doctor if

symptoms occur. Move affected person to fresh air.

· After inhalation Supply fresh air; seek medical advice if symptoms occur.

If unconscious, place in recovery position and seek medical advice.

• After skin contact In case of contact with skin, wash carefully with plenty of soap and

water. Consult a doctor in case of skin reactions.

· After eye contact Rinse opened eye for several minutes under running water.

Call a doctor immediately

· After swallowing Rinse mouth with water. Never give anything by mouth to an

unconscious person. DO NOT induce vomiting. If symptoms

persist, consult a doctor.

· 4.2 Most important symptoms and effects, both acute and

delayed

Advice for the doctor: Elementary aid, decontamination,

symptomatic treatment.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

• Suitable extinguishing agents CO2, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam.

· For safety reasons unsuitable

extinguishing agents

Water with a full water jet.

5.2 Special hazards arising from the substance or

mixture Can be released in case of fire

(Contd. on page 4)



Page 4/12

Safety data sheet according to UK REACH

Printing date 14.04.2025 Version number 53 (replaces version 52) Revision: 14.04.2025

Trade name MBC-VT 116 - Komponente A

(Contd. of page 3)

Carbon monoxide (CO) *Nitrogen oxides (NOx)* (Traces)

5.3 Advice for firefighters

· Protective equipment: Wear self-contained breathing apparatus.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

· 6.2 Environmental precautions:

Wear protective equipment. Keep unprotected persons away.

Prevent material from reaching sewage system, holes and cellars. Inform respective authorities in case product reaches water or

sewage system.

· 6.3 Methods and material for

containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders,

universal binders, sawdust). Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Open and handle containers with care.

Ventilation measures are required in rooms without sufficient air exchange (e.g. closed rooms),

because the occupational exposure limit values (see chapter 8)

could be exceeded. This must be avoided.

Wear suitable personal protective equipment (see section 8). Avoid contact with eyes, skin and clothing. Change contaminated or damaged gloves and contaminated clothing immediately and wash skin immediately. Mix slowly, partially covering the mixing container. Pour carefully and slowly when repotting. Observe the BGBau technical data sheet and practical guide for handling epoxy resins.

· Information about protection

against explosions and fires: Ensure sufficient air exchange and/or extraction in the working

areas. Take precautionary measures to avoid electrostatic

discharges.

· 7.2 Conditions for safe storage, including any incompatibilities

Storage

· Requirements to be met by

storerooms and containers: No special requirements.

(Contd. on page 5)



Page 5/12

Safety data sheet according to UK REACH

Printing date 14.04.2025 Version number 53 (replaces version 52) Revision: 14.04.2025

Trade name MBC-VT 116 - Komponente A

(Contd. of page 4)

· Information about storage in

one common storage facility: Store away from foodstuffs.

· Further information about

storage conditions: None.
Storage class 6.1C

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Components with critical

values that require

monitoring at the workplace: The product does not contain any relevant quantities of materials

with critical values that have to be monitored at the workplace.

· DNELs

CAS: 2461-15-6 [[(2-ethylhexyl)oxy]methyl]oxirane

Dermal DNEL 4.17 mg/kg bw/day (ArL)

CAS: 68609-97-2 Oxirane, mono((C12-14-alkyloxy)methyl)derivatives

Dermal DNEL 0.75 mg/kg bw/day (ArL)

Inhalative DNEL 0.49 mg/m³ (ArL)

· PNECs

CAS: 2461-15-6 [[(2-ethylhexyl)oxy]methyl]oxirane

PNEC 0.0072 mg/l (Fresh water)

PNEC 57.16 mg/kg dwt (Bod)

28.66 mg/kg dwt (Sediment)

286.66 mg/kg dwt (Fresh water sediment)

CAS: 68609-97-2 Oxirane, mono((C12-14-alkyloxy)methyl)derivatives

PNEC 0.00072 mg/l (Mew)

0.0072 mg/l (Freshwater)

PNEC 80.12 mg/kg dwt (Bod)

6.677 mg/kg dwt (Sediment)

66.77 mg/kg dwt (Fresh water sediment)

• Additional information: The lists that were valid during the compilation were used as basis.

· 8.2 Exposure controls

· Appropriate engineering

controls No further data; see section 7.

· Individual protection measures, such as personal protective equipment

General protective and

hygienic measures Keep away from food, drink and animal feed.

Remove soiled, soaked clothing immediately.
Wash hands before breaks and at the end of work.

Avoid contact with eyes and skin.

· Breathing equipment: If workplace limit values cannot be complied with by ventilation

measures or if rooms cannot be technically ventilated, respiratory protection must be worn: Use combination filter A1-P2 (brown/

(Contd. on page 6)



Page 6/12

Safety data sheet according to UK REACH

Printing date 14.04.2025 Version number 53 (replaces version 52) Revision: 14.04.2025

Trade name MBC-VT 116 - Komponente A

(Contd. of page 5)

white) in rooms that cannot be ventilated. If oxygen deficiency is expected, use self-contained breathing apparatus. Observe wearing time limits according to §9 (3) GefStoffV in conjunction with BGR 190.

· Hand protection

Selection of the glove material on consideration of the penetration

times, rates of diffusion and the degradation

· Material of gloves

You can find help with choosing gloves on the website https://www.bgbau.de/fileadmin/Gisbau/Projekte.pdf

For example, we recommend the Sol-vex 37-900 protective gloves from Ansell GmbH. The breakthrough time of the protective gloves can be found under point 8 "Penetration time of the glove material". The selection of a suitable glove depends not only on the material, but also on other quality features and varies from manufacturer to manufacturer. As the product

is a preparation of several substances, the resistance of glove materials cannot be calculated in advance and must therefore be checked before use.

Nitrile rubber

Recommended material thickness:≥ 0.4 mm

· Penetration time of glove material

The breakthrough times of the Sol-vex 37-900 protective gloves

are around 8 hours.

The following applies to all other gloves:

The exact breakthrough time must be obtained from the protective

glove manufacturer and adhered to.

Nitrile rubber

Material thickness: \geq 0.40 mm Penetration time: \geq 480 min

Butyl rubber:

Material thickness: ≥ 0.5 mm Penetration time: ≥ 480 min Tight-fitting safety goggles.

· Body protection:

· Eye/face protection

Safety goggles.
Protective clothing

Suitable protective clothing should be worn when working with epoxy resins. In addition to normal work clothing (long trousers, long-sleeved shirt or T-shirt), disposable overalls, aprons, overshoes, sleeve protectors etc. may be necessary depending on the activity. Uncovered areas of skin should be avoided as far as possible, even in hot weather. If the work involves kneeling, the lower leg area should be protected by protective trousers.

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Colour: Transparent

(Contd. on page 7)



Page 7/12

Safety data sheet according to UK REACH

Printing date 14.04.2025 Version number 53 (replaces version 52) Revision: 14.04.2025

Trade name MBC-VT 116 - Komponente A

(Contd. of page 6)

Smell: CharacteristicMelting point/freezing point: Not determined

Boiling point or initial boiling point and

boiling range >200 °C

· Lower and upper explosion limit

· Lower: 1.3 Vol %
 · Upper: 13 Vol %
 · Flash point: 101 °C
 · Auto-ignition temperature: 184 °C

· pH Not determined.

Viscosity:

Kinematic viscositydynamic at 20 °C:Not determined.2000 mPas

Solubility

Water: Not miscible or difficult to mix

· Steam pressure at 20 °C: 0.1 hPa

· Density and/or relative density

Density at 20 °C 1.12 g/cm³

· 9.2 Other information

· Corrosive to metals

· Appearance:

· Form: Fluid

· Important information on protection of health

and environment, and on safety.

• Self-inflammability: Product is not selfigniting. Explosive properties: Product is not explosive.

Void

· Information with regard to physical hazard

classes

· Explosives Void Flammable gases Void Void Aerosols · Oxidising gases Void · Gases under pressure Void Flammable liquids Void Flammable solids Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void · Pyrophoric solids Void Self-heating substances and mixtures Void · Substances and mixtures, which emit flammable gases in contact with water Void · Oxidising liquids Void · Oxidising solids Void · Organic peroxides Void

(Contd. on page 8)



Page 8/12

Safety data sheet according to UK REACH

Printing date 14.04.2025 Version number 53 (replaces version 52) Revision: 14.04.2025

Trade name MBC-VT 116 - Komponente A

(Contd. of page 7)

Desensitised explosives

Void

SECTION 10: Stability and reactivity

• 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability · Thermal decomposition /

conditions to be avoided: No decomposition if used according to specifications.

· 10.3 Possibility of hazardous

reactions No dangerous reactions known

• 10.4 Conditions to avoid No further relevant information available. • 10.5 Incompatible materials: No further relevant information available.

· 10.6 Hazardous

decomposition products: No dangerous decomposition products known

SECTION 11: Toxicological information

· 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

· Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50	values that	t are reievant fol	r ciassification:

CAS: 1675-54-3 4,4'-Methylenediphenyldiglycidyl ether

 Oral
 LD50
 11400 mg/kg (rat)

 Dermal
 LD50
 23000 mg/kg (rabbit)

 >2000 mg/kg (rat)
 >2000 mg/kg (rat)

CAS: 2461-15-6 [[(2-ethylhexyl)oxy]methyl]oxirane

 Oral
 LD50
 5000 mg/kg (rat)

 Dermal
 LD50
 2000 mg/kg (rat)

CAS: 9003-36-5 Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)] bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)] bis(oxirane) and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)

oxirane

Oral LD50 >2000 mg/kg (rat)

Dermal LD50 >2000 mg/kg (rabbit)

CAS: 68609-97-2 Oxirane, mono((C12-14-alkyloxy)methyl)derivatives

Oral LD50 17100 mg/kg (rat)

Primary irritant effect:

· Skin corrosion/irritation Causes skin irritation.

· Serious eye damage/irritation Causes serious eye irritation.

· Respiratory or skin

sensitisation May cause an allergic skin reaction.

• Germ cell mutagenicity
• Carcinogenicity

Based on available data, the classification criteria are not met.

Based on available data, the classification criteria are not met.

· Reproductive toxicity May damage fertility.

· STOT-single exposure Based on available data, the classification criteria are not met.

(Contd. on page 9)



Page 9/12

Safety data sheet according to UK REACH

Printing date 14.04.2025 Version number 53 (replaces version 52) Revision: 14.04.2025

Trade name MBC-VT 116 - Komponente A

(Contd. of page 8)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Based on available data, the classification criteria are not met.

· 11.2 Information on other hazards

· Endocrine disrupting properties		
	Phenol, methylstyrolised	List II
CAS: 128-3	37-0 2,6-Di-tert-butyl-p-cresol	List II

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:	
---------------------	--

CAS: 1675-54-3 4,4'-Methylenediphenyldiglycidyl ether

LC50/72h >11 mg/l (algae) IC50 >42.6 mg/l (Bak)

LC50/96h 2 mg/l (Oncorhynchus mykiss)

1.3 mg/l (fish)

EC50/48h 2.1 mg/l (daphnia)

1.8 mg/l (Daphnia magna)

ErC50/72h 11 mg/l (Selenastrum capricornutum)

CAS: 9003-36-5 Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)] bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)] bis(oxirane) and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl) oxirane

LC50/96h >100 mg/l (Daphnia magna) EC50/96h >100 mg/l (Leucidus idus)

CAS: 68609-97-2 Oxirane, mono((C12-14-alkyloxy)methyl)derivatives

EbC50/72h 843 mg/l (Pseudokirchneriella subcapitata)

LC50/96h | >5000 mg/l (Oncorhynchus mykiss)

1800 mg/l (Lepomis macrochirus)

EC50 >100 mg/l (BEL)

NOEC 500 mg/l (Pseudokirchneriella subcapitata)

12.2 Persistence and

degradability No further relevant information available.

· 12.3 Bioaccumulative

potential
No further relevant information available.

12.4 Mobility in soil
No further relevant information available.

· 12.5 Results of PBT and vPvB assessment · PBT: Not applicable. · vPvB: Not applicable.

· 12.6 Endocrine disrupting

properties For information on endocrine disrupting properties see section 11.

(Contd. on page 10)

- GB



Page 10/12

Safety data sheet according to UK REACH

Version number 53 (replaces version 52) Revision: 14.04.2025 Printing date 14.04.2025

Trade name MBC-VT 116 - Komponente A

(Contd. of page 9)

· 12.7 Other adverse effects

· Additional ecological information:

· General notes: Do not allow product to reach ground water, water bodies or

sewage system.

Danger to drinking water if even small quantities leak into soil.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation Must not be disposed of together with household garbage. Do not

allow product to reach sewage system.

· Uncleaned packagings:

Empty contaminated packagings thoroughly. They can be recycled · Recommendation:

after thorough and proper cleaning.

UN number or ID number R, IMDG, IATA	UN3082
UN proper shipping name	
R, IATA	ENVIRONMENTALLY HAZARDOU SUBSTANCE, LIQUID, N.O.S. (Epoxide resin)
G	ENVIRONMENTALLY HAZARDOU
	SUBSTANCE, LIQUID, N.O.S. (Epoxide resin
	MARINE POLLUTANT
Transport hazard class(es)	
?	
s	9 (M6) Miscellaneous dangerous substances ar
-1	articles. 9
el 	
G, IATA	
s	9 Miscellaneous dangerous substances an
e/	articles. 9
<u> </u>	9
Packing group	
R, IMDG, IATA	III
Environmental hazards:	
ne pollutant:	Yes
	Symbol (fish and tree)
	,
cial marking (ADR): cial marking (IATA):	Symbol (fish and tree) Symbol (fish and tree) Symbol (fish and tree)





Safety data sheet according to UK REACH

Printing date 14.04.2025 Version number 53 (replaces version 52) Revision: 14.04.2025

Trade name MBC-VT 116 - Komponente A

	(Contd. of page 1
14.6 Special precautions for user	Warning: Miscellaneous dangerous substances and articles.
Kemler Number:	90
EMS Number:	F-A,S-F
Stowage Category	Α
14.7 Maritime transport in bulk accordi	ing to
IMO instruments	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 100 ml
Transport category	3
Tunnel restriction code	(-)
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 100 ml
UN "Model Regulation":	UN 3082 ENVIRONMENTALLY HAZARDOU
	SUBSTANCE, LIQUID, N.O.S. (EPOXIDE RESIN 9. III

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Poisons Act
- · Regulated explosives precursors

None of the ingredients is listed.

· Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors

None of the ingredients is listed.

· Reportable poisons

None of the ingredients is listed.

(Contd. on page 12)



Page 12/12

Safety data sheet according to UK REACH

Version number 53 (replaces version 52) Revision: 14.04.2025 Printing date 14.04.2025

Trade name MBC-VT 116 - Komponente A

(Contd. of page 11)

· Directive 2012/18/EU

Qualifying quantity (tonnes) for the application of lower-

tier requirements 200 t

Qualifying quantity (tonnes) for the application of upper-

tier requirements 15.2 Chemical safety

assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases H315 Causes skin irritation.

500 t

H317 May cause an allergic skin reaction. H319 Causes serious eye irritation.

H360F May damage fertility.

H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects.

· Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International

Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous

Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (UK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation - Category 1 Repr. 1B: Reproductive toxicity - Category 1B

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic

hazard - Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic

hazard - Category 3

· * Data compared to the previous version altered.