



BE SURE. BUILD SURE.

Page 1/14

Safety data sheet according to UK REACH

Printing date 14.04.2025

Version number 46 (replaces version 45)

Revision: 14.04.2025

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

· 1.1 Product identifier

· Trade name **MBC-VT 116 - Komponente B**

· Article number: 2432

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance / the mixture

Epoxy impregnation
Hardening agent/ Curing agent

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier: MC-Bauchemie Müller GmbH & Co. KG
Am Kruppwald 1-8
D-46238 Bottrop
Tel.: +49(0)2041-101-0
Fax.: +49(0)2041-101-400
E-Mail: info@mc-bauchemie.de

MC-Bauchemie AG
Hagackerstr. 10
CH-8953 Dietikon
Tel.: +44-7400510
Fax : +44-7400533

· Informing department: msds@mc-bauchemie.de

· 1.4 Emergency telephone number:

Tel.: +49 / (0)700 24112112 (MCR)
Tel.: +1 872 5888271 (MCR)

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

Acute Tox. 4	H302	Harmful if swallowed.
Acute Tox. 4	H312	Harmful in contact with skin.
Skin Corr. 1A	H314	Causes severe skin burns and eye damage.
Eye Dam. 1	H318	Causes serious eye damage.
Skin Sens. 1	H317	May cause an allergic skin reaction.
Repr. 2	H361fd	Suspected of damaging fertility. Suspected of damaging the unborn child.
STOT SE 3	H335	May cause respiratory irritation.
STOT RE 2	H373	May cause damage to organs through prolonged or repeated exposure.
Aquatic Chronic 3	H412	Harmful to aquatic life with long lasting effects.

· 2.2 Label elements

· Labelling according to

Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation.

(Contd. on page 2)

GB



BE SURE. BUILD SURE.

Safety data sheet according to UK REACH

Printing date 14.04.2025

Version number 46 (replaces version 45)

Revision: 14.04.2025

Trade name MBC-VT 116 - Komponente B

(Contd. of page 1)

Hazard pictograms



GHS05 GHS07 GHS08

Signal word

Danger

Hazard-determining components of labelling:

2-Methylpentamethylenediamine
Isophorone diamine
2-piperazin-1-ylethylamine
Polymer with amino-functional groups
Phenol, mono- and distyrolised

Hazard statements

H302 Harmful if swallowed.
H312 Harmful in contact with skin.
H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.
H361fd Suspected of damaging fertility. Suspected of damaging the unborn child.
H335 May cause respiratory irritation.
H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

H412 Harmful to aquatic life with long lasting effects.
P260 Do not breathe dusts or mists.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a POISON CENTER/doctor.
P321 Specific treatment (see on this label).
P362+P364 Take off contaminated clothing and wash it before reuse.
P403+P233 Store in a well-ventilated place. Keep container tightly closed.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable.
vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: Mixture consisting of the following components.

Dangerous components:

EC number: 949-140-2	Polymer with amino-functional groups Eye Dam. 1, H318; Skin Irrit. 2, H315; Skin Sens. 1B, H317	30-60%
----------------------	--	--------

(Contd. on page 3)



BE SURE. BUILD SURE.

**Safety data sheet
according to UK REACH**

Printing date 14.04.2025

Version number 46 (replaces version 45)

Revision: 14.04.2025

Trade name MBC-VT 116 - Komponente B

(Contd. of page 2)

CAS: 15520-10-2 EINECS: 239-556-6	2-Methylpentamethylenediamine Skin Corr. 1A, H314; Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; STOT SE 3, H335	≥20-≤30%
CAS: 100-51-6 EINECS: 202-859-9	Benzyl alcohol Acute Tox. 4, H302; Acute Tox. 4, H332; Eye Irrit. 2, H319	10-30%
CAS: 2855-13-2 EINECS: 220-666-8 Reg.nr.: 01-2119514687-32	Isophorone diamine Skin Corr. 1B, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1, H317; Aquatic Chronic 3, H412 ATE: LD50 oral: 1030 mg/kg Specific concentration limit: Skin Sens. 1A; H317: C ≥ 0.001 %	≥10-<25%
CAS: 140-31-8 EINECS: 205-411-0 Reg.nr.: 01-2119471486-30	2-piperazin-1-ylethylamine Repr. 2, H361fd; STOT RE 1, H372; Skin Corr. 1B, H314; Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1, H317; Aquatic Chronic 3, H412	≥5-<10%
	Phenol, mono- and distyrolised Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Skin Sens. 1A, H317	≥1-<1.5%

· **Additional information**

For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· **4.1 Description of first aid measures**

- **General information** Remove contaminated clothing immediately. Consult a doctor if symptoms occur. Move affected person to fresh air.
- **After inhalation** Supply fresh air; seek medical advice if symptoms occur.
If unconscious, place in recovery position and seek medical advice.
- **After skin contact** In case of contact with skin, wash carefully with plenty of soap and water. Consult a doctor in case of skin reactions.
- **After eye contact** Rinse opened eye for several minutes under running water.
Call a doctor immediately
- **After swallowing** Rinse mouth with water. Never give anything by mouth to an unconscious person. DO NOT induce vomiting. If symptoms persist, consult a doctor.
- **4.2 Most important symptoms and effects, both acute and delayed** Advice for the doctor: Elementary aid, decontamination, symptomatic treatment.
- **Danger** Danger of gastric perforation.

GB

(Contd. on page 4)



BE SURE. BUILD SURE.

Safety data sheet according to UK REACH

Printing date 14.04.2025

Version number 46 (replaces version 45)

Revision: 14.04.2025

Trade name **MBC-VT 116 - Komponente B**

(Contd. of page 3)

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents** Use fire fighting measures that suit the environment.
- **5.2 Special hazards arising from the substance or mixture**
 - Can be released in case of fire
 - Carbon monoxide (CO)
 - Nitrogen oxides (NO_x)
 - (Traces)
- **5.3 Advice for firefighters**
- **Protective equipment:** Wear self-contained breathing apparatus.
Put on breathing apparatus.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
 - Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**
 - Inform respective authorities in case product reaches water or sewage system.
- **6.3 Methods and material for containment and cleaning up:** Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Use neutralising agent.
Dispose of contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **6.4 Reference to other sections**
 - See Section 8 for information on personal protection equipment.
 - See Section 7 for information on safe handling

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
 - Open and handle containers with care.
 - Ventilation measures are required in rooms without sufficient air exchange (e.g. closed rooms), because the occupational exposure limit values (see chapter 8) could be exceeded. This must be avoided.
 - Wear suitable personal protective equipment (see section 8). Avoid contact with eyes, skin and clothing. Change contaminated or damaged gloves and contaminated clothing immediately and wash skin immediately. Mix slowly, partially covering the mixing container. Pour carefully and slowly when repotting. Observe the BGBau technical data sheet and practical guide for handling epoxy resins.

(Contd. on page 5)



BE SURE. BUILD SURE.

Safety data sheet according to UK REACH

Printing date 14.04.2025

Version number 46 (replaces version 45)

Revision: 14.04.2025

Trade name MBC-VT 116 - Komponente B

(Contd. of page 4)

- **Information about protection against explosions and fires:** *Ensure sufficient air exchange and/or extraction in the working areas. Take precautionary measures to avoid electrostatic discharges.*
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage**
- **Requirements to be met by storerooms and containers:** *No special requirements.*
- **Information about storage in one common storage facility:** *Store away from foodstuffs.*
- **Further information about storage conditions:** *None.*
- **Storage class** *8A*

SECTION 8: Exposure controls/personal protection

- **8.1 Control parameters**
- **Components with critical values that require monitoring at the workplace:** *The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.*

· **DNELs**

CAS: 15520-10-2 2-Methylpentamethylenediamine

Dermal	DNEL	1.5 mg/kg bw/day (ArL)
Inhalative	DNEL	0.25 mg/m ³ (ArL)
		0.5 mg/m ³ (Ark)

CAS: 100-51-6 Benzyl alcohol

Oral	DNEL	4 mg/kg bw/Tag (ArL)
		20 mg/kg bw/Tag (Ark)
Dermal	DNEL	8 mg/kg bw/day (ArL)
		40 mg/kg bw/day (Ark)
Inhalative	DNEL	22 mg/m ³ (ArL)
		110 mg/m ³ (Ark)

CAS: 2855-13-2 Isophorone diamine

Oral	DNEL	0.526 mg/kg bw/Tag (ArL)
Inhalative	DNEL	20.1 mg/m ³ (ArL)

CAS: 140-31-8 2-piperazin-1-ylethylamine

Dermal	DNEL	3.33 mg/kg bw/day (ArL)
Inhalative	DNEL	10.6 mg/m ³ (ArL)

· **PNECs**

CAS: 15520-10-2 2-Methylpentamethylenediamine

PNEC	0.042 mg/l (Mew)
------	------------------

(Contd. on page 6)



BE SURE. BUILD SURE.

Safety data sheet according to UK REACH

Printing date 14.04.2025

Version number 46 (replaces version 45)

Revision: 14.04.2025

Trade name MBC-VT 116 - Komponente B

(Contd. of page 5)

	0.42 mg/l (Freshwater)
CAS: 100-51-6 Benzyl alcohol	
PNEC	0.527 mg/l (Marine water sediment) 0.1 mg/l (Mew) 1 mg/l (Fresh water sediment)
PNEC	0.456 mg/kg dwt (Bod) 5.27 mg/kg dwt (Fresh water sediment)
CAS: 2855-13-2 Isophorone diamine	
PNEC	0.006 mg/l (Mew) 0.06 mg/l (Freshwater)
PNEC	0.578 mg/kg dwt (Sediment) 5.784 mg/kg dwt (Fresh water sediment)
CAS: 140-31-8 2-piperazin-1-ylethylamine	
PNEC	250 mg/l (Kla) 0.0058 mg/l (Mew) 0.058 mg/l (Freshwater)
PNEC	1 mg/kg dwt (Bod) 21.5 mg/kg dwt (Sediment) 215 mg/kg dwt (Fresh water sediment)

· **Additional information:** The lists that were valid during the compilation were used as basis.

· **8.2 Exposure controls**

· **Appropriate engineering controls**

No further data; see section 7.

· **Individual protection measures, such as personal protective equipment**

· **General protective and hygienic measures**

Keep away from food, drink and animal feed.
Remove soiled, soaked clothing immediately.
Wash hands before breaks and at the end of work.
Avoid contact with eyes and skin.

· **Breathing equipment:**

If workplace limit values cannot be complied with by ventilation measures or if rooms cannot be technically ventilated, respiratory protection must be worn: Use combination filter A1-P2 (brown/white) in rooms that cannot be ventilated. If oxygen deficiency is expected, use self-contained breathing apparatus. Observe wearing time limits according to §9 (3) GefStoffV in conjunction with BGR 190.

· **Hand protection**

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

You can find help with choosing gloves on the website <https://www.bgbau.de/fileadmin/Gisbau/Projekte.pdf>

For example, we recommend the Sol-vex 37-900 protective gloves from Ansell GmbH. The breakthrough time of the protective gloves can be found under point 8 "Penetration time of the glove material". The selection of a suitable glove depends not only on the material, but also on other quality features and varies from manufacturer to

(Contd. on page 7)



BE SURE. BUILD SURE.

Page 7/14

Safety data sheet according to UK REACH

Printing date 14.04.2025

Version number 46 (replaces version 45)

Revision: 14.04.2025

Trade name MBC-VT 116 - Komponente B

(Contd. of page 6)

manufacturer. As the product is a preparation of several substances, the resistance of glove materials cannot be calculated in advance and must therefore be checked before use.

Nitrile rubber

Recommended material thickness: ≥ 0.4 mm

· **Penetration time of glove material**

The breakthrough times of the Sol-vex 37-900 protective gloves are around 8 hours.

The following applies to all other gloves:

The exact breakthrough time must be obtained from the protective glove manufacturer and adhered to.

Nitrile rubber

Material thickness: ≥ 0.40 mm

Penetration time: ≥ 480 min

Butyl rubber:

Material thickness: ≥ 0.5 mm

Penetration time: ≥ 480 min

· **Eye/face protection**

Tight-fitting safety goggles.

Safety goggles.

· **Body protection:**

Protective clothing

Suitable protective clothing should be worn when working with epoxy resins. In addition to normal work clothing (long trousers, long-sleeved shirt or T-shirt), disposable overalls, aprons, overshoes, sleeve protectors etc. may be necessary depending on the activity. Uncovered areas of skin should be avoided as far as possible, even in hot weather. If the work involves kneeling, the lower leg area should be protected by protective trousers.

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Colour:**

Transparent

· **Smell:**

Characteristic

· **Melting point/freezing point:**

Not determined

· **Boiling point or initial boiling point and boiling range**

>200 °C

· **Lower and upper explosion limit**

· **Lower:**

1.3 Vol %

· **Upper:**

13 Vol %

· **Flash point:**

101 °C

· **Auto-ignition temperature:**

380 °C

· **pH**

Not determined.

· **Viscosity:**

· **Kinematic viscosity**

Not determined.

· **dynamic at 20 °C:**

300 mPas

(Contd. on page 8)



BE SURE. BUILD SURE.

Safety data sheet according to UK REACH

Printing date 14.04.2025

Version number 46 (replaces version 45)

Revision: 14.04.2025

Trade name MBC-VT 116 - Komponente B

(Contd. of page 7)

- **Solubility**
- **Water:** Not miscible or difficult to mix
- **Steam pressure at 20 °C:** 0.1 hPa
- **Density and/or relative density**
- **Density at 20 °C** 0.98 g/cm³

- **9.2 Other information**
- **Appearance:**
- **Form:** Fluid
- **Important information on protection of health and environment, and on safety.**
- **Self-inflammability:** Product is not selfigniting.
- **Explosive properties:** Product is not explosive.

- **Information with regard to physical hazard classes**
- **Explosives** Void
- **Flammable gases** Void
- **Aerosols** Void
- **Oxidising gases** Void
- **Gases under pressure** Void
- **Flammable liquids** Void
- **Flammable solids** Void
- **Self-reactive substances and mixtures** Void
- **Pyrophoric liquids** Void
- **Pyrophoric solids** Void
- **Self-heating substances and mixtures** Void
- **Substances and mixtures, which emit flammable gases in contact with water** Void
- **Oxidising liquids** Void
- **Oxidising solids** Void
- **Organic peroxides** Void
- **Corrosive to metals** Void
- **Desensitised explosives** Void

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.

(Contd. on page 9)



BE SURE. BUILD SURE.

**Safety data sheet
according to UK REACH**

Printing date 14.04.2025

Version number 46 (replaces version 45)

Revision: 14.04.2025

Trade name MBC-VT 116 - Komponente B

(Contd. of page 8)

- **10.6 Hazardous decomposition products:** No dangerous decomposition products known

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Harmful if swallowed.
Harmful in contact with skin.

· **LD/LC50 values that are relevant for classification:**

CAS: 15520-10-2 2-Methylpentamethylenediamine

Oral	LD50	1170 mg/kg (rat)
Dermal	LD50	1870 mg/kg (rabbit)
Inhalative	LC50/4 h	19.6 mg/l (rat)

CAS: 100-51-6 Benzyl alcohol

Oral	LD50	1230 mg/kg (rat)
	NOAEL 2nd year study	200 mg/kg (mouse) 200 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rabbit)
Inhalative	LC50/4 h	>4178 mg/l (rat)

CAS: 2855-13-2 Isophorone diamine

Oral	LD50	1030 mg/kg (ATE) 1030 mg/kg (rat)
	NOAEL	250 mg/kg (rat)
Dermal	LD50	1840 mg/kg (rabbit) >2000 mg/kg (rat) 1840 mg/kg (rabbit)

CAS: 140-31-8 2-piperazin-1-ylethylamine

Oral	LD50	2000-5000 mg/kg (rat) 500 mg/kg (rabbit)
Dermal	LD50	200-1000 mg/kg (rabbit)

- **Primary irritant effect:**
- **Skin corrosion/irritation** Causes severe skin burns and eye damage.
- **Serious eye damage/irritation** Causes serious eye damage.
- **Respiratory or skin sensitisation** May cause an allergic skin reaction.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Suspected of damaging fertility. Suspected of damaging the unborn child.
- **STOT-single exposure** May cause respiratory irritation.
- **STOT-repeated exposure** May cause damage to organs through prolonged or repeated exposure.

(Contd. on page 10)



BE SURE. BUILD SURE.

Safety data sheet according to UK REACH

Printing date 14.04.2025

Version number 46 (replaces version 45)

Revision: 14.04.2025

Trade name MBC-VT 116 - Komponente B

(Contd. of page 9)

- **Aspiration hazard** Based on available data, the classification criteria are not met.
- **11.2 Information on other hazards**

· **Endocrine disrupting properties**

None of the ingredients is listed.

SECTION 12: Ecological information

· **12.1 Toxicity**

· **Aquatic toxicity:**

CAS: 15520-10-2 2-Methylpentamethylenediamine

EC50/72h	>100 mg/l (algae)
EC50	1825 mg/l (fish)
EC50/48h	19.8 mg/l (Daphnia magna)

CAS: 100-51-6 Benzyl alcohol

IC50/72h	700 mg/l (algae)
LC50/96h	460 mg/l (Pimephales promelas) 10 mg/l (Lepomis macrochirus)

CAS: 2855-13-2 Isophorone diamine

LC50/96h	110 mg/l (fish) 110 mg/l (Leucidus idus)
EC50	1120 mg/l (Pseudomonas putida)
EC50/48h	23 mg/l (daphnia) 23 mg/l (Daphnia magna)
NOEC	1.5 mg/l (Desmodesmus subspicatus) 3 mg/l (Daphnia magna)
ErC50/72h	>50 mg/l (Desmodesmus subspicatus) >50 mg/l (algae)

CAS: 140-31-8 2-piperazin-1-ylethylamine

EC50/72h	>1000 mg/l (algae)
LC50/96h	2190 mg/l (fish)

· **12.2 Persistence and degradability**

No further relevant information available.

· **12.3 Bioaccumulative potential**

No further relevant information available.

· **12.4 Mobility in soil**

No further relevant information available.

· **12.5 Results of PBT and vPvB assessment**

· **PBT:**

Not applicable.

· **vPvB:**

Not applicable.

· **12.6 Endocrine disrupting properties**

The product does not contain substances with endocrine disrupting properties.

(Contd. on page 11)



BE SURE. BUILD SURE.

Safety data sheet according to UK REACH

Printing date 14.04.2025

Version number 46 (replaces version 45)

Revision: 14.04.2025

Trade name MBC-VT 116 - Komponente B

(Contd. of page 10)

· **12.7 Other adverse effects**

- **Remark:** Toxic for fish
- **Additional ecological information:**
- **General notes:** Also poisonous for fish and plankton in water bodies.
Toxic for aquatic organisms
Must not reach sewage water or drainage ditch undiluted or unneutralised.
Do not allow product to reach ground water, water bodies or sewage system.
Danger to drinking water if even small quantities leak into soil.

SECTION 13: Disposal considerations

· **13.1 Waste treatment methods**

- **Recommendation** Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Empty contaminated packagings thoroughly. They can be recycled after thorough and proper cleaning.

SECTION 14: Transport information

· **14.1 UN number or ID number**

· **ADR, IMDG, IATA** UN2289

· **14.2 UN proper shipping name**

· **ADR, IMDG, IATA** ISOPHORONEDIAMINE solution

· **14.3 Transport hazard class(es)**

· **ADR**

· **Class** 8 (C7) Corrosive substances.

· **Label** 8

· **IMDG, IATA**

· **Class** 8 Corrosive substances.

· **Label** 8

· **14.4 Packing group**

· **ADR, IMDG, IATA** III

· **14.5 Environmental hazards:**

· **Marine pollutant:** No

· **14.6 Special precautions for user**

· **Warning:** Corrosive substances.

· **Kemler Number:** 80

· **EMS Number:** F-A, S-B

· **Stowage Category** A

(Contd. on page 12)



BE SURE. BUILD SURE.

Safety data sheet according to UK REACH

Printing date 14.04.2025

Version number 46 (replaces version 45)

Revision: 14.04.2025

Trade name MBC-VT 116 - Komponente B

(Contd. of page 11)

· Segregation Code	SG35 Stow "separated from" SGG1-acids
· 14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· Transport category	3
· Tunnel restriction code	E
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 2289 ISOPHORONEDIAMINE SOLUTION, 8, III

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/ legislation specific for the substance or mixture *No further relevant information available.*
- Poisons Act

· Regulated explosives precursors

None of the ingredients is listed.

· Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors

None of the ingredients is listed.

· Reportable poisons

None of the ingredients is listed.

· 15.2 Chemical safety assessment:

A Chemical Safety Assessment has not been carried out.

GB

(Contd. on page 13)



BE SURE. BUILD SURE.

Page 13/14

Safety data sheet according to UK REACH

Printing date 14.04.2025

Version number 46 (replaces version 45)

Revision: 14.04.2025

Trade name MBC-VT 116 - Komponente B

(Contd. of page 12)

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H302 Harmful if swallowed.
H312 Harmful in contact with skin.
H314 Causes severe skin burns and eye damage.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H361fd Suspected of damaging fertility. Suspected of damaging the unborn child.
H372 Causes damage to organs through prolonged or repeated exposure.
H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
ICAO: International Civil Aviation Organisation
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
DNEL: Derived No-Effect Level (UK REACH)
PNEC: Predicted No-Effect Concentration (UK REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
ATE: Acute toxicity estimate values
Acute Tox. 4: Acute toxicity – Category 4
Skin Corr. 1A: Skin corrosion/irritation – Category 1A
Skin Corr. 1B: Skin corrosion/irritation – Category 1B
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Skin Sens. 1: Skin sensitisation – Category 1
Skin Sens. 1A: Skin sensitisation – Category 1A
Skin Sens. 1B: Skin sensitisation – Category 1B
Repr. 2: Reproductive toxicity – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

(Contd. on page 14)

GB



BE SURE. BUILD SURE.

Page 14/14

**Safety data sheet
according to UK REACH**

Printing date 14.04.2025

Version number 46 (replaces version 45)

Revision: 14.04.2025

Trade name MBC-VT 116 - Komponente B

**· * Data compared to the
previous version altered.**

(Contd. of page 13)

GB