

Page 1/10

Safety data sheet

according to UK REACH

Printing date 01.03.2025

Version number 20 (replaces version 19)

Revision: 01.03.2025

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

Trade name 1.2 Relevant identified uses	MC-Adhesive PU solid - Komponente A
of the substance or mixture and uses advised against Application of the substance	No further relevant information available.
/ the mixture	Adhesives
[.] 1.3 Details of the supplier of t	he safety data sheet
Manufacturer/Supplier:	MC-Bauchemie Müller GmbH & Co. KG Am Kruppwald 1-8 D-46238 Bottrop Tel.: +49(0)2041-101-0 Fax.: +49(0)2041-101-400 E-Mail: info@mc-bauchemie.de MC-Bauchemie AG Hagackerstr. 10 CH-8953 Dietikon Tel.: +44-7400510 Fax : +44-7400533
Informing department: 1.4 Emergency telephone	msds@mc-bauchemie.de
number:	Tel.: +49 / (0)700 24112112 (MCR) Tel.: +1 872 5888271 (MCR)

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

· Classification according to

Regulation (EC) No 1272/2008 The product is not classified, according to the GB CLP regulation.

· 2.2 Label elements

- Labelling according to
- Regulation (EC) No 1272/2008 Void
- · Hazard pictograms Void
- Signal word Void
- Hazard statements Void
 2.3 Other hazards
- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- vPvB: Not appli
 - Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description:

Resin mixture.

(Contd. on page 2)

GB



Page 2/10

Safety data sheet according to UK REACH

Printing date 01.03.2025

Version number 20 (replaces version 19)

Revision: 01.03.2025

Trade name MC-Adhesive PU solid - Komponente A

	(Co Mixture of the substances listed below with harmless ad	ontd. of page 1) dditions.
 Dangerous comport 	ents:	
	Calcium carbonate substance with a Community workplace exposure limit	30-60%
CAS: 13463-67-7 EINECS: 236-675-5	Titanium dioxide Carc. 2, H351	<1%
· Additional informat	ion For the wording of the listed hazard phrases refer to se	ction 16.

SECTION 4: First aid measures

• 4.1 Description of first aid me	35/1705
· General information	Remove, decontaminate and dispose of soiled, soaked clothing
	and shoes immediately.
· After inhalation	Remove person to fresh air, keep warm, allow to rest; if breathing is difficult, seek medical attention.
· After skin contact	In case of contact with skin, preferably wash with polyethylene glycol-based cleaner or clean with plenty of warm water and soap.
	Consult a doctor in case of skin reactions.
· After eye contact	Rinse the eyes with open eyelids for a sufficiently long time (at least 10 minutes) with water that is as lukewarm as possible. Consult an ophthalmologist.
· After swallowing	Do NOT induce vomiting. Rinse mouth with water. Medical attention required.
· 4.2 Most important symptoms	; ;
and effects, both acute and	
delayed	Information for the doctor: The product irritates the respiratory tract and is a potential trigger for skin and respiratory sensitisation. Treatment of acute irritation or bronchial constriction is primarily symptomatic. Depending on the extent of exposure and the symptoms, prolonged medical treatment may be necessary.
 4.3 Indication of any 	
immediate medical attention	
and special treatment needed	No information available.

SECTION 5: Firefighting measures • 5.1 Extinguishing media • Suitable extinguishing agents Use fire fighting measures that suit the environment. • 5.2 Special hazards arising from the substance or mixture • 5.3 Advice for firefighters • Protective equipment:

(Contd. on page 3)

GB



Page 3/10

Safety data sheet according to UK REACH

Printing date 01.03.2025

Version number 20 (replaces version 19)

Revision: 01.03.2025

Trade name MC-Adhesive PU solid - Komponente A

(Contd. of page 2)

SECTION 6: Accidental release measures

 6.1 Personal precautions, protective equipment and 	
emergency procedures	Not required.
· 6.2 Environmental	,
precautions:	No special measures required.
⁶ .3 Methods and material for	
containment and cleaning up	Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
[•] 6.4 Reference to other	
sections	No dangerous materials are released.

SECTION 7: Handling and storage

 7.1 Precautions for safe handling 	Ensure sufficient air exchange and/or extraction in the work areas. Air extraction is required for spray application. For solid products: Avoid dust formation and dust deposits. Air limit values mentioned in section 8 must be monitored. At workplaces where isocyanate aerosols and/or vapours can occur in higher concentrations, targeted air extraction must be used to prevent the occupational hygiene limit value from being exceeded. The air must be moved away from people. For products containing solvents: Explosion protection required. The personal protective measures described in section 8 must be observed. The protective measures required when handling isocyanates must be observed. Avoid contact with skin and eyes and inhalation of vapours. Keep away from food and beverages. Wash hands before breaks and at the end of work and apply skin protection ointment. Store work clothes separately. Remove soiled, soaked clothing immediately.
 7.2 Conditions for safe storage, including any incompatibilities 	Keep container dry and tightly closed. Further information on the storage conditions that must be observed for quality assurance reasons can be found in our technical data sheet.
 Storage Requirements to be met by storerooms and containers: Further information about storage conditions: Storage class 7.3 Specific end use(s) 	Store only in the original container. None. 12 No further relevant information available.

(Contd. on page 4)



Page 4/10

Safety data sheet according to UK REACH

Printing date 01.03.2025

Version number 20 (replaces version 19)

Revision: 01.03.2025

Trade name MC-Adhesive PU solid - Komponente A

(Contd. of page 3)

SECTION 8: Exposure	controls/personal protection
8.1 Control parameters	
-	values that require monitoring at the workplace:
CAS: 1317-65-3 Calcium ca	arbonate
WEL Long-term value: 10* 4	
*inhalable dust; **resp	irable
DNELs	
CAS: 1317-65-3 Calcium ca	arbonate
Oral DNEL 6.1 mg/kg	bw/Tag (ArL)
Inhalative DNEL 10 mg/m ³	(ArL)
PNECs	
CAS: 1317-65-3 Calcium ca	arbonate
PNEC 100 mg/l (Sewage Tr	
Additional information:	The lists that were valid during the compilation were used as bas
8.2 Exposure controls Appropriate engineering	
controls	No further data; see section 7.
	sures, such as personal protective equipment
General protective and	
hygienic measures	Keep away from food, drink and animal feed.
	Remove soiled, soaked clothing immediately.
	Wash hands before breaks and at the end of work.
Draathing any inmants	Avoid contact with eyes and skin.
Breathing equipment:	Respiratory protection required at insufficiently ventilat workplaces and when working with splashes. Fresh air masks
	combination filters A2-P2 (EN529) are recommended for she
	term work.
	If applicable, further recommendations for respiratory protect
	can be found in the appendix.
	In case of hypersensitivity of the respiratory tract (asthma, chro
Hand protection	bronchitis), handling of the product is not recommended. Suitable materials for protective gloves; EN 374:
Hand protection	Butyl rubber, nitrile rubber, chloroprene rubber (neoprene).
	Note: suitable materials that provide sufficient protection
	industrial cleaning with aprotic polar solvents (according to IUP
	definition): butyl rubber.
	In case of prolonged or frequently repeated contact, a glove wit
	protection class of 5 or higher is recommended (breakthrough ti
	greater than 240 minutes according to EN374). For short-te contact, a glove with a protection class of 3 or higher
	recommended (breakthrough time greater than 60 minu
	according to EN374).
	The thickness of the material is not the only criterion for the leve
	protection of a glove against a chemical substance. The protect
	effect also depends to a large extent on the type of glove materia
	(Contd. on page



Page 5/10

GB

Safety data sheet according to UK REACH

Printing date 01.03.2025

Version number 20 (replaces version 19)

Revision: 01.03.2025

Trade name MC-Adhesive PU solid - Komponente A

	(Contd. of page 4) Depending on the type and material, the thickness must be more than 0.35 mm to ensure adequate protection in the event of prolonged and frequent contact. Exceptions to this rule are multi- layer gloves, which guarantee sufficient protection even with a thickness of less than 0.35 mm during prolonged wear. Other glove materials with a thickness of less than 0.35 mm only provide sufficient protection for short periods of wear. For solvent-free products: Example: Polychloroprene - CR: thickness ≥0.5mm; breakthrough time ≥480min. Nitrile rubber - NBR: thickness ≥0.35mm; breakthrough time ≥480min. Butyl rubber - IIR: thickness ≥0.5mm; breakthrough time ≥480min. Fluoro rubber - FKM: thickness ≥0.4mm; breakthrough time
	Recommendation: Dispose of contaminated gloves.
 Material of gloves 	Polychloroprene - CR
	Nitrile rubber - NBR
	Butyl rubber - IIR
	Fluoro rubber - FKM
Penetration time of glove	
material	Polychloroprene - CR: thickness ≥0.5mm; breakthrough time ≥480min.
	Nitrile rubber - NBR: thickness ≥0.35mm; breakthrough time >480min.
	Butyl rubber - IIR: thickness ≥0.5mm; breakthrough time ≥480min.
	Fluoro rubber - FKM: Thickness 20.4mm; Breakthrough time 2480min.
	-
 Eye/face protection Body protection: 	Safety goggles with side protection in accordance with EN 166. Use chemical-resistant protective clothing.
	In case of hypersensitivity of the skin, handling the product is not recommended.

SECTION 9: Physical and chemical properties

 9.1 Information on basic physical and c 	chemical properties
· General Information	
· Colour:	Grey
· Smell:	Characteristic
 Melting point/freezing point: 	Not determined
· Boiling point or initial boiling point and	I
boiling range	Not determined
· Flash point:	Not applicable
• Auto-ignition temperature:	>350 °C (triglyceride, polycondensate)
· pH	Not determined.
	(Contd. on page 6)



Page 6/10

Safety data sheet according to UK REACH

Printing date 01.03.2025

Version number 20 (replaces version 19)

Revision: 01.03.2025

Trade name MC-Adhesive PU solid - Komponente A

	(Contd. of p	age
Viscosity:		
Kinematic viscosity	Not determined.	
dynamic at 20 °C:	3950000 mPas	
Solubility		
Water:	Not miscible or difficult to mix	
Steam pressure:	Not determined.	
Density and/or relative density		
Density at 20 °C	1.8 g/cm³	
9.2 Other information		
Appearance:		
Form:	Pasty	
Important information on protection of hea		
and environment, and on safety.		
Self-inflammability:	Product is not selfigniting.	
Explosive properties:	Product is not explosive.	
classes Explosives	Void Void	
Flammable gases		
Aerosols	Void	
Oxidising gases	Void	
Gases under pressure	Void	
Flammable liquids	Void	
Flammable solids	Void	
Self-reactive substances and mixtures	Void	
Pyrophoric liquids	Void	
Pyrophoric solids	Void	
Self-heating substances and mixtures	Void	
Substances and mixtures, which emit		
flammable gases in contact with water	Void	
Oxidising liquids	Void	
Oxidising solids	Void	
Organic peroxides	Void	
Corrosive to metals	Void	
Desensitised explosives	Void	

SECTION 10: Stability and reactivity

· 10.1 Reactivity

No further relevant information available.

· 10.2 Chemical stability · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

· 10.3 Possibility of hazardous reactions

No dangerous reactions known

· 10.4 Conditions to avoid

No further relevant information available.

· 10.5 Incompatible materials: No further relevant information available.

(Contd. on page 7)

GB



Page 7/10

Safety data sheet

according to UK REACH

Printing date 01.03.2025

Version number 20 (replaces version 19)

Revision: 01.03.2025

(Contd. of page 6)

Trade name MC-Adhesive PU solid - Komponente A

 10.6 Hazardous decomposition products:

No dangerous decomposition products known

SECTION 11: Toxicological information

• **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008** • **Acute toxicity** Based on available data, the classification criteria are not met.

	,				
· LD/LC50	values tha	nt are releva	ant for classification:		
CAS: 1317-65-3 Calcium carbonate					
Oral	LD50	>2000 mg/	>2000 mg/kg (rat)		
Dermal	LD50	>2000 mg/kg (rat)			
CAS: 134	63-67-7 Ti	tanium dio	xide		
Oral	LD50 >5000 mg/kg (rat)		/kg (rat)		
Dermal	LD50	>10000 mg	>10000 mg/kg (rabbit)		
Inhalative	LC50/4 h	0/4 h >6.8 mg/l (rat)			
Respirato sensitisat Germ cell Carcinogo Reproduc STOT-sin STOT-rep Aspiration 11.2 Infor	osion/irrita ye damag ry or skin tion mutagen enicity tive toxic gle expos eated exp n hazard mation on	ation e/irritation icity ity ure			
	-	nts is listed.			
		113 13 113180.			

SECTION 12: Ecological information

· 12.1 Toxicity			
· Aquatic toxicity:	· Aquatic toxicity:		
CAS: 1317-65-3 Calciur	n carbonate		
EC50/72h >14 mg/l (De	smodesmus subspicatus)		
LC50/96h >10000 mg/l	.C50/96h >10000 mg/l (Oncorhynchus mykiss)		
LC50/48h >1000 mg/l (L	LC50/48h >1000 mg/l (Daphnia magna)		
EC50/48h >1000 mg/l (l	>1000 mg/l (Daphnia magna)		
12.2 Persistence and degradability 12.3 Bioaccumulative	No further relevant information available.		
potential	No further relevant information available.	(Contd. on page 8)	



Page 8/10

Safety data sheet according to UK REACH

Printing date 01.03.2025

5 Version number 20 (replaces version 19)

Revision: 01.03.2025

Trade name MC-Adhesive PU solid - Komponente A

· Additional ecological informa · General notes:	tion: Do not allow undiluted product or large quantities of it to reach
· 12.7 Other adverse effects	properties.
 12.6 Endocrine disrupting properties 	The product does not contain substances with endocrine disrupting
· vPvB:	Not applicable.
· PBT:	Not applicable.
· 12.5 Results of PBT and vPvB	assessment
· 12.4 Mobility in soil	(Contd. of page 7) No further relevant information available.

SECTION 13: Disposal considerations

 13.1 Waste treatment method Recommendation 	ds Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
 Uncleaned packagings: Recommendation: 	Dispose of packaging according to regulations on the disposal of packagings. Empty contaminated packagings thoroughly. They can be recycled after thorough and proper cleaning.

SECTION 14: Transport information

 14.1 UN number or ID number ADR, ADN, IMDG, IATA 	Void
 14.2 UN proper shipping name ADR, ADN, IMDG, IATA 	Void
· 14.3 Transport hazard class(es)	
· ADR, ADN, IMDG, IATA · Class	Void
· 14.4 Packing group · ADR, IMDG, IATA	Void
 14.5 Environmental hazards: Marine pollutant: 	No
· 14.6 Special precautions for user	Not applicable.
 14.7 Maritime transport in bulk according IMO instruments 	g to Not applicable.
• Transport/Additional information:	Not dangerous according to the above specifications.
	(Contd. on page



Page 9/10

(Contd. of page 8)

GB

Safety data sheet

according to UK REACH

Printing date 01.03.2025

Version number 20 (replaces version 19)

Void

Revision: 01.03.2025

Trade name MC-Adhesive PU solid - Komponente A

· UN "Model Regulation":

15.1 Safety, health and environmental regulations/ legislation specific for the substance or mixture Poisons Act	No further relevant information available.
Regulated explosives precur	sors
None of the ingredients is listed	1.
Regulated poisons	
None of the ingredients is listed	1.
Reportable explosives precu	rsors
None of the ingredients is listed	1.
Reportable poisons	
None of the ingredients is listed	1

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases	H351 Suspected of causing cancer.
 Department issuing data specification sheet: Abbreviations and acronyms: 	Environment protection department. RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) DNEL: Derived No-Effect Level (UK REACH) PNEC: Predicted No-Effect Concentration (UK REACH) LC50: Lethal concentration, 50 percent DD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Carc. 2: Carcinogenicity – Category 2 (Contd. on page 10)



Safety data sheet according to UK REACH

Printing date 01.03.2025

Version number 20 (replaces version 19)

Revision: 01.03.2025

Trade name MC-Adhesive PU solid - Komponente A

• * Data compared to the previous version altered.

(Contd. of page 9)

GB

Page 10/10