



BE SURE. BUILD SURE.

Page 1/13

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 13.05.2023

Version number 23 (replaces version 22)

Revision: 13.05.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name **MC-Ballastbond 60 - Komponente B**

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture

Epoxy resin adhesive
Hardening agent/ Curing agent

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: MC-Bauchemie Müller GmbH & Co. KG
Am Kruppwald 1-8
D-46238 Bottrop
Tel.: +49(0)2041-101-0
Fax.: +49(0)2041-101-400
E-Mail: info@mc-bauchemie.de

MC-Bauchemie AG
Hagackerstr. 10
CH-8953 Dietikon
Tel.: +44-7400510
Fax : +44-7400533

Informing department: msds@mc-bauchemie.de

1.4 Emergency telephone number:

Tel.: +49 / (0)700 24112112 (MCR)
Tel.: +48612864565

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Acute Tox. 4	H302	Harmful if swallowed.
Acute Tox. 4	H312	Harmful in contact with skin.
Skin Corr. 1A	H314	Causes severe skin burns and eye damage.
Eye Dam. 1	H318	Causes serious eye damage.
Skin Sens. 1	H317	May cause an allergic skin reaction.
Repr. 2	H361fd	Suspected of damaging fertility. Suspected of damaging the unborn child.
STOT RE 2	H373	May cause damage to organs through prolonged or repeated exposure.
Aquatic Chronic 2	H411	Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to

Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation.

(Contd. on page 2)

GB

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 13.05.2023

Version number 23 (replaces version 22)

Revision: 13.05.2023

Trade name MC-Ballastbond 60 - Komponente B

(Contd. of page 1)

· **Hazard pictograms**



GHS05 GHS07 GHS08 GHS09

· **Signal word**

Danger

· **Hazard-determining components of labelling:**

Benzyl alcohol
2-methylpentane-1,5-diamine
polymer amine terminated
2-piperazin-1-ylethylamine
Tetraethylenepentamine

· **Hazard statements**

H302 Harmful if swallowed.
H312 Harmful in contact with skin.
H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.
H361fd Suspected of damaging fertility. Suspected of damaging the unborn child.
H373 May cause damage to organs through prolonged or repeated exposure.

· **Precautionary statements**

H411 Toxic to aquatic life with long lasting effects.
P260 Do not breathe dusts or mists.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a POISON CENTER/doctor.
P321 Specific treatment (see on this label).
P362+P364 Take off contaminated clothing and wash it before reuse.

· **2.3 Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.
· **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· **3.2 Mixtures**

· **Description:** Mixture consisting of the following components.

(Contd. on page 3)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 13.05.2023

Version number 23 (replaces version 22)

Revision: 13.05.2023

Trade name MC-Ballastbond 60 - Komponente B

(Contd. of page 2)

· Dangerous components:

CAS: 100-51-6	Benzyl alcohol Acute Tox. 4, H302; Acute Tox. 4, H332; Eye Irrit. 2, H319	10-30%
CAS: 38640-62-9 EINECS: 254-052-6 Reg.nr.: 01-2119565150-48-0000	Diisopropylnaphthalin-Isomere Asp. Tox. 1, H304; Aquatic Chronic 1, H410	≥10-<25%
	polymer amine terminated Eye Dam. 1, H318; Skin Irrit. 2, H315; Skin Sens. 1B, H317	10-30%
CAS: 15520-10-2 EINECS: 239-556-6	2-methylpentane-1,5-diamine Skin Corr. 1A, H314; Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; STOT SE 3, H335	≥10-<20%
CAS: 90640-66-7 EINECS: 292-587-7 Reg.nr.: 01-2119487290-37	Tetraethylenepentamine Skin Corr. 1B, H314; Aquatic Chronic 2, H411; Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1, H317	≥10-<25%
CAS: 140-31-8 EINECS: 205-411-0 Reg.nr.: 01-2119471486-30	2-piperazin-1-ylethylamine Acute Tox. 3, H311; Repr. 2, H361fd; STOT RE 1, H372; Skin Corr. 1B, H314; Acute Tox. 4, H302; Skin Sens. 1, H317; Aquatic Chronic 3, H412	≥5-<10%

· Additional information

For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· General information

Instantly remove any clothing soiled by the product.
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation

Supply fresh air and call for doctor for safety reasons.
In case of unconsciousness bring patient into stable side position for transport.

· After skin contact

Instantly wash with water and soap and rinse thoroughly.

· After eye contact

Rinse opened eye for several minutes under running water. Then consult a doctor.

· After swallowing

Instantly call for doctor.

Drink copious amounts of water and provide fresh air. Instantly call for doctor.

· 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

(Contd. on page 4)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 13.05.2023

Version number 23 (replaces version 22)

Revision: 13.05.2023

Trade name MC-Ballastbond 60 - Komponente B

(Contd. of page 3)

- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents** CO₂, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam.
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** No special measures required.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures** Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:** Do not allow product to reach sewage system or water bodies. Inform respective authorities in case product reaches water or sewage system.
- **6.3 Methods and material for containment and cleaning up:** Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Use neutralising agent. Dispose of contaminated material as waste according to item 13. Ensure adequate ventilation.
- **6.4 Reference to other sections** See Section 7 for information on safe handling
See Section 8 for information on personal protection equipment.
See Section 13 for information on disposal.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Store in cool, dry place in tightly closed containers. Open and handle container with care.
- **Information about protection against explosions and fires:** No special measures required.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage**
- **Requirements to be met by storerooms and containers:** No special requirements.

(Contd. on page 5)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 13.05.2023

Version number 23 (replaces version 22)

Revision: 13.05.2023

Trade name MC-Ballastbond 60 - Komponente B

(Contd. of page 4)

- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep container tightly sealed.
- **Storage class** 8A
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **8.1 Control parameters**
- **Components with critical values that require monitoring at the workplace:** The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

· **DNELs**

100-51-6 Benzyl alcohol

Oral	DNEL	4 mg/kg bw/Tag (ArL) 20 mg/kg bw/Tag (Ark)
Dermal	DNEL	8 mg/kg bw/day (ArL) 40 mg/kg bw/day (Ark)
Inhalative	DNEL	22 mg/m ³ (ArL) 110 mg/m ³ (Ark)

15520-10-2 2-methylpentane-1,5-diamine

Dermal	DNEL	1.5 mg/kg bw/day (ArL)
Inhalative	DNEL	0.25 mg/m ³ (ArL) 0.5 mg/m ³ (Ark)

140-31-8 2-piperazin-1-ylethylamine

Dermal	DNEL	3.33 mg/kg bw/day (ArL)
Inhalative	DNEL	10.6 mg/m ³ (ArL)

· **PNECs**

100-51-6 Benzyl alcohol

PNEC	0.527 mg/l (Marine water sediment) 0.1 mg/l (Mew) 1 mg/l (Fresh water sediment)
PNEC	0.456 mg/kg dwt (Bod) 5.27 mg/kg dwt (Fresh water sediment)

15520-10-2 2-methylpentane-1,5-diamine

PNEC	0.042 mg/l (Mew) 0.42 mg/l (Suw)
------	-------------------------------------

140-31-8 2-piperazin-1-ylethylamine

PNEC	250 mg/l (Kla)
------	----------------

(Contd. on page 6)



BE SURE. BUILD SURE.

Page 6/13

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 13.05.2023

Version number 23 (replaces version 22)

Revision: 13.05.2023

Trade name MC-Ballastbond 60 - Komponente B

(Contd. of page 5)

PNEC	0.0058 mg/l (Mew)
	0.058 mg/l (Suw)
	1 mg/kg dwt (Bod)
	21.5 mg/kg dwt (Sediment)
	215 mg/kg dwt (Fresh water sediment)

· **Additional information:** The lists that were valid during the compilation were used as basis.

· **8.2 Exposure controls**

· **Appropriate engineering controls**

No further data; see section 7.

· **Individual protection measures, such as personal protective equipment**

· **General protective and hygienic measures**

Keep away from foodstuffs, beverages and food.
Instantly remove any soiled and impregnated garments.
Wash hands during breaks and at the end of the work.
Avoid contact with the eyes and skin.

· **Hand protection**

Protective gloves.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
After use of gloves apply skin-cleaning agents and skin cosmetics.

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye/face protection**

Safety glasses
Tightly sealed safety glasses.

· **Body protection:**

Protective work clothing.

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Colour:**

Colourless

· **Smell:**

Characteristic

· **Melting point/freezing point:**

Not determined

· **Boiling point or initial boiling point and boiling range**

193 °C (15520-10-2 2-methylpentane-1,5-diamine)

· **Lower and upper explosion limit**

· **Lower:**

1.3 Vol % (100-51-6 Benzyl alcohol)

· **Upper:**

13 Vol % (100-51-6 Benzyl alcohol)

(Contd. on page 7)

GB



BE SURE. BUILD SURE.

Page 7/13

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 13.05.2023

Version number 23 (replaces version 22)

Revision: 13.05.2023

Trade name MC-Ballastbond 60 - Komponente B

(Contd. of page 6)

· Flash point:	83 °C
· pH at 20 °C	>10
· Viscosity:	
· Kinematic viscosity	Not determined.
· dynamic at 20 °C:	1800 mPas
· Solubility	
· Water:	Not miscible or difficult to mix
· Steam pressure at 20 °C:	0.1 hPa
· Vapour pressure at 50 °C:	0.7 hPa
· Density and/or relative density	
· Density at 20 °C	1 g/cm ³

· 9.2 Other information

· **Appearance:**

· **Form:**

Fluid

· **Important information on protection of health and environment, and on safety.**

· **Self-inflammability:**

Product is not selfigniting.

· **Explosive properties:**

Product is not explosive.

· **Information with regard to physical hazard classes**

· Explosives	Void
· Flammable gases	Void
· Aerosols	Void
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Void
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

SECTION 10: Stability and reactivity

· 10.1 Reactivity

No further relevant information available.

(Contd. on page 8)

GB

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 13.05.2023

Version number 23 (replaces version 22)

Revision: 13.05.2023

Trade name MC-Ballastbond 60 - Komponente B

(Contd. of page 7)

- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Harmful if swallowed.
Harmful in contact with skin.

· **LD/LC50 values that are relevant for classification:**

100-51-6 Benzyl alcohol

Oral	LD50	1230 mg/kg (rat)
	NOAEL 2nd year study	200 mg/kg (mouse)
		200 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rabbit)
Inhalative	LC50/4 h	>4178 mg/l (rat)

38640-62-9 Diisopropylnaphthalin-Isomere

Oral	LD50	>4000 mg/kg (rat)
Dermal	LD50	>4000 mg/kg (rat)
Inhalative	LC50 OECD 403	>5.6 mg/l (rat)

15520-10-2 2-methylpentane-1,5-diamine

Oral	LD50	1170 mg/kg (rat)
Dermal	LD50	1870 mg/kg (rabbit)
Inhalative	LC50/4 h	19.6 mg/l (rat)

140-31-8 2-piperazin-1-ylethylamine

Oral	LD50	2000-5000 mg/kg (rat)
Dermal	LD50	200-1000 mg/kg (rabbit)

- **Skin corrosion/irritation** Causes severe skin burns and eye damage.
- **Serious eye damage/irritation** Causes serious eye damage.
- **Respiratory or skin sensitisation** May cause an allergic skin reaction.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Suspected of damaging fertility. Suspected of damaging the unborn child.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** May cause damage to organs through prolonged or repeated exposure.

(Contd. on page 9)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 13.05.2023

Version number 23 (replaces version 22)

Revision: 13.05.2023

Trade name MC-Ballastbond 60 - Komponente B

(Contd. of page 8)

- **Aspiration hazard** Based on available data, the classification criteria are not met.
- **11.2 Information on other hazards**

· **Endocrine disrupting properties**

None of the ingredients is listed.

SECTION 12: Ecological information

· **12.1 Toxicity**

· **Aquatic toxicity:**

100-51-6 Benzyl alcohol

IC50/72h	700 mg/l (algae)
LC50/96h	460 mg/l (Pimephales promelas)
	10 mg/l (Lepomis macrochirus)

38640-62-9 Diisopropylnaphthalin-Isomere

EC50/72h	0.15 mg/l (algae)
LC50/48h	1.7 mg/l (Daphnia magna)
EC50/48h	0.16 mg/l (Daphnia magna)

15520-10-2 2-methylpentane-1,5-diamine

EC50/72h	>100 mg/l (algae)
EC50	1825 mg/l (fish)
EC50/48h	19.8 mg/l (Daphnia magna)

140-31-8 2-piperazin-1-ylethylamine

EC50/72h	>1000 mg/l (algae)
LC50/96h	2190 mg/l (fish)

· **12.2 Persistence and degradability**

No further relevant information available.

· **12.3 Bioaccumulative potential**

No further relevant information available.

· **12.4 Mobility in soil**

No further relevant information available.

· **12.5 Results of PBT and vPvB assessment**

· **PBT:**

Not applicable.

· **vPvB:**

Not applicable.

· **12.6 Endocrine disrupting properties**

The product does not contain substances with endocrine disrupting properties.

· **12.7 Other adverse effects**

· **Remark:**

Toxic for fish

· **Additional ecological information:**

· **General notes:**

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

Must not reach sewage water or drainage ditch undiluted or unneutralised.

(Contd. on page 10)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 13.05.2023

Version number 23 (replaces version 22)

Revision: 13.05.2023

Trade name MC-Ballastbond 60 - Komponente B

(Contd. of page 9)

Danger to drinking water if even extremely small quantities leak into soil.

SECTION 13: Disposal considerations

· **13.1 Waste treatment methods**

· **Recommendation** *Must not be disposed of together with household garbage. Do not allow product to reach sewage system.*

· **Uncleaned packagings:**

· **Recommendation:** *Disposal must be made according to official regulations.*

SECTION 14: Transport information

· **14.1 UN number or ID number**

· **ADR, IMDG, IATA** UN2735

· **14.2 UN proper shipping name**

· **ADR** AMINES, LIQUID, CORROSIVE, N.O.S. (2-methylpentane-1,5-diamine, Tetraethylenepentamine), ENVIRONMENTALLY HAZARDOUS

· **IMDG** AMINES, LIQUID, CORROSIVE, N.O.S. (2-methylpentane-1,5-diamine, Tetraethylenepentamine), MARINE POLLUTANT

· **IATA** AMINES, LIQUID, CORROSIVE, N.O.S. (2-methylpentane-1,5-diamine, Tetraethylenepentamine)

· **14.3 Transport hazard class(es)**

· **ADR**

· **Class** 8 (C7) Corrosive substances.

· **Label** 8

· **IMDG, IATA**

· **Class** 8 Corrosive substances.

· **Label** 8

· **14.4 Packing group**

· **ADR, IMDG, IATA** II

· **14.5 Environmental hazards:**

Product contains environmentally hazardous substances: Tetraethylenepentamine

· **Marine pollutant:** Yes

Symbol (fish and tree)

· **Special marking (ADR):** *Symbol (fish and tree)*

· **14.6 Special precautions for user**

Warning: Corrosive substances.

· **Kemler Number:** 80

(Contd. on page 11)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 13.05.2023

Version number 23 (replaces version 22)

Revision: 13.05.2023

Trade name MC-Ballastbond 60 - Komponente B

(Contd. of page 10)

· EMS Number:	F-A, S-B
· Segregation groups	(SGG18) Alkalies
· Stowage Category	A
· Segregation Code	SG35 Stow "separated from" SGG1-acids
· 14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· Transport category	2
· Tunnel restriction code	E
· IMDG	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 2735 AMINES, LIQUID, CORROSIVE, N.O.S. (2-METHYLPENTANE-1,5-DIAMINE, TETRAETHYLENEPENTAMINE), 8, II, ENVIRONMENTALLY HAZARDOUS

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 200 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases** H302 Harmful if swallowed.

(Contd. on page 12)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 13.05.2023

Version number 23 (replaces version 22)

Revision: 13.05.2023

Trade name MC-Ballastbond 60 - Komponente B

(Contd. of page 11)

H304 May be fatal if swallowed and enters airways.
H311 Toxic in contact with skin.
H312 Harmful in contact with skin.
H314 Causes severe skin burns and eye damage.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H361fd Suspected of damaging fertility. Suspected of damaging the unborn child.
H372 Causes damage to organs through prolonged or repeated exposure.
H410 Very toxic to aquatic life with long lasting effects.
H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.

· **Department issuing data specification sheet:**

· **Abbreviations and acronyms:**

Environment protection department.

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (UK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Acute Tox. 4: Acute toxicity – Category 4

Acute Tox. 3: Acute toxicity – Category 3

Skin Corr. 1A: Skin corrosion/irritation – Category 1A

Skin Corr. 1B: Skin corrosion/irritation – Category 1B

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Skin Sens. 1B: Skin sensitisation – Category 1B

Repr. 2: Reproductive toxicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

(Contd. on page 13)



BE SURE. BUILD SURE.

Page 13/13

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 13.05.2023

Version number 23 (replaces version 22)

Revision: 13.05.2023

Trade name MC-Ballastbond 60 - Komponente B

(Contd. of page 12)

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

· * **Data compared to the
previous version altered.**

GB