

## Safety data sheet

### according to Regulation (EC) No 1907/2006, Article 31

Printing date 27.05.2024

Version number 31 (replaces version 30)

Revision: 11.05.2024

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

##### 1.1 Product identifier

Trade name **MC-CarboSolid 1280 - Komponente B**

Article number: 4504

##### 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

##### Application of the substance / the mixture

Epoxy coating

##### 1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: MC-Bauchemie Müller GmbH & Co. KG  
Am Kruppwald 1-8  
D-46238 Bottrop  
Tel.: +49(0)2041-101-0  
Fax.: +49(0)2041-101-400  
E-Mail: info@mc-bauchemie.de

MC-Bauchemie AG  
Hagackerstr. 10  
CH-8953 Dietikon  
Tel.: +44-7400510  
Fax : +44-7400533

Informing department: msds@mc-bauchemie.de

##### 1.4 Emergency telephone number:

Tel.: +49 / (0)700 24112112 (MCR)  
Tel.: +1 872 5888271 (MCR)

#### SECTION 2: Hazards identification

##### 2.1 Classification of the substance or mixture

##### Classification according to Regulation (EC) No 1272/2008

Skin Corr. 1A H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT RE 2 H373 May cause damage to the lung through prolonged or repeated exposure.  
Route of exposure: Inhalation.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

##### 2.2 Label elements

##### Labelling according to

Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation.

##### Hazard pictograms



(Contd. on page 2)

## Safety data sheet

### according to Regulation (EC) No 1907/2006, Article 31

Printing date 27.05.2024

Version number 31 (replaces version 30)

Revision: 11.05.2024

**Trade name MC-CarboSolid 1280 - Komponente B**

(Contd. of page 1)

- **Signal word** Danger
- **Hazard-determining components of labelling:** Isophorone diamine  
crystalline silica  
Amine polymer  
Polyoxypropylenediamine  
4,4'-methylenebis(cyclohexylamine)  
Fettsäuren, C18- unges., Dimere, Reaktionsprodukte mit N,N-Dimethyl-1,3-propanediamin und 1,3-Propanediamin
- **Hazard statements** H314 Causes severe skin burns and eye damage.  
H317 May cause an allergic skin reaction.  
H373 May cause damage to the lung through prolonged or repeated exposure. Route of exposure: Inhalation.  
H412 Harmful to aquatic life with long lasting effects.
- **Precautionary statements** P260 Do not breathe dusts or mists.  
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P310 Immediately call a POISON CENTER/doctor.  
P321 Specific treatment (see on this label).  
P362+P364 Take off contaminated clothing and wash it before reuse.
- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

## SECTION 3: Composition/information on ingredients

### · 3.2 Mixtures

· **Description:** Mixture consisting of the following components.

#### · **Dangerous components:**

EC number: 948-369-5	Amine polymer Eye Dam. 1, H318; Skin Irrit. 2, H315; Skin Sens. 1B, H317	≥3-<10%
CAS: 2855-13-2 EINECS: 220-666-8 Reg.nr.: 01-2119514687-32	Isophorone diamine Skin Corr. 1B, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1, H317; Aquatic Chronic 3, H412 Specific concentration limit: Skin Sens. 1A; H317: C <sub>≥</sub> 0.001 %	≥5-<10%

(Contd. on page 3)

## Safety data sheet

### according to Regulation (EC) No 1907/2006, Article 31

Printing date 27.05.2024

Version number 31 (replaces version 30)

Revision: 11.05.2024

**Trade name MC-CarboSolid 1280 - Komponente B**

(Contd. of page 2)		
CAS: 9046-10-0 Reg.nr.: 01-2119557899-12	Polyoxypropylenediamine Skin Corr. 1B, H314; Aquatic Chronic 3, H412	≥5-<10%
	Amine polymer Eye Dam. 1, H318; Skin Irrit. 2, H315; Skin Sens. 1B, H317	≥3-<10%
CAS: 15520-10-2 EINECS: 239-556-6	2-methylpentane-1,5-diamine Skin Corr. 1A, H314; Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; STOT SE 3, H335	≥1-<5%
CAS: 14808-60-7	crystalline silica STOT RE 1, H372	<5%
CAS: 1761-71-3 EINECS: 217-168-8	4,4'-methylenebis(cyclohexylamine) STOT RE 2, H373; Skin Corr. 1B, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Skin Sens. 1B, H317	≥3-<5%
CAS: 39423-51-3	Polyoxypropylene triamine Eye Dam. 1, H318; Aquatic Chronic 2, H411; Acute Tox. 4, H302; Acute Tox. 4, H312	≥1-<2.5%
CAS: 69-72-7 EINECS: 200-712-3	salicylic acid Repr. 2, H361d; Eye Dam. 1, H318; Acute Tox. 4, H302	<1%
CAS: 162627-17-0 Reg.nr.: 01-2119970640-38-0000	Fettsäuren, C18- unges., Dimere, Reaktionsprodukte mit N,N-Dimethyl-1,3-propanediamin und 1,3-Propanediamin Skin Sens. 1A, H317	≥0.1-<0.5%

**Additional information**

For the wording of the listed hazard phrases refer to section 16.

## SECTION 4: First aid measures

**4.1 Description of first aid measures**

**General information**

Remove contaminated clothing immediately. Consult a doctor if symptoms occur. Move affected person to fresh air.

**After inhalation**

Supply fresh air; seek medical advice if symptoms occur.

**After skin contact**

If unconscious, place in recovery position and seek medical advice. In case of contact with skin, wash carefully with plenty of soap and water. Consult a doctor in case of skin reactions.

**After eye contact**

Rinse opened eye for several minutes under running water. Call a doctor immediately

**After swallowing**

Rinse mouth with water. Never give anything by mouth to an unconscious person. DO NOT induce vomiting. If symptoms persist, consult a doctor.

**4.2 Most important symptoms and effects, both acute and delayed**

Advice for the doctor: Elementary aid, decontamination, symptomatic treatment.

GB

(Contd. on page 4)

## Safety data sheet

### according to Regulation (EC) No 1907/2006, Article 31

Printing date 27.05.2024

Version number 31 (replaces version 30)

Revision: 11.05.2024

**Trade name MC-CarboSolid 1280 - Komponente B**

(Contd. of page 3)

### SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents** Use fire fighting measures that suit the environment.
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** No special measures required.

### SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures** Not required.
- **6.2 Environmental precautions:** No special measures required.
- **6.3 Methods and material for containment and cleaning up:** Collect mechanically.
- **6.4 Reference to other sections** See Section 7 for information on safe handling  
See Section 8 for information on personal protection equipment.  
See Section 13 for information on disposal.

### SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Open and handle containers with care.  
Ventilation measures are required in rooms without sufficient air exchange (e.g. closed rooms), because the occupational exposure limit values (see chapter 8) could be exceeded. This must be avoided.  
Wear suitable personal protective equipment (see section 8). Avoid contact with eyes, skin and clothing. Change contaminated or damaged gloves and contaminated clothing immediately and wash skin immediately. Mix slowly, partially covering the mixing container. Pour carefully and slowly when repotting. Observe the BGBau technical data sheet and practical guide for handling epoxy resins.
- **Information about protection against explosions and fires:** Ensure sufficient air exchange and/or extraction in the working areas. Take precautionary measures to avoid electrostatic discharges.

(Contd. on page 5)

## Safety data sheet

### according to Regulation (EC) No 1907/2006, Article 31

Printing date 27.05.2024

Version number 31 (replaces version 30)

Revision: 11.05.2024

**Trade name MC-CarboSolid 1280 - Komponente B**

(Contd. of page 4)

- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage**
- **Requirements to be met by storerooms and containers:** No special requirements.
- **Further information about storage conditions:** Keep container tightly closed in a well-ventilated place.
- **Storage class** 8A

## SECTION 8: Exposure controls/personal protection

- **8.1 Control parameters**
- **Components with critical values that require monitoring at the workplace:** The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

### · DNELs

#### **CAS: 2855-13-2 Isophorone diamine**

Oral	DNEL	0.526 mg/kg bw/Tag (ArL)
Inhalative	DNEL	20.1 mg/m <sup>3</sup> (ArL)

#### **CAS: 9046-10-0 Polyoxypropylenediamine**

Oral	DNEL	0.04 mg/kg bw/Tag (ArL)
Dermal	DNEL	2.5 mg/kg bw/day (ArL)

#### **CAS: 15520-10-2 2-methylpentane-1,5-diamine**

Dermal	DNEL	1.5 mg/kg bw/day (ArL)
Inhalative	DNEL	0.25 mg/m <sup>3</sup> (ArL) 0.5 mg/m <sup>3</sup> (Ark)

#### **CAS: 1761-71-3 4,4'-methylenebis(cyclohexylamine)**

Oral	DNEL	0.06 mg/kg bw/Tag (ArL)
Dermal	DNEL	0.1 mg/kg bw/day (ArL)
Inhalative	DNEL	1 mg/m <sup>3</sup> (ArL)

#### **CAS: 39423-51-3 Polyoxypropylene triamine**

Inhalative	DNEL	14 mg/m <sup>3</sup> (ArL)
------------	------	----------------------------

### · PNECs

#### **CAS: 2855-13-2 Isophorone diamine**

PNEC	0.006 mg/l (Mew)
	0.06 mg/l (Freshwater)
PNEC	0.578 mg/kg dwt (Sediment)
	5.784 mg/kg dwt (Fresh water sediment)

#### **CAS: 9046-10-0 Polyoxypropylenediamine**

PNEC	7.5 mg/l (Sewage Treatment Plant)
	0.015 mg/l (Fresh water)

(Contd. on page 6)

## Safety data sheet

### according to Regulation (EC) No 1907/2006, Article 31

Printing date 27.05.2024

Version number 31 (replaces version 30)

Revision: 11.05.2024

**Trade name MC-CarboSolid 1280 - Komponente B**

(Contd. of page 5)

PNEC	0.0176 mg/kg dwt (Bod) 0.125 mg/kg dwt (Sediment) 0.132 mg/kg dwt (Fresh water sediment)
<b>CAS: 15520-10-2 2-methylpentane-1,5-diamine</b>	
PNEC	0.042 mg/l (Mew) 0.42 mg/l (Freshwater)
<b>CAS: 1761-71-3 4,4'-methylenebis(cyclohexylamine)</b>	
PNEC	0.08 mg/l (Fresh water) 3.2 mg/l (Kla) 13.7 mg/l (Mew)
PNEC	27.2 mg/kg dwt (Bod) 13.7 mg/kg dwt (Sediment) 137 mg/kg dwt (Fresh water sediment)
<b>CAS: 39423-51-3 Polyoxypropylene triamine</b>	
PNEC	10 mg/l (Sewage Treatment Plant) 0.00044 mg/l (Mew) 0.0044 mg/l (Freshwater)
PNEC	0.002 mg/kg dwt (Bod) 0.002 mg/kg dwt (Sediment) 0.02 mg/kg dwt (Fresh water sediment)

- **Additional information:** The lists that were valid during the compilation were used as basis.
- **8.2 Exposure controls**
- **Appropriate engineering controls** No further data; see section 7.
- **Individual protection measures, such as personal protective equipment**
- **General protective and hygienic measures**
  - Keep away from food, drink and animal feed.
  - Remove soiled, soaked clothing immediately.
  - Wash hands before breaks and at the end of work.
  - Avoid contact with eyes and skin.
- **Breathing equipment:** If workplace limit values cannot be complied with by ventilation measures or if rooms cannot be technically ventilated, respiratory protection must be worn: Use combination filter A1-P2 (brown/white) in rooms that cannot be ventilated. If oxygen deficiency is expected, use self-contained breathing apparatus. Observe wearing time limits according to §9 (3) GefStoffV in conjunction with BGR 190.
- **Hand protection** Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
- **Material of gloves** You can find help with choosing gloves on the website <https://www.bgbau.de/fileadmin/Gisbau/Projekte.pdf>  
For example, we recommend the Sol-vex 37-900 protective gloves from Ansell GmbH. The breakthrough time of the protective gloves can be found under point 8 "Penetration time of the glove material".

(Contd. on page 7)



## Safety data sheet

### according to Regulation (EC) No 1907/2006, Article 31

Printing date 27.05.2024

Version number 31 (replaces version 30)

Revision: 11.05.2024

**Trade name MC-CarboSolid 1280 - Komponente B**

(Contd. of page 6)

The selection of a suitable glove depends not only on the material, but also on other quality features and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of glove materials cannot be calculated in advance and must therefore be checked before use.

Nitrile rubber

Recommended material thickness:  $\geq 0.4$  mm

· **Penetration time of glove material**

The breakthrough times of the Sol-vex 37-900 protective gloves are around 8 hours.

The following applies to all other gloves:

The exact breakthrough time must be obtained from the protective glove manufacturer and adhered to.

Nitrile rubber

Material thickness:  $\geq 0.40$  mm

Penetration time:  $\geq 480$  min

Butyl rubber:

Material thickness:  $\geq 0.5$  mm

Penetration time:  $\geq 480$  min

· **Eye/face protection**

Tight-fitting safety goggles.

Safety goggles.

· **Body protection:**

Protective clothing

Suitable protective clothing should be worn when working with epoxy resins. In addition to normal work clothing (long trousers, long-sleeved shirt or T-shirt), disposable overalls, aprons, overshoes, sleeve protectors etc. may be necessary depending on the activity. Uncovered areas of skin should be avoided as far as possible, even in hot weather. If the work involves kneeling, the lower leg area should be protected by protective trousers.

## SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Colour:**

light yellow

· **Smell:**

Amine-like

· **Melting point/freezing point:**

Not determined

· **Boiling point or initial boiling point and boiling range**

2230 °C (CAS: 14808-60-7 Quartz (SiO<sub>2</sub>))

· **Flash point:**

$\geq 61$  °C

· **Auto-ignition temperature:**

>370 °C (CAS: 7631-86-9 silicon dioxide, chemically prepared)

· **pH at 20 °C**

12

· **Viscosity:**

· **Kinematic viscosity**

Not determined.

· **dynamic at 20 °C:**

250000 mPas

(Contd. on page 8)

## Safety data sheet

### according to Regulation (EC) No 1907/2006, Article 31

Printing date 27.05.2024

Version number 31 (replaces version 30)

Revision: 11.05.2024

**Trade name MC-CarboSolid 1280 - Komponente B**

(Contd. of page 7)

- **Solubility**
- **Water:** Partly miscible
- **Steam pressure at 1732 °C:** 13.5 hPa (CAS: 14808-60-7 Quartz (SiO<sub>2</sub>))
- **Density and/or relative density**
- **Density at 20 °C** 1.55 g/cm<sup>3</sup>

- **9.2 Other information**
- **Appearance:**
- **Form:** Pasty
- **Important information on protection of health and environment, and on safety.**
- **Self-inflammability:** Product is not selfigniting.
- **Explosive properties:** Product is not explosive.

- **Information with regard to physical hazard classes**
- **Explosives** Void
- **Flammable gases** Void
- **Aerosols** Void
- **Oxidising gases** Void
- **Gases under pressure** Void
- **Flammable liquids** Void
- **Flammable solids** Void
- **Self-reactive substances and mixtures** Void
- **Pyrophoric liquids** Void
- **Pyrophoric solids** Void
- **Self-heating substances and mixtures** Void
- **Substances and mixtures, which emit flammable gases in contact with water** Void
- **Oxidising liquids** Void
- **Oxidising solids** Void
- **Organic peroxides** Void
- **Corrosive to metals** Void
- **Desensitised explosives** Void

## SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.

(Contd. on page 9)



## Safety data sheet

### according to Regulation (EC) No 1907/2006, Article 31

Printing date 27.05.2024

Version number 31 (replaces version 30)

Revision: 11.05.2024

**Trade name MC-CarboSolid 1280 - Komponente B**

(Contd. of page 8)

- **10.6 Hazardous decomposition products:** No dangerous decomposition products known

## SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

- **LD/LC50 values that are relevant for classification:**

### CAS: 2855-13-2 Isophorone diamine

Oral	LD50	1030 mg/kg (ATE)
		1030 mg/kg (rat)
Dermal	NOAEL	250 mg/kg (rat)
	LD50	1840 mg/kg (rabbit)
		>2000 mg/kg (rat)

### CAS: 9046-10-0 Polyoxypropylenediamine

Oral	LD50	2855 mg/kg (Rat)
Dermal	LD50	2980 mg/kg (Kan)

### CAS: 15520-10-2 2-methylpentane-1,5-diamine

Oral	LD50	1170 mg/kg (rat)
Dermal	LD50	1870 mg/kg (rabbit)
Inhalative	LC50/4 h	19.6 mg/l (rat)

### CAS: 1761-71-3 4,4'-methylenebis(cyclohexylamine)

Oral	LD50	380 mg/kg (rat)
Dermal	LD50	2110 mg/kg (rat)

### CAS: 39423-51-3 Polyoxypropylene triamine

Oral	LD50	550 mg/kg (rat)
Dermal	LD50	>1000 mg/kg (rat)

### CAS: 69-72-7 salicylic acid

Oral	LD50	891 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rat)

- **Skin corrosion/irritation** Causes severe skin burns and eye damage.
- **Serious eye damage/irritation** Causes serious eye damage.
- **Respiratory or skin sensitisation** May cause an allergic skin reaction.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** May cause damage to the lung through prolonged or repeated exposure. Route of exposure: Inhalation.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

(Contd. on page 10)

## Safety data sheet

### according to Regulation (EC) No 1907/2006, Article 31

Printing date 27.05.2024

Version number 31 (replaces version 30)

Revision: 11.05.2024

**Trade name MC-CarboSolid 1280 - Komponente B**

(Contd. of page 9)

· **11.2 Information on other hazards**

· **Endocrine disrupting properties**

CAS: 69-72-7 salicylic acid

List II; III

## SECTION 12: Ecological information

· **12.1 Toxicity**

· **Aquatic toxicity:**

**CAS: 2855-13-2 Isophorone diamine**

LC50/96h	110 mg/l (Leucidus idus)
EC50	1120 mg/l (Pseudomonas putida)
EC50/48h	23 mg/l (Daphnia magna)
NOEC	1.5 mg/l (Desmodesmus subspicatus)
	3 mg/l (Daphnia magna)
ErC50/72h	>50 mg/l (Desmodesmus subspicatus)

**CAS: 15520-10-2 2-methylpentane-1,5-diamine**

EC50/72h	>100 mg/l (algae)
EC50	1825 mg/l (fish)
EC50/48h	19.8 mg/l (Daphnia magna)

**CAS: 1761-71-3 4,4'-methylenbis(cyclohexylamine)**

LC50/96h	>100 mg/l (Leucidus idus)
EC50/48h	6.84 mg/l (Daphnia magna)
NOEC	4 mg/l (Daphnia magna)
ErC50/72h	141.2 mg/l (Desmodesmus subspicatus)

**CAS: 39423-51-3 Polyoxypropylene triamine**

LC50/96h	>100 mg/l (Oncorhynchus mykiss)
EC50/48h	13 mg/l (Daphnia magna)
ErC50/72h	4.4 mg/l (algae)

· **12.2 Persistence and degradability**

No further relevant information available.

· **12.3 Bioaccumulative potential**

No further relevant information available.

· **12.4 Mobility in soil**

No further relevant information available.

· **12.5 Results of PBT and vPvB assessment**

· **PBT:**

Not applicable.

· **vPvB:**

Not applicable.

· **12.6 Endocrine disrupting properties**

For information on endocrine disrupting properties see section 11.

· **12.7 Other adverse effects**

· **Additional ecological information:**

· **General notes:**

Do not allow product to reach ground water, water bodies or sewage system.

(Contd. on page 11)

## Safety data sheet

### according to Regulation (EC) No 1907/2006, Article 31

Printing date 27.05.2024

Version number 31 (replaces version 30)

Revision: 11.05.2024

**Trade name MC-CarboSolid 1280 - Komponente B**

(Contd. of page 10)

Danger to drinking water if even small quantities leak into soil.

### SECTION 13: Disposal considerations

· **13.1 Waste treatment methods**

· **Recommendation**                      *Must not be disposed of together with household garbage. Do not allow product to reach sewage system.*

· **Uncleaned packagings:**

· **Recommendation:**                      *Empty contaminated packagings thoroughly. They can be recycled after thorough and proper cleaning.*

### SECTION 14: Transport information

· **14.1 UN number or ID number**

· **ADR, IMDG, IATA**                                      UN2735

· **14.2 UN proper shipping name**

· **ADR, IMDG, IATA**                                      AMINES, LIQUID, CORROSIVE, N.O.S.  
(ISOPHORONEDIAMINE, 2-methylpentane-1,5-diamine)

· **14.3 Transport hazard class(es)**

· **ADR**

· **Class**    8 (C7) Corrosive substances.

· **Label**    8

· **IMDG, IATA**

· **Class**    8 Corrosive substances.

· **Label**    8

· **14.4 Packing group**

· **ADR, IMDG, IATA**                                      II

· **14.5 Environmental hazards:**

· **Marine pollutant:**                                      No

· **14.6 Special precautions for user**

· **Warning:** Corrosive substances.

· **Kemler Number:**                                      80

· **EMS Number:**                                      F-A, S-B

· **Segregation groups**                                      (SGG18) Alkalies

· **Stowage Category**                                      A

· **Segregation Code**                                      SG35 Stow "separated from" SGG1-acids

· **14.7 Maritime transport in bulk according to**

**IMO instruments**                                      Not applicable.

(Contd. on page 12)

## Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 27.05.2024

Version number 31 (replaces version 30)

Revision: 11.05.2024

**Trade name MC-CarboSolid 1280 - Komponente B**

(Contd. of page 11)

· **Transport/Additional information:**

· **ADR**

· **Limited quantities (LQ)**

1L

· **Excepted quantities (EQ)**

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

· **Transport category**

2

· **Tunnel restriction code**

E

· **IMDG**

· **Limited quantities (LQ)**

1L

· **Excepted quantities (EQ)**

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

· **UN "Model Regulation":**

UN 2735 AMINES, LIQUID, CORROSIVE, N.O.S.  
(ISOPHORONEDIAMINE, 2-METHYLPENTANE-  
1,5-DIAMINE), 8, II

### SECTION 15: Regulatory information

· **15.1 Safety, health and environmental regulations/ legislation specific for the substance or mixture**

No further relevant information available.

· **Poisons Act**

· **Regulated explosives precursors**

None of the ingredients is listed.

· **Regulated poisons**

None of the ingredients is listed.

· **Reportable explosives precursors**

None of the ingredients is listed.

· **Reportable poisons**

None of the ingredients is listed.

· **15.2 Chemical safety assessment:**

A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

(Contd. on page 13)

## Safety data sheet

### according to Regulation (EC) No 1907/2006, Article 31

Printing date 27.05.2024

Version number 31 (replaces version 30)

Revision: 11.05.2024

**Trade name MC-CarboSolid 1280 - Komponente B**

(Contd. of page 12)

H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H318 Causes serious eye damage.  
H332 Harmful if inhaled.  
H335 May cause respiratory irritation.  
H361d Suspected of damaging the unborn child.  
H372 Causes damage to organs through prolonged or repeated exposure.  
H373 May cause damage to organs through prolonged or repeated exposure.  
H411 Toxic to aquatic life with long lasting effects.  
H412 Harmful to aquatic life with long lasting effects.

· **Department issuing data specification sheet:**

· **Abbreviations and acronyms:**

Environment protection department.

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (UK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Acute Tox. 4: Acute toxicity – Category 4

Skin Corr. 1A: Skin corrosion/irritation – Category 1A

Skin Corr. 1B: Skin corrosion/irritation – Category 1B

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Skin Sens. 1: Skin sensitisation – Category 1

Skin Sens. 1A: Skin sensitisation – Category 1A

Skin Sens. 1B: Skin sensitisation – Category 1B

Repr. 2: Reproductive toxicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

· **\* Data compared to the previous version altered.**