

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 26.05.2024

Version number 22 (replaces version 21)

Revision: 08.05.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name **MC-Color Flair vision - Komponente B**

Article number: 3911

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture

Coating compound/ Surface coating/ paint
Hardening agent/ Curing agent

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: MC-Bauchemie Müller GmbH & Co. KG
Am Kruppwald 1-8
D-46238 Bottrop
Tel.: +49(0)2041-101-0
Fax.: +49(0)2041-101-400
E-Mail: info@mc-bauchemie.de

MC-Bauchemie AG
Hagackerstr. 10
CH-8953 Dietikon
Tel.: +44-7400510
Fax : +44-7400533

Informing department: msds@mc-bauchemie.de

1.4 Emergency telephone number:

Tel.: +49 / (0)700 24112112 (MCR)
Tel.: +1 872 5888271 (MCR)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Acute Tox. 4 H332 Harmful if inhaled.
Skin Irrit. 2 H315 Causes skin irritation.
Skin Sens. 1 H317 May cause an allergic skin reaction.
STOT SE 3 H335 May cause respiratory irritation.
Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to

Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms



GHS07

(Contd. on page 2)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 26.05.2024

Version number 22 (replaces version 21)

Revision: 08.05.2024

Trade name MC-Color Flair vision - Komponente B

(Contd. of page 1)

· Signal word	Warning
· Hazard-determining components of labelling:	Hydrophiles, aliphatisches Polyisocyanat Hexamethylen-1,6-diisocyanat Homopolymer hexamethylene diisocyanate
· Hazard statements	H332 Harmful if inhaled. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H335 May cause respiratory irritation. H412 Harmful to aquatic life with long lasting effects.
· Precautionary statements	P261 Avoid breathing dust/fume/gas/mist/vapours/spray. P280 Wear protective gloves. P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P312 Call a POISON CENTER/doctor if you feel unwell. P403+P233 Store in a well-ventilated place. Keep container tightly closed. P405 Store locked up.
· Additional information:	EUH204 Contains isocyanates. May produce an allergic reaction.
· 2.3 Other hazards	
· Results of PBT and vPvB assessment	
· PBT:	Not applicable.
· vPvB:	Not applicable.

SECTION 3: Composition/information on ingredients

· **3.2 Mixtures**

· **Description:** Mixture consisting of the following components.

· **Dangerous components:**

CAS: 160994-68-3	Hydrophiles, aliphatisches Polyisocyanat Acute Tox. 4, H332; Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335; Aquatic Chronic 3, H412, EUH204	50-70%
CAS: 3779-63-3 EINECS: 223-242-0	Hexamethylen-1,6-diisocyanat Homopolymer Acute Tox. 4, H332; Skin Sens. 1, H317; STOT SE 3, H335	≥1-<5%
CAS: 822-06-0 EINECS: 212-485-8 Reg.nr.: 01-2119457571-37-0000	hexamethylene diisocyanate Acute Tox. 3, H331; Resp. Sens. 1, H334; Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335, EUH204 Specific concentration limits: Resp. Sens. 1; H334: C ≥ 0.5 % Skin Sens. 1; H317: C ≥ 0.5 %	<0.1%

· **Additional information** For the wording of the listed hazard phrases refer to section 16.

GB

(Contd. on page 3)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 26.05.2024

Version number 22 (replaces version 21)

Revision: 08.05.2024

Trade name MC-Color Flair vision - Komponente B

(Contd. of page 2)

SECTION 4: First aid measures

4.1 Description of first aid measures

- **General information** Remove soiled, soaked clothing immediately.
- **After inhalation** Remove person to fresh air, keep warm, allow to rest; if breathing is difficult, seek medical attention.
- **After skin contact** In case of contact with skin, wash carefully with plenty of soap and water. Consult a doctor in case of skin reactions.
- **After eye contact** Rinse the eyes with open eyelids for a sufficiently long time (at least 10 minutes) with water that is as lukewarm as possible. Consult an ophthalmologist.
- **After swallowing** Do NOT induce vomiting. Rinse mouth with water. Medical attention required.

4.2 Most important symptoms and effects, both acute and delayed

Advice for the doctor: Elementary aid, decontamination, symptomatic treatment.

4.3 Indication of any immediate medical attention and special treatment needed

Therapeutic measures: No information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- **Suitable extinguishing agents** CO₂, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam.

5.2 Special hazards arising from the substance or mixture

No further relevant information available.

5.3 Advice for firefighters

Protective equipment:

No special measures required.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Not required.

6.2 Environmental precautions:

Inform respective authorities in case product reaches water or sewage system.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling
See Section 8 for information on personal protection equipment.

(Contd. on page 4)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 26.05.2024

Version number 22 (replaces version 21)

Revision: 08.05.2024

Trade name MC-Color Flair vision - Komponente B

See Section 13 for information on disposal.

(Contd. of page 3)

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure sufficient air exchange and/or extraction in the work areas. Air extraction is required for spray application.
For solid products: Avoid dust formation and dust deposits. Air limit values mentioned in section 8 must be monitored.
At workplaces where isocyanate aerosols and/or vapours can occur in higher concentrations, targeted air extraction must be used to prevent the occupational hygiene limit value from being exceeded. The air must be moved away from people.
For products containing solvents: Explosion protection required. The personal protective measures described in section 8 must be observed. The protective measures required when handling isocyanates must be observed. Avoid contact with skin and eyes and inhalation of vapours.
Keep away from food and beverages. Wash hands before breaks and at the end of work and apply skin protection ointment. Store work clothes separately. Remove soiled, soaked clothing immediately.

· Information about protection against explosions and fires:

Keep ignition sources away - do not smoke.
Protect from heat.
Do not store near heat sources.

· 7.2 Conditions for safe storage, including any incompatibilities

Keep container dry and tightly closed. Further information on the storage conditions that must be observed for quality assurance reasons can be found in our technical data sheet.

· Storage

· Requirements to be met by storerooms and containers:

Keep tightly closed in original packaging. Ventilate storage rooms well. Carefully close opened containers and store upright to prevent any leakage.

Storage temperature >5°C and <30°C

· Information about storage in one common storage facility:

May be stored together with hazardous substances of other classes up to 200 kg.

· Further information about storage conditions:

Keep container tightly closed in a well-ventilated place.

· Storage class

10

· 7.3 Specific end use(s)

No further relevant information available.

GB

(Contd. on page 5)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 26.05.2024

Version number 22 (replaces version 21)

Revision: 08.05.2024

Trade name MC-Color Flair vision - Komponente B

(Contd. of page 4)

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Components with critical values that require monitoring at the workplace:

CAS: 822-06-0 hexamethylene diisocyanate

WEL	Short-term value: 0.07 mg/m ³ Long-term value: 0.02 mg/m ³ Sen; as -NCO
-----	---

· DNELs

CAS: 822-06-0 hexamethylene diisocyanate

Inhalative	DNEL	0.5 mg/m ³ (ArL)
------------	------	-----------------------------

· PNECs

CAS: 822-06-0 hexamethylene diisocyanate

PNEC	100 mg/l (Sewage Treatment Plant) 0.0199 mg/l (Mew) 0.199 mg/l (Freshwater)
PNEC	8884 mg/kg dwt (Bod) 4455 mg/kg dwt (Marine water sediment) 44551 mg/kg dwt (Fresh water sediment)

· Ingredients with biological limit values:

CAS: 822-06-0 hexamethylene diisocyanate

BMGV	1 µmol creatinine/mol Medium: urine Sampling time: At the end of the period of exposure Parameter: isocyanate-derived diamine
------	--

· **Additional information:** The lists that were valid during the compilation were used as basis.

· 8.2 Exposure controls

· Appropriate engineering controls

No further data; see section 7.

· Individual protection measures, such as personal protective equipment

· General protective and hygienic measures

Do not smoke, eat or drink while working. Have eye wash equipment ready.
Do not inhale gases/vapours/aerosols. Avoid contact with eyes and skin.
Do not store food in the work area. Wash hands before breaks and at the end of work.

· Breathing equipment:

Respiratory protection required at insufficiently ventilated workplaces and when working with splashes. Fresh air masks or combination filters A2-P2 (EN529) are recommended for short-term work.
If applicable, further recommendations for respiratory protection can be found in the appendix.
In case of hypersensitivity of the respiratory tract (asthma, chronic bronchitis), handling of the product is not recommended.

(Contd. on page 6)



BE SURE. BUILD SURE.

Page 6/10

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 26.05.2024

Version number 22 (replaces version 21)

Revision: 08.05.2024

Trade name MC-Color Flair vision - Komponente B

(Contd. of page 5)

· **Hand protection**

Suitable materials for protective gloves; EN 374:

Butyl rubber - IIR: thickness $\geq 0.5\text{mm}$; breakthrough time $\geq 480\text{min}$.

Fluororubber - FKM: thickness $\geq 0.4\text{mm}$; breakthrough time $\geq 480\text{min}$.

Multi-layer glove - PE/EVAL/PE ; Breakthrough time $\geq 480\text{ min}$.

Recommendation: Dispose of contaminated gloves.

· **Penetration time of glove material**

Butyl rubber - IIR: thickness $\geq 0.5\text{mm}$; breakthrough time $\geq 480\text{min}$.

Fluoro rubber - FKM: thickness $\geq 0.4\text{mm}$; breakthrough time $\geq 480\text{min}$.

Multi-layer glove - PE/EVAL/PE ; Breakthrough time $\geq 480\text{ min}$.

· **Eye/face protection**

Wear safety goggles/face protection.

· **Body protection:**

Wear suitable protective clothing when working.

In case of hypersensitivity of the skin, handling of the product is not recommended.

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Colour:**

Colourless

· **Smell:**

Characteristic

· **Melting point/freezing point:**

Not determined

· **Boiling point or initial boiling point and boiling range**

175 °C

· **Flash point:**

70 °C

· **pH at 20 °C**

7

· **Viscosity:**

· **Kinematic viscosity**

Not determined.

· **dynamic at 20 °C:**

2000 mPas

· **Solubility**

· **Water:**

Not miscible or difficult to mix

· **Steam pressure:**

Not determined.

· **Density and/or relative density**

· **Density at 20 °C**

1.1 g/cm³

· **9.2 Other information**

· **Appearance:**

· **Form:**

Fluid

· **Important information on protection of health and environment, and on safety.**

· **Self-flammability:**

Product is not selfigniting.

· **Explosive properties:**

Product is not explosive.

· **Information with regard to physical hazard classes**

· **Explosives**

Void

· **Flammable gases**

Void

(Contd. on page 7)

GB

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 26.05.2024

Version number 22 (replaces version 21)

Revision: 08.05.2024

Trade name MC-Color Flair vision - Komponente B

(Contd. of page 6)

· Aerosols	Void
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Void
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** Reacts with amines
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Harmful if inhaled.

· **LD/LC50 values that are relevant for classification:**

CAS: 160994-68-3 Hydrophiles, aliphatisches Polyisocyanat

Oral	LD50	>2000 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rat)
Inhalative	LC50/4 h	0.39 mg/l (rat)

CAS: 822-06-0 hexamethylene diisocyanate

Oral	LD50	738 mg/kg (rat)
Inhalative	LC50/4 h	0.39 mg/l (rat)

- **Skin corrosion/irritation** Causes skin irritation.
- **Respiratory or skin sensitisation** May cause an allergic skin reaction.

(Contd. on page 8)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 26.05.2024

Version number 22 (replaces version 21)

Revision: 08.05.2024

Trade name MC-Color Flair vision - Komponente B

(Contd. of page 7)

- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** May cause respiratory irritation.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.
- **11.2 Information on other hazards**

· **Endocrine disrupting properties**

None of the ingredients is listed.

SECTION 12: Ecological information

· **12.1 Toxicity**

· **Aquatic toxicity:**

CAS: 160994-68-3 Hydrophiles, aliphatisches Polyisocyanat

LC50/96h	28.3 mg/l (Danio rerio)
EC50	>10000 mg/l (BEL)
EC50/48h	>100 mg/l (Daphnia magna)
ErC50/72h	>100 mg/l (Scenedesmus subspicatus)

· **12.2 Persistence and degradability**

No further relevant information available.

· **12.3 Bioaccumulative potential**

No further relevant information available.

· **12.4 Mobility in soil**

No further relevant information available.

· **12.5 Results of PBT and vPvB assessment**

· **PBT:**

Not applicable.

· **vPvB:**

Not applicable.

· **12.6 Endocrine disrupting properties**

The product does not contain substances with endocrine disrupting properties.

· **12.7 Other adverse effects**

· **Remark:**

Harmful to fish

· **Additional ecological information:**

· **General notes:**

Harmful to aquatic organisms

Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system.

SECTION 13: Disposal considerations

· **13.1 Waste treatment methods**

· **Recommendation**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 9)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 26.05.2024

Version number 22 (replaces version 21)

Revision: 08.05.2024

Trade name MC-Color Flair vision - Komponente B

(Contd. of page 8)

· **Uncleaned packagings:**

· **Recommendation:**

Empty contaminated packagings thoroughly. They can be recycled after thorough and proper cleaning.

SECTION 14: Transport information

· **14.1 UN number or ID number**

· **ADR, ADN, IMDG, IATA**

Void

· **14.2 UN proper shipping name**

· **ADR, ADN, IMDG, IATA**

Void

· **14.3 Transport hazard class(es)**

· **ADR, ADN, IMDG, IATA**

· **Class**

Void

· **14.4 Packing group**

· **ADR, IMDG, IATA**

Void

· **14.5 Environmental hazards:**

· **Marine pollutant:**

No

· **14.6 Special precautions for user**

Not applicable.

· **14.7 Maritime transport in bulk according to IMO instruments**

Not applicable.

· **UN "Model Regulation":**

Void

SECTION 15: Regulatory information

· **15.1 Safety, health and environmental regulations/ legislation specific for the substance or mixture**

No further relevant information available.

· **Poisons Act**

· **Regulated explosives precursors**

None of the ingredients is listed.

· **Regulated poisons**

None of the ingredients is listed.

· **Reportable explosives precursors**

None of the ingredients is listed.

· **Reportable poisons**

None of the ingredients is listed.

(Contd. on page 10)



BE SURE. BUILD SURE.

Page 10/10

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 26.05.2024

Version number 22 (replaces version 21)

Revision: 08.05.2024

Trade name MC-Color Flair vision - Komponente B

(Contd. of page 9)

**15.2 Chemical safety
assessment:**

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H302 Harmful if swallowed.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H331 Toxic if inhaled.
H332 Harmful if inhaled.
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335 May cause respiratory irritation.
H412 Harmful to aquatic life with long lasting effects.
EUH204 Contains isocyanates. May produce an allergic reaction.

**Department issuing data
specification sheet:**

Environment protection department.

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
ICAO: International Civil Aviation Organisation
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
DNEL: Derived No-Effect Level (UK REACH)
PNEC: Predicted No-Effect Concentration (UK REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Acute Tox. 3: Acute toxicity – Category 3
Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Resp. Sens. 1: Respiratory sensitisation – Category 1
Skin Sens. 1: Skin sensitisation – Category 1
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

*** Data compared to the
previous version altered.**

GB