

Page 1/11

Safety data sheet according to UK REACH

Printing date 12.04.2025 Version number 38 (replaces version 37) Revision: 12.04.2025

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

· 1.1 Product identifier

MC-Color Flair vision T - Komponente B · Trade name

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance / the mixture

Coating compound/ Surface coating/ paint

Hardening agent/ Curing agent

· 1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: MC-Bauchemie Müller GmbH & Co. KG

> Am Kruppwald 1-8 D-46238 Bottrop Tel.: +49(0)2041-101-0 Fax.: +49(0)2041-101-400 E-Mail: info@mc-bauchemie.de

MC-Bauchemie AG Hagackerstr. 10 CH-8953 Dietikon Tel.: +44-7400510 Fax: +44-7400533

Informing department:

msds@mc-bauchemie.de

1.4 Emergency telephone

number: Tel.: +49 / (0)700 24112112 (MCR)

Tel.: +1 872 5888271 (MCR)

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

Acute Tox. 4 H332 Harmful if inhaled.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

· 2.2 Label elements

Labelling according to

Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms



· Signal word Warning

Hazard-determining

components of labelling: Aliphatisches Polyisocyanat

(Contd. on page 2)



Page 2/11

Safety data sheet according to UK REACH

Printing date 12.04.2025 Version number 38 (replaces version 37) Revision: 12.04.2025

Trade name MC-Color Flair vision T - Komponente B

(Contd. of page 1)

Hydrophiles, aliphatisches Polyisocyanat

hexamethylene diisocyanate

· **Hazard statements** H332 Harmful if inhaled.

H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

• **Precautionary statements** P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves.

P304+P340 IF INHALED: Remove person to fresh air and keep

comfortable for breathing.

P312 Call a POISON CENTER/doctor if you feel unwell. P403+P233 Store in a well-ventilated place. Keep container tightly

closed.

P405 Store locked up.

· Additional information: EUH204 Contains isocyanates. May produce an allergic reaction.

As from 24 August 2023 adequate training is required before

industrial or professional use.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· **PBT:** Not applicable. · **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

• **Description:** Mixture consisting of the following components.

	· Dangerous components:			
Ī	CAS: 28182-81-2	Aliphatisches Polyisocyanat	30-60%	
		Acute Tox. 4, H332; Skin Sens. 1, H317; STOT SE 3, H335, EUH204		
Ī	CAS: 666723-27-9	Hydrophiles, aliphatisches Polyisocyanat	≥10-<20%	
		Acute Tox. 3, H331; Skin Sens. 1, H317; STOT SE 3, H335; Aquatic Chronic 3, H412		
	CAS: 822-06-0 EINECS: 212-485-8 Reg.nr.: 01-2119457571-37- 0000	hexamethylene diisocyanate Acute Tox. 1, H330; Resp. Sens. 1, H334; Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335, EUH204 Specific concentration limits: Resp. Sens. 1; H334: C≥ 0.5 % Skin Sens. 1; H317: C ≥ 0.5 %	≥0.1-<0.5%	
Ī	· Additional information	For the wording of the listed hazard phrases refer to s	ection 16.	

SECTION 4: First aid measures

· 4.1 Description of first aid measures

General information Remove soiled, soaked clothing immediately.

· After inhalation Remove person to fresh air, keep warm, allow to rest; if breathing

is difficult, seek medical attention.

(Contd. on page 3)



Page 3/11

Safety data sheet according to UK REACH

Printing date 12.04.2025 Version number 38 (replaces version 37) Revision: 12.04.2025

Trade name MC-Color Flair vision T - Komponente B

(Contd. of page 2)

· After skin contact In case of contact with skin, wash carefully with plenty of soap and

water. Consult a doctor in case of skin reactions.

· After eye contact Rinse the eyes with open eyelids for a sufficiently long time (at

least 10 minutes) with water that is as lukewarm as possible.

Consult an ophthalmologist.

· After swallowing Do NOT induce vomiting. Rinse mouth with water. Medical

attention required.

· 4.2 Most important symptoms and effects, both acute and

delayed Advice for the doctor: Elementary aid, decontamination,

symptomatic treatment.

4.3 Indication of any

immediate medical attention

and special treatment needed Therapeutic measures: No information available.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

Suitable extinguishing agents CO2, extinguishing powder or water jet. Fight larger fires with

water jet or alcohol-resistant foam.

 5.2 Special hazards arising from the substance or

mixture

No further relevant information available.

· 5.3 Advice for firefighters

· Protective equipment: No special measures required.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and

emergency procedures

Not required.

· 6.2 Environmental

precautions:

Inform respective authorities in case product reaches water or

sewage system.

· 6.3 Methods and material for

containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders,

universal binders, sawdust).

Ensure adequate ventilation.

· 6.4 Reference to other

sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

GB



Page 4/11

Safety data sheet according to UK REACH

Printing date 12.04.2025 Version number 38 (replaces version 37) Revision: 12.04.2025

Trade name MC-Color Flair vision T - Komponente B

(Contd. of page 3)

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure sufficient air exchange and/or extraction in the work areas.

Air extraction is required for spray application.

For solid products: Avoid dust formation and dust deposits. Air limit values mentioned in section 8 must be monitored.

At workplaces where isocyanate aerosols and/or vapours can occur in higher concentrations, targeted air extraction must be used to prevent the occupational hygiene limit value from being

exceeded. The air must be moved away from people.

For products containing solvents: Explosion protection required. The personal protective measures described in section 8 must be observed. The protective measures required when handling isocyanates must be observed. Avoid contact with skin and eyes and inhalation of vapours.

Keep away from food and beverages. Wash hands before breaks and at the end of work and apply skin protection ointment. Store work clothes separately. Remove soiled, soaked clothing

immediately.

· Information about protection

against explosions and fires: Keep ignition sources away - do not smoke.

Protect from heat.

Do not store near heat sources.

· 7.2 Conditions for safe storage, including any incompatibilities

Keep container dry and tightly closed. Further information on the

storage conditions that must be observed for quality assurance reasons can be found in our technical data sheet.

· Storage

Requirements to be met by

storerooms and containers: Keep tightly closed in original packaging. Ventilate storage rooms

well. Carefully close opened containers and store upright to

prevent any leakage.

Storage temperature >5°C and <30°C

· Information about storage in

one common storage facility: May be stored together with hazardous substances of other

classes up to 200 kg.

Further information about

storage conditions:

Keep container tightly closed in a well-ventilated place.

Storage class

· 7.3 Specific end use(s)

No further relevant information available.

GB



Page 5/11

Safety data sheet according to UK REACH

Printing date 12.04.2025 Version number 38 (replaces version 37) Revision: 12.04.2025

Trade name MC-Color Flair vision T - Komponente B

(Contd. of page 4)

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

Components with critical values that require monitoring at the workplace:

CAS: 822-06-0 hexamethylene diisocyanate

WEL Short-term value: 0.07 mg/m³

Long-term value: 0.02 mg/m3

Sen; as -NCO

· DNELs

CAS: 28182-81-2 Aliphatisches Polyisocyanat

Inhalative DNEL 0.5 mg/m³ (Workers) (long term local)

1 mg/m³ (kei) (acute local eff)

CAS: 822-06-0 hexamethylene diisocyanate

Inhalative DNEL 0.5 mg/m³ (ArL)

PNECs

CAS: 28182-81-2 Aliphatisches Polyisocyanat

PNEC aqua 12.7 μg/l (Daphnia magna) (marine)

PNEC 38.28 mg/l (kei) (STP)

CAS: 822-06-0 hexamethylene diisocyanate

PNEC 100 mg/l (Sewage Treatment Plant)

0.0199 mg/l (Mew)

0.199 mg/l (Freshwater)

PNEC 8884 mg/kg dwt (Bod)

4455 mg/kg dwt (Marine water sediment)

44551 mg/kg dwt (Fresh water sediment)

Ingredients with biological limit values:

CAS: 822-06-0 hexamethylene diisocyanate

BMGV 1 µmol creatinine/mol

Medium: urine

Sampling time: At the end of the period od exposure

Parameter: isocyanate-derived diamine

· Additional information:

The lists that were valid during the compilation were used as basis.

8.2 Exposure controls

Appropriate engineering

controls No further data; see section 7.

· Individual protection measures, such as personal protective equipment

· General protective and

hygienic measures Do not smoke, eat or drink while working. Have eye wash

equipment ready.

Do not inhale gases/vapours/aerosols. Avoid contact with eyes and

skin.

Do not store food in the work area. Wash hands before breaks and

at the end of work.

(Contd. on page 6)



Page 6/11

Safety data sheet according to UK REACH

Printing date 12.04.2025 Version number 38 (replaces version 37) Revision: 12.04.2025

Trade name MC-Color Flair vision T - Komponente B

(Contd. of page 5)

· Breathing equipment: Respiratory protection required at insufficiently ventilated

workplaces and when working with splashes. Fresh air masks or combination filters A2-P2 (EN529) are recommended for short-

term work.

If applicable, further recommendations for respiratory protection

can be found in the appendix.

In case of hypersensitivity of the respiratory tract (asthma, chronic

bronchitis), handling of the product is not recommended.

· Hand protection Suitable materials for protective gloves; EN 374:

Butyl rubber - IIR: thickness \geq 0.5mm; breakthrough time \geq 480min. Fluororubber - FKM: thickness \geq 0.4mm; breakthrough time

≥480min.

Multi-layer glove - PE/EVAL/PE; Breakthrough time ≥480 min.

Recommendation: Dispose of contaminated gloves.

• Material of gloves The selection of the suitable gloves does not only depend on the

material, but also on further marks of quality and varies from

manufacturer to manufacturer.

· Penetration time of glove

material Butyl rubber - IIR: thickness ≥0.5mm; breakthrough time ≥480min.

Fluoro rubber - FKM: thickness ≥0.4mm; breakthrough time

>480min.

Multi-layer glove - PE/EVAL/PE; Breakthrough time ≥480 min.

· Eye/face protection

Wear safety goggles/face protection.

· **Body protection:** Wear suitable protective clothing when working.

In case of hypersensitivity of the skin, handling of the product is not

recommended.

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

Colour: Colourless
 Smell: Characteristic
 Melting point/freezing point: Not determined

· Boiling point or initial boiling point and

boiling range 175 °C
• Flash point: 70 °C
• pH at 20 °C 7

· Viscosity:

Kinematic viscositydynamic at 20 °C:Not determined.2000 mPas

Solubility

Water: Not miscible or difficult to mix

· Steam pressure: Not determined.

· Density and/or relative density

Density at 20 °C 1.1 g/cm³

(Contd. on page 7)



Page 7/11

Safety data sheet according to UK REACH

Printing date 12.04.2025 Version number 38 (replaces version 37) Revision: 12.04.2025

Trade name MC-Color Flair vision T - Komponente B

(Contd. of page 6)

· 9.2 Other information

· Appearance:

· Form: Fluid

· Important information on protection of health

and environment, and on safety.

· Self-inflammability: Product is not selfigniting. · Explosive properties: Product is not explosive.

· Information with regard to physical hazard

classes

· Explosives Void Flammable gases Void Void · Aerosols · Oxidising gases Void · Gases under pressure Void Flammable liquids Void

· Flammable solids Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void

· Pyrophoric solids Void · Self-heating substances and mixtures Void

· Substances and mixtures, which emit

flammable gases in contact with water Void · Oxidising liquids Void Oxidising solids Void Void · Organic peroxides Void · Corrosive to metals · Desensitised explosives Void

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability · Thermal decomposition /

conditions to be avoided: No decomposition if used according to specifications.

· 10.3 Possibility of hazardous

reactions Reacts with amines

· 10.4 Conditions to avoid No further relevant information available. · 10.5 Incompatible materials: No further relevant information available.

· 10.6 Hazardous

decomposition products: No dangerous decomposition products known



Page 8/11

Safety data sheet according to UK REACH

Printing date 12.04.2025 Version number 38 (replaces version 37) Revision: 12.04.2025

Trade name MC-Color Flair vision T - Komponente B

(Contd. of page 7)

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Harmful if inhaled.

· LD/LC50	values tha	lues that are relevant for classification:	
CAS: 281	82-81-2 AI	iphatisches Polyisocyanat	
Oral	LD50	>2500 mg/kg (rat) (OECD 423)	
Dermal	LD50	>2000 mg/kg (rat) (OECD 402)	

Inhalative LC50/4 h 1.5 mg/l (rat)

CAS: 666723-27-9 Hydrophiles, aliphatisches Polyisocyanat

Oral	LD50	>5000 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rat)
Inhalative	LC50/4 h	0.5 mg/l (rat)

CAS: 822-06-0 hexamethylene diisocyanate

Oral LD50 738 mg/kg (rat) Inhalative LC50/4 h 0.39 mg/l (rat)

· Primary irritant effect:

· Skin corrosion/irritation Based on available data, the classification criteria are not met.

· Respiratory or skin

sensitisation May cause an allergic skin reaction.

Germ cell mutagenicity
 Carcinogenicity
 Reproductive toxicity
 Based on available data, the classification criteria are not met.
 Based on available data, the classification criteria are not met.
 Based on available data, the classification criteria are not met.

· **STOT-single exposure** May cause respiratory irritation.

• STOT-repeated exposure
• Aspiration hazard

Based on available data, the classification criteria are not met.

Based on available data, the classification criteria are not met.

· 11.2 Information on other hazards

· Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic	toxicity:

CAS: 28182-81-2 Aliphatisches Polyisocyanat

ErC10/72h 370 mg/l (Desmodesmus subspicatus) (EU C.3) ErC50/72h >1000 mg/l (Desmodesmus subspicatus) (EU C.3)

CAS: 666723-27-9 Hydrophiles, aliphatisches Polyisocyanat

LC50/96h | 35.2 mg/l (Danio rerio) EC50 | >10000 mg/l (BEL)

EC50/48h >100 mg/l (Daphnia magna)

(Contd. on page 9)



Page 9/11

Safety data sheet according to UK REACH

Printing date 12.04.2025 Version number 38 (replaces version 37) Revision: 12.04.2025

Trade name MC-Color Flair vision T - Komponente B

(Contd. of page 8)

ErC50/72h | 72 mg/l (Desmodesmus subspicatus)

· 12.2 Persistence and

degradability No further relevant information available.

· 12.3 Bioaccumulative

potential No further relevant information available.

12.4 Mobility in soil No further relevant information available.

· 12.5 Results of PBT and vPvB assessment
· PBT:
· vPvB:
Not applicable.
Not applicable.

· 12.6 Endocrine disrupting

properties The product does not contain substances with endocrine disrupting

properties.

· 12.7 Other adverse effects

· Remark: Harmful to fish

· Additional ecological information:

• General notes: Harmful to aquatic organisms

Do not allow undiluted product or large quantities of it to reach

ground water, water bodies or sewage system.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

• Recommendation Must not be disposed of together with household garbage. Do not

allow product to reach sewage system.

· Uncleaned packagings:

• Recommendation: Empty contaminated packagings thoroughly. They can be recycled

after thorough and proper cleaning.

14.1 UN number or ID number	Void	
ADR, ADN, IMDG, IATA	VOIU	
14.2 UN proper shipping name		
ADR, ADN, IMDG, IATA	Void	
14.3 Transport hazard class(es)		
ADR, ADN, IMDG, IATA		
Class	Void	
14.4 Packing group		
ADR, IMDG, IĂTA	Void	
14.5 Environmental hazards:		
Marine pollutant:	No	

(Contd. on page 10)



Page 10/11

Safety data sheet according to UK REACH

Printing date 12.04.2025 Version number 38 (replaces version 37) Revision: 12.04.2025

Trade name MC-Color Flair vision T - Komponente B

(Contd. of page 9)

· 14.6 Special precautions for user

· 14.7 Maritime transport in bulk according to IMO instruments

· UN "Model Regulation":

Void

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/ legislation specific for the

substance or mixture No further relevant information available.

· Poisons Act

· Regulated explosives precursors

None of the ingredients is listed.

· Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors

None of the ingredients is listed.

· Reportable poisons

None of the ingredients is listed.

15.2 Chemical safety

assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases H302 Harmful if swallowed.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H330 Fatal if inhaled. H331 Toxic if inhaled. H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing

difficulties if inhaled.

H335 May cause respiratory irritation.

H412 Harmful to aquatic life with long lasting effects.

EUH204 Contains isocyanates. May produce an allergic reaction.

Department issuing data

specification sheet: Environment protection department.

(Contd. on page 11)



Page 11/11

Safety data sheet according to UK REACH

Printing date 12.04.2025

Version number 38 (replaces version 37)

Trade name MC-Color Flair vision T - Komponente B

(Contd. of page 10)

Revision: 12.04.2025

· Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (UK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Acute Tox. 1: Acute toxicity – Category 1 Acute Tox. 3: Acute toxicity – Category 3

Acute Tox. 4: Acute toxicity - Category 4

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 Resp. Sens. 1: Respiratory sensitisation – Category 1

Skin Sens. 1: Skin sensitisation - Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic

hazard - Category 3

· * Data compared to the previous version altered.

GB