



BE SURE. BUILD SURE.

Page 1/11

Safety data sheet according to UK REACH

Printing date 10.12.2024

Version number 33 (replaces version 32)

Revision: 10.12.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· **1.1 Product identifier**

· **Trade name** MC-Color Flex pure

· **1.2 Relevant identified uses of the substance or mixture and uses advised against**

No further relevant information available.

· **Application of the substance / the mixture**

Dispersion paint/ Latex paint
Surface protection

· **1.3 Details of the supplier of the safety data sheet**

· **Manufacturer/Supplier:** MC-Bauchemie Müller GmbH & Co. KG
Am Kruppwald 1-8
D-46238 Bottrop
Tel.: +49(0)2041-101-0
Fax.: +49(0)2041-101-400
E-Mail: info@mc-bauchemie.de

MC-Bauchemie AG
Hagackerstr. 10
CH-8953 Dietikon
Tel.: +44-7400510
Fax : +44-7400533

· **Informing department:** msds@mc-bauchemie.de

· **1.4 Emergency telephone number:**

Tel.: +49 / (0)700 24112112 (MCR)
Tel.: +1 872 5888271 (MCR)

SECTION 2: Hazards identification

· **2.1 Classification of the substance or mixture**

· **Classification according to Regulation (EC) No 1272/2008**

Skin Sens. 1 H317 May cause an allergic skin reaction.

· **2.2 Label elements**

· **Labelling according to**

Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation.

· **Hazard pictograms**



GHS07

· **Signal word**

Warning

· **Hazard-determining**

components of labelling:

2-methyl-2H-isothiazol-3-one

(Contd. on page 2)

GB



BE SURE. BUILD SURE.

Safety data sheet according to UK REACH

Printing date 10.12.2024

Version number 33 (replaces version 32)

Revision: 10.12.2024

Trade name MC-Color Flex pure

(Contd. of page 1)

- **Hazard statements**
 - **Precautionary statements**
 - **Additional information:**
 - **2.3 Other hazards**
 - **Results of PBT and vPvB assessment**
 - **PBT:**
 - **vPvB:**
- 1,2-benzisothiazol-3(2H)-one
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)
- H317 May cause an allergic skin reaction.*
- P261 Avoid breathing dust/fume/gas/mist/vapours/spray.*
- P280 Wear protective gloves.*
- P362+P364 Take off contaminated clothing and wash it before reuse.*
- P333+P313 If skin irritation or rash occurs: Get medical advice/attention.*
- P321 Specific treatment (see on this label).*
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.*
- EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.*
- Contains biocidal products: 1,2-benzisothiazol-3(2H)-one, 2-methyl-2H-isothiazol-3-one, reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)*
- Not applicable.
- Not applicable.

SECTION 3: Composition/information on ingredients

- **3.2 Mixtures**
- **Description:** Mixture consisting of the following components.

· **Dangerous components:**

CAS: 1317-65-3	Calcium carbonate substance with a Community workplace exposure limit	10-30%
CAS: 13463-67-7 EINECS: 236-675-5	Titanium Dioxide Carc. 2, H351	10-30%
CAS: 2634-33-5 EINECS: 236-671-3	1,2-benzisothiazol-3(2H)-one Acute Tox. 2, H330; Eye Dam. 1, H318; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Acute Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 1, H317 Specific concentration limit: Skin Sens. 1; H317: C ≥ 0.05 %	≥0.025-<0.05%
CAS: 2682-20-4 EINECS: 220-239-6	2-methyl-2H-isothiazol-3-one Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 2, H330; Skin Corr. 1B, H314; Eye Dam. 1, H318; Aquatic Acute 1, H400 (M=10); Aquatic Chronic 1, H410 (M=1); Skin Sens. 1A, H317, EUH071 Specific concentration limit: Skin Sens. 1A; H317: C ≥ 0.0015 %	≥0.0015-<0.025%

(Contd. on page 3)



BE SURE. BUILD SURE.

Safety data sheet according to UK REACH

Printing date 10.12.2024

Version number 33 (replaces version 32)

Revision: 10.12.2024

Trade name MC-Color Flex pure

(Contd. of page 2)

CAS: 55965-84-9

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

≥0.00025-<0.0015%

Acute Tox. 3, H301; Acute Tox. 2, H310; Acute Tox. 2, H330; Skin Corr. 1C, H314; Eye Dam. 1, H318; Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 (M=100); Skin Sens. 1A, H317, EUH071

Specific concentration limits:

Skin Corr. 1C; H314: C ≥ 0.6 %

Skin Irrit. 2; H315: 0.06 % ≤ C < 0.6 %

Eye Dam. 1; H318: C ≥ 0.6 %

Eye Irrit. 2; H319: 0.06 % ≤ C < 0.6 %

Skin Sens. 1A; H317: C ≥ 0.0015 %

· **Additional information**

For the wording of the listed hazard phrases refer to section 16.
Acrylic dispersion
Chalk
Water

SECTION 4: First aid measures

· **4.1 Description of first aid measures**

· **General information**

For all first aid measures: observe self-protection and consult a doctor!

· **After inhalation**

Take the person out into the fresh air.

· **After skin contact**

Remove heavily soiled clothing.

Clean with plenty of water.

Do not use thinner or similar.

· **After eye contact**

Rinse for 10 minutes under running water with the eyelids open or use eye rinsing solution. Always consult an ophthalmologist!

· **After swallowing**

Do not induce vomiting.

Drink plenty of water in small sips.

SECTION 5: Firefighting measures

· **5.1 Extinguishing media**

· **Suitable extinguishing agents** Use fire fighting measures that suit the environment.

· **5.2 Special hazards arising from the substance or mixture**

No further relevant information available.

· **5.3 Advice for firefighters**

· **Protective equipment:**

No special measures required.

GB



BE SURE. BUILD SURE.

Safety data sheet according to UK REACH

Printing date 10.12.2024

Version number 33 (replaces version 32)

Revision: 10.12.2024

Trade name MC-Color Flex pure

(Contd. of page 3)

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures** *Not required.*
- **6.2 Environmental precautions:** *Dilute with much water.*
- **6.3 Methods and material for containment and cleaning up:** *Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).*
- **6.4 Reference to other sections** *No dangerous materials are released.*

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** *No special measures required.
No special precautions necessary if used correctly.*
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage**
- **Requirements to be met by storerooms and containers:** *Protect containers from frost!
Only store in the original container or in containers recommended by the manufacturer.
After decanting, label containers as original containers.
Do not store in break rooms, recreation rooms or sanitary facilities as well as in stairwells, corridors, escape and rescue routes, passages, passageways and confined spaces.*
- **Further information about storage conditions:** *None.*
- **Storage class** *12*

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

· **Components with critical values that require monitoring at the workplace:**

CAS: 1317-65-3 Calcium carbonate

WEL Long-term value: 10^{-4} mg/m³
**inhalable dust; **respirable*

· DNELs

CAS: 1317-65-3 Calcium carbonate

Oral DNEL 6.1 mg/kg bw/Tag (ArL)

Inhalative DNEL 10 mg/m³ (ArL)

(Contd. on page 5)



BE SURE. BUILD SURE.

Safety data sheet according to UK REACH

Printing date 10.12.2024

Version number 33 (replaces version 32)

Revision: 10.12.2024

Trade name MC-Color Flex pure

(Contd. of page 4)

· **PNECs**

CAS: 1317-65-3 Calcium carbonate

PNEC 100 mg/l (Sewage Treatment Plant)

· **Additional information:** The lists that were valid during the compilation were used as basis.

· **8.2 Exposure controls**

· **Appropriate engineering controls**

No further data; see section 7.

· **Individual protection measures, such as personal protective equipment**

· **General protective and hygienic measures**

Do not store any foodstuffs or eat, drink, snuff or smoke in the work area!

Avoid contact with eyes and skin!

Preventively apply skin protection ointment to facilitate skin cleansing.

Remove product residues from the skin!

Clean hands thoroughly at the end of work and before cleaning!

Remove product residues from the skin with a suitable cleaning agent - never use solvents or thinners to clean the skin!

Use skin care products after work (moisturising cream).

· **Breathing equipment:**

For spraying processes:

Particle filter P2 (white)

· **Hand protection**

Gloves made of: Natural latex, polychloroprene, nitrile rubber.

(Category 3 chemical protective gloves, recognisable by the CE mark with four-digit test number).

When wearing protective gloves, cotton undergloves are recommended.

· **Material of gloves**

Natural latex, polychloroprene, nitrile rubber.

· **Penetration time of glove material**

The exact breakthrough time must be obtained from the protective glove manufacturer and must be observed.

· **Eye/face protection**

Frame glasses

· **Body protection:**

Protective work clothing.

· **Skin protection**

Use greasy skin protection ointment for all uncovered parts of the body!

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Colour:**

According to product specification

· **Smell:**

Characteristic

· **Melting point/freezing point:**

Not determined

· **Boiling point or initial boiling point and boiling range**

100 °C (CAS: 7732-18-5 water, distilled, conductivity or of similar purity)

· **Flash point:**

Not applicable

(Contd. on page 6)



BE SURE. BUILD SURE.

Page 6/11

Safety data sheet according to UK REACH

Printing date 10.12.2024

Version number 33 (replaces version 32)

Revision: 10.12.2024

Trade name MC-Color Flex pure

(Contd. of page 5)

· pH at 20 °C	8
· Viscosity:	
· Kinematic viscosity	Not determined.
· dynamic at 20 °C:	32500 mPas
· Solubility	
· Water:	Fully miscible
· Steam pressure at 20 °C:	23 hPa (CAS: 7732-18-5 water, distilled, conductivity or of similar purity)
· Density and/or relative density	
· Density at 20 °C	1.42 g/cm ³
· Relative density	Not determined.

9.2 Other information

· Appearance:	
· Form:	Pasty
· Important information on protection of health and environment, and on safety.	
· Self-inflammability:	Product is not selfigniting.
· Explosive properties:	Product is not explosive.

Information with regard to physical hazard classes

· Explosives	Void
· Flammable gases	Void
· Aerosols	Void
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Void
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

SECTION 10: Stability and reactivity

· 10.1 Reactivity	No further relevant information available.
· 10.2 Chemical stability	
· Thermal decomposition / conditions to be avoided:	No decomposition if used according to specifications.
· 10.3 Possibility of hazardous reactions	No dangerous reactions known

(Contd. on page 7)

GB



BE SURE. BUILD SURE.

Safety data sheet according to UK REACH

Printing date 10.12.2024

Version number 33 (replaces version 32)

Revision: 10.12.2024

Trade name MC-Color Flex pure

(Contd. of page 6)

- **10.4 Conditions to avoid** *No further relevant information available.*
- **10.5 Incompatible materials:** *No further relevant information available.*
- **10.6 Hazardous decomposition products:** *No dangerous decomposition products known*

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** *Based on available data, the classification criteria are not met.*

- **LD/LC50 values that are relevant for classification:**

CAS: 1317-65-3 Calcium carbonate

Oral	LD50	>2000 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rat)

CAS: 13463-67-7 Titanium Dioxide

Oral	LD50	>5000 mg/kg (rat)
Dermal	LD50	>10000 mg/kg (rabbit)
Inhalative	LC50/4 h	>6.8 mg/l (rat)

CAS: 2634-33-5 1,2-benzisothiazol-3(2H)-one

Oral	LD50	1020 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rat)

CAS: 2682-20-4 2-methyl-2H-isothiazol-3-one

Oral	LD50	50-300 mg/kg (rat)
Inhalative	LC50/4 h	0.11 mg/l (rat)

CAS: 55965-84-9 reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

Oral	LD50	49.6-75 mg/kg (rat)
Dermal	LD50	87.12 mg/kg (rabbit)
Inhalative	LC50/4 h	0.171 mg/l (rat)

- **Primary irritant effect:**
- **Skin corrosion/irritation** *Based on available data, the classification criteria are not met.*
- **Respiratory or skin sensitisation** *May cause an allergic skin reaction.*
- **Germ cell mutagenicity** *Based on available data, the classification criteria are not met.*
- **Carcinogenicity** *Based on available data, the classification criteria are not met.*
- **Reproductive toxicity** *Based on available data, the classification criteria are not met.*
- **STOT-single exposure** *Based on available data, the classification criteria are not met.*
- **STOT-repeated exposure** *Based on available data, the classification criteria are not met.*
- **Aspiration hazard** *Based on available data, the classification criteria are not met.*

(Contd. on page 8)



BE SURE. BUILD SURE.

**Safety data sheet
according to UK REACH**

Printing date 10.12.2024

Version number 33 (replaces version 32)

Revision: 10.12.2024

Trade name MC-Color Flex pure

(Contd. of page 7)

· **11.2 Information on other hazards**

· **Endocrine disrupting properties**

None of the ingredients is listed.

SECTION 12: Ecological information

· **12.1 Toxicity**

· **Aquatic toxicity:**

CAS: 1317-65-3 Calcium carbonate

EC50/72h >14 mg/l (*Desmodesmus subspicatus*)

LC50/96h >10000 mg/l (*Oncorhynchus mykiss*)

LC50/48h >1000 mg/l (*Daphnia magna*)

EC50/48h >1000 mg/l (*Daphnia magna*)

CAS: 2634-33-5 1,2-benzisothiazol-3(2H)-one

EC50/72h 0.067 mg/l (*Pseudokirchneriella subcapitata*)

0.11 mg/l (*Selenastrum capricornutum*)

LC50/96h 1.6 mg/l (*Oncorhynchus mykiss*)

EC50/48h 1.1 mg/l (*Daphnia magna*)

CAS: 2682-20-4 2-methyl-2H-isothiazol-3-one

EC50/72h 0.157 mg/l (*Pseudokirchneriella subcapitata*)

LC50/96h 6 mg/l (*Oncorhynchus mykiss*)

EC50/48h 1.68 mg/l (*Daphnies*)

CAS: 55965-84-9 reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

LC50/24h 0.19 mg/l (fish)

EC50/72h 0.027 mg/l (*Pseudokirchneriella subcapitata*)

LC50/96h 0.19 mg/l (*Oncorhynchus mykiss*)

LC50/48h 0.28 mg/l (fish)

EC50/48h 0.16 mg/l (*Daphnia magna*)

NOEC 0.02 mg/l (*Oncorhynchus mykiss*)

0.00049 mg/l (Ske)

0.1 mg/l (*Daphnia magna*)

· **12.2 Persistence and degradability**

No further relevant information available.

· **12.3 Bioaccumulative potential**

No further relevant information available.

· **12.4 Mobility in soil**

No further relevant information available.

· **12.5 Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

(Contd. on page 9)



BE SURE. BUILD SURE.

Safety data sheet according to UK REACH

Printing date 10.12.2024

Version number 33 (replaces version 32)

Revision: 10.12.2024

Trade name MC-Color Flex pure

(Contd. of page 8)

· **12.6 Endocrine disrupting properties**

The product does not contain substances with endocrine disrupting properties.

· **12.7 Other adverse effects**

· **Additional ecological information:**

· **General notes:**

Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system.

SECTION 13: Disposal considerations

· **13.1 Waste treatment methods**

· **Recommendation**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· **Uncleaned packagings:**

· **Recommendation:**

Empty contaminated packagings thoroughly. They can be recycled after thorough and proper cleaning.

· **Recommended cleaning agent:**

Water, if necessary with cleaning agent.

SECTION 14: Transport information

· **14.1 UN number or ID number**

· **ADR, ADN, IMDG, IATA**

Void

· **14.2 UN proper shipping name**

· **ADR, ADN, IMDG, IATA**

Void

· **14.3 Transport hazard class(es)**

· **ADR, ADN, IMDG, IATA**

· **Class**

Void

· **14.4 Packing group**

· **ADR, IMDG, IATA**

Void

· **14.5 Environmental hazards:**

· **Marine pollutant:**

No

· **14.6 Special precautions for user**

Not applicable.

· **14.7 Maritime transport in bulk according to IMO instruments**

Not applicable.

· **Transport/Additional information:**

Not dangerous according to the above specifications.

· **UN "Model Regulation":**

Void

GB

(Contd. on page 10)



BE SURE. BUILD SURE.

Safety data sheet according to UK REACH

Printing date 10.12.2024

Version number 33 (replaces version 32)

Revision: 10.12.2024

Trade name MC-Color Flex pure

(Contd. of page 9)

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/ legislation specific for the substance or mixture**
- **Poisons Act**

No further relevant information available.

- **Regulated explosives precursors**

None of the ingredients is listed.

- **Regulated poisons**

None of the ingredients is listed.

- **Reportable explosives precursors**

None of the ingredients is listed.

- **Reportable poisons**

None of the ingredients is listed.

- **15.2 Chemical safety assessment:**

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**

H301 Toxic if swallowed.
 H302 Harmful if swallowed.
 H310 Fatal in contact with skin.
 H311 Toxic in contact with skin.
 H314 Causes severe skin burns and eye damage.
 H315 Causes skin irritation.
 H317 May cause an allergic skin reaction.
 H318 Causes serious eye damage.
 H319 Causes serious eye irritation.
 H330 Fatal if inhaled.
 H351 Suspected of causing cancer.
 H400 Very toxic to aquatic life.
 H410 Very toxic to aquatic life with long lasting effects.
 EUH071 Corrosive to the respiratory tract.

- **Department issuing data specification sheet:**

Environment protection department.

- **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
 ICAO: International Civil Aviation Organisation
 ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods
 IATA: International Air Transport Association

(Contd. on page 11)



BE SURE. BUILD SURE.

Page 11/11

Safety data sheet according to UK REACH

Printing date 10.12.2024

Version number 33 (replaces version 32)

Revision: 10.12.2024

Trade name MC-Color Flex pure

(Contd. of page 10)

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (UK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Acute Tox. 3: Acute toxicity – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Acute Tox. 2: Acute toxicity – Category 2

Skin Corr. 1B: Skin corrosion/irritation – Category 1B

Skin Corr. 1C: Skin corrosion/irritation – Category 1C

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Skin Sens. 1: Skin sensitisation – Category 1

Skin Sens. 1A: Skin sensitisation – Category 1A

Carc. 2: Carcinogenicity – Category 2

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

*** Data compared to the
previous version altered.**

GB