



BE SURE. BUILD SURE.

Page 1/11

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 31.12.2022

Version number 8 (replaces version 7)

Revision: 31.12.2022

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

· **1.1 Product identifier**

· **Trade name** MC-Color Proof vision - Komponente A

· **Article number:** 3917

· **1.2 Relevant identified uses of the substance or mixture and uses advised against**

No further relevant information available.

· **Application of the substance / the mixture**

Coating material

· **1.3 Details of the supplier of the safety data sheet**

· **Manufacturer/Supplier:** MC-Bauchemie Müller GmbH & Co. KG  
Am Kruppwald 1-8  
D-46238 Bottrop  
Tel.: +49(0)2041-101-0  
Fax.: +49(0)2041-101-400  
E-Mail: info@mc-bauchemie.de

MC-Bauchemie AG  
Hagackerstr. 10  
CH-8953 Dietikon  
Tel.: +44-7400510  
Fax : +44-7400533

· **Informing department:** msds@mc-bauchemie.de

· **1.4 Emergency telephone number:**

Tel.: +49 / (0)700 24112112 (MCR)  
Tel.: +48612864565

### SECTION 2: Hazards identification

· **2.1 Classification of the substance or mixture**

· **Classification according to Regulation (EC) No 1272/2008**

Skin Sens. 1 H317 May cause an allergic skin reaction.

· **2.2 Label elements**

· **Labelling according to**

**Regulation (EC) No 1272/2008** The product is classified and labelled according to the GB CLP regulation.

· **Hazard pictograms**



GHS07

· **Signal word**

Warning

· **Hazard-determining**

**components of labelling:**

2-methyl-2H-isothiazol-3-one  
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

(Contd. on page 2)

GB



BE SURE. BUILD SURE.

### Safety data sheet according to 1907/2006/EC, Article 31

Printing date 31.12.2022

Version number 8 (replaces version 7)

Revision: 31.12.2022

**Trade name MC-Color Proof vision - Komponente A**

(Contd. of page 1)

- **Hazard statements** formaldehyde
- **Precautionary statements** 1,2-benzisothiazol-3(2H)-one  
H317 May cause an allergic skin reaction.  
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.  
P280 Wear protective gloves.  
P362+P364 Take off contaminated clothing and wash it before reuse.  
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.  
P321 Specific treatment (see on this label).  
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

### SECTION 3: Composition/information on ingredients

- **3.2 Mixtures**
- **Description:** Mixture consisting of the following components.

· **Dangerous components:**

CAS: 5131-66-8 EINECS: 225-878-4	3-butoxypropan-2-ol Acute Tox. 3, H331; Skin Irrit. 2, H315; Eye Irrit. 2, H319	<0.5%
CAS: 50-00-0 EINECS: 200-001-8	formaldehyde Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331; Muta. 2, H341; Carc. 1B, H350; Skin Corr. 1B, H314; Skin Sens. 1, H317 Specific concentration limits: Skin Corr. 1B; H314: C ≥ 25 % Skin Irrit. 2; H315: 5 % ≤ C < 25 % Eye Irrit. 2; H319: 5 % ≤ C < 25 % Skin Sens. 1; H317: C ≥ 0.2 % STOT SE 3; H335: C ≥ 5 %	<0.1%

(Contd. on page 3)



BE SURE. BUILD SURE.

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 31.12.2022

Version number 8 (replaces version 7)

Revision: 31.12.2022

**Trade name MC-Color Proof vision - Komponente A**

(Contd. of page 2)

CAS: 2634-33-5 EINECS: 220-120-9	1,2-benzisothiazol-3(2H)-one Acute Tox. 2, H330; Eye Dam. 1, H318; Aquatic Acute 1, H400; Aquatic Chronic 2, H411; Acute Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 1, H317 Specific concentration limits: Skin Sens. 1; H317: C $\geq$ 0.05 % Aquatic Acute 1; H400: C $\geq$ 1 %	<0.05%
CAS: 2682-20-4	2-methyl-2H-isothiazol-3-one Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 2, H330; Skin Corr. 1B, H314; Aquatic Acute 1, H400 (M=10); Aquatic Chronic 2, H411; Skin Sens. 1A, H317; STOT SE 3, H335 Specific concentration limit: Skin Sens. 1A; H317: C $\geq$ 0.0015 %	$\geq$ 0.0015-<0.025%
CAS: 55965-84-9	reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) Acute Tox. 3, H301; Acute Tox. 2, H310; Acute Tox. 2, H330; Skin Corr. 1C, H314; Eye Dam. 1, H318; Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 (M=100); Skin Sens. 1A, H317 Specific concentration limits: Skin Corr. 1C; H314: C $\geq$ 0.6 % Skin Irrit. 2; H315: 0.06 % $\leq$ C < 0.6 % Eye Dam. 1; H318: C $\geq$ 0.6 % Eye Irrit. 2; H319: 0.06 % $\leq$ C < 0.6 % Skin Sens. 1A; H317: C $\geq$ 0.0015 %	$\geq$ 0.00025-<0.0015%

· **Additional information** For the wording of the listed hazard phrases refer to section 16.

**SECTION 4: First aid measures**

· **4.1 Description of first aid measures**

- **General information** No special measures required.
- **After inhalation** Supply fresh air; consult doctor in case of symptoms.
- **After skin contact** The product is not skin irritating.
- **After eye contact** Rinse opened eye for several minutes under running water.
- **After swallowing** In case of persistent symptoms consult doctor.

· **4.2 Most important symptoms and effects, both acute and delayed**

No further relevant information available.

· **4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

GB

(Contd. on page 4)



BE SURE. BUILD SURE.

Page 4/11

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 31.12.2022

Version number 8 (replaces version 7)

Revision: 31.12.2022

Trade name MC-Color Proof vision - Komponente A

(Contd. of page 3)

### SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents** Use fire fighting measures that suit the environment.
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** No special measures required.

### SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures** Not required.
- **6.2 Environmental precautions:** Dilute with much water.
- **6.3 Methods and material for containment and cleaning up:** Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
- **6.4 Reference to other sections** No dangerous materials are released.

### SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** No special measures required.
- **Information about protection against explosions and fires:** No special measures required.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage**
- **Requirements to be met by storerooms and containers:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** None.
- **7.3 Specific end use(s)** No further relevant information available.

GB

(Contd. on page 5)



BE SURE. BUILD SURE.

### Safety data sheet according to 1907/2006/EC, Article 31

Printing date 31.12.2022

Version number 8 (replaces version 7)

Revision: 31.12.2022

Trade name MC-Color Proof vision - Komponente A

(Contd. of page 4)

#### SECTION 8: Exposure controls/personal protection

##### 8.1 Control parameters

Components with critical values that require monitoring at the workplace:

##### 50-00-0 formaldehyde

WEL	Short-term value: 2.5 mg/m <sup>3</sup> , 2 ppm
	Long-term value: 2.5 mg/m <sup>3</sup> , 2 ppm
	Carc

##### DNELs

##### 5131-66-8 3-butoxypropan-2-ol

Oral	DNEL	8.75 mg/kg bw/Tag (ArL)
Dermal	DNEL	44 mg/kg bw/day (ArL)
Inhalative	DNEL	270.5 mg/m <sup>3</sup> (ArL)

##### PNECs

##### 5131-66-8 3-butoxypropan-2-ol

PNEC	10 mg/l (Sewage Treatment Plant)
	0.0525 mg/l (Mew)
	0.525 mg/l (Suw)
PNEC	0.16 mg/kg dwt (Bod)
	0.236 mg/kg dwt (Sediment)
	2.36 mg/kg dwt (Fresh water sediment)

Additional information: The lists that were valid during the compilation were used as basis.

##### 8.2 Exposure controls

Appropriate engineering controls

No further data; see item 7.

Individual protection measures, such as personal protective equipment

General protective and hygienic measures

The usual precautionary measures should be adhered to in handling the chemicals.

Breathing equipment:

Not required.

Hand protection

Impervious gloves

Material of gloves

Butyl rubber, BR

Penetration time of glove material

-

Eye/face protection

Safety glasses

#### SECTION 9: Physical and chemical properties

##### 9.1 Information on basic physical and chemical properties

General Information

Colour:

Whitish

Smell:

Characteristic

(Contd. on page 6)



BE SURE. BUILD SURE.

Page 6/11

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 31.12.2022

Version number 8 (replaces version 7)

Revision: 31.12.2022

Trade name MC-Color Proof vision - Komponente A

(Contd. of page 5)

· <b>Melting point/freezing point:</b>	Not determined
· <b>Boiling point or initial boiling point and boiling range</b>	100 °C (7732-18-5 water, distilled, conductivity or of similar purity)
· <b>Flash point:</b>	Not applicable
· <b>pH at 20 °C</b>	7
· <b>Viscosity:</b>	
· <b>dynamic at 20 °C:</b>	4000 mPas
· <b>Solubility</b>	
· <b>Water:</b>	Fully miscible
· <b>Steam pressure at 20 °C:</b>	23 hPa (7732-18-5 water, distilled, conductivity or of similar purity)
· <b>Density and/or relative density</b>	
· <b>Density at 20 °C</b>	1.08 g/cm <sup>3</sup>

### · 9.2 Other information

· <b>Appearance:</b>	
· <b>Form:</b>	Fluid
· <b>Important information on protection of health and environment, and on safety.</b>	
· <b>Self-inflammability:</b>	Product is not selfigniting.
· <b>Explosive properties:</b>	Product is not explosive.

### · Information with regard to physical hazard classes

· <b>Explosives</b>	Void
· <b>Flammable gases</b>	Void
· <b>Aerosols</b>	Void
· <b>Oxidising gases</b>	Void
· <b>Gases under pressure</b>	Void
· <b>Flammable liquids</b>	Void
· <b>Flammable solids</b>	Void
· <b>Self-reactive substances and mixtures</b>	Void
· <b>Pyrophoric liquids</b>	Void
· <b>Pyrophoric solids</b>	Void
· <b>Self-heating substances and mixtures</b>	Void
· <b>Substances and mixtures, which emit flammable gases in contact with water</b>	Void
· <b>Oxidising liquids</b>	Void
· <b>Oxidising solids</b>	Void
· <b>Organic peroxides</b>	Void
· <b>Corrosive to metals</b>	Void
· <b>Desensitised explosives</b>	Void

GB

(Contd. on page 7)



BE SURE. BUILD SURE.

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 31.12.2022

Version number 8 (replaces version 7)

Revision: 31.12.2022

Trade name MC-Color Proof vision - Komponente A

(Contd. of page 6)

**SECTION 10: Stability and reactivity**

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known

**SECTION 11: Toxicological information**

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values that are relevant for classification:**

**5131-66-8 3-butoxypropan-2-ol**

Oral	LD50	3300 mg/kg (rat)
	NOAEL	350 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rat)
Inhalative	LC50/4 h	>3.4 mg/l (rat)

**50-00-0 formaldehyde**

Oral	LD50	>200 mg/kg (rat)
Dermal	LD50	300 mg/kg (rat)

**2634-33-5 1,2-benzisothiazol-3(2H)-one**

Oral	LD50	1020 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rat)

**2682-20-4 2-methyl-2H-isothiazol-3-one**

Oral	LD50	50-300 mg/kg (rat)
------	------	--------------------

**55965-84-9 reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)**

Oral	LD50	49.6-75 mg/kg (rat)
Dermal	LD50	87.12 mg/kg (rabbit)
Inhalative	LC50/4 h	0.171 mg/l (rat)

- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation** May cause an allergic skin reaction.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.

(Contd. on page 8)



BE SURE. BUILD SURE.

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 31.12.2022

Version number 8 (replaces version 7)

Revision: 31.12.2022

**Trade name MC-Color Proof vision - Komponente A**

(Contd. of page 7)

- **Aspiration hazard** Based on available data, the classification criteria are not met.
- **11.2 Information on other hazards**

· **Endocrine disrupting properties**

None of the ingredients is listed.

**SECTION 12: Ecological information**

· **12.1 Toxicity**

· **Aquatic toxicity:**

**5131-66-8 3-butoxypropan-2-ol**

LC50/96h	>560 mg/l (Gup)
EC50	>1000 mg/l (BEL)
EC50/48h	>1000 mg/l (Daphnia magna)
NOEC	180 mg/l (Gup)
	560 mg/l (Selenastrum capricornutum)
	560 mg/l (Daphnia magna)

**2634-33-5 1,2-benzisothiazol-3(2H)-one**

EC50/72h	0.067 mg/l (Pseudokirchneriella subcapitata)
	0.11 mg/l (Selenastrum capricornutum)
LC50/96h	1.6 mg/l (Oncorhynchus mykiss)
EC50/48h	1.1 mg/l (Daphnia magna)

**2682-20-4 2-methyl-2H-isothiazol-3-one**

EC50/72h	0.157 mg/l (Pseudokirchneriella subcapitata)
LC50/96h	6 mg/l (Oncorhynchus mykiss)
EC50/48h	1.68 mg/l (Daphnies)

**55965-84-9 reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)**

LC50/24h	0.19 mg/l (fish)
EC50/72h	0.027 mg/l (Pseudokirchneriella subcapitata)
LC50/96h	0.19 mg/l (Oncorhynchus mykiss)
LC50/48h	0.28 mg/l (fish)
EC50/48h	0.16 mg/l (Daphnia magna)
NOEC	0.02 mg/l (Oncorhynchus mykiss)
	0.00049 mg/l (Ske)
	0.1 mg/l (Daphnia magna)

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.

(Contd. on page 9)





BE SURE. BUILD SURE.

### Safety data sheet according to 1907/2006/EC, Article 31

Printing date 31.12.2022

Version number 8 (replaces version 7)

Revision: 31.12.2022

**Trade name MC-Color Proof vision - Komponente A**

(Contd. of page 8)

- **vPvB:** *Not applicable.*
- **12.6 Endocrine disrupting properties** *The product does not contain substances with endocrine disrupting properties.*
- **12.7 Other adverse effects**
- **Additional ecological information:**
- **General notes:** *Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system.*

#### SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation** *Must not be disposed of together with household garbage. Do not allow product to reach sewage system.*
- **Uncleaned packagings:**
- **Recommendation:** *Disposal must be made according to official regulations.*
- **Recommended cleaning agent:** *Water, if necessary with cleaning agent.*

#### SECTION 14: Transport information

- |   |   |
|---|---|
| · <b>14.1 UN number or ID number</b>                                  |   |
| · <b>ADR, ADN, IMDG, IATA</b>   | <i>Void</i>   |
| · <b>14.2 UN proper shipping name</b>                                 |   |
| · <b>ADR, ADN, IMDG, IATA</b>   | <i>Void</i>   |
| · <b>14.3 Transport hazard class(es)</b>                              |   |
| · <b>ADR, ADN, IMDG, IATA</b>   |   |
| · <b>Class</b>  | <i>Void</i>   |
| · <b>14.4 Packing group</b>   |   |
| · <b>ADR, IMDG, IATA</b>  | <i>Void</i>   |
| · <b>14.5 Environmental hazards:</b>                                  |   |
| · <b>Marine pollutant:</b>  | <i>No</i>   |
| · <b>14.6 Special precautions for user</b>                            | <i>Not applicable.</i>                                      |
| · <b>14.7 Maritime transport in bulk according to IMO instruments</b> | <i>Not applicable.</i>                                      |
| · <b>Transport/Additional information:</b>                            | <i>Not dangerous according to the above specifications.</i> |
| · <b>UN "Model Regulation":</b>                                       | <i>Void</i>   |

GB

(Contd. on page 10)



BE SURE. BUILD SURE.

Page 10/11

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 31.12.2022

Version number 8 (replaces version 7)

Revision: 31.12.2022

Trade name **MC-Color Proof vision - Komponente A**

(Contd. of page 9)

### SECTION 15: Regulatory information

· **15.1 Safety, health and environmental regulations/ legislation specific for the substance or mixture**

No further relevant information available.

· **15.2 Chemical safety assessment:**

A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H301 Toxic if swallowed.  
H302 Harmful if swallowed.  
H310 Fatal in contact with skin.  
H311 Toxic in contact with skin.  
H314 Causes severe skin burns and eye damage.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H318 Causes serious eye damage.  
H319 Causes serious eye irritation.  
H330 Fatal if inhaled.  
H331 Toxic if inhaled.  
H335 May cause respiratory irritation.  
H341 Suspected of causing genetic defects.  
H350 May cause cancer.  
H400 Very toxic to aquatic life.  
H410 Very toxic to aquatic life with long lasting effects.  
H411 Toxic to aquatic life with long lasting effects.

· **Department issuing data specification sheet:**

Environment protection department.

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)  
ICAO: International Civil Aviation Organisation  
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)  
IMDG: International Maritime Code for Dangerous Goods  
IATA: International Air Transport Association  
GHS: Globally Harmonised System of Classification and Labelling of Chemicals  
EINECS: European Inventory of Existing Commercial Chemical Substances  
ELINCS: European List of Notified Chemical Substances  
CAS: Chemical Abstracts Service (division of the American Chemical Society)  
DNEL: Derived No-Effect Level (UK REACH)  
PNEC: Predicted No-Effect Concentration (UK REACH)  
LC50: Lethal concentration, 50 percent  
LD50: Lethal dose, 50 percent  
PBT: Persistent, Bioaccumulative and Toxic  
vPvB: very Persistent and very Bioaccumulative

(Contd. on page 11)

GB



BE SURE. BUILD SURE.

Page 11/11

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 31.12.2022

Version number 8 (replaces version 7)

Revision: 31.12.2022

**Trade name MC-Color Proof vision - Komponente A**

(Contd. of page 10)

*Acute Tox. 4: Acute toxicity – Category 4*  
*Acute Tox. 2: Acute toxicity – Category 2*  
*Acute Tox. 3: Acute toxicity – Category 3*  
*Skin Corr. 1B: Skin corrosion/irritation – Category 1B*  
*Skin Corr. 1C: Skin corrosion/irritation – Category 1C*  
*Skin Irrit. 2: Skin corrosion/irritation – Category 2*  
*Eye Dam. 1: Serious eye damage/eye irritation – Category 1*  
*Eye Irrit. 2: Serious eye damage/eye irritation – Category 2*  
*Skin Sens. 1: Skin sensitisation – Category 1*  
*Skin Sens. 1A: Skin sensitisation – Category 1A*  
*Muta. 2: Germ cell mutagenicity – Category 2*  
*Carc. 1B: Carcinogenicity – Category 1B*  
*STOT SE 3: Specific target organ toxicity (single exposure) – Category 3*  
*Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1*  
*Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1*  
*Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2*

**\* Data compared to the  
previous version altered.**

GB