



BE SURE. BUILD SURE.

Page 1/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.10.2021

Version number 12

Revision: 16.10.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name **MC-DUR 1800 TX-AS - Komponente A**

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

1.3 Application of the substance / the mixture

Epoxy coating

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

MC-Bauchemie Müller GmbH & Co. KG
Am Kruppwald 1-8
D-46238 Bottrop
Tel.: +49(0)2041-101-0
Fax.: +49(0)2041-101-400
E-Mail: info@mc-bauchemie.de

MC-Bauchemie AG
Hagackerstr. 10
CH-8953 Dietikon
Tel.: +44-7400510
Fax : +44-7400533

Informing department:

msds@mc-bauchemie.de

1.4 Emergency telephone number:

Tel.: +49 / (0)700 24112112 (MCR)
Tel.: +48612864565

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to

Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation.

Hazard pictograms



GHS07 GHS09

Signal word

Warning

(Contd. on page 2)

GB



BE SURE. BUILD SURE.

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 23.10.2021

Version number 12

Revision: 16.10.2021

Trade name MC-DUR 1800 TX-AS - Komponente A

(Contd. of page 1)

- **Hazard-determining components of labelling:** 2,2'-[methylenebis(p-phenyleneoxymethylene)]bisoxirane polymers and homologues, molecular weight < 700
Propyl -2,2-diphenyl-4,4'dipropoxyirane polymers and homologues molecular weight < 700
- **Hazard statements** N,N'-ethane-1,2-diylbis(12-hydroxyoctadecan-1-amide)
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
H411 Toxic to aquatic life with long lasting effects.
- **Precautionary statements** P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P273 Avoid release to the environment.
P280 Wear protective gloves / eye protection / face protection.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 If eye irritation persists: Get medical advice/attention.
- **Additional information:** Contains epoxy constituents. May produce an allergic reaction.
Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- **3.2 Chemical characterisation: Mixtures**
- **Description:** Mixture consisting of the following components.

· **Dangerous components:**

CAS: 9003-36-5 NLP: 500-006-8	2,2'-[methylenebis(p-phenyleneoxymethylene)]bisoxirane polymers and homologues, molecular weight < 700 Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	25-50%
CAS: 1675-54-3 EINECS: 216-823-5	bis[4-(2,3-epoxypropoxy)phenyl]propane Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	≥5-<25%

(Contd. on page 3)



BE SURE. BUILD SURE.

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 23.10.2021

Version number 12

Revision: 16.10.2021

Trade name MC-DUR 1800 TX-AS - Komponente A

(Contd. of page 2)

CAS: 13463-67-7 EINECS: 236-675-5	titanium dioxide Carc. 2, H351	≥0.1-<10%
EC number: 905-588-0 Reg.nr.: 01-2119488216-32 01-2119486136-34	Reaction mass of ethylbenzene and xylene Flam. Liq. 3, H226; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	<5%
CAS: 546-93-0 EINECS: 208-915-9	Magnesite substance with a Community workplace exposure limit	<1.5%
CAS: 67762-90-7	Siloxane und Silicone, di-Me, Reaktionsprodukte mit Siliciumdioxid Acute Tox. 4, H302	<1.5%
CAS: 123-26-2	N,N'-ethane-1,2-diylbis(12-hydroxyoctadecan-1-amide) Skin Sens. 1, H317; Aquatic Chronic 3, H412	≥0.1-<0.5%

· **Additional information** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· **4.1 Description of first aid measures**

- **After inhalation** Supply fresh air; consult doctor in case of symptoms.
- **After skin contact** Instantly wash with water and soap and rinse thoroughly.
- **After eye contact** Rinse opened eye for several minutes under running water. Seek medical treatment.
- **After swallowing** Rinse out mouth and then drink plenty of water. Seek medical treatment.

· **4.2 Most important symptoms and effects, both acute and delayed**

No further relevant information available.

· **4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

SECTION 5: Firefighting measures

· **5.1 Extinguishing media**

· **Suitable extinguishing agents** Use fire fighting measures that suit the environment.

· **5.2 Special hazards arising from the substance or mixture**

No further relevant information available.

· **5.3 Advice for firefighters**

· **Protective equipment:** No special measures required.

GB

(Contd. on page 4)



BE SURE. BUILD SURE.

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.10.2021

Version number 12

Revision: 16.10.2021

Trade name MC-DUR 1800 TX-AS - Komponente A

(Contd. of page 3)

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures** Not required.
- **6.2 Environmental precautions:** Prevent material from reaching sewage system, holes and cellars.
- **6.3 Methods and material for containment and cleaning up:** Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
- **6.4 Reference to other sections** See Section 7 for information on safe handling
See Section 8 for information on personal protection equipment.
See Section 13 for information on disposal.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Store in cool, dry place in tightly closed containers.
Open and handle container with care.
- **Information about protection against explosions and fires:** No special measures required.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage**
- **Requirements to be met by storerooms and containers:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep container tightly sealed.
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **8.1 Control parameters**
- **Additional information about design of technical systems:** No further data; see item 7.

· **Components with critical values that require monitoring at the workplace:**

546-93-0 Magnesite

WEL	Long-term value: 10* 4** mg/m ³ *inhalable dust **respirable dust
-----	---

· **DNELs**

Reaction mass of ethylbenzene and xylene

Oral	DNEL	1.6 mg/kg bw/Tag (ArL)
------	------	------------------------

(Contd. on page 5)



BE SURE. BUILD SURE.

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.10.2021

Version number 12

Revision: 16.10.2021

Trade name MC-DUR 1800 TX-AS - Komponente A

(Contd. of page 4)

		mg/kg bw/Tag (Workers)
Dermal	DNEL	180 mg/kg bw/day (ArL)
Inhalative	DNEL	211 mg/m ³ (ArL)

Additional Occupational Exposure Limit Values for possible hazards during processing:

1330-20-7 xylene

WEL	Short-term value: 441 mg/m ³ , 100 ppm
	Long-term value: 220 mg/m ³ , 50 ppm
	Sk; BMGV

100-41-4 ethylbenzene

WEL	Short-term value: 552 mg/m ³ , 125 ppm
	Long-term value: 441 mg/m ³ , 100 ppm
	Sk

Additional information: The lists that were valid during the compilation were used as basis.

- 8.2 Exposure controls
- Personal protective equipment
- General protective and hygienic measures

Keep away from foodstuffs, beverages and food.
Instantly remove any soiled and impregnated garments.
Wash hands during breaks and at the end of the work.
Avoid contact with the eyes and skin.

Protection of hands:

Protective gloves.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
After use of gloves apply skin-cleaning agents and skin cosmetics.

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection:

Safety glasses
Tightly sealed safety glasses.

Body protection:

Protective work clothing.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Appearance:

Form:	Viscous
Colour:	According to product specification

(Contd. on page 6)



BE SURE. BUILD SURE.

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 23.10.2021

Version number 12

Revision: 16.10.2021

Trade name MC-DUR 1800 TX-AS - Komponente A

(Contd. of page 5)

· Smell:	Characteristic
· pH-value:	Not applicable.
· Change in condition	
Melting point/freezing point:	Not determined
Initial boiling point and boiling range:	> 200 °C
· Flash point:	151 °C
· Ignition temperature:	184 °C
· Self-inflammability:	Product is not selfigniting.
· Explosive properties:	Product is not explosive.
· Steam pressure at 20 °C:	0.1 hPa
· Density	Not determined
· Solubility in / Miscibility with Water:	Not miscible or difficult to mix
· 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values that are relevant for classification:**

9003-36-5 2,2'-[methylenebis(p-phenyleneoxymethylene)]bisoxirane polymers and homologues, molecular weight < 700		
Oral	LD50	>2000 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rabbit)
1675-54-3 bis[4-(2,3-epoxypropoxy)phenyl]propane		
Dermal	LD50	23000 mg/kg (rabbit)

(Contd. on page 7)



BE SURE. BUILD SURE.

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 23.10.2021

Version number 12

Revision: 16.10.2021

Trade name MC-DUR 1800 TX-AS - Komponente A

(Contd. of page 6)

13463-67-7 titanium dioxide

Oral	LD50	>10000 mg/kg (rat)
Dermal	LD50	>10000 mg/kg (rabbit)
Inhalative	LC50/4 h	>6.8 mg/l (rat)

Reaction mass of ethylbenzene and xylene

Oral	LD50	3523-4000 mg/kg (rat)
Dermal	LD50	12126 mg/kg (rabbit)
Inhalative	LC50/4 h	6350-6700 mg/l (rat)

67762-90-7 Siloxane und Silicone, di-Me, Reaktionsprodukte mit Siliciumdioxid

Oral	LD50	>5000 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rabbit)

- **Primary irritant effect:**
- **Skin corrosion/irritation** Causes skin irritation.
- **Serious eye damage/irritation** Causes serious eye irritation.
- **Respiratory or skin sensitisation** May cause an allergic skin reaction.
- **Additional toxicological information:**
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· **12.1 Toxicity**

· **Aquatic toxicity:**

9003-36-5 2,2'-[methylenebis(p-phenyleneoxymethylene)]bisoxirane polymers and homologues, molecular weight < 700

LC50/96h	>100 mg/l (Daphnia magna)
EC50/96h	>100 mg/l (Leucidus idus)

1675-54-3 bis[4-(2,3-epoxypropoxy)phenyl]propane

IC50	>42.6 mg/l (Bak)
LC50/96h	2 mg/l (Oncorhynchus mykiss)
EC50/48h	1.8 mg/l (Daphnia magna)
ErC50/72h	11 mg/l (Selenastrum capricornutum)

Reaction mass of ethylbenzene and xylene

EC50/72h	2.2 mg/l (Selenastrum capricornutum)
LC50/96h	2.6 mg/l (Oncorhynchus mykiss)

(Contd. on page 8)



BE SURE. BUILD SURE.

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.10.2021

Version number 12

Revision: 16.10.2021

Trade name MC-DUR 1800 TX-AS - Komponente A

(Contd. of page 7)

	NOEC	16 mg/l (BEL)
67762-90-7 Siloxane und Silicone, di-Me, Reaktionsprodukte mit Siliciumdioxid		
Sensitisation	EL50	10000 mg/l (Daphnien)
	LC50/96h	>10000 mg/l (Brachydanio rerio)

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:** Do not allow product to reach ground water, water bodies or sewage system.
Danger to drinking water if even small quantities leak into soil.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation** Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Empty contaminated packagings thoroughly. They can be recycled after thorough and proper cleaning.

SECTION 14: Transport information

- **14.1 UN-Number**
- **ADR, IMDG, IATA** UN3082
- **14.2 UN proper shipping name**
- **ADR, IATA** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (epoxide derivates)
- **IMDG** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (epoxide derivates), MARINE POLLUTANT
- **14.3 Transport hazard class(es)**
- **ADR**
- **Class** 9 (M6) Miscellaneous dangerous substances and articles.

(Contd. on page 9)



BE SURE. BUILD SURE.

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.10.2021

Version number 12

Revision: 16.10.2021

Trade name MC-DUR 1800 TX-AS - Komponente A

(Contd. of page 8)

· Label	9
· IMDG, IATA	
· Class	9 Miscellaneous dangerous substances and articles.
· Label	9
· 14.4 Packing group	
· ADR, IMDG, IATA	III
· 14.5 Environmental hazards:	Product contains environmentally hazardous substances: epoxide derivates
· Marine pollutant:	no Yes Symbol (fish and tree)
· Special marking (ADR):	Symbol (fish and tree)
· Special marking (IATA):	Symbol (fish and tree)
· 14.6 Special precautions for user	Warning: Miscellaneous dangerous substances and articles.
· Kemler Number:	90
· EMS Number:	F-A,S-F
· Stowage Category	A
· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· Transport category	3
· Tunnel restriction code	(-)
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXIDE DERIVATES), 9, III

GB

(Contd. on page 10)



BE SURE. BUILD SURE.

Page 10/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.10.2021

Version number 12

Revision: 16.10.2021

Trade name MC-DUR 1800 TX-AS - Komponente A

(Contd. of page 9)

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- Directive 2012/18/EU
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 200 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**
 - H226 Flammable liquid and vapour.
 - H302 Harmful if swallowed.
 - H304 May be fatal if swallowed and enters airways.
 - H312 Harmful in contact with skin.
 - H315 Causes skin irritation.
 - H317 May cause an allergic skin reaction.
 - H319 Causes serious eye irritation.
 - H332 Harmful if inhaled.
 - H335 May cause respiratory irritation.
 - H351 Suspected of causing cancer.
 - H373 May cause damage to organs through prolonged or repeated exposure.
 - H411 Toxic to aquatic life with long lasting effects.
 - H412 Harmful to aquatic life with long lasting effects.
- **Department issuing data specification sheet:** Environment protection department.
- **Abbreviations and acronyms:**
 - RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
 - ICAO: International Civil Aviation Organisation
 - ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
 - IMDG: International Maritime Code for Dangerous Goods
 - IATA: International Air Transport Association
 - GHS: Globally Harmonised System of Classification and Labelling of Chemicals
 - EINECS: European Inventory of Existing Commercial Chemical Substances
 - ELINCS: European List of Notified Chemical Substances
 - CAS: Chemical Abstracts Service (division of the American Chemical Society)
 - DNEL: Derived No-Effect Level (REACH)
 - LC50: Lethal concentration, 50 percent
 - LD50: Lethal dose, 50 percent

(Contd. on page 11)

GB



BE SURE. BUILD SURE.

Page 11/11

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 23.10.2021

Version number 12

Revision: 16.10.2021

Trade name MC-DUR 1800 TX-AS - Komponente A

(Contd. of page 10)

PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 3: Flammable liquids – Category 3
Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Skin Sens. 1: Skin sensitisation – Category 1
Carc. 2: Carcinogenicity – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

*** Data compared to the
previous version altered.**

GB