

Page 1/12

Safety data sheet according to UK REACH

Printing date 13.07.2024

Version number 30 (replaces version 29)

Revision: 13.07.2024

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

· 1.1 Product identifier	
· Trade name	MC-DUR 1000 Parat 04 - Komponente A
 Article number: 1.2 Relevant identified uses of the substance or mixture and uses advised against 	1076 No further relevant information available.
• Application of the substance	
/ the mixture	Repair mortar
• 1.3 Details of the supplier of t • Manufacturer/Supplier:	he safety data sheet MC-Bauchemie Müller GmbH & Co. KG Am Kruppwald 1-8 D-46238 Bottrop Tel.: +49(0)2041-101-0 Fax.: +49(0)2041-101-400 E-Mail: info@mc-bauchemie.de MC-Bauchemie AG Hagackerstr. 10 CH-8953 Dietikon Tel.: +44-7400510 Fax : +44-7400533
 Informing department: 1.4 Emergency telephone number: 	msds@mc-bauchemie.de Tel.: +49 / (0)700 24112112 (MCR)
	Tel.: +1 872 5888271 (MCR)

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT RE 2 H373 May cause damage to the lung through prolonged or repeated exposure. Route of exposure: Inhalation.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

[•] 2.2 Label elements

· Labelling according to

Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms





Page 2/12

Safety data sheet according to UK REACH

Printing date 13.07.2024

Version number 30 (replaces version 29)

Revision: 13.07.2024

Trade name MC-DUR 1000 Parat 04 - Komponente A

		(Contd. of page 1)
· Signal word	Warning	
· Hazard-determining		
components of labelling:	epoxide derivates	;
	crystalline silica	
		⁵ 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]
		<pre>[2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)</pre>
		'-[methylenebis(2,1-phenyleneoxymethylene)]
	dioxirane	a of however 1 C dial with 2 (able remathed) avirage
	-	s of hexane-1,6-diol with 2-(chloromethyl)oxirane
	(1:2) Hydrocarbons Ci	9-unsaturated, polymerised
	Alkyl Glycidyl Eth	
	[[(2-ethylhexyl)ox]	
· Hazard statements	H315 Causes skil	
	H319 Causes ser	
		an allergic skin reaction.
	H373 May cause	e damage to the lung through prolonged or
		posure. Route of exposure: Inhalation.
		aquatic life with long lasting effects.
 Precautionary statements 	P260	Do not breathe dust/fume/gas/mist/vapours/
	P273	spray. Avoid release to the environment.
	P273 P280	Wear protective gloves / eye protection / face
	F200	protection.
	P305+P351+P33	8 IF IN EYES: Rinse cautiously with water for
		several minutes. Remove contact lenses, if
		present and easy to do. Continue rinsing.
	P333+P313	If skin irritation or rash occurs: Get medical
		advice/attention.
	P337+P313	If eye irritation persists: Get medical advice/
		attention.
· Additional information:	EUH205 Contain reaction.	s epoxy constituents. May produce an allergic
		! Hazardous respirable droplets may be formed
		rayed. Do not breathe spray or mist.
· 2.3 Other hazards	interiop	
· Results of PBT and vPvB ass	essment	
· PBT:	Not applicable.	
· vPvB:	Not applicable.	

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description:

Mixture consisting of the following components.

(Contd. on page 3)

GB



Page 3/12

Safety data sheet according to UK REACH

Printing date 13.07.2024

Version number 30 (replaces version 29)

Revision: 13.07.2024

Trade name MC-DUR 1000 Parat 04 - Komponente A

Dangerous componen	ts:	
CAS: 1675-54-3	epoxide derivates	<i>≥</i> 5-<10%
EINECS: 216-823-5	Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317, EUH205 Specific concentration limits: Skin Irrit. 2; H315: C \geq 5 %	
	Eye Irrit. 2; H319: $C \ge 5\%$	
CAS: 14808-60-7	crystalline silica	<5%
	STOT RE 1, H372	
CAS: 13463-67-7	titanium dioxide	<i>≥</i> 1-<2.5%
EINECS: 236-675-5	Carc. 2, H351	
CAS: 9003-36-5	Reaction mass of 2,2'-[methylenebis(4,1-	≥1-<1.5%
EC number: 701-263-0	phenyleneoxymethylene)]dioxirane and 2-({2-[4-(oxiran-2-	
	ylmethoxy)benzyl]phenoxy}methyl)oxirane and 2,2'-	
	[methylenebis(2,1-phenyleneoxymethylene)]dioxirane	
	Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Skin Sens. 1, H317	
CAS: 933999-84-9	Reaction products of hexane-1,6-diol with 2-(chloromethyl) oxirane (1:2)	<i>≥</i> 0.1-<1%
	Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; Aquatic Chronic 3, H412	
CAS: 68609-97-2	Alkyl Glycidyl Ether	<i>≥</i> 0.1-<0.3%
	Repr. 1B, H360F; Skin Irrit. 2, H315; Skin Sens. 1, H317	
CAS: 2461-15-6	[[(2-ethylhexyl)oxy]methyl]oxirane	<i>≥</i> 0.1-<0.5%
EINECS: 219-553-6	Skin Irrit. 2, H315; Skin Sens. 1, H317	
CAS: 71302-83-5	Hydrocarbons, C9-unsaturated, polymerised	<0.1%
	Asp. Tox. 1, H304; Skin Sens. 1A, H317; Aquatic Chronic 3, H412	

SECTION 4: First aid measures

· 4.1 Description of first aid measures General information Remove contaminated clothing immediately. Consult a doctor if symptoms occur. Move affected person to fresh air. · After inhalation Supply fresh air; seek medical advice if symptoms occur. If unconscious, place in recovery position and seek medical advice. · After skin contact In case of contact with skin, wash carefully with plenty of soap and water. Consult a doctor in case of skin reactions. · After eye contact Rinse opened eye for several minutes under running water. Call a doctor immediately Rinse mouth with water. Never give anything by mouth to an · After swallowing unconscious person. DO NOT induce vomiting. If symptoms persist, consult a doctor. (Contd. on page 4) GB



Page 4/12

Safety data sheet

according to UK REACH

Printing date 13.07.2024

Version number 30 (replaces version 29)

Revision: 13.07.2024

(Contd. of page 3)

Trade name MC-DUR 1000 Parat 04 - Komponente A

 4.2 Most important symptoms and effects, both acute and delayed

Advice for the doctor: Elementary aid, decontamination, symptomatic treatment.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

· Suitable extinguishing agents Use fire fighting measures that suit the environment.

- 5.2 Special hazards arising from the substance or mixture
- 5.3 Advice for firefighters
 Protective equipment:
- No special measures required.

No further relevant information available.

SECTION 6: Accidental release measures

 6.1 Personal precautions, protective equipment and 	
emergency procedures	Not required.
· 6.2 Environmental	
precautions:	Prevent material from reaching sewage system, holes and cellars.
6.3 Methods and material for	
containment and cleaning up	: Collect mechanically.
· 6.4 Reference to other	•
sections	See Section 7 for information on safe handling
	See Section 8 for information on personal protection equipment.
	See Section 13 for information on disposal.

SECTION 7: Handling and storage

 7.1 Precautions for safe handling
 Open and handle containers with care. Ventilation measures are required in rooms without sufficient air exchange (e.g. closed rooms), because the occupational exposure limit values (see chapter 8) could be exceeded. This must be avoided. Wear suitable personal protective equipment (see section 8). Avoid contact with eyes, skin and clothing. Change contaminated or damaged gloves and contaminated clothing immediately and wash skin immediately. Mix slowly, partially covering the mixing container. Pour carefully and slowly when repotting. Observe the BGBau technical data sheet and practical guide for handling epoxy resins.

GB



Page 5/12

Safety data sheet according to UK REACH

Printing date 13.07.2024

Version number 30 (replaces version 29)

Revision: 13.07.2024

Trade name MC-DUR 1000 Parat 04 - Komponente A

(Contd. of page 4) · Information about protection against explosions and fires: Ensure sufficient air exchange and/or extraction in the working areas. Take precautionary measures to avoid electrostatic discharges. · 7.2 Conditions for safe storage, including any incompatibilities · Storage · Requirements to be met by storerooms and containers: No special requirements. · Further information about storage conditions: None. · Storage class 10 **SECTION 8: Exposure controls/personal protection**

• 8.1 Control parameters • Components with critical values that require monitoring at the workplace: The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

· DNELs

Г

DINLLS	,		
CAS: 6	CAS: 68609-97-2 Alkyl Glycidyl Ether		
Dermal	DNEL	_ 0.75 mg/kg bw/day (ArL)	
Inhalati	ive DNEL	_ 0.49 mg/m³ (ArL)	
CAS: 2	2461-15-6	[[(2-ethylhexyl)oxy]methyl]oxirane	
Dermal	DNEL	4.17 mg/kg bw/day (ArL)	
· PNECs	; ;		
CAS: 6	8609-97-2	2 Alkyl Glycidyl Ether	
PNEC	0.00072 n	mg/l (Mew)	
	0.0072 mg	ng/l (Freshwater)	
PNEC	80.12 mg/	g/kg dwt (Bod)	
	6.677 mg/	g/kg dwt (Sediment)	
	66.77 mg/	g/kg dwt (Fresh water sediment)	
CAS: 2	2461-15-6	[[(2-ethylhexyl)oxy]methyl]oxirane	
PNEC	0.0072 mg	ng/l (Fresh water)	
PNEC	57.16 mg/	g/kg dwt (Bod)	
	28.66 mg/	g/kg dwt (Sediment)	
	286.66 mg	ng/kg dwt (Fresh water sediment)	
· Additic	onal infori	rmation: The lists that were valid during the compilation were used as l	basis.
	posure co		
	oriate eng '		
contro	IS	No further data; see section 7. (Contd. on p	nage 6)
		(Conta: On	g0 0)



Page 6/12

Safety data sheet according to UK REACH

Printing date 13.07.2024

Version number 30 (replaces version 29)

Revision: 13.07.2024

Trade name MC-DUR 1000 Parat 04 - Komponente A

	Contd. of page cures, such as personal protective equipment
General protective and	
hygienic measures	Keep away from food, drink and animal feed.
	Remove soiled, soaked clothing immediately.
	Wash hands before breaks and at the end of work.
	Avoid contact with eyes and skin.
Breathing equipment:	If workplace limit values cannot be complied with by ventilati
Dicatining equipment.	measures or if rooms cannot be technically ventilated, respirate
	protection must be worn: Use combination filter A1-P2 (brow
	white) in rooms that cannot be ventilated. If oxygen deficiency
	expected, use self-contained breathing apparatus. Obser
	wearing time limits according to §9 (3) GefStoffV in conjuncti
	with BGR 190.
Hand protection	Selection of the glove material on consideration of the penetrati
	times, rates of diffusion and the degradation
Material of gloves	You can find help with choosing gloves on the website https
-	www.bgbau.de/fileadmin/Gisbau/Projekte.pdf
	For example, we recommend the Sol-vex 37-900 protective glov
	from Ansell GmbH. The breakthrough time of the protective glov
	can be found under point 8 "Penetration time of the glove materia
	The selection of a suitable glove depends not only on the materia
	but also on other quality features and varies from manufacturer
	manufacturer. As the product
	is a preparation of several substances, the resistance of glo
	materials cannot be calculated in advance and must therefore
	checked before use.
	Nitrile rubber
	Recommended material thickness:≥ 0.4 mm
Penetration time of glove	
material	The breakthrough times of the Sol-vex 37-900 protective glov
	are around 8 hours.
	The following applies to all other gloves:
	The exact breakthrough time must be obtained from the protect
	glove manufacturer and adhered to.
	Nitrile rubber
	Material thickness: \geq 0.40 mm
	Penetration time: \geq 480 min
	Butyl rubber:
	Material thickness: > 0.5 mm
	Penetration time: ≥ 480 min
Eye/face protection	Tight-fitting safety goggles.
	Safety goggles.
Body protection:	Protective clothing
	Suitable protective clothing should be worn when working w
	epoxy resins. In addition to normal work clothing (long trouse
	long-sleeved shirt or T-shirt), disposable overalls, apror
	overshoes, sleeve protectors etc. may be necessary depending
	the activity. Uncovered areas of skin should be avoided as far
	the activity. Uncovered areas of skin should be avoided as far possible, even in hot weather. If the work involves kneeling, to lower leg area should be protected by protective trousers.



Safety data sheet according to UK REACH

Printing date 13.07.2024

Version number 30 (replaces version 29)

Revision: 13.07.2024

Trade name MC-DUR 1000 Parat 04 - Komponente A

(Contd. of page 6)

Page 7/12

9.1 Information on basic physical and che	mical properties	
General Information Colour:	light yellow	
Smell:	Characteristic	
Melting point/freezing point:	Not determined	
Boiling point or initial boiling point and	Not determined	
boiling range	Not determined	
Flash point:	>120 °C	
pH	Not determined.	
Viscosity:		
Kinematic viscosity	Not determined.	
dynamic:	Not determined.	
Solubility		
Water:	Not miscible or difficult to mix	
Steam pressure:	Not determined.	
Density and/or relative density		
Density at 20 °C	2.5 g/cm³	
9.2 Other information		
Appearance:		
Form:	Pasty	
Important information on protection of hea	alth	
and environment, and on safety.		
Self-inflammability:	Product is not selfigniting.	
Explosive properties:	Product is not explosive.	
Information with regard to physical haz	ard	
classes		
Explosives	Void	
Flammable gases	Void	
Aerosols	Void	
Oxidising gases	Void	
Gases under pressure	Void	
Flammable liquids	Void	
Flammable solids	Void	
Self-reactive substances and mixtures	Void	
Pyrophoric liquids	Void	
Pyrophoric solids	Void	
Self-heating substances and mixtures	Void	
Substances and mixtures, which emit		
flammable gases in contact with water	Void	
Oxidising liquids	Void	
Oxidising solids	Void	
Organic peroxides Corrosive to metals	Void Void	
	N / 1 / 1	



Safety data sheet

according to UK REACH

Printing date 13.07.2024

Version number 30 (replaces version 29)

Revision: 13.07.2024

(Contd. of page 7)

Page 8/12

Trade name MC-DUR 1000 Parat 04 - Komponente A

Desensitised explosives

Void

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available. 10.2 Chemical stability Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications. 10.3 Possibility of hazardous reactions No dangerous reactions known · 10.4 Conditions to avoid No further relevant information available. · 10.5 Incompatible materials: No further relevant information available. · 10.6 Hazardous decomposition products: No dangerous decomposition products known

SECTION 11: Toxicological information

• **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008** • **Acute toxicity** Based on available data, the classification criteria are not met.

	-	·
LD/LC50	values tha	t are relevant for classification:
CAS: 167	5-54-3 ерс	oxide derivates
Dermal	LD50	23000 mg/kg (rabbit)
CAS: 134	63-67-7 tit	anium dioxide
Oral	LD50	>5000 mg/kg (rat)
Dermal	LD50	>10000 mg/kg (rabbit)
Inhalative	LC50/4 h	>6.8 mg/l (rat)
CAS: 900	and	action mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane d 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane and 2,2' ethylenebis(2,1-phenyleneoxymethylene)]dioxirane
Oral	LD50	>2000 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rabbit)
CAS: 686	09-97-2 Al	kyl Glycidyl Ether
Oral	LD50	17100 mg/kg (rat)
CAS: 246	1-15-6 [[(2	-ethylhexyl)oxy]methyl]oxirane
Oral	LD50	5000 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rat)
Skin corre Serious e Respirato	ye damag	e/irritation Causes serious eye irritation.
sensitisat		May cause an allergic skin reaction.
Germ cell		<i>icity</i> Based on available data, the classification criteria are not met.
· Carcinogo · Reproduc		<i>Based on available data, the classification criteria are not met.</i> <i>Based on available data, the classification criteria are not met.</i> (Contd. on page)



Page 9/12

Safety data sheet according to UK REACH

Printing date 13.07.2024

Version number 30 (replaces version 29)

Revision: 13.07.2024

Trade name MC-DUR 1000 Parat 04 - Komponente A

STOT-single exposure STOT-repeated exposure	(Contd. of page 8) Based on available data, the classification criteria are not met. May cause damage to the lung through prolonged or repeated exposure. Route of exposure: Inhalation.	
Aspiration hazard 11.2 Information on other		
 Endocrine disrupting pro 	perties	
CAS: 61788-44-1 2,4,6-Tr	is-(1-Phenyl-Ethyl) carbolic acid List	
CAS: 128-37-0 2,6-Di-te	ert-butyl-p-cresol List	
SECTION 12: Ecolog	ical information	
· 12.1 Toxicity		

· Aquatic toxicity:			
CAS: 1675-	CAS: 1675-54-3 epoxide derivates		
IC50	>42.6 mg/l (Bak)		
LC50/96h	2 mg/l (Oncorhynchus mykiss)		
EC50/48h	1.8 mg/l (Daphnia magna)		
ErC50/72h	11 mg/l (Selenastrum capricornutum)		
CAS: 9003-	36-5 Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane and 2,2'- [methylenebis(2,1-phenyleneoxymethylene)]dioxirane		
LC50/96h	>100 mg/l (Daphnia magna)		
EC50/96h	>100 mg/l (Leucidus idus)		
CAS: 68609	9-97-2 Alkyl Glycidyl Ether		
EbC50/72h	843 mg/l (Pseudokirchneriella subcapitata)		
LC50/96h	>5000 mg/l (Oncorhynchus mykiss)		
	1800 mg/l (Lepomis macrochirus)		
EC50	>100 mg/l (BEL)		
NOEC	500 mg/l (Pseudokirchneriella subcapitata)		
· 12.2 Persis degradabili · 12.3 Bioaco	ity No further relevant information available.		
potential	No further relevant information available.		
· 12.4 Mobili			
	s of PBT and vPvB assessment		
· PBT:	Not applicable.		

PB1:Not applicable.**vPvB:**Not applicable.

- 12.6 Endocrine disrupting
propertiesFor information on endocrine disrupting properties see section 11.12.7 Other adverse effectsFor information on endocrine disrupting properties see section 11.Additional ecological information:Do not allow product to reach ground water, water bodies of the section of the sectio
 - I notes: Do not allow product to reach ground water, water bodies or sewage system.

(Contd. on page 10)

GB



Page 10/12

Safety data sheet

according to UK REACH

Printing date 13.07.2024

Version number 30 (replaces version 29)

Revision: 13.07.2024

Trade name MC-DUR 1000 Parat 04 - Komponente A

(Contd. of page 9)

Danger to drinking water if even small quantities leak into soil.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- Uncleaned packagings:
- Recommendation:

Empty contaminated packagings thoroughly. They can be recycled after thorough and proper cleaning.

SECTION 14: Transport information

 14.1 UN number or ID number ADR, ADN, IMDG, IATA 	Void
 14.2 UN proper shipping name ADR, ADN, IMDG, IATA 	Void
· 14.3 Transport hazard class(es)	
· ADR, ADN, IMDG, IATA · Class	Void
· 14.4 Packing group · ADR, IMDG, IATA	Void
 14.5 Environmental hazards: Marine pollutant: 	No
· 14.6 Special precautions for user	Not applicable.
 14.7 Maritime transport in bulk according IMO instruments 	g to Not applicable.
· UN "Model Regulation":	Void

SECTION 15: Regulatory information

 15.1 Safety, health and environmental regulations/ legislation specific for the substance or mixture No further relevant information available.
 Poisons Act
 Regulated explosives precursors None of the ingredients is listed.

on page 11

GB



Page 11/12

Safety data sheet according to UK REACH

Printing date 13.07.2024

Version number 30 (replaces version 29)

Revision: 13.07.2024

Trade name MC-DUR 1000 Parat 04 - Komponente A

	(Contd. of page 10)
· Regulated poisons	
None of the ingredients is li	sted.
· Reportable explosives pre	ecursors
None of the ingredients is li	sted.
· Reportable poisons	
None of the ingredients is li	sted.
 15.2 Chemical safety assessment: 	A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases	 H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H351 Suspected of causing cancer. H360F May damage fertility. H372 Causes damage to organs through prolonged or repeated exposure. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects. EUH205 Contains epoxy constituents. May produce an allergic reaction.
Department issuing data specification sheet: Abbreviations and acronyms:	Environment protection department. RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) DNEL: Derived No-Effect Level (UK REACH) PNEC: Predicted No-Effect Concentration (UK REACH) LC50: Lethal concentration, 50 percent LD50: Lethal concentration, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 Skin Sens. 1: Skin sensitisation – Category 1 Skin Sens. 1A: Skin sensitisation – Category 2 (Contd. on page



Safety data sheet according to UK REACH

Printing date 13.07.2024

Version number 30 (replaces version 29)

Revision: 13.07.2024

Page 12/12

Trade name MC-DUR 1000 Parat 04 - Komponente A

(Contd. of page 11) Repr. 1B: Reproductive toxicity – Category 1B STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2 Asp. Tox. 1: Aspiration hazard – Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3 * * Data compared to the previous version altered.