

Page 1/11

Safety data sheet according to UK REACH

Printing date 12.04.2025 Version number 56 (replaces version 55) Revision: 12.04.2025

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

· 1.1 Product identifier

· Trade name MC-DUR 111 eco - Komponente B

1.2 Relevant identified uses of the substance or mixture and uses advised against

· Sector of Use SU22 Professional uses: Public domain (administration,

education, entertainment, services, craftsmen)

· Application of the substance

/ the mixture Coating

· 1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: MC-Bauchemie Müller GmbH & Co. KG

Am Kruppwald 1-8 D-46238 Bottrop Tel.: +49(0)2041-101-0 Fax.: +49(0)2041-101-400

E-Mail: info@mc-bauchemie.de

MC-Bauchemie AG Hagackerstr. 10 CH-8953 Dietikon Tel.: +44-7400510 Fax: +44-7400533

Informing department:

msds@mc-bauchemie.de

· 1.4 Emergency telephone

number:

Tel.: +49 / (0)700 24112112 (MCR)

Tel.: +1 872 5888271 (MCR)

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

- · 2.2 Label elements
- Labelling according to

Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms



GHS07

· Signal word Warning

· Hazard-determining

components of labelling: Polypropylenglycole-diepoxidresin · Hazard statements H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

(Contd. on page 2)



Page 2/11

Safety data sheet according to UK REACH

Printing date 12.04.2025 Version number 56 (replaces version 55) Revision: 12.04.2025

Trade name MC-DUR 111 eco - Komponente B

(Contd. of page 1)

· Precautionary statements P261 Avoid breathing dust/fume/gas/mist/vapours/

sprav.

P280 Wear protective gloves / eye protection / face

protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for

several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P333+P313 If skin irritation or rash occurs: Get medical

advice/attention.

P337+P313 If eye irritation persists: Get medical advice/

attention.

P501 Dispose of contents/container in accordance

with local/regional/national/international

regulations.

· Additional information: EUH205 Contains epoxy constituents. May produce an allergic

reaction.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

⋅ PBT: Not applicable.⋅ ∨P∨B: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

• **Description:** Mixture consisting of the following components.

· Dangerous components:		
CAS: 100-51-6 EINECS: 202-859-9	Benzyl alcohol Acute Tox. 4, H302; Acute Tox. 4, H332; Eye Irrit. 2, H319	<10%
CAS: 107-98-2 EINECS: 203-539-1 Reg.nr.: 01-2119457435-35- xxxx	1-Methoxy-2-propanol Flam. Liq. 3, H226; STOT SE 3, H336	<10%
CAS: 26142-30-3	Polypropylenglycole-diepoxidresin Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1B, H317, EUH205	≥1-<10%
· Additional information	For the wording of the listed hazard phrases refer to see	ction 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

General information Remove contaminated clothing immediately. Consult a doctor if

symptoms occur. Move affected person to fresh air.

• After inhalation Supply fresh air; seek medical advice if symptoms occur.

If unconscious, place in recovery position and seek medical advice.

· After skin contact In case of contact with skin, wash carefully with plenty of soap and

water. Consult a doctor in case of skin reactions.

(Contd. on page 3)



Page 3/11

Safety data sheet according to UK REACH

Printing date 12.04.2025 Version number 56 (replaces version 55) Revision: 12.04.2025

Trade name MC-DUR 111 eco - Komponente B

(Contd. of page 2)

Rinse opened eye for several minutes under running water. · After eye contact

Call a doctor immediately

· After swallowing Rinse mouth with water. Never give anything by mouth to an

unconscious person. DO NOT induce vomiting. If symptoms

persist, consult a doctor.

· 4.2 Most important symptoms and effects, both acute and

delayed Advice for the doctor: Elementary aid, decontamination,

symptomatic treatment.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

· Suitable extinguishing agents CO2, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam.

5.2 Special hazards arising from the substance or

mixture

No further relevant information available.

· 5.3 Advice for firefighters

· Protective equipment: No special measures required.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and

emergency procedures Not required.

· 6.2 Environmental

precautions: No special measures required.

· 6.3 Methods and material for

containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders,

universal binders, sawdust).

· 6.4 Reference to other

sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Open and handle containers with care.

Ventilation measures are required in rooms without sufficient air

exchange (e.g. closed rooms),

because the occupational exposure limit values (see chapter 8)

could be exceeded. This must be avoided.

Wear suitable personal protective equipment (see section 8). Avoid contact with eyes, skin and clothing. Change contaminated or damaged gloves and contaminated clothing immediately and wash (Contd. on page 4)



Page 4/11

Safety data sheet according to UK REACH

Printing date 12.04.2025 Version number 56 (replaces version 55) Revision: 12.04.2025

Trade name MC-DUR 111 eco - Komponente B

(Contd. of page 3)

skin immediately. Mix slowly, partially covering the mixing container. Pour carefully and slowly when repotting. Observe the BGBau technical data sheet and practical guide for handling epoxy

resins.

Information about protection

against explosions and fires: Ensure sufficient air exchange and/or extraction in the working

areas. Take precautionary measures to avoid electrostatic

discharges.

· 7.2 Conditions for safe storage, including any incompatibilities

Storage

· Requirements to be met by

storerooms and containers: No special requirements.

· Further information about

storage conditions: Keep container tightly closed in a well-ventilated place.

· Storage class 10

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

CAS: 107-98-2 1-Methoxy-2-propanol

WEL Short-term value: 560 mg/m³, 150 ppm

Long-term value: 375 mg/m³, 100 ppm

Sk

· DNELs

CAS: 100-51-6 Benzyl alcohol

Oral	DNEL	4 mg/kg bw/Tag (ArL)
		00

20 mg/kg bw/Tag (Ark)
Dermal DNEL 8 mg/kg bw/day (ArL)

DNEL 8 mg/kg bw/day (ArL) 40 mg/kg bw/day (Ark)

Inhalative DNEL 22 mg/m³ (ArL) 110 mg/m³ (Ark)

CAS: 107-98-2 1-Methoxy-2-propanol

Oral DNEL 3.3 mg/kg bw/Tag (ArL)
Dermal DNEL 50.6 mg/kg bw/day (ArL)
Inhalative DNEL 369 mg/m³ (ArL)

· PNECs

CAS: 100-51-6 Benzyl alcohol

PNEC 0.527 mg/l (Marine water sediment)

0.1 mg/l (Mew)

1 mg/l (Fresh water sediment)

PNEC 0.456 mg/kg dwt (Bod)

5.27 mg/kg dwt (Fresh water sediment)

(Contd. on page 5)



Page 5/11

Safety data sheet according to UK REACH

Printing date 12.04.2025 Version number 56 (replaces version 55) Revision: 12.04.2025

Trade name MC-DUR 111 eco - Komponente B

(Contd. of page 4)

• Additional information: The lists that were valid during the compilation were used as basis.

· 8.2 Exposure controls · Appropriate engineering

controls No further data; see section 7.

· Individual protection measures, such as personal protective equipment

· General protective and

hygienic measures Keep away from food, drink and animal feed.

Remove soiled, soaked clothing immediately.

Wash hands before breaks and at the end of work.

Avoid contact with eyes and skin.

· Breathing equipment: If workplace limit values cannot be complied with by ventilation

measures or if rooms cannot be technically ventilated, respiratory protection must be worn: Use combination filter A1-P2 (brown/white) in rooms that cannot be ventilated. If oxygen deficiency is expected, use self-contained breathing apparatus. Observe wearing time limits according to §9 (3) GefStoffV in conjunction

with BGR 190.

· Hand protection Selection of the glove material on consideration of the penetration

times, rates of diffusion and the degradation

• Material of gloves You can find help with choosing gloves on the website https://

www.bgbau.de/fileadmin/Gisbau/Projekte.pdf

For example, we recommend the Sol-vex 37-900 protective gloves from Ansell GmbH. The breakthrough time of the protective gloves can be found under point 8 "Penetration time of the glove material". The selection of a suitable glove depends not only on the material, but also on other quality features and varies from manufacturer to

manufacturer. As the product

is a preparation of several substances, the resistance of glove materials cannot be calculated in advance and must therefore be

checked before use.

Nitrile rubber

Recommended material thickness:≥ 0.4 mm

Penetration time of glove

material

The breakthrough times of the Sol-vex 37-900 protective gloves

are around 8 hours.

The following applies to all other gloves:

The exact breakthrough time must be obtained from the protective

glove manufacturer and adhered to.

Nitrile rubber

Material thickness: ≥ 0.40 mm Penetration time: ≥ 480 min

Butvl rubber:

Material thickness: ≥ 0.5 mm Penetration time: ≥ 480 min Tight-fitting safety goggles.

· Eye/face protection Tight-fitting safety goggle

Safety goggles.

Body protection: Protective clothing

Suitable protective clothing should be worn when working with epoxy resins. In addition to normal work clothing (long trousers,

long-sleeved shirt or T-shirt), disposable overalls, aprons,

(Contd. on page 6)



Page 6/11

Safety data sheet according to UK REACH

Printing date 12.04.2025 Version number 56 (replaces version 55) Revision: 12.04.2025

Trade name MC-DUR 111 eco - Komponente B

(Contd. of page 5)

overshoes, sleeve protectors etc. may be necessary depending on the activity. Uncovered areas of skin should be avoided as far as possible, even in hot weather. If the work involves kneeling, the lower leg area should be protected by protective trousers.

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

Colour: Light grey
 Smell: Characteristic
 Odour threshold: Not determined
 Melting point/freezing point: Not determined

· Boiling point or initial boiling point and

boiling range 100 °C (CAS: 7732-18-5 Water)

· Flammability Not applicable.

· Lower and upper explosion limit

Lower: Not determined.Upper: Not determined.

· Flash point: >94 °C

Decomposition temperature: Not determined.pH Not determined.

· Viscosity:

· Kinematic viscosity Not determined. · dynamic: Not determined.

Solubility

· Water: Not miscible or difficult to mix

· Partition coefficient n-octanol/water (log

value) Not determined.

· Steam pressure at 20 °C: 23 hPa (CAS: 7732-18-5 Water)

Density and/or relative density

Density at 20 °C
 Relative density
 Vapour density
 Not determined.
 Not determined.

· 9.2 Other information

· Appearance:

· Form: Fluid

· Important information on protection of health

and environment, and on safety.

• Self-inflammability: Product is not selfigniting. • Explosive properties: Product is not explosive.

· Change in condition

· Evaporation rate Not determined.

· Information with regard to physical hazard

classes

· Explosives Void

(Contd. on page 7)



Page 7/11

Safety data sheet according to UK REACH

Printing date 12.04.2025 Version number 56 (replaces version 55) Revision: 12.04.2025

Trade name MC-DUR 111 eco - Komponente B

(Contd. of page 6)

· Flammable gases	Void	
Aerosols	Void	
· Oxidising gases	Void	
· Gases under pressure	Void	
Flammable liquids	Void	
Flammable solids	Void	
· Self-reactive substances and mixtures	Void	
· Pyrophoric liquids	Void	
Pyrophoric solids	Void	
Self-heating substances and mixtures	Void	
· Substances and mixtures, which emit		
flammable gases in contact with water	Void	
· Oxidising liquids	Void	
Oxidising solids	Void	
· Organic peroxides	Void	
Corrosive to metals	Void	
· Desensitised explosives	Void	

SECTION 10: Stability and reactivity

• 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability

Thermal decomposition /

conditions to be avoided: No decomposition if used according to specifications.

· 10.3 Possibility of hazardous

reactions No dangerous reactions known

10.4 Conditions to avoid No further relevant information available.
 10.5 Incompatible materials: No further relevant information available.

· 10.6 Hazardous

decomposition products: No dangerous decomposition products known

SECTION 11: Toxicological information

· 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

· Acute toxicity Based on available data, the classification criteria are not met.

	· LD/LC50 values that are relevant for classification:			
Γ	CAS: 100-	CAS: 100-51-6 Benzyl alcohol		
Γ	Oral	LD50	1230 mg/kg (rat)	
		NOAEL 2nd year study	200 mg/kg (mouse)	
			200 mg/kg (rat)	
	Dermal	LD50	2000 mg/kg (rabbit)	
	Inhalative	LC50/4 h	>4178 mg/l (rat)	

(Contd. on page 8)



Page 8/11

Safety data sheet according to UK REACH

Printing date 12.04.2025 Version number 56 (replaces version 55) Revision: 12.04.2025

Trade name MC-DUR 111 eco - Komponente B

		(Contd. of page 7)	
CAS: 107	CAS: 107-98-2 1-Methoxy-2-propanol		
Oral	LD50	4016 mg/kg (rat)	
Dermal	LD50	13000 mg/kg (rabbit)	
Inhalative	LC50/4 h	54.6 mg/l (rat)	
CAS: 261	CAS: 26142-30-3 Polypropylenglycole-diepoxidresin		
Oral	LD50	>2000 mg/kg (rat)	
Dermal	LD50	>2000 mg/kg (rat)	

· Primary irritant effect:

· Skin corrosion/irritation Based on available data, the classification criteria are not met.

· Serious eye damage/irritation Causes serious eye irritation.

· Respiratory or skin

sensitisation May cause an allergic skin reaction.

Germ cell mutagenicity
 Carcinogenicity
 Reproductive toxicity
 STOT-single exposure
 STOT-repeated exposure
 Aspiration hazard
 Based on available data, the classification criteria are not met.
 Based on available data, the classification criteria are not met.
 Based on available data, the classification criteria are not met.
 Based on available data, the classification criteria are not met.
 Based on available data, the classification criteria are not met.
 Based on available data, the classification criteria are not met.

· 11.2 Information on other hazards

Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

· 12.1 Toxicity

•	A	qu	atı	c t	OX	ICI	ty:
---	---	----	-----	-----	----	-----	-----

CAS: 100-51-6 Benzyl alcohol

IC50/72h | 700 mg/l (algae)

LC50/96h 460 mg/l (Pimephales promelas)

10 mg/l (Lepomis macrochirus)

CAS: 107-98-2 1-Methoxy-2-propanol

IC50 1000 mg/l (BEL)

LC50/96h 6812 mg/l (Leucidus idus) LC50/48h 23300 mg/l (Daphnia magna) EC50/48h 23300 mg/l (Daphnia magna)

CAS: 26142-30-3 Polypropylenglycole-diepoxidresin

LC50/96h 160 mg/l (Leucidus idus) EC50/48h 220 mg/l (Daphnia magna)

12.2 Persistence and

degradability No further relevant information available.

· 12.3 Bioaccumulative

potential No further relevant information available.

(Contd. on page 9)



Page 9/11

Safety data sheet according to UK REACH

Printing date 12.04.2025 Version number 56 (replaces version 55) Revision: 12.04.2025

Trade name MC-DUR 111 eco - Komponente B

(Contd. of page 8)

• **12.4 Mobility in soil** No further relevant information available.

12.5 Results of PBT and vPvB assessment
 PBT: Not applicable.
 vPvB: Not applicable.

· 12.6 Endocrine disrupting

properties The product does not contain substances with endocrine disrupting

properties.

· 12.7 Other adverse effects

· Additional ecological information:

• General notes: Do not allow undiluted product or large quantities of it to reach

ground water, water bodies or sewage system.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

• Recommendation Must not be disposed of together with household garbage. Do not

allow product to reach sewage system.

· Uncleaned packagings:

• Recommendation: Disposal must be made according to official regulations.

14.1 UN number or ID number ADR, IMDG, IATA	Void
14.2 UN proper shipping name ADR, IMDG, IATA	Void
14.3 Transport hazard class(es)	
ADR, ADN, IMDG, IATA Class	Void
14.4 Packing group ADR, IMDG, IATA	Void
14.5 Environmental hazards:	Not applicable.
14.6 Special precautions for user	Not applicable.
14.7 Maritime transport in bulk accordii IMO instruments	ng to Not applicable.
Transport/Additional information:	Not dangerous according to the abov specifications.
UN "Model Regulation":	Void

GB



Page 10/11

Safety data sheet according to UK REACH

Printing date 12.04.2025 Version number 56 (replaces version 55) Revision: 12.04.2025

Trade name MC-DUR 111 eco - Komponente B

(Contd. of page 9)

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Poisons Act
- Regulated explosives precursors

None of the ingredients is listed.

· Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors

None of the ingredients is listed.

Reportable poisons

None of the ingredients is listed.

Directive 2012/18/EU

· Named dangerous

substances - ANNEX I

· 15.2 Chemical safety

assessment:

None of the ingredients is listed.

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases H226 Flammable liquid and vapour.

H302 Harmful if swallowed. H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H336 May cause drowsiness or dizziness.

EUH205 Contains epoxy constituents. May produce an allergic

reaction.

· Department issuing data specification sheet:

Environment protection department.

· Abbreviations and acronyms: ADR: Accord relatif au transport international des marchandises dangereuses par

route (European Agreement Concerning the International Carriage of Dangerous

Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (ÚK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

(Contd. on page 11)



Page 11/11

Safety data sheet according to UK REACH

Version number 56 (replaces version 55) Revision: 12.04.2025 Printing date 12.04.2025

Trade name MC-DUR 111 eco - Komponente B

(Contd. of page 10)

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 3: Flammable liquids – Category 3
Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1 Skin Sens. 1B: Skin sensitisation – Category 1B

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

* * Data compared to the previous version altered.

GB