

Page 1/11

Safety data sheet according to UK REACH

Printing date 14.04.2025

Version number 48 (replaces version 47)

Revision: 14.04.2025

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

· 1.1 Product identifier	
 Trade name 1.2 Relevant identified uses o Sector of Use Application of the substance / the mixture 	<u>MC-DUR 111 eco transparent - Komponente A</u> f the substance or mixture and uses advised against SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen) Priming
1.3 Details of the supplier of t	-
• Manufacturer/Supplier:	MC-Bauchemie Müller GmbH & Co. KG Am Kruppwald 1-8 D-46238 Bottrop Tel.: +49(0)2041-101-0 Fax.: +49(0)2041-101-400 E-Mail: info@mc-bauchemie.de MC-Bauchemie AG Hagackerstr. 10 CH-8953 Dietikon Tel.: +44-7400510 Fax : +44-7400533
 Informing department: 1.4 Emergency telephone number: 	msds@mc-bauchemie.de Tel.: +49 / (0)700 24112112 (MCR) Tel.: +1 872 5888271 (MCR)

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

[•] 2.2 Label elements

• Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms



· Signal word

· Hazard-determining

components of labelling:

· Hazard statements

Polypropylenglycole-diepoxidresin H315 Causes skin irritation.

(Contd. on page 2)

GB



Page 2/11

Safety data sheet according to UK REACH

Printing date 14.04.2025

Version number 48 (replaces version 47)

Revision: 14.04.2025

Trade name MC-DUR 111 eco transparent - Komponente A

		(Contd. of page 1)
	H319 Causes s	erious eye irritation.
		e an allergic skin reaction.
Precautionary statements	P261	Avoid breathing dust/fume/gas/mist/vapours/ spray.
	P280	Wear protective gloves / eye protection / face protection.
	P305+P351+P3	338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
	P332+P313	If skin irritation occurs: Get medical advice/ attention.
	P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
	P337+P313	If eye irritation persists: Get medical advice/ attention.
· Additional information:	EUH205 Conta reactio	ins epoxy constituents. May produce an allergic
 2.3 Other hazards Results of PBT and vPvB as 	easemant	
· PBT:		
· vPvB:	Not applicable. Not applicable.	
	iver applicable.	

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures · Description:	Mixture consisting of the following components.	
· Dangerous components:		
CAS: 26142-30-3	Polypropylenglycole-diepoxidresin Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1B, H317, EUH205	10-30%
CAS: 100-51-6 EINECS: 202-859-9	Benzyl alcohol Acute Tox. 4, H302; Acute Tox. 4, H332; Eye Irrit. 2, H319	<10%
CAS: 107-98-2 EINECS: 203-539-1 Reg.nr.: 01-2119457435-35- xxxx	1-Methoxy-2-propanol Flam. Liq. 3, H226; STOT SE 3, H336	<10%
· Additional information	For the wording of the listed hazard phrases refer to see	ction 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

General informationRemove contaminated clothing immediately. Consult a doctor if
symptoms occur. Move affected person to fresh air.
Supply fresh air; seek medical advice if symptoms occur.
If unconscious, place in recovery position and seek medical advice.
(Contd. on page 3)

GB



Page 3/11

Safety data sheet according to UK REACH

Printing date 14.04.2025 Version number 48 (replaces version 47)

Revision: 14.04.2025

Trade name MC-DUR 111 eco transparent - Komponente A

	(Contd. of page 2)
 After skin contact 	In case of contact with skin, wash carefully with plenty of soap and
	water. Consult a doctor in case of skin reactions.
· After eye contact	Rinse opened eye for several minutes under running water.
•	Call a doctor immediately
• After swallowing	Rinse mouth with water. Never give anything by mouth to an
5	unconscious person. DO NOT induce vomiting. If symptoms
	persist, consult a doctor.
 4.2 Most important symptoms 	

and effects, both acute and delayed

Advice for the doctor: Elementary aid, decontamination, symptomatic treatment.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents Use fire fighting measures that suit the environment.
- 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

- 5.3 Advice for firefighters • Protective equipment:
 - ment: No special measures required.

SECTION 6: Accidental release measures

 6.1 Personal precautions, protective equipment and 	
emergency procedures	Not required.
6.2 Environmental	'
precautions:	Dilute with much water.
⁶ .3 Methods and material for	
containment and cleaning up:	Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
[·] 6.4 Reference to other	
sections	See Section 7 for information on safe handling
	See Section 8 for information on personal protection equipment.
	See Section 13 for information on disposal.

SECTION 7: Handling and storage

[.] 7.1 Precautions for safe	
handling	Open and handle containers with care.
C C	Ventilation measures are required in rooms without sufficient air exchange (e.g. closed rooms),
	because the occupational exposure limit values (see chapter 8) could be exceeded. This must be avoided.
	Wear suitable personal protective equipment (see section 8). Avoid contact with eyes, skin and clothing. Change contaminated or
	(Contd. on page 4)



Page 4/11

Safety data sheet according to UK REACH

Printing date 14.04.2025

Version number 48 (replaces version 47)

Revision: 14.04.2025

Trade name MC-DUR 111 eco transparent - Komponente A

	(Contd. of page 3) damaged gloves and contaminated clothing immediately and wash skin immediately. Mix slowly, partially covering the mixing container. Pour carefully and slowly when repotting. Observe the BGBau technical data sheet and practical guide for handling epoxy
	resins.
· Information about protection	
	Ensure sufficient air exchange and/or extraction in the working areas. Take precautionary measures to avoid electrostatic discharges.
· 7.2 Conditions for safe storad	ge, including any incompatibilities
· Storage	,
· Requirements to be met by	
storerooms and containers:	No special requirements.
· Further information about	
storage conditions:	None.
· Storage class	12
Silviaye class	12

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

CAS: 107	-98-2 1	-Methoxy-2-propanol	
		value: 560 mg/m³, 150 ppm value: 375 mg/m³, 100 ppm	
DNELs			
CAS: 100-	-51-6 B	Benzyl alcohol	
Oral	DNEL	4 mg/kg bw/Tag (ArL)	
		20 mg/kg bw/Tag (Ark)	
Dermal	DNEL	8 mg/kg bw/day (ArL)	
		40 mg/kg bw/day (Ark)	
Inhalative	DNEL	22 mg/m³ (ArL)	
		110 mg/m³ (Ark)	
CAS: 107-	-98-2 1	-Methoxy-2-propanol	
Oral	DNEL	3.3 mg/kg bw/Tag (ArL)	
Dermal	DNEL	50.6 mg/kg bw/day (ArL)	
Inhalative	DNEL	369 mg/m³ (ArL)	
PNECs			
CAS: 100-	-51-6 B	Benzyl alcohol	
PNEC 0.5	527 mg/	/l (Marine water sediment)	
0.1	' mg/l (l	Mew)	
1 n	ng/l (Fr	esh water sediment)	
		(Cor	ntd. on pag



Page 5/11

GB

Safety data sheet according to UK REACH

Printing date 14.04.2025

Version number 48 (replaces version 47)

Revision: 14.04.2025

Trade name MC-DUR 111 eco transparent - Komponente A

		(Contd. of page 4
	456 mg/kg dwt (Bo	
	27 mg/kg dwt (Fres	,
Addition	al information:	The lists that were valid during the compilation were used as basis
	sure controls	
	iate engineering	
controls		No further data; see section 7.
		sures, such as personal protective equipment
	protective and	Keen survey from food, drink and an inset food
nygienic	measures	Keep away from food, drink and animal feed.
		Remove soiled, soaked clothing immediately.
		Wash hands before breaks and at the end of work.
Broathin	a oquinmont:	Avoid contact with eyes and skin. If workplace limit values cannot be complied with by ventilatio
Dieatiiii	g equipment:	measures or if rooms cannot be technically ventilated, respirator
		protection must be worn: Use combination filter A1-P2 (brown
		white) in rooms that cannot be ventilated. If oxygen deficiency
		expected, use self-contained breathing apparatus. Observ
		wearing time limits according to §9 (3) GefStoffV in conjunctio
		with BGR 190.
Hand pro	otection	Selection of the glove material on consideration of the penetratio
		times, rates of diffusion and the degradation
Material of	of gloves	You can find help with choosing gloves on the website https:
	•	www.bgbau.de/fileadmin/Gisbau/Projekte.pdf
		For example, we recommend the Sol-vex 37-900 protective glove
		from Ansell GmbH. The breakthrough time of the protective glove
		can be found under point 8 "Penetration time of the glove material
		The selection of a suitable glove depends not only on the materia
		but also on other quality features and varies from manufacturer t
		manufacturer. As the product
		is a preparation of several substances, the resistance of glov
		materials cannot be calculated in advance and must therefore b checked before use.
		Nitrile rubber
		Recommended material thickness: ≥ 0.4 mm
Penetrati	ion time of glove	
material	on time of giove	The breakthrough times of the Sol-vex 37-900 protective glove
utorrur		are around 8 hours.
		The following applies to all other gloves:
		The exact breakthrough time must be obtained from the protectiv
		glove manufacturer and adhered to.
		Nitrile rubber
		Material thickness: ≥ 0.40 mm
		Penetration time: \geq 480 min
		Butyl rubber:
		Material thickness: \geq 0.5 mm
_ /-		Penetration time: \geq 480 min
Eye/face	protection	Tight-fitting safety goggles.
		Safety goggles.
		(Contd. on page)



Page 6/11

GB

Safety data sheet according to UK REACH

Printing date 14.04.2025

Version number 48 (replaces version 47)

Revision: 14.04.2025

Trade name MC-DUR 111 eco transparent - Komponente A

• Body protection:

(Contd. of page 5) Protective clothing Suitable protective clothing should be worn when working with epoxy resins. In addition to normal work clothing (long trousers, long-sleeved shirt or T-shirt), disposable overalls, aprons, overshoes, sleeve protectors etc. may be necessary depending on the activity. Uncovered areas of skin should be avoided as far as possible, even in hot weather. If the work involves kneeling, the lower leg area should be protected by protective trousers.

SECTION 9: Physical and chemical properties

• 9.1 Information on basic physical and chem	nical properties
· General Information	
· Physical state	Liquid
· Colour:	White
· Smell:	Characteristic
· Odour threshold:	Not determined.
· Melting point/freezing point:	Not determined
· Boiling point or initial boiling point and	
boiling range	Not determined
Flammability	Not applicable.
· Lower and upper explosion limit	
· Lower:	Not determined.
· Upper:	Not determined.
· Flash point:	Not applicable
· Auto-ignition temperature:	300 °C (CAS: 26142-30-3 Polypropylenglycole-
fate ignition temperature.	diepoxidresin)
· Decomposition temperature:	Not determined.
· pH	Not determined.
· Viscosity:	Not dotommod.
· Kinematic viscosity	Not determined.
· dynamic at 20 °C:	3900 mPas
· Solubility	
· Water:	Emulsifiable
· Partition coefficient n-octanol/water (log	Emaismable
value)	Not determined.
· Steam pressure at 20 °C:	23 hPa (CAS: 7732-18-5 Water)
· Density and/or relative density	20 11 0 (0) 02 10 0 Water)
· Density at 20 °C	1.1 g/cm³
· Relative density	Not determined.
· Vapour density	Not determined.
[•] 9.2 Other information	
· Appearance:	
· Form:	Fluid
	(Contd. on page 7)



Page 7/11

Safety data sheet according to UK REACH

Printing date 14.04.2025

Version number 48 (replaces version 47)

Revision: 14.04.2025

Trade name MC-DUR 111 eco transparent - Komponente A

		(Contd. of page
Important information on protection of hea	alth	
and environment, and on safety.		
Self-inflammability:	Product is not selfigniting.	
Explosive properties:	Product is not explosive.	
Change in condition		
Evaporation rate	Not determined.	
Information with regard to physical haz	ard	
classes		
Explosives	Void	
Flammable gases	Void	
Aerosols	Void	
Oxidising gases	Void	
Gases under pressure	Void	
Flammable liquids	Void	
Flammable solids	Void	
Self-reactive substances and mixtures	Void	
Pyrophoric liquids	Void	
Pyrophoric solids	Void	
Self-heating substances and mixtures	Void	
Substances and mixtures, which emit		
flammable gases in contact with water	Void	
• Oxidising liquids	Void	
Oxidising solids	Void	
Organic peroxides	Void	
Corrosive to metals	Void	
Desensitised explosives	Void	

SECTION 10: Stability and reactivity

10.1 Reactivity 10.2 Chemical stability	No further relevant information available.
Thermal decomposition / conditions to be avoided:	No decomposition if used according to specifications
10.3 Possibility of hazardous reactions	No dangerous reactions known
10.4 Conditions to avoid 10.5 Incompatible materials:	No further relevant information available. No further relevant information available.
10.6 Hazardous	
decomposition products:	No dangerous decomposition products known

SECTION 11: Toxicological information

· 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008 · Acute toxicity

Based on available data, the classification criteria are not met.

(Contd. on page 8) GB



Page 8/11

Safety data sheet according to UK REACH

Printing date 14.04.2025

Version number 48 (replaces version 47)

Revision: 14.04.2025

Trade name MC-DUR 111 eco transparent - Komponente A

		(Contd. of page
	values that are relevant	
CAS: 261	42-30-3 Polypropylengi	lycole-diepoxidresin
Oral	LD50	>2000 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rat)
CAS: 100-	-51-6 Benzyl alcohol	·
Oral	LD50	1230 mg/kg (rat)
	NOAEL 2nd year study	200 mg/kg (mouse)
		200 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rabbit)
Inhalative	LC50/4 h	>4178 mg/l (rat)
CAS: 107	-98-2 1-Methoxy-2-prop	banol
Oral	LD50	4016 mg/kg (rat)
Dermal	LD50	13000 mg/kg (rabbit)
Inhalative	LC50/4 h	54.6 mg/l (rat)
Skin corre Serious e		auses skin irritation. auses serious eye irritation.
sensitisat	•	lay cause an allergic skin reaction. ds
Endocrin	e disrupting properties	
None of th	e ingredients is listed.	

SECTION 12: Ecological information

Aquatic to	oxicity:	
CAS: 2614	12-30-3 Polypropylenglycole-diepoxidresin	
LC50/96h	160 mg/l (Leucidus idus)	
EC50/48h	220 mg/l (Daphnia magna)	
CAS: 100-	51-6 Benzyl alcohol	
IC50/72h	700 mg/l (algae)	
LC50/96h	460 mg/l (Pimephales promelas)	
	10 mg/l (Lepomis macrochirus)	
CAS: 107-	98-2 1-Methoxy-2-propanol	
IC50	1000 mg/l (BEL)	
LC50/96h	6812 mg/l (Leucidus idus)	
LC50/48h	23300 mg/l (Daphnia magna)	
EC50/48h	23300 mg/l (Daphnia magna)	
		(Contd. on page



Page 9/11

GB

Safety data sheet according to UK REACH

Printing date 14.04.2025

Version number 48 (replaces version 47)

Revision: 14.04.2025

Trade name MC-DUR 111 eco transparent - Komponente A

(Contd. of page 8
No further relevant information available.
No further relevant information available.
No further relevant information available.
vB assessment
Not applicable.
Not applicable.
The product does not contain substances with endocrine disruptin properties.
mation:
Do not allow undiluted product or large quantities of it to reac ground water, water bodies or sewage system.

SECTION 13: Disposal considerations

 13.1 Waste treatment method Recommendation 	ds Must not be disposed of together with household garbage. Do not allow product to reach sewage system.	
 Uncleaned packagings: Recommendation: Recommended cleaning 	Disposal must be made according to official regulations.	
agent:	Water, if necessary with cleaning agent.	

SECTION 14: Transport information

 14.1 UN number or ID number ADR, IMDG, IATA 	Void	
 14.2 UN proper shipping name ADR, IMDG, IATA 	Void	
 14.3 Transport hazard class(es) 		
· ADR, ADN, IMDG, IATA · Class	Void	
· 14.4 Packing group · ADR, IMDG, IATA	Void	
· 14.5 Environmental hazards: · Marine pollutant:	No	
· 14.6 Special precautions for user	Not applicable.	
 14.7 Maritime transport in bulk accordi IMO instruments 	ng to Not applicable.	
		(Contd. on page 10)



Page 10/11

Safety data sheet

according to UK REACH

Printing date 14.04.2025

Version number 48 (replaces version 47)

Revision: 14.04.2025

(Contd. of page 9)

Trade name MC-DUR 111 eco transparent - Komponente A

· UN "Model Regulation":

Void

SECTION 15: Regulatory information

 \cdot 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Poisons Act

· Regulated explosives precursors

None of the ingredients is listed.

· Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors None of the ingredients is listed.

· Reportable poisons

None of the ingredients is listed.

· Directive 2012/18/EU Named dangerous substances - ANNEX I

None of the ingredients is listed.

· 15.2 Chemical safety assessment:

A Chemical Safety Assessment has not been carried out.

Relevant phrases	H226 Flammable liquid and vapour.
	H302 Harmful if swallowed.
	H315 Causes skin irritation.
	H317 May cause an allergic skin reaction.
	H319 Causes serious eye irritation.
	H332 Harmful if inhaled.
	H336 May cause drowsiness or dizziness.
	EUH205 Contains epoxy constituents. May produce an allergi
	reaction.
	ADR: Accord relatif au transport international des marchandises dangereuses pa route (European Agreement Concerning the International Carriage of Dangerou Goods by Road)
	IMDG: International Maritime Code for Dangerous Goods
	IATA: International Air Transport Association
	GHS: Globally Harmonised System of Classification and Labelling of Chemicals
	EINECS: European Inventory of Existing Commercial Chemical Substances
	ELINCS: European List of Notified Chemical Substances
	CAS: Chemical Abstracts Service (division of the American Chemical Society) DNEL: Derived No-Effect Level (UK REACH)
	PNEC: Predicted No-Effect Concentration (UK REACH)
	LC50: Lethal concentration, 50 percent
	LD50: Lethal dose, 50 percent
	PBT: Persistent, Bioaccumulative and Toxic
	(Contd. on page 11



Safety data sheet according to UK REACH

Printing date 14.04.2025

Version number 48 (replaces version 47)

Revision: 14.04.2025

Trade name MC-DUR 111 eco transparent - Komponente A

(Contd. of page 10)

Page 11/11

vPvB: very Persistent and very Bioaccumulative Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 4: Acute toxicity – Category 4 Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 Skin Sens. 1: Skin sensitisation – Category 1 Skin Sens. 1B: Skin sensitisation – Category 1B STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

 * Data compared to the previous version altered.

GB -