



BE SURE. BUILD SURE.

Page 1/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.02.2023

Version number 33 (replaces version 32)

Revision: 24.02.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name **MC-DUR 1200 VK - Komponente A**

Article number: 4

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture

Epoxy coating
Epoxy impregnation

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: MC-Bauchemie Müller GmbH & Co. KG
Am Kruppwald 1-8
D-46238 Bottrop
Tel.: +49(0)2041-101-0
Fax.: +49(0)2041-101-400
E-Mail: info@mc-bauchemie.de

MC-Bauchemie AG
Hagackerstr. 10
CH-8953 Dietikon
Tel.: +44-7400510
Fax : +44-7400533

Informing department: msds@mc-bauchemie.de

1.4 Emergency telephone number:

Tel.: +49 / (0)700 24112112 (MCR)
Tel.: +48612864565

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to

Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms



GHS07 GHS09

(Contd. on page 2)

GB



BE SURE. BUILD SURE.

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 24.02.2023

Version number 33 (replaces version 32)

Revision: 24.02.2023

Trade name MC-DUR 1200 VK - Komponente A

(Contd. of page 1)

- **Signal word** Warning
- **Hazard-determining components of labelling:** epoxide derivates
2,2'-[methylenebis(p-phenyleneoxymethylene)]bisoxirane polymers and homologues, molecular weight < 700
oxirane, mono[(C12-14-alkyloxy)methyl] derivs
1,6-hexene-diglycidylether
- **Hazard statements** H315 Causes skin irritation.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
H411 Toxic to aquatic life with long lasting effects.
- **Precautionary statements** P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P273 Avoid release to the environment.
P280 Wear protective gloves / eye protection / face protection.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 If eye irritation persists: Get medical advice/attention.
- **Additional information:** Contains epoxy constituents. May produce an allergic reaction.
- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- **3.2 Mixtures**
- **Description:** Resin mixture with colouring agents.
Mixture consisting of the following components.

· **Dangerous components:**

CAS: 1675-54-3 EINECS: 216-823-5	epoxide derivates Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	60-80%
CAS: 100-51-6 EINECS: 202-859-9 Reg.nr.: 01-2119492630-38	Benzyl alcohol Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332	<10%
EC number: 701-263-0	Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl}oxirane and 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Skin Sens. 1, H317	≥2.5-<10%

(Contd. on page 3)



BE SURE. BUILD SURE.

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 24.02.2023

Version number 33 (replaces version 32)

Revision: 24.02.2023

Trade name MC-DUR 1200 VK - Komponente A

(Contd. of page 2)

CAS: 68609-97-2 EINECS: 271-846-8	oxirane, mono[(C12-14-alkyloxy)methyl] derivs Skin Irrit. 2, H315; Skin Sens. 1, H317, EUH205	≥1-<5%
CAS: 933999-84-9	Reaction products of hexane-1,6-diol with 2-(chloromethyl)oxirane (1;2) Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; Aquatic Chronic 3, H412	≥1-<2.5%

· **Additional information** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· **4.1 Description of first aid measures**

- **After inhalation** Supply fresh air.
- **After skin contact** Instantly wash with water and soap and rinse thoroughly.
- **After eye contact** Rinse opened eye for several minutes under running water. Seek medical treatment.
- **After swallowing** Rinse out mouth and then drink plenty of water. Seek medical treatment.

- **4.2 Most important symptoms and effects, both acute and delayed** Allergic reactions

- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents** CO₂, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam.
- **For safety reasons unsuitable extinguishing agents** Water with a full water jet.
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** Wear self-contained breathing apparatus.
- **Additional information** Cool endangered containers with water spray jet.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures** Wear protective equipment. Keep unprotected persons away.

(Contd. on page 4)



BE SURE. BUILD SURE.

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.02.2023

Version number 33 (replaces version 32)

Revision: 24.02.2023

Trade name MC-DUR 1200 VK - Komponente A

(Contd. of page 3)

- **6.2 Environmental precautions:** Inform respective authorities in case product reaches water or sewage system.
Prevent material from reaching sewage system, holes and cellars.
- **6.3 Methods and material for containment and cleaning up:** Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
- **6.4 Reference to other sections**
See Section 7 for information on safe handling
See Section 8 for information on personal protection equipment.
See Section 13 for information on disposal.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Store in cool, dry place in tightly closed containers.
Open and handle container with care.
- **Information about protection against explosions and fires:** No special measures required.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage**
- **Requirements to be met by storerooms and containers:** Store only in the original container.
- **Information about storage in one common storage facility:** Store away from foodstuffs.
- **Further information about storage conditions:** Keep container tightly sealed.
- **Storage class** 10
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **8.1 Control parameters**
- **Components with critical values that require monitoring at the workplace:** The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

· **DNELs**

100-51-6 Benzyl alcohol

Oral	DNEL	4 mg/kg bw/Tag (ArL) 20 mg/kg bw/Tag (Ark)
Dermal	DNEL	8 mg/kg bw/day (ArL) 40 mg/kg bw/day (Ark)
Inhalative	DNEL	22 mg/m ³ (ArL)

(Contd. on page 5)



BE SURE. BUILD SURE.

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.02.2023

Version number 33 (replaces version 32)

Revision: 24.02.2023

Trade name MC-DUR 1200 VK - Komponente A

(Contd. of page 4)

		110 mg/m ³ (ArL)
68609-97-2 oxirane, mono[(C12-14-alkyloxy)methyl] derivs		
Oral	DNEL	1 mg/kg bw/Tag (ArL)
Dermal	DNEL	1.7 mg/kg bw/day (ArL)
Inhalative	DNEL	0.98 mg/m ³ (ArL)
· PNECs		
100-51-6 Benzyl alcohol		
PNEC	0.527 mg/l (Marine water sediment) 0.1 mg/l (Mew) 1 mg/l (Fresh water sediment)	
PNEC	0.456 mg/kg dwt (Bod) 5.27 mg/kg dwt (Fresh water sediment)	
68609-97-2 oxirane, mono[(C12-14-alkyloxy)methyl] derivs		
PNEC	0.00072 mg/l (Mew) 0.0072 mg/l (Suw)	
PNEC	80.12 mg/kg dwt (Bod) 6.677 mg/kg dwt (Sediment) 66.77 mg/kg dwt (Fresh water sediment)	

- **Additional information:** The lists that were valid during the compilation were used as basis.
- **8.2 Exposure controls**
- **Appropriate engineering controls** No further data; see item 7.
- **Individual protection measures, such as personal protective equipment**
- **General protective and hygienic measures** Keep away from foodstuffs, beverages and food.
Instantly remove any soiled and impregnated garments.
Wash hands during breaks and at the end of the work.
Avoid contact with the eyes and skin.
- **Hand protection** Protective gloves.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
After use of gloves apply skin-cleaning agents and skin cosmetics.
- **Material of gloves** The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material** The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye/face protection** Safety glasses
Tightly sealed safety glasses.

(Contd. on page 6)



BE SURE. BUILD SURE.

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.02.2023

Version number 33 (replaces version 32)

Revision: 24.02.2023

Trade name MC-DUR 1200 VK - Komponente A

· **Body protection:** Protective work clothing.

(Contd. of page 5)

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Colour:	Light yellow
· Smell:	Characteristic
· Melting point/freezing point:	Not determined
· Boiling point or initial boiling point and boiling range	>200 °C
· Lower and upper explosion limit	
· Lower:	1.3 Vol %
· Upper:	13 Vol %
· Flash point:	101 °C
· Ignition temperature:	184 °C
· pH	Not determined.
· Viscosity:	
· Kinematic viscosity	Not determined.
· dynamic at 20 °C:	820 mPas
· Solubility	
· Water:	Not miscible or difficult to mix
· Steam pressure at 20 °C:	0.1 hPa
· Density and/or relative density	
· Density at 20 °C	1.14 g/cm ³

· 9.2 Other information

· Appearance:	
· Form:	Fluid
· Important information on protection of health and environment, and on safety.	
· Self-inflammability:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosive air/steam mixtures is possible.

· Information with regard to physical hazard classes

· Explosives	Void
· Flammable gases	Void
· Aerosols	Void
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Void
· Flammable solids	Void
· Self-reactive substances and mixtures	
	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void

(Contd. on page 7)



BE SURE. BUILD SURE.

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 24.02.2023

Version number 33 (replaces version 32)

Revision: 24.02.2023

Trade name MC-DUR 1200 VK - Komponente A

(Contd. of page 6)

- **Self-heating substances and mixtures**
Void
- **Substances and mixtures, which emit flammable gases in contact with water**
Void
- **Oxidising liquids**
Void
- **Oxidising solids**
Void
- **Organic peroxides**
Void
- **Corrosive to metals**
Void
- **Desensitised explosives**
Void

SECTION 10: Stability and reactivity

- **10.1 Reactivity**
No further relevant information available.
- **10.3 Possibility of hazardous reactions**
No dangerous reactions known
- **10.4 Conditions to avoid**
No further relevant information available.
- **10.5 Incompatible materials:**
No further relevant information available.
- **10.6 Hazardous decomposition products:**
Possible in traces.

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity**
Based on available data, the classification criteria are not met.

· **LD/LC50 values that are relevant for classification:**

1675-54-3 epoxide derivates

Dermal	LD50	23000 mg/kg (rabbit)
--------	------	----------------------

100-51-6 Benzyl alcohol

Oral	LD50	1230 mg/kg (rat)
	NOAEL 2nd year study	200 mg/kg (mouse) 200 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rabbit)
Inhalative	LC50/4 h	>4178 mg/l (rat)

68609-97-2 oxirane, mono[(C12-14-alkyloxy)methyl] derivs

Oral	LD50	17100 mg/kg (rat)
------	------	-------------------

- **Skin corrosion/irritation**
Causes skin irritation.
- **Serious eye damage/irritation**
Causes serious eye irritation.
- **Respiratory or skin sensitisation**
May cause an allergic skin reaction.
- **Germ cell mutagenicity**
Based on available data, the classification criteria are not met.
- **Carcinogenicity**
Based on available data, the classification criteria are not met.
- **Reproductive toxicity**
Based on available data, the classification criteria are not met.
- **STOT-single exposure**
Based on available data, the classification criteria are not met.

(Contd. on page 8)



BE SURE. BUILD SURE.

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 24.02.2023

Version number 33 (replaces version 32)

Revision: 24.02.2023

Trade name MC-DUR 1200 VK - Komponente A

(Contd. of page 7)

- **STOT-repeated exposure** *Based on available data, the classification criteria are not met.*
- **Aspiration hazard** *Based on available data, the classification criteria are not met.*
- **11.2 Information on other hazards**

· **Endocrine disrupting properties**

None of the ingredients is listed.

SECTION 12: Ecological information

· **12.1 Toxicity**

· **Aquatic toxicity:**

1675-54-3 epoxide derivates

IC50	>42.6 mg/l (Bak)
LC50/96h	2 mg/l (Oncorhynchus mykiss)
EC50/48h	1.8 mg/l (Daphnia magna)
ErC50/72h	11 mg/l (Selenastrum capricornutum)

100-51-6 Benzyl alcohol

IC50/72h	700 mg/l (algae)
LC50/96h	460 mg/l (Pimephales promelas)
	10 mg/l (Lepomis macrochirus)

68609-97-2 oxirane, mono[(C12-14-alkyloxy)methyl] derivs

EbC50/72h	843 mg/l (Pseudokirchneriella subcapitata)
LC50/96h	>5000 mg/l (Oncorhynchus mykiss)
	1800 mg/l (Lepomis macrochirus)
EC50	>100 mg/l (BEL)
NOEC	500 mg/l (Pseudokirchneriella subcapitata)

· **12.2 Persistence and degradability**

No further relevant information available.

· **12.3 Bioaccumulative potential**

No further relevant information available.

· **12.4 Mobility in soil**

No further relevant information available.

· **12.5 Results of PBT and vPvB assessment**

· **PBT:**

Not applicable.

· **vPvB:**

Not applicable.

· **12.6 Endocrine disrupting properties**

The product does not contain substances with endocrine disrupting properties.

· **12.7 Other adverse effects**

· **Remark:**

Toxic for fish

· **Additional ecological information:**

· **General notes:**

*Toxic for aquatic organisms
Also poisonous for fish and plankton in water bodies.
Do not allow product to reach ground water, water bodies or sewage system.*

(Contd. on page 9)



BE SURE. BUILD SURE.

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.02.2023

Version number 33 (replaces version 32)

Revision: 24.02.2023

Trade name MC-DUR 1200 VK - Komponente A

(Contd. of page 8)
Danger to drinking water if even small quantities leak into soil.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Uncleaned packagings:

Recommendation: Empty contaminated packagings thoroughly. They can be recycled after thorough and proper cleaning.

SECTION 14: Transport information

14.1 UN number or ID number

ADR, IMDG, IATA UN3082

14.2 UN proper shipping name

ADR, IATA ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (epoxide derivatives)
IMDG ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (epoxide derivatives), MARINE POLLUTANT

14.3 Transport hazard class(es)

ADR
Class 9 (M6) Miscellaneous dangerous substances and articles.
Label 9

IMDG, IATA

Class 9 Miscellaneous dangerous substances and articles.
Label 9

14.4 Packing group

ADR, IMDG, IATA III

14.5 Environmental hazards:

Marine pollutant: Yes
Symbol (fish and tree)
Special marking (ADR): Symbol (fish and tree)
Special marking (IATA): Symbol (fish and tree)

14.6 Special precautions for user

Warning: Miscellaneous dangerous substances and articles.
Kemler Number: 90
EMS Number: F-A, S-F

(Contd. on page 10)



BE SURE. BUILD SURE.

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 24.02.2023

Version number 33 (replaces version 32)

Revision: 24.02.2023

Trade name MC-DUR 1200 VK - Komponente A

(Contd. of page 9)

· Stowage Category	A
· 14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· Transport category	3
· Tunnel restriction code	(-)
· Remarks:	1 kg: LQ
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXIDE DERIVATES), 9, III

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 200 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases** H302 Harmful if swallowed.
H312 Harmful in contact with skin.

(Contd. on page 11)



BE SURE. BUILD SURE.

Page 11/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.02.2023

Version number 33 (replaces version 32)

Revision: 24.02.2023

Trade name MC-DUR 1200 VK - Komponente A

(Contd. of page 10)

H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.
EUH205 Contains epoxy constituents. May produce an allergic reaction.

· **Department issuing data specification sheet:**

Environment protection department.

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (UK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

· *** Data compared to the previous version altered.**

GB