



BE SURE. BUILD SURE.

Page 1/12

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 13.05.2023

Version number 26 (replaces version 25)

Revision: 13.05.2023

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name **MC-DUR 1320 VK - Komponente B**

Article number: 4068

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

#### Application of the substance / the mixture

Epoxy coating  
Hardening agent/ Curing agent

#### 1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: MC-Bauchemie Müller GmbH & Co. KG  
Am Kruppwald 1-8  
D-46238 Bottrop  
Tel.: +49(0)2041-101-0  
Fax.: +49(0)2041-101-400  
E-Mail: info@mc-bauchemie.de

MC-Bauchemie AG  
Hagackerstr. 10  
CH-8953 Dietikon  
Tel.: +44-7400510  
Fax : +44-7400533

Informing department: msds@mc-bauchemie.de

#### 1.4 Emergency telephone number:

Tel.: +49 / (0)700 24112112 (MCR)  
Tel.: +48612864565

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification according to Regulation (EC) No 1272/2008

Skin Corr. 1A H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.

Skin Sens. 1 H317 May cause an allergic skin reaction.

#### 2.2 Label elements

##### Labelling according to

Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation.

##### Hazard pictograms



GHS05 GHS07

##### Signal word

Danger

(Contd. on page 2)

GB



BE SURE. BUILD SURE.

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 13.05.2023

Version number 26 (replaces version 25)

Revision: 13.05.2023

**Trade name MC-DUR 1320 VK - Komponente B**

(Contd. of page 1)

- **Hazard-determining components of labelling:** polymer amine terminated  
Polyoxypropylenediamine  
Isophorone diamine  
2-methylpentane-1,5-diamine
- **Hazard statements** H314 Causes severe skin burns and eye damage.  
H317 May cause an allergic skin reaction.
- **Precautionary statements** P260 Do not breathe dusts or mists.  
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P310 Immediately call a POISON CENTER/doctor.  
P321 Specific treatment (see on this label).  
P362+P364 Take off contaminated clothing and wash it before reuse.
- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

**SECTION 3: Composition/information on ingredients**

- **3.2 Mixtures**
- **Description:** Mixture consisting of the following components.

· **Dangerous components:**

CAS: 100-51-6	Benzyl alcohol Acute Tox. 4, H302; Acute Tox. 4, H332; Eye Irrit. 2, H319	30-60%
	polymer amine terminated Eye Dam. 1, H318; Skin Irrit. 2, H315; Skin Sens. 1B, H317	10-30%
CAS: 9046-10-0 Reg.nr.: 01-2119557899-12	Polyoxypropylenediamine Skin Corr. 1B, H314; Aquatic Chronic 3, H412	≥10-<25%
CAS: 2855-13-2	Isophorone diamine Skin Corr. 1B, H314; Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1, H317; Aquatic Chronic 3, H412	≥5-<10%
CAS: 15520-10-2 EINECS: 239-556-6	2-methylpentane-1,5-diamine Skin Corr. 1A, H314; Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; STOT SE 3, H335	≥5-<10%
CAS: 90-72-2 EINECS: 202-013-9 Reg.nr.: 2119560597-27	2,4,6-tris(dimethylaminomethyl)phenol Skin Corr. 1C, H314; Eye Dam. 1, H318; Acute Tox. 4, H302	≥1-<2.5%

(Contd. on page 3)



BE SURE. BUILD SURE.

Page 3/12

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 13.05.2023

Version number 26 (replaces version 25)

Revision: 13.05.2023

Trade name **MC-DUR 1320 VK - Komponente B**

· **Additional information**

For the wording of the listed hazard phrases refer to section 16.

(Contd. of page 2)

### SECTION 4: First aid measures

· **4.1 Description of first aid measures**

- **General information** Instantly remove any clothing soiled by the product. Seek medical treatment.
- **After inhalation** Supply fresh air and call for doctor for safety reasons.
- **After skin contact** Instantly wash with water and soap and rinse thoroughly.
- **After eye contact** Rinse opened eye for several minutes under running water. Seek medical treatment.
- **After swallowing** Drink copious amounts of water and provide fresh air. Instantly call for doctor.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

### SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents** CO<sub>2</sub>, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam.
- **For safety reasons unsuitable extinguishing agents** Water with a full water jet.
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** Put on breathing apparatus.

### SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures** Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:** Prevent material from reaching sewage system, holes and cellars.
- **6.3 Methods and material for containment and cleaning up:** Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose of contaminated material as waste according to item 13. Ensure adequate ventilation.

(Contd. on page 4)

GB



BE SURE. BUILD SURE.

### Safety data sheet according to 1907/2006/EC, Article 31

Printing date 13.05.2023

Version number 26 (replaces version 25)

Revision: 13.05.2023

**Trade name MC-DUR 1320 VK - Komponente B**

(Contd. of page 3)

· **6.4 Reference to other sections**

See Section 7 for information on safe handling  
See Section 8 for information on personal protection equipment.  
See Section 13 for information on disposal.

## SECTION 7: Handling and storage

· **7.1 Precautions for safe handling**

Store in cool, dry place in tightly closed containers.  
Open and handle container with care.

· **Information about protection against explosions and fires:** No special measures required.

· **7.2 Conditions for safe storage, including any incompatibilities**

· **Storage**

· **Requirements to be met by storerooms and containers:** No special requirements.

· **Information about storage in one common storage facility:** Not required.

· **Further information about storage conditions:**

Keep container tightly sealed.

· **Storage class**

8A

· **7.3 Specific end use(s)**

No further relevant information available.

## SECTION 8: Exposure controls/personal protection

· **8.1 Control parameters**

· **Components with critical values that require monitoring at the workplace:**

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

· **DNELs**

**100-51-6 Benzyl alcohol**

Oral DNEL 4 mg/kg bw/Tag (ArL)  
20 mg/kg bw/Tag (Ark)

Dermal DNEL 8 mg/kg bw/day (ArL)  
40 mg/kg bw/day (Ark)

Inhalative DNEL 22 mg/m<sup>3</sup> (ArL)  
110 mg/m<sup>3</sup> (Ark)

**9046-10-0 Polyoxypropylenediamine**

Oral DNEL 0.04 mg/kg bw/Tag (ArL)

Dermal DNEL 2.5 mg/kg bw/day (ArL)

**2855-13-2 Isophorone diamine**

Oral DNEL 0.526 mg/kg bw/Tag (ArL)

(Contd. on page 5)



BE SURE. BUILD SURE.

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 13.05.2023

Version number 26 (replaces version 25)

Revision: 13.05.2023

**Trade name MC-DUR 1320 VK - Komponente B**

(Contd. of page 4)

Inhalative	DNEL	20.1 mg/m <sup>3</sup> (ArL)
<b>15520-10-2 2-methylpentane-1,5-diamine</b>		
Dermal	DNEL	1.5 mg/kg bw/day (ArL)
Inhalative	DNEL	0.25 mg/m <sup>3</sup> (ArL)
		0.5 mg/m <sup>3</sup> (Ark)
<b>90-72-2 2,4,6-tris(dimethylaminomethyl)phenol</b>		
Inhalative	DNEL	0.31 mg/m <sup>3</sup> (ArL)
<b>· PNECs</b>		
<b>100-51-6 Benzyl alcohol</b>		
PNEC	0.527 mg/l (Marine water sediment)	
	0.1 mg/l (Mew)	
	1 mg/l (Fresh water sediment)	
PNEC	0.456 mg/kg dwt (Bod)	
	5.27 mg/kg dwt (Fresh water sediment)	
<b>9046-10-0 Polyoxypropylenediamine</b>		
PNEC	7.5 mg/l (Sewage Treatment Plant)	
	0.015 mg/l (Fresh water)	
PNEC	0.0176 mg/kg dwt (Bod)	
	0.125 mg/kg dwt (Sediment)	
	0.132 mg/kg dwt (Fresh water sediment)	
<b>2855-13-2 Isophorone diamine</b>		
PNEC	0.006 mg/l (Mew)	
	0.06 mg/l (Suw)	
PNEC	0.578 mg/kg dwt (Sediment)	
	5.784 mg/kg dwt (Fresh water sediment)	
<b>15520-10-2 2-methylpentane-1,5-diamine</b>		
PNEC	0.042 mg/l (Mew)	
	0.42 mg/l (Suw)	
<b>90-72-2 2,4,6-tris(dimethylaminomethyl)phenol</b>		
PNEC	0.2 mg/l (Sewage Treatment Plant)	
	0.0084 mg/l (Mew)	
	0.084 mg/l (Suw)	

· **Additional information:** The lists that were valid during the compilation were used as basis.

· **8.2 Exposure controls**

· **Appropriate engineering controls**

No further data; see section 7.

· **Individual protection measures, such as personal protective equipment**

· **General protective and hygienic measures**

Keep away from foodstuffs, beverages and food.  
Instantly remove any soiled and impregnated garments.  
Wash hands during breaks and at the end of the work.  
Avoid contact with the eyes and skin.

(Contd. on page 6)



BE SURE. BUILD SURE.

### Safety data sheet according to 1907/2006/EC, Article 31

Printing date 13.05.2023

Version number 26 (replaces version 25)

Revision: 13.05.2023

**Trade name MC-DUR 1320 VK - Komponente B**

(Contd. of page 5)

- **Hand protection** *Protective gloves.  
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation*
- **Material of gloves** *After use of gloves apply skin-cleaning agents and skin cosmetics.  
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.*
- **Penetration time of glove material** *The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.*
- **Eye/face protection** *Safety glasses  
Tightly sealed safety glasses.*
- **Body protection:** *Protective work clothing.*

## SECTION 9: Physical and chemical properties

### · 9.1 Information on basic physical and chemical properties

#### · General Information

- **Colour:** *Yellow*
- **Smell:** *Amine-like*
- **Melting point/freezing point:** *Not determined*
- **Boiling point or initial boiling point and boiling range** *205 °C*
- **Lower and upper explosion limit**
- **Lower:** *1.3 Vol %*
- **Upper:** *13 Vol %*
- **Flash point:** *>100 °C*
- **Auto-ignition temperature:** *380 °C*
- **pH at 20 °C** *12.5*
- **Viscosity:**
- **Kinematic viscosity** *Not determined.*
- **dynamic at 20 °C:** *195 mPas*
- **Solubility**
- **Water:** *Partly miscible*
- **Steam pressure at 20 °C:** *0.1 hPa*
- **Density and/or relative density**
- **Density at 20 °C** *1.02 g/cm<sup>3</sup>*

### · 9.2 Other information

- **Appearance:**
- **Form:** *Fluid*
- **Important information on protection of health and environment, and on safety.**
- **Self-inflammability:** *Product is not selfigniting.*

(Contd. on page 7)



BE SURE. BUILD SURE.

Page 7/12

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 13.05.2023

Version number 26 (replaces version 25)

Revision: 13.05.2023

Trade name **MC-DUR 1320 VK - Komponente B**

(Contd. of page 6)

· **Explosive properties:** *Product is not explosive.*

· **Information with regard to physical hazard classes**

· **Explosives** *Void*

· **Flammable gases** *Void*

· **Aerosols** *Void*

· **Oxidising gases** *Void*

· **Gases under pressure** *Void*

· **Flammable liquids** *Void*

· **Flammable solids** *Void*

· **Self-reactive substances and mixtures**

*Void*

· **Pyrophoric liquids** *Void*

· **Pyrophoric solids** *Void*

· **Self-heating substances and mixtures**

*Void*

· **Substances and mixtures, which emit flammable gases in contact with water**

*Void*

· **Oxidising liquids** *Void*

· **Oxidising solids** *Void*

· **Organic peroxides** *Void*

· **Corrosive to metals** *Void*

· **Desensitised explosives** *Void*

### SECTION 10: Stability and reactivity

· **10.1 Reactivity** *No further relevant information available.*

· **10.2 Chemical stability**

· **Thermal decomposition /**

**conditions to be avoided:** *No decomposition if used according to specifications.*

· **10.3 Possibility of hazardous**

**reactions**

*No dangerous reactions known*

· **10.4 Conditions to avoid**

*No further relevant information available.*

· **10.5 Incompatible materials:**

*No further relevant information available.*

· **10.6 Hazardous**

**decomposition products:**

*No dangerous decomposition products known*

### SECTION 11: Toxicological information

· **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**

· **Acute toxicity**

*Based on available data, the classification criteria are not met.*

(Contd. on page 8)

GB



BE SURE. BUILD SURE.

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 13.05.2023

Version number 26 (replaces version 25)

Revision: 13.05.2023

**Trade name MC-DUR 1320 VK - Komponente B**

(Contd. of page 7)

**· LD/LC50 values that are relevant for classification:**

**100-51-6 Benzyl alcohol**

Oral	LD50	1230 mg/kg (rat)
	NOAEL 2nd year study	200 mg/kg (mouse)
Dermal	LD50	200 mg/kg (rat)
	LD50	2000 mg/kg (rabbit)
Inhalative	LC50/4 h	>4178 mg/l (rat)

**9046-10-0 Polyoxypropylenediamine**

Oral	LD50	2855 mg/kg (Rat)
Dermal	LD50	2980 mg/kg (Kan)

**2855-13-2 Isophorone diamine**

Oral	LD50	1030 mg/kg (ATE)
	LD50	1030 mg/kg (rat)
Dermal	NOAEL	250 mg/kg (rat)
	LD50	1840 mg/kg (rabbit)
		>2000 mg/kg (rat)

**15520-10-2 2-methylpentane-1,5-diamine**

Oral	LD50	1170 mg/kg (rat)
Dermal	LD50	1870 mg/kg (rabbit)
Inhalative	LC50/4 h	19.6 mg/l (rat)

**90-72-2 2,4,6-tris(dimethylaminomethyl)phenol**

Oral	LD50	2169 mg/kg (rat)
	NOAEL	15 mg/kg (rat)

- **Skin corrosion/irritation** Causes severe skin burns and eye damage.
- **Serious eye damage/irritation** Causes serious eye damage.
- **Respiratory or skin sensitisation** May cause an allergic skin reaction.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.
- **11.2 Information on other hazards**

**· Endocrine disrupting properties**

None of the ingredients is listed.

GB

(Contd. on page 9)





BE SURE. BUILD SURE.

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 13.05.2023

Version number 26 (replaces version 25)

Revision: 13.05.2023

**Trade name MC-DUR 1320 VK - Komponente B**

(Contd. of page 8)

**SECTION 12: Ecological information**

**12.1 Toxicity**

**Aquatic toxicity:**

**100-51-6 Benzyl alcohol**

IC50/72h	700 mg/l (algae)
LC50/96h	460 mg/l ( <i>Pimephales promelas</i> ) 10 mg/l ( <i>Lepomis macrochirus</i> )

**2855-13-2 Isophorone diamine**

LC50/96h	110 mg/l ( <i>Leucidus idus</i> )
EC50	1120 mg/l ( <i>Pseudomonas putida</i> )
EC50/48h	23 mg/l ( <i>Daphnia magna</i> )
NOEC	1.5 mg/l ( <i>Desmodesmus subspicatus</i> ) 3 mg/l ( <i>Daphnia magna</i> )
ErC50/72h	>50 mg/l ( <i>Desmodesmus subspicatus</i> )

**15520-10-2 2-methylpentane-1,5-diamine**

EC50/72h	>100 mg/l (algae)
EC50	1825 mg/l (fish)
EC50/48h	19.8 mg/l ( <i>Daphnia magna</i> )

**90-72-2 2,4,6-tris(dimethylaminomethyl)phenol**

EC50/72h	84 mg/l ( <i>Desmodesmus subspicatus</i> )
LC50/96h	175 mg/l (Cyp)
NOEC	2 mg/l (BEL) 6.25 mg/l ( <i>Desmodesmus subspicatus</i> )

**12.2 Persistence and degradability**

No further relevant information available.

**12.3 Bioaccumulative potential**

No further relevant information available.

**12.4 Mobility in soil**

No further relevant information available.

**12.5 Results of PBT and vPvB assessment**

**PBT:**

Not applicable.

**vPvB:**

Not applicable.

**12.6 Endocrine disrupting properties**

The product does not contain substances with endocrine disrupting properties.

**12.7 Other adverse effects**

**Additional ecological information:**

**General notes:**

Do not allow product to reach ground water, water bodies or sewage system.  
Danger to drinking water if even small quantities leak into soil.

GB

(Contd. on page 10)



BE SURE. BUILD SURE.

### Safety data sheet according to 1907/2006/EC, Article 31

Printing date 13.05.2023

Version number 26 (replaces version 25)

Revision: 13.05.2023

Trade name MC-DUR 1320 VK - Komponente B

(Contd. of page 9)

#### SECTION 13: Disposal considerations

**13.1 Waste treatment methods**

**Recommendation** Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

**Uncleaned packagings:**

**Recommendation:** Empty contaminated packagings thoroughly. They can be recycled after thorough and proper cleaning.

#### SECTION 14: Transport information

**14.1 UN number or ID number**

**ADR, IMDG, IATA** UN2735

**14.2 UN proper shipping name**

**ADR, IMDG, IATA** AMINES, LIQUID, CORROSIVE, N.O.S. (Isophorone diamine, 2-methylpentane-1,5-diamine)

**14.3 Transport hazard class(es)**

**ADR**

**Class** 8 (C7) Corrosive substances.

**Label** 8

**IMDG, IATA**

**Class** 8 Corrosive substances.

**Label** 8

**14.4 Packing group**

**ADR, IMDG, IATA** II

**14.5 Environmental hazards:**

**Marine pollutant:** No

**14.6 Special precautions for user**

**Warning:** Corrosive substances.

**Kemler Number:** 80

**EMS Number:** F-A, S-B

**Segregation groups** (SGG18) Alkalis

**Stowage Category** A

**Segregation Code** SG35 Stow "separated from" SGG1-acids

**14.7 Maritime transport in bulk according to IMO instruments**

Not applicable.

**Transport/Additional information:**

**ADR**

**Limited quantities (LQ)** 1L

(Contd. on page 11)



BE SURE. BUILD SURE.

Page 11/12

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 13.05.2023

Version number 26 (replaces version 25)

Revision: 13.05.2023

**Trade name MC-DUR 1320 VK - Komponente B**

(Contd. of page 10)

· <b>Excepted quantities (EQ)</b>	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· <b>Transport category</b>	2
· <b>Tunnel restriction code</b>	E
<hr/>	
· <b>IMDG</b>	
· <b>Limited quantities (LQ)</b>	1L
· <b>Excepted quantities (EQ)</b>	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· <b>UN "Model Regulation":</b>	UN 2735 AMINES, LIQUID, CORROSIVE, N.O.S. (ISOPHORONE DIAMINE, 2-METHYLPENTANE-1,5-DIAMINE), 8, II

### SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/ legislation specific for the substance or mixture**  
No further relevant information available.
- **15.2 Chemical safety assessment:**  
A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**  
H302 Harmful if swallowed.  
H312 Harmful in contact with skin.  
H314 Causes severe skin burns and eye damage.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H318 Causes serious eye damage.  
H319 Causes serious eye irritation.  
H332 Harmful if inhaled.  
H335 May cause respiratory irritation.  
H412 Harmful to aquatic life with long lasting effects.
- **Department issuing data specification sheet:**  
Environment protection department.
- **Abbreviations and acronyms:**  
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)  
ICAO: International Civil Aviation Organisation  
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

(Contd. on page 12)

GB



BE SURE. BUILD SURE.

Page 12/12

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 13.05.2023

Version number 26 (replaces version 25)

Revision: 13.05.2023

**Trade name MC-DUR 1320 VK - Komponente B**

(Contd. of page 11)

*IMDG: International Maritime Code for Dangerous Goods*

*IATA: International Air Transport Association*

*GHS: Globally Harmonised System of Classification and Labelling of Chemicals*

*EINECS: European Inventory of Existing Commercial Chemical Substances*

*ELINCS: European List of Notified Chemical Substances*

*CAS: Chemical Abstracts Service (division of the American Chemical Society)*

*DNEL: Derived No-Effect Level (UK REACH)*

*PNEC: Predicted No-Effect Concentration (UK REACH)*

*LC50: Lethal concentration, 50 percent*

*LD50: Lethal dose, 50 percent*

*PBT: Persistent, Bioaccumulative and Toxic*

*vPvB: very Persistent and very Bioaccumulative*

*Acute Tox. 4: Acute toxicity – Category 4*

*Skin Corr. 1A: Skin corrosion/irritation – Category 1A*

*Skin Corr. 1B: Skin corrosion/irritation – Category 1B*

*Skin Corr. 1C: Skin corrosion/irritation – Category 1C*

*Skin Irrit. 2: Skin corrosion/irritation – Category 2*

*Eye Dam. 1: Serious eye damage/eye irritation – Category 1*

*Eye Irrit. 2: Serious eye damage/eye irritation – Category 2*

*Skin Sens. 1: Skin sensitisation – Category 1*

*Skin Sens. 1B: Skin sensitisation – Category 1B*

*STOT SE 3: Specific target organ toxicity (single exposure) – Category 3*

*Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3*

**\* Data compared to the  
previous version altered.**

GB