



BE SURE. BUILD SURE.

Page 1/12

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 29.04.2023

Version number 24 (replaces version 23)

Revision: 29.04.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name **MC-DUR 1390 VK - Komponente B**

Article number: 2673

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture

Epoxy impregnation
Hardening agent/ Curing agent

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: MC-Bauchemie Müller GmbH & Co. KG
Am Kruppwald 1-8
D-46238 Bottrop
Tel.: +49(0)2041-101-0
Fax.: +49(0)2041-101-400
E-Mail: info@mc-bauchemie.de

MC-Bauchemie AG
Hagackerstr. 10
CH-8953 Dietikon
Tel.: +44-7400510
Fax : +44-7400533

Informing department: msds@mc-bauchemie.de

1.4 Emergency telephone number:

Tel.: +49 / (0)700 24112112 (MCR)
Tel.: +48612864565

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Skin Corr. 1A H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.

Skin Sens. 1 H317 May cause an allergic skin reaction.

2.2 Label elements

Labelling according to

Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms



GHS05 GHS07

Signal word

Danger

(Contd. on page 2)

GB



BE SURE. BUILD SURE.

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 29.04.2023

Version number 24 (replaces version 23)

Revision: 29.04.2023

Trade name MC-DUR 1390 VK - Komponente B

(Contd. of page 1)

- **Hazard-determining components of labelling:** polymer amine terminated
2-methylpentane-1,5-diamine
salicylic acid
3,6,9-triazaundecamethylenediamine
Tetraethylenepentamine
- **Hazard statements** H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.
- **Precautionary statements** P260 Do not breathe dusts or mists.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a POISON CENTER/doctor.
P321 Specific treatment (see on this label).
P362+P364 Take off contaminated clothing and wash it before reuse.
- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- **3.2 Mixtures**
- **Description:** Binding agent with colouring agents.
Mixture consisting of the following components.

Dangerous components:

	polymer amine terminated Eye Dam. 1, H318; Skin Irrit. 2, H315; Skin Sens. 1B, H317	30-60%
CAS: 100-51-6	Benzyl alcohol Acute Tox. 4, H302; Acute Tox. 4, H332; Eye Irrit. 2, H319	10-30%
CAS: 100-51-6 EINECS: 202-859-9 Reg.nr.: 01-2119492630-38	Benzyl alcohol Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332	10-30%
CAS: 15520-10-2 EINECS: 239-556-6	2-methylpentane-1,5-diamine Skin Corr. 1A, H314; Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; STOT SE 3, H335	≥10-<20%

(Contd. on page 3)



BE SURE. BUILD SURE.

Page 3/12

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 29.04.2023

Version number 24 (replaces version 23)

Revision: 29.04.2023

Trade name MC-DUR 1390 VK - Komponente B

		(Contd. of page 2)
CAS: 69-72-7 EINECS: 200-712-3	salicylic acid Repr. 2, H361d; Eye Dam. 1, H318; Acute Tox. 4, H302	≥1-<1.5%
CAS: 112-57-2 EINECS: 203-986-2	3,6,9-triazaundecamethylenediamine Skin Corr. 1B, H314; Aquatic Chronic 2, H411; Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1B, H317	≥0.25-<1%
CAS: 90640-66-7 EINECS: 292-587-7 Reg.nr.: 01-2119487290-37	Tetraethylenepentamine Skin Corr. 1B, H314; Aquatic Chronic 2, H411; Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1, H317	≥0.25-<0.5%

· **Additional information**

For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· **General information**

Seek medical treatment.

Instantly remove any clothing soiled by the product.

· **After inhalation**

Supply fresh air; consult doctor in case of symptoms.

· **After skin contact**

Instantly wash with water and soap and rinse thoroughly.

· **After eye contact**

Rinse opened eye for several minutes under running water.

Seek medical treatment.

· **After swallowing**

Drink copious amounts of water and provide fresh air. Instantly call for doctor.

· 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

· **Suitable extinguishing agents** Use fire fighting measures that suit the environment.

· 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

· 5.3 Advice for firefighters

· **Protective equipment:**

Put on breathing apparatus.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

(Contd. on page 4)

GB



BE SURE. BUILD SURE.

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 29.04.2023

Version number 24 (replaces version 23)

Revision: 29.04.2023

Trade name MC-DUR 1390 VK - Komponente B

(Contd. of page 3)

- **6.2 Environmental precautions:** Prevent material from reaching sewage system, holes and cellars.
- **6.3 Methods and material for containment and cleaning up:** Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose of contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling
See Section 8 for information on personal protection equipment.
See Section 13 for information on disposal.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Store in cool, dry place in tightly closed containers.
Open and handle container with care.
- **Information about protection against explosions and fires:** Protect from heat.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage**
- **Requirements to be met by storerooms and containers:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep container tightly sealed.
- **Storage class** 8A
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **8.1 Control parameters**
- **Components with critical values that require monitoring at the workplace:** The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

· **DNELs**

100-51-6 Benzyl alcohol

Oral	DNEL	4 mg/kg bw/Tag (ArL) 20 mg/kg bw/Tag (Ark)
Dermal	DNEL	8 mg/kg bw/day (ArL) 40 mg/kg bw/day (Ark)
Inhalative	DNEL	22 mg/m ³ (ArL)

(Contd. on page 5)



BE SURE. BUILD SURE.

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 29.04.2023

Version number 24 (replaces version 23)

Revision: 29.04.2023

Trade name MC-DUR 1390 VK - Komponente B

(Contd. of page 4)

		110 mg/m ³ (Ark)
100-51-6 Benzyl alcohol		
Oral	DNEL	4 mg/kg bw/Tag (ArL) 20 mg/kg bw/Tag (Ark)
Dermal	DNEL	8 mg/kg bw/day (ArL) 40 mg/kg bw/day (Ark)
Inhalative	DNEL	22 mg/m ³ (ArL) 110 mg/m ³ (Ark)
15520-10-2 2-methylpentane-1,5-diamine		
Dermal	DNEL	1.5 mg/kg bw/day (ArL)
Inhalative	DNEL	0.25 mg/m ³ (ArL) 0.5 mg/m ³ (Ark)
112-57-2 3,6,9-triazaundecamethylenediamine		
Oral	DNEL	0.53 mg/kg bw/Tag (ArL)
Dermal	DNEL	0.74 mg/kg bw/day (ArL)
Inhalative	DNEL	6940 mg/m ³ (ArL)

· PNECs

100-51-6 Benzyl alcohol		
PNEC	0.527 mg/l (Marine water sediment)	
	0.1 mg/l (Mew)	
	1 mg/l (Fresh water sediment)	
PNEC	0.456 mg/kg dwt (Bod)	
	5.27 mg/kg dwt (Fresh water sediment)	
100-51-6 Benzyl alcohol		
PNEC	0.527 mg/l (Marine water sediment)	
	0.1 mg/l (Mew)	
	1 mg/l (Fresh water sediment)	
PNEC	0.456 mg/kg dwt (Bod)	
	5.27 mg/kg dwt (Fresh water sediment)	
15520-10-2 2-methylpentane-1,5-diamine		
PNEC	0.042 mg/l (Mew)	
	0.42 mg/l (Suw)	
112-57-2 3,6,9-triazaundecamethylenediamine		
PNEC	9.73 mg/l (BEL)	
	0.0068 mg/l (Fresh water)	
	0.0068 mg/l (Mew)	
PNEC	0.343 mg/kg dwt (Sediment)	
	3.43 mg/kg dwt (Fresh water sediment)	

· Additional information: The lists that were valid during the compilation were used as basis.
(Contd. on page 6)



BE SURE. BUILD SURE.

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 29.04.2023

Version number 24 (replaces version 23)

Revision: 29.04.2023

Trade name MC-DUR 1390 VK - Komponente B

(Contd. of page 5)

- **8.2 Exposure controls**
- **Appropriate engineering controls** *No further data; see section 7.*
- **Individual protection measures, such as personal protective equipment**
- **General protective and hygienic measures** *Keep away from foodstuffs, beverages and food.
Instantly remove any soiled and impregnated garments.
Wash hands during breaks and at the end of the work.
Avoid contact with the eyes and skin.*
- **Hand protection** *Protective gloves.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
After use of gloves apply skin-cleaning agents and skin cosmetics.*
- **Material of gloves** *The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.*
- **Penetration time of glove material** *The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.*
- **Eye/face protection** *Safety glasses
Tightly sealed safety glasses.*
- **Body protection:** *Boots
Protective work clothing.*

SECTION 9: Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**
- **General Information**
- **Colour:** *Yellowish*
- **Smell:** *Amine-like*
- **Melting point/freezing point:** *Not determined*
- **Boiling point or initial boiling point and boiling range** *205 °C*
- **Lower and upper explosion limit**
- **Lower:** *1.3 Vol %*
- **Upper:** *13 Vol %*
- **Flash point:** *≥61 °C*
- **Auto-ignition temperature:** *435 °C*
- **pH at 20 °C** *12*
- **Viscosity:**
- **Kinematic viscosity** *Not determined.*
- **dynamic at 20 °C:** *480 mPas*

(Contd. on page 7)



BE SURE. BUILD SURE.

Page 7/12

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 29.04.2023

Version number 24 (replaces version 23)

Revision: 29.04.2023

Trade name MC-DUR 1390 VK - Komponente B

(Contd. of page 6)

- **Solubility**
- **Water:** Not miscible or difficult to mix
- **Steam pressure at 20 °C:** 0.1 hPa
- **Density and/or relative density**
- **Density at 20 °C** 1.04 g/cm³

· 9.2 Other information

- **Appearance:**
- **Form:** Fluid
- **Important information on protection of health and environment, and on safety.**
- **Self-inflammability:** Product is not selfigniting.
- **Explosive properties:** Product is not explosive.

· Information with regard to physical hazard classes

- **Explosives** Void
- **Flammable gases** Void
- **Aerosols** Void
- **Oxidising gases** Void
- **Gases under pressure** Void
- **Flammable liquids** Void
- **Flammable solids** Void
- **Self-reactive substances and mixtures** Void
- **Pyrophoric liquids** Void
- **Pyrophoric solids** Void
- **Self-heating substances and mixtures** Void
- **Substances and mixtures, which emit flammable gases in contact with water** Void
- **Oxidising liquids** Void
- **Oxidising solids** Void
- **Organic peroxides** Void
- **Corrosive to metals** Void
- **Desensitised explosives** Void

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.

(Contd. on page 8)

GB



BE SURE. BUILD SURE.

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 29.04.2023

Version number 24 (replaces version 23)

Revision: 29.04.2023

Trade name MC-DUR 1390 VK - Komponente B

(Contd. of page 7)

- **10.6 Hazardous decomposition products:** No dangerous decomposition products known

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

- **LD/LC50 values that are relevant for classification:**

100-51-6 Benzyl alcohol

Oral	LD50	1230 mg/kg (rat)
	NOAEL 2nd year study	200 mg/kg (mouse) 200 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rabbit)
Inhalative	LC50/4 h	>4178 mg/l (rat)

100-51-6 Benzyl alcohol

Oral	LD50	1230 mg/kg (rat)
	NOAEL 2nd year study	200 mg/kg (mouse) 200 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rabbit)
Inhalative	LC50/4 h	>4178 mg/l (rat)

15520-10-2 2-methylpentane-1,5-diamine

Oral	LD50	1170 mg/kg (rat)
Dermal	LD50	1870 mg/kg (rabbit)
Inhalative	LC50/4 h	19.6 mg/l (rat)

69-72-7 salicylic acid

Oral	LD50	891 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rat)

112-57-2 3,6,9-triazaundecamethylenediamine

Oral	LD50	2140 mg/kg (rat)
Dermal	LD50	1260 mg/kg (rabbit)

- **Skin corrosion/irritation** Causes severe skin burns and eye damage.
- **Serious eye damage/irritation** Causes serious eye damage.
- **Respiratory or skin sensitisation** May cause an allergic skin reaction.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

(Contd. on page 9)



BE SURE. BUILD SURE.

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 29.04.2023

Version number 24 (replaces version 23)

Revision: 29.04.2023

Trade name MC-DUR 1390 VK - Komponente B

(Contd. of page 8)

· **11.2 Information on other hazards**

· **Endocrine disrupting properties**

69-72-7 salicylic acid

List II; III

SECTION 12: Ecological information

· **12.1 Toxicity**

· **Aquatic toxicity:**

100-51-6 Benzyl alcohol

IC50/72h 700 mg/l (algae)

LC50/96h 460 mg/l (*Pimephales promelas*)

10 mg/l (*Lepomis macrochirus*)

100-51-6 Benzyl alcohol

IC50/72h 700 mg/l (algae)

LC50/96h 460 mg/l (*Pimephales promelas*)

10 mg/l (*Lepomis macrochirus*)

15520-10-2 2-methylpentane-1,5-diamine

EC50/72h >100 mg/l (algae)

EC50 1825 mg/l (fish)

EC50/48h 19.8 mg/l (*Daphnia magna*)

112-57-2 3,6,9-triazaundecamethylenediamine

EC50/72h 2.1 mg/l (algae)

LC50/96h 420 mg/l (*Gup*)

EC50/48h 24.1 mg/l (*Daphnia magna*)

· **12.2 Persistence and degradability**

No further relevant information available.

· **12.3 Bioaccumulative potential**

No further relevant information available.

· **12.4 Mobility in soil**

No further relevant information available.

· **12.5 Results of PBT and vPvB assessment**

· **PBT:**

Not applicable.

· **vPvB:**

Not applicable.

· **12.6 Endocrine disrupting properties**

For information on endocrine disrupting properties see section 11.

· **12.7 Other adverse effects**

· **Additional ecological information:**

· **General notes:**

Do not allow product to reach ground water, water bodies or sewage system.

Danger to drinking water if even small quantities leak into soil.

GB

(Contd. on page 10)



BE SURE. BUILD SURE.

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 29.04.2023

Version number 24 (replaces version 23)

Revision: 29.04.2023

Trade name MC-DUR 1390 VK - Komponente B

(Contd. of page 9)

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Uncleaned packagings:

Recommendation: Empty contaminated packagings thoroughly. They can be recycled after thorough and proper cleaning.

SECTION 14: Transport information

14.1 UN number or ID number

ADR, IMDG, IATA UN2735

14.2 UN proper shipping name

ADR, IMDG, IATA AMINES, LIQUID, CORROSIVE, N.O.S. (2-methylpentane-1,5-diamine)

14.3 Transport hazard class(es)

ADR

Class 8 (C7) Corrosive substances.

Label 8

IMDG, IATA

Class 8 Corrosive substances.

Label 8

14.4 Packing group

ADR, IMDG, IATA II

14.5 Environmental hazards:

Marine pollutant: No

14.6 Special precautions for user

Warning: Corrosive substances.

Kemler Number: 80

EMS Number: F-A, S-B

Segregation groups (SGG18) Alkalis

Stowage Category A

Segregation Code SG35 Stow "separated from" SGG1-acids

14.7 Maritime transport in bulk according to IMO instruments

Not applicable.

Transport/Additional information:

ADR

Limited quantities (LQ) 1L

Excepted quantities (EQ) Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

(Contd. on page 11)



BE SURE. BUILD SURE.

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 29.04.2023

Version number 24 (replaces version 23)

Revision: 29.04.2023

Trade name MC-DUR 1390 VK - Komponente B

(Contd. of page 10)

· Transport category	2
· Tunnel restriction code	E
<hr/>	
· IMDG	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 2735 AMINES, LIQUID, CORROSIVE, N.O.S. (2-METHYLPENTANE-1,5-DIAMINE), 8, II

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture** No further relevant information available.
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**
 - H302 Harmful if swallowed.
 - H312 Harmful in contact with skin.
 - H314 Causes severe skin burns and eye damage.
 - H315 Causes skin irritation.
 - H317 May cause an allergic skin reaction.
 - H318 Causes serious eye damage.
 - H319 Causes serious eye irritation.
 - H332 Harmful if inhaled.
 - H335 May cause respiratory irritation.
 - H361d Suspected of damaging the unborn child.
 - H411 Toxic to aquatic life with long lasting effects.
- **Department issuing data specification sheet:** Environment protection department.
- **Abbreviations and acronyms:**
 - RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
 - ICAO: International Civil Aviation Organisation
 - ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
 - IMDG: International Maritime Code for Dangerous Goods
 - IATA: International Air Transport Association
 - GHS: Globally Harmonised System of Classification and Labelling of Chemicals
 - EINECS: European Inventory of Existing Commercial Chemical Substances

(Contd. on page 12)



BE SURE. BUILD SURE.

Page 12/12

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 29.04.2023

Version number 24 (replaces version 23)

Revision: 29.04.2023

Trade name MC-DUR 1390 VK - Komponente B

(Contd. of page 11)

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (UK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Acute Tox. 4: Acute toxicity – Category 4

Skin Corr. 1A: Skin corrosion/irritation – Category 1A

Skin Corr. 1B: Skin corrosion/irritation – Category 1B

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Skin Sens. 1B: Skin sensitisation – Category 1B

Repr. 2: Reproductive toxicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

*** Data compared to the
previous version altered.**

GB