



BE SURE. BUILD SURE.

Page 1/15

Safety data sheet according to UK REACH

Printing date 03.05.2025

Version number 5 (replaces version 4)

Revision: 03.05.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name **MC-DUR 1680 - Komponente A**

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Epoxy resin

MC-Bauchemie Müller GmbH & Co. KG
Am Kruppwald 1-8
D-46238 Bottrop
Tel.: +49(0)2041-101-0
Fax.: +49(0)2041-101-400
E-Mail: info@mc-bauchemie.de

MC-Bauchemie AG
Hagackerstr. 10
CH-8953 Dietikon
Tel.: +44-7400510
Fax : +44-7400533

Informing department:

msds@mc-bauchemie.de

1.4 Emergency telephone number:

Tel.: +49 / (0)700 24112112 (MCR)

Tel.: +1 872 5888271 (MCR)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT RE 1 H372 Causes damage to the lung through prolonged or repeated exposure.
Route of exposure: Inhalation.

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to

Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms



GHS05

GHS07

GHS08

GHS09

(Contd. on page 2)

GB



BE SURE. BUILD SURE.

Safety data sheet according to UK REACH

Printing date 03.05.2025

Version number 5 (replaces version 4)

Revision: 03.05.2025

Trade name MC-DUR 1680 - Komponente A

(Contd. of page 1)

- **Signal word** Danger
- **Hazard-determining components of labelling:** *Hydrocarbons, C9-unsaturated, polymerised
Fatty acids, tall-oil, reaction products with bisphenol A, alkyl glycidyl tolyl ether and triethylenetetramine
Quartz sand
Polyoxypropylenediamine
Phenol, mono- and distyrolised
Hydrocarbons, C9-ungesättigt, polymd.
Polymer with amino-functional groups
m-phenylenebis(methylamine)
Triethylenetetramine
Fatty acids, C18-unsatd., trimers, compds. with oleylamine*
- **Hazard statements** *H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.
H372 Causes damage to the lung through prolonged or repeated exposure. Route of exposure: Inhalation.
H411 Toxic to aquatic life with long lasting effects.*
- **Precautionary statements** *P260 Do not breathe dusts or mists.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a POISON CENTER/doctor.
P321 Specific treatment (see on this label).
P362+P364 Take off contaminated clothing and wash it before reuse.*
- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** *Not applicable.*
- **vPvB:** *Not applicable.*

SECTION 3: Composition/information on ingredients

- **3.2 Mixtures**
- **Description:** *Mixture consisting of the following components.*

· **Dangerous components:**

CAS: 14808-60-7 EINECS: 238-878-4	Quartz sand STOT RE 1, H372	10-30%
CAS: 71302-83-5 EC number: 701-299-7	Hydrocarbons, C9-unsaturated, polymerised Asp. Tox. 1, H304; Skin Sens. 1A, H317; Aquatic Chronic 3, H412	≥2.5-<10%

(Contd. on page 3)



BE SURE. BUILD SURE.

Page 3/15

Safety data sheet according to UK REACH

Printing date 03.05.2025

Version number 5 (replaces version 4)

Revision: 03.05.2025

Trade name **MC-DUR 1680 - Komponente A**

(Contd. of page 2)

CAS: 64742-16-1 EINECS: 265-116-8	Kohlenwasserstoffharz Aquatic Chronic 4, H413	<10%
EC number: 905-588-0 Reg.nr.: 01-2119488216-32 01-2119486136-34	Reaction mass of ethylbenzene and xylene Flam. Liq. 3, H226; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	<5%
CAS: 186321-96-0	Fatty acids, tall-oil, reaction products with bisphenol A, alkyl glycidyl tolyl ether and triethylenetetramine Eye Dam. 1, H318; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Irrit. 2, H315; Skin Sens. 1, H317	≥2.5-<3%
CAS: 9046-10-0 Reg.nr.: 01-2119557899-12	Polyoxypropylenediamine Skin Corr. 1B, H314; Aquatic Chronic 3, H412	≥1-<2.5%
EC number: 701-443-9	Phenol, mono- and distyrolised Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Skin Sens. 1A, H317	≥1-<2.5%
EC number: 949-140-2	Polymer with amino-functional groups Eye Dam. 1, H318; Skin Irrit. 2, H315; Skin Sens. 1B, H317	≥1-<2.5%
CAS: 71302-83-5	Hydrocarbons, C9-ungesättigt, polymd. Skin Sens. 1A, H317; Aquatic Chronic 3, H412	≥1-<1.5%
CAS: 100-51-6 EINECS: 202-859-9	Benzyl alcohol Acute Tox. 4, H302; Acute Tox. 4, H332; Eye Irrit. 2, H319	<1.5%
CAS: 93281-16-4 EINECS: 297-029-6	Phenol, reaction products with divinylbenzene Aquatic Chronic 3, H412	<1.5%
CAS: 1477-55-0 EINECS: 216-032-5 Reg.nr.: 01-2119480150-50	m-phenylenebis(methylamine) Skin Corr. 1B, H314; Acute Tox. 4, H302; Acute Tox. 4, H332; Skin Sens. 1, H317; Aquatic Chronic 3, H412	≥0.1-<1%
CAS: 90640-67-8 EINECS: 292-588-2	Triethylenetetramine Skin Corr. 1B, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1, H317; Aquatic Chronic 3, H412	≥0.1-<0.5%
CAS: 147900-93-4 EC number: 604-612-4	Fatty acids, C18-unsatd., trimers, compds. with oleylamine STOT RE 2, H373; Aquatic Chronic 2, H411; Skin Sens. 1, H317	≥0.1-<0.25%

· **Additional information**

For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· **4.1 Description of first aid measures**· **General information**

Remove contaminated clothing immediately. Consult a doctor if symptoms occur. Move affected person to fresh air.

· **After inhalation**

Supply fresh air; seek medical advice if symptoms occur.

If unconscious, place in recovery position and seek medical advice.

(Contd. on page 4)

GB



BE SURE. BUILD SURE.

Page 4/15

Safety data sheet according to UK REACH

Printing date 03.05.2025

Version number 5 (replaces version 4)

Revision: 03.05.2025

Trade name MC-DUR 1680 - Komponente A

(Contd. of page 3)

- **After skin contact** *In case of contact with skin, wash carefully with plenty of soap and water. Consult a doctor in case of skin reactions.*
- **After eye contact** *Rinse opened eye for several minutes under running water.
Call a doctor immediately*
- **After swallowing** *Rinse mouth with water. Never give anything by mouth to an unconscious person. DO NOT induce vomiting. If symptoms persist, consult a doctor.*
- **4.2 Most important symptoms and effects, both acute and delayed** *Advice for the doctor: Elementary aid, decontamination, symptomatic treatment.*

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents** *Use fire fighting measures that suit the environment.*
- **5.2 Special hazards arising from the substance or mixture** *No further relevant information available.*
- **5.3 Advice for firefighters**
- **Protective equipment:** *No special measures required.*

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures** *Not required.*
- **6.2 Environmental precautions:** *Prevent material from reaching sewage system, holes and cellars.*
- **6.3 Methods and material for containment and cleaning up:** *Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).*
- **6.4 Reference to other sections** *See Section 7 for information on safe handling
See Section 8 for information on personal protection equipment.
See Section 13 for information on disposal.*

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** *Open and handle containers with care.
Ventilation measures are required in rooms without sufficient air exchange (e.g. closed rooms), because the occupational exposure limit values (see chapter 8) could be exceeded. This must be avoided.
Wear suitable personal protective equipment (see section 8). Avoid contact with eyes, skin and clothing. Change contaminated or*

(Contd. on page 5)



BE SURE. BUILD SURE.

Safety data sheet according to UK REACH

Printing date 03.05.2025

Version number 5 (replaces version 4)

Revision: 03.05.2025

Trade name MC-DUR 1680 - Komponente A

(Contd. of page 4)

damaged gloves and contaminated clothing immediately and wash skin immediately. Mix slowly, partially covering the mixing container. Pour carefully and slowly when repotting. Observe the BGBau technical data sheet and practical guide for handling epoxy resins.

- **Information about protection against explosions and fires:** *Ensure sufficient air exchange and/or extraction in the working areas. Take precautionary measures to avoid electrostatic discharges.*
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage**
- **Requirements to be met by storerooms and containers:** *No special requirements.*
- **Further information about storage conditions:** *None.*
- **Storage class** *6.1C*

SECTION 8: Exposure controls/personal protection

- **8.1 Control parameters**
- **Components with critical values that require monitoring at the workplace:** *The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.*

· **DNELs**

Reaction mass of ethylbenzene and xylene

Oral	DNEL	1.6 mg/kg bw/Tag (ArL) mg/kg bw/Tag (Workers)
Dermal	DNEL	180 mg/kg bw/day (ArL)
Inhalative	DNEL	211 mg/m ³ (ArL)

CAS: 9046-10-0 Polyoxypropylenediamine

Oral	DNEL	0.04 mg/kg bw/Tag (ArL)
Dermal	DNEL	2.5 mg/kg bw/day (ArL)

CAS: 100-51-6 Benzyl alcohol

Oral	DNEL	4 mg/kg bw/Tag (ArL) 20 mg/kg bw/Tag (Ark)
Dermal	DNEL	8 mg/kg bw/day (ArL) 40 mg/kg bw/day (Ark)
Inhalative	DNEL	22 mg/m ³ (ArL) 110 mg/m ³ (Ark)

CAS: 1477-55-0 m-phenylenebis(methylamine)

Dermal	DNEL	0.33 mg/kg bw/day (Workers)
--------	------	-----------------------------

(Contd. on page 6)



BE SURE. BUILD SURE.

Safety data sheet according to UK REACH

Printing date 03.05.2025

Version number 5 (replaces version 4)

Revision: 03.05.2025

Trade name MC-DUR 1680 - Komponente A

(Contd. of page 5)

Inhalative DNEL 1.2 mg/m³ (Workers)

· PNECs

CAS: 9046-10-0 Polyoxypropylenediamine

PNEC	7.5 mg/l (Sewage Treatment Plant)
	0.015 mg/l (Fresh water)
PNEC	0.0176 mg/kg dwt (Bod)
	0.125 mg/kg dwt (Sediment)
	0.132 mg/kg dwt (Fresh water sediment)

CAS: 100-51-6 Benzyl alcohol

PNEC	0.527 mg/l (Marine water sediment)
	0.1 mg/l (Mew)
	1 mg/l (Fresh water sediment)
PNEC	0.456 mg/kg dwt (Bod)
	5.27 mg/kg dwt (Fresh water sediment)

CAS: 1477-55-0 m-phenylenebis(methylamine)

PNEC	10 mg/l (Kla)
	0.009 mg/l (Mew)
	0.094 mg/l (Freshwater)
PNEC	0.045 mg/kg dwt (Bod)
	0.43 mg/kg dwt (Marine water sediment)
	0.43 mg/kg dwt (Fresh water sediment)

· CAS No. Designation of material % Type Value Unit

· Additional Occupational Exposure Limit Values for possible hazards during processing:

CAS: 1330-20-7 xylene

WEL	Short-term value: 441 mg/m ³ , 100 ppm
	Long-term value: 220 mg/m ³ , 50 ppm
	Sk; BMGV

CAS: 100-41-4 ethylbenzene

WEL	Short-term value: 552 mg/m ³ , 125 ppm
	Long-term value: 441 mg/m ³ , 100 ppm
	Sk

· Additional information: The lists that were valid during the compilation were used as basis.

· 8.2 Exposure controls

· Appropriate engineering controls

No further data; see section 7.

· Individual protection measures, such as personal protective equipment

· General protective and hygienic measures

Keep away from food, drink and animal feed.
Remove soiled, soaked clothing immediately.
Wash hands before breaks and at the end of work.
Avoid contact with eyes and skin.

· Breathing equipment:

If workplace limit values cannot be complied with by ventilation measures or if rooms cannot be technically ventilated, respiratory

(Contd. on page 7)



BE SURE. BUILD SURE.

Page 7/15

Safety data sheet according to UK REACH

Printing date 03.05.2025

Version number 5 (replaces version 4)

Revision: 03.05.2025

Trade name MC-DUR 1680 - Komponente A

(Contd. of page 6)

protection must be worn: Use combination filter A1-P2 (brown/white) in rooms that cannot be ventilated. If oxygen deficiency is expected, use self-contained breathing apparatus. Observe wearing time limits according to §9 (3) GefStoffV in conjunction with BGR 190.

· **Hand protection**

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

You can find help with choosing gloves on the website <https://www.bgbau.de/fileadmin/Gisbau/Projekte.pdf>

For example, we recommend the Sol-vex 37-900 protective gloves from Ansell GmbH. The breakthrough time of the protective gloves can be found under point 8 "Penetration time of the glove material". The selection of a suitable glove depends not only on the material, but also on other quality features and varies from manufacturer to manufacturer. As the product

is a preparation of several substances, the resistance of glove materials cannot be calculated in advance and must therefore be checked before use.

Nitrile rubber

Recommended material thickness: ≥ 0.4 mm

· **Penetration time of glove material**

The breakthrough times of the Sol-vex 37-900 protective gloves are around 8 hours.

The following applies to all other gloves:

The exact breakthrough time must be obtained from the protective glove manufacturer and adhered to.

Nitrile rubber

Material thickness: ≥ 0.40 mm

Penetration time: ≥ 480 min

Butyl rubber:

Material thickness: ≥ 0.5 mm

Penetration time: ≥ 480 min

· **Eye/face protection**

Tight-fitting safety goggles.

Safety goggles.

· **Body protection:**

Protective clothing

Suitable protective clothing should be worn when working with epoxy resins. In addition to normal work clothing (long trousers, long-sleeved shirt or T-shirt), disposable overalls, aprons, overshoes, sleeve protectors etc. may be necessary depending on the activity. Uncovered areas of skin should be avoided as far as possible, even in hot weather. If the work involves kneeling, the lower leg area should be protected by protective trousers.

GB

(Contd. on page 8)



BE SURE. BUILD SURE.

Safety data sheet according to UK REACH

Printing date 03.05.2025

Version number 5 (replaces version 4)

Revision: 03.05.2025

Trade name MC-DUR 1680 - Komponente A

(Contd. of page 7)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

· Colour:	Black
· Smell:	Amine-like
· Melting point/freezing point:	Not determined
· Boiling point or initial boiling point and boiling range	>2200 °C (CAS: 14808-60-7 Quartz sand)
· Lower and upper explosion limit	
· Lower:	1.3 Vol %
· Upper:	13.0 Vol %
· Flash point:	>61 °C
· Auto-ignition temperature:	435 °C
· pH at 20 °C	12
· Viscosity:	
· Kinematic viscosity	Not determined.
· dynamic at 20 °C:	19500 mPas
· Solubility	
· Water:	Partly miscible
· Steam pressure at 20 °C:	0 hPa (CAS: 7727-43-7 Barium sulphate)
· Density and/or relative density	
· Density at 20 °C	1.73 g/cm ³

9.2 Other information

· Appearance:	
· Form:	Viscous
· Important information on protection of health and environment, and on safety.	
· Self-inflammability:	Product is not selfigniting.
· Explosive properties:	Product is not explosive.

Information with regard to physical hazard classes

· Explosives	Void
· Flammable gases	Void
· Aerosols	Void
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Void
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void

(Contd. on page 9)



BE SURE. BUILD SURE.

**Safety data sheet
according to UK REACH**

Printing date 03.05.2025

Version number 5 (replaces version 4)

Revision: 03.05.2025

Trade name MC-DUR 1680 - Komponente A

(Contd. of page 8)

- | | |
|----------------------------------|------|
| · Organic peroxides | Void |
| · Corrosive to metals | Void |
| · Desensitised explosives | Void |

SECTION 10: Stability and reactivity

- **10.1 Reactivity** *No further relevant information available.*
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** *No decomposition if used according to specifications.*
- **10.3 Possibility of hazardous reactions** *No dangerous reactions known*
- **10.4 Conditions to avoid** *No further relevant information available.*
- **10.5 Incompatible materials:** *No further relevant information available.*
- **10.6 Hazardous decomposition products:** *No dangerous decomposition products known*

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** *Based on available data, the classification criteria are not met.*

· **LD/LC50 values that are relevant for classification:**

Reaction mass of ethylbenzene and xylene

Oral	LD50	3523-4000 mg/kg (rat)
Dermal	LD50	1100 mg/kg (rabbit)
Inhalative	LC50/4 h	11 mg/l (rat)

CAS: 9046-10-0 Polyoxypropylenediamine

Oral	LD50	2855 mg/kg (Rat)
		2885 mg/kg (rat)
Dermal	LD50	2980 mg/kg (Kan)
		2980 mg/kg (rabbit)

CAS: 100-51-6 Benzyl alcohol

Oral	LD50	1230 mg/kg (rat)
	NOAEL 2nd year study	200 mg/kg (mouse)
		200 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rabbit)
Inhalative	LC50/4 h	>4178 mg/l (rat)

CAS: 93281-16-4 Phenol, reaction products with divinylbenzene

Oral	LD50	>5000 mg/kg (rat)
Dermal	LD50	>5000 mg/kg (rat)

(Contd. on page 10)



BE SURE. BUILD SURE.

**Safety data sheet
according to UK REACH**

Printing date 03.05.2025

Version number 5 (replaces version 4)

Revision: 03.05.2025

Trade name MC-DUR 1680 - Komponente A

(Contd. of page 9)

CAS: 1477-55-0 m-phenylenebis(methylamine)

Oral	LD50	1180 mg/kg (mouse) 930 mg/kg (rat)
Dermal	LD50	>3100 mg/kg (rabbit)

CAS: 90640-67-8 Triethylenetetramine

Oral	LD50	1716 mg/kg (rat)
Dermal	LD50	1465 mg/kg (rat)

- **Primary irritant effect:**
- **Skin corrosion/irritation** Causes severe skin burns and eye damage.
- **Serious eye damage/irritation** Causes serious eye damage.
- **Respiratory or skin sensitisation** May cause an allergic skin reaction.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Causes damage to the lung through prolonged or repeated exposure. Route of exposure: Inhalation.
- **Aspiration hazard** Based on available data, the classification criteria are not met.
- **11.2 Information on other hazards**

· **Endocrine disrupting properties**

CAS: 556-67-2 octamethylcyclotetrasiloxane

List II

SECTION 12: Ecological information

· **12.1 Toxicity**

· **Aquatic toxicity:**

Reaction mass of ethylbenzene and xylene

EC50/72h	2.2 mg/l (Selenastrum capricornutum)
LC50/96h	2.6 mg/l (Oncorhynchus mykiss)
NOEC	16 mg/l (BEL)

CAS: 9046-10-0 Polyoxypropylenediamine

EC50/72h	15 mg/l (algae)
LC50/96h	>15 mg/l (fish)
EC50/48h	80 mg/l (daphnia)

CAS: 100-51-6 Benzyl alcohol

IC50/72h	700 mg/l (algae)
LC50/96h	460 mg/l (Pimephales promelas) 10 mg/l (Lepomis macrochirus)

CAS: 1477-55-0 m-phenylenebis(methylamine)

IC50/72h	12 mg/l (algae)
----------	-----------------

(Contd. on page 11)



BE SURE. BUILD SURE.

Safety data sheet according to UK REACH

Printing date 03.05.2025

Version number 5 (replaces version 4)

Revision: 03.05.2025

Trade name MC-DUR 1680 - Komponente A

(Contd. of page 10)

EC50/72h 12 mg/l (*Scenedesmus subspicatus*)

LC50/96h >100 mg/l (*Oncorhynchus mykiss*)

87.6 mg/l (*Ory*)

EC50/48h 15.2 mg/l (*Daphnia magna*)

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties** For information on endocrine disrupting properties see section 11.
- **12.7 Other adverse effects**
- **Additional ecological information:**
- **General notes:** Do not allow product to reach ground water, water bodies or sewage system.
Danger to drinking water if even small quantities leak into soil.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation** Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Empty contaminated packagings thoroughly. They can be recycled after thorough and proper cleaning.

SECTION 14: Transport information

- **14.1 UN number or ID number**
- **ADR, IMDG, IATA** UN3082
- **14.2 UN proper shipping name**
- **ADR, IATA** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Fatty acids, tall-oil, reaction products with bisphenol A, alkyl glycidyl tolyl ether and triethylenetetramine, Solvent naphtha (petroleum), light, aromatic)

(Contd. on page 12)

GB



BE SURE. BUILD SURE.

Safety data sheet according to UK REACH

Printing date 03.05.2025

Version number 5 (replaces version 4)

Revision: 03.05.2025

Trade name MC-DUR 1680 - Komponente A

(Contd. of page 11)

· IMDG	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Fatty acids, tall-oil, reaction products with bisphenol A, alkyl glycidyl tolyl ether and triethylenetetramine, Solvent naphtha (petroleum), light, aromatic), MARINE POLLUTANT
· 14.3 Transport hazard class(es)	
· ADR	
· Class	9 (M6) Miscellaneous dangerous substances and articles.
· Label	9
· IMDG, IATA	
· Class	9 Miscellaneous dangerous substances and articles.
· Label	9
· 14.4 Packing group	
· ADR, IMDG, IATA	III
· 14.5 Environmental hazards:	
· Marine pollutant:	Yes Symbol (fish and tree)
· Special marking (ADR):	Symbol (fish and tree)
· Special marking (IATA):	Symbol (fish and tree)
· 14.6 Special precautions for user	Warning: Miscellaneous dangerous substances and articles.
· Kemler Number:	90
· EMS Number:	F-A, S-F
· Stowage Category	A
· 14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
· Transport/Additional information:	Not dangerous according to the above specifications.
· ADR	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· Transport category	3
· Tunnel restriction code	(-)
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000

(Contd. on page 13)



BE SURE. BUILD SURE.

Safety data sheet according to UK REACH

Printing date 03.05.2025

Version number 5 (replaces version 4)

Revision: 03.05.2025

Trade name MC-DUR 1680 - Komponente A

(Contd. of page 12)

	ml
· UN "Model Regulation":	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (FATTY ACIDS, TALL-OIL, REACTION PRODUCTS WITH BISPHENOL A, ALKYL GLYCIDYL TOLYL ETHER AND TRIETHYLENETETRAMINE, SOLVENT NAPHTHA (PETROLEUM), LIGHT, AROMATIC), 9, III

SECTION 15: Regulatory information

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **Poisons Act**

· **Regulated explosives precursors**

None of the ingredients is listed.

· **Regulated poisons**

None of the ingredients is listed.

· **Reportable explosives precursors**

None of the ingredients is listed.

· **Reportable poisons**

None of the ingredients is listed.

· **Directive 2012/18/EU**

· **Qualifying quantity (tonnes) for the application of lower-tier requirements**

200 t

· **Qualifying quantity (tonnes) for the application of upper-tier requirements**

500 t

· **15.2 Chemical safety assessment:**

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

(Contd. on page 14)



BE SURE. BUILD SURE.

Page 14/15

Safety data sheet according to UK REACH

Printing date 03.05.2025

Version number 5 (replaces version 4)

Revision: 03.05.2025

Trade name MC-DUR 1680 - Komponente A

(Contd. of page 13)

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H372 Causes damage to organs through prolonged or repeated exposure.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

H413 May cause long lasting harmful effects to aquatic life.

· **Department issuing data specification sheet:**

· **Abbreviations and acronyms:**

Environment protection department.

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (UK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Corr. 1B: Skin corrosion/irritation – Category 1B

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Skin Sens. 1A: Skin sensitisation – Category 1A

Skin Sens. 1B: Skin sensitisation – Category 1B

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

(Contd. on page 15)

GB



BE SURE. BUILD SURE.

Page 15/15

**Safety data sheet
according to UK REACH**

Printing date 03.05.2025

Version number 5 (replaces version 4)

Revision: 03.05.2025

Trade name MC-DUR 1680 - Komponente A

(Contd. of page 14)

Aquatic Chronic 4: Hazardous to the aquatic environment - long-term aquatic hazard – Category 4

**· * Data compared to the
previous version altered.**

GB