



BE SURE. BUILD SURE.

Page 1/12

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 13.05.2023

Version number 26 (replaces version 25)

Revision: 13.05.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name **MC-DUR 1800 - Komponente B**

Article number: 3155

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture

Epoxy coating
Hardening agent/ Curing agent

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: MC-Bauchemie Müller GmbH & Co. KG
Am Kruppwald 1-8
D-46238 Bottrop
Tel.: +49(0)2041-101-0
Fax.: +49(0)2041-101-400
E-Mail: info@mc-bauchemie.de

MC-Bauchemie AG
Hagackerstr. 10
CH-8953 Dietikon
Tel.: +44-7400510
Fax : +44-7400533

Informing department: msds@mc-bauchemie.de

1.4 Emergency telephone number:

Tel.: +49 / (0)700 24112112 (MCR)
Tel.: +48612864565

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Acute Tox. 4 H302 Harmful if swallowed.
Skin Corr. 1B H314 Causes severe skin burns and eye damage.
Eye Dam. 1 H318 Causes serious eye damage.
Skin Sens. 1 H317 May cause an allergic skin reaction.
Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to

Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms



GHS05 GHS07

(Contd. on page 2)

GB



BE SURE. BUILD SURE.

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 13.05.2023

Version number 26 (replaces version 25)

Revision: 13.05.2023

Trade name MC-DUR 1800 - Komponente B

(Contd. of page 1)

- **Signal word** Danger
- **Hazard-determining components of labelling:**
 - Benzyl alcohol
 - Isophorone diamine
 - Amine polymer
 - Tetraethylenepentamine
 - m-phenylenebis(methylamine)
 - 3,6-diazaoctanethylenediamin
- **Hazard statements**
 - H302 Harmful if swallowed.
 - H314 Causes severe skin burns and eye damage.
 - H317 May cause an allergic skin reaction.
 - H412 Harmful to aquatic life with long lasting effects.
- **Precautionary statements**
 - P260 Do not breathe dusts or mists.
 - P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
 - P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 - P310 Immediately call a POISON CENTER/doctor.
 - P321 Specific treatment (see on this label).
 - P362+P364 Take off contaminated clothing and wash it before reuse.
- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- **3.2 Mixtures**
- **Description:** Binding agent with colouring agents.
Mixture consisting of the following components.

Dangerous components:

| | | |
|---|--|----------|
| CAS: 100-51-6 | Benzyl alcohol Acute Tox. 4, H302; Acute Tox. 4, H332; Eye Irrit. 2, H319 | 30-60% |
| EC number: 948-369-5 | Amine polymer Eye Dam. 1, H318; Skin Irrit. 2, H315; Skin Sens. 1B, H317 | 10-30% |
| CAS: 2855-13-2 | Isophorone diamine Skin Corr. 1B, H314; Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1, H317; Aquatic Chronic 3, H412 | ≥10-<25% |
| CAS: 90640-66-7 EINECS: 292-587-7 Reg.nr.: 01-2119487290-37 | Tetraethylenepentamine Skin Corr. 1B, H314; Aquatic Chronic 2, H411; Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1, H317 | ≥10-<25% |

(Contd. on page 3)



BE SURE. BUILD SURE.

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 13.05.2023

Version number 26 (replaces version 25)

Revision: 13.05.2023

Trade name MC-DUR 1800 - Komponente B

(Contd. of page 2)

| | | |
|--|---|----------|
| CAS: 1477-55-0 EINECS: 216-032-5 Reg.nr.: 01-2119480150-50 | <i>m</i> -phenylenebis(methylamine) Skin Corr. 1B, H314; Acute Tox. 4, H302; Acute Tox. 4, H332; Skin Sens. 1, H317; Aquatic Chronic 3, H412 | ≥5-<10% |
| CAS: 112-24-3 EINECS: 203-950-6 | 3,6-diazaoctanethylenediamin Skin Corr. 1B, H314; Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1, H317; Aquatic Chronic 3, H412 | ≥1-<1.5% |
| CAS: 69-72-7 EINECS: 200-712-3 | salicylic acid Repr. 2, H361d; Eye Dam. 1, H318; Acute Tox. 4, H302 | ≥1-<1.5% |

· **Additional information** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· **4.1 Description of first aid measures**

- **General information** Instantly remove any clothing soiled by the product. Seek medical treatment.
- **After inhalation** Supply fresh air and call for doctor for safety reasons.
- **After skin contact** Instantly wash with water and soap and rinse thoroughly.
- **After eye contact** Rinse opened eye for several minutes under running water. Seek medical treatment.
- **After swallowing** Drink copious amounts of water and provide fresh air. Instantly call for doctor.

· **4.2 Most important symptoms and effects, both acute and delayed**

No further relevant information available.

· **4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

SECTION 5: Firefighting measures

· **5.1 Extinguishing media**

· **Suitable extinguishing agents** CO₂, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam.

· **For safety reasons unsuitable extinguishing agents**

Water with a full water jet.

· **5.2 Special hazards arising from the substance or mixture**

Formation of toxic gases is possible during heating or in case of fire.

Can be released in case of fire

Nitrogen oxides (NO_x)

Carbon monoxide (CO)

· **5.3 Advice for firefighters**

· **Protective equipment:**

Wear self-contained breathing apparatus.

(Contd. on page 4)



BE SURE. BUILD SURE.

Page 4/12

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 13.05.2023

Version number 26 (replaces version 25)

Revision: 13.05.2023

Trade name **MC-DUR 1800 - Komponente B**

Wear full protective suit.

(Contd. of page 3)

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**
Prevent material from reaching sewage system, holes and cellars.
- **6.3 Methods and material for containment and cleaning up:**
*Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose of contaminated material as waste according to item 13.
Ensure adequate ventilation.*
- **6.4 Reference to other sections**
*See Section 7 for information on safe handling
See Section 8 for information on personal protection equipment.
See Section 13 for information on disposal.*

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
*Store in cool, dry place in tightly closed containers.
Open and handle container with care.*
- **Information about protection against explosions and fires:**
Protect against electrostatic charges.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage**
- **Requirements to be met by storerooms and containers:**
*Store in cool location.
Store only in the original container.*
- **Information about storage in one common storage facility:**
Not required.
- **Further information about storage conditions:**
*Caution when reopening containers with broken seal.
Keep container tightly sealed.*
- **Storage class**
8A
- **7.3 Specific end use(s)**
No further relevant information available.

GB

(Contd. on page 5)



BE SURE. BUILD SURE.

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 13.05.2023

Version number 26 (replaces version 25)

Revision: 13.05.2023

Trade name MC-DUR 1800 - Komponente B

(Contd. of page 4)

SECTION 8: Exposure controls/personal protection

- **8.1 Control parameters**
- **Components with critical values that require**

monitoring at the workplace: *The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.*

· **DNELs**

100-51-6 Benzyl alcohol

| | | |
|------------|------|---|
| Oral | DNEL | 4 mg/kg bw/Tag (ArL) 20 mg/kg bw/Tag (Ark) |
| Dermal | DNEL | 8 mg/kg bw/day (ArL) 40 mg/kg bw/day (Ark) |
| Inhalative | DNEL | 22 mg/m ³ (ArL) 110 mg/m ³ (Ark) |

2855-13-2 Isophorone diamine

| | | |
|------------|------|------------------------------|
| Oral | DNEL | 0.526 mg/kg bw/Tag (ArL) |
| Inhalative | DNEL | 20.1 mg/m ³ (ArL) |

1477-55-0 m-phenylenebis(methylamine)

| | | |
|------------|------|---------------------------------|
| Dermal | DNEL | 0.33 mg/kg bw/day (Workers) |
| Inhalative | DNEL | 1.2 mg/m ³ (Workers) |

· **PNECs**

100-51-6 Benzyl alcohol

| | |
|------|---|
| PNEC | 0.527 mg/l (Marine water sediment) 0.1 mg/l (Mew) 1 mg/l (Fresh water sediment) |
| PNEC | 0.456 mg/kg dwt (Bod) 5.27 mg/kg dwt (Fresh water sediment) |

2855-13-2 Isophorone diamine

| | |
|------|--|
| PNEC | 0.006 mg/l (Mew) 0.06 mg/l (Suw) |
| PNEC | 0.578 mg/kg dwt (Sediment) 5.784 mg/kg dwt (Fresh water sediment) |

1477-55-0 m-phenylenebis(methylamine)

| | |
|------|--|
| PNEC | 10 mg/l (Kla) 0.009 mg/l (Mew) 0.094 mg/l (Suw) |
| PNEC | 0.045 mg/kg dwt (Bod) 0.43 mg/kg dwt (Marine water sediment) 0.43 mg/kg dwt (Fresh water sediment) |

(Contd. on page 6)



BE SURE. BUILD SURE.

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 13.05.2023

Version number 26 (replaces version 25)

Revision: 13.05.2023

Trade name MC-DUR 1800 - Komponente B

(Contd. of page 5)

- **Additional information:** *The lists that were valid during the compilation were used as basis.*
- **8.2 Exposure controls**
- **Appropriate engineering controls** *No further data; see section 7.*
- **Individual protection measures, such as personal protective equipment**
- **General protective and hygienic measures** *Keep away from foodstuffs, beverages and food.
Instantly remove any soiled and impregnated garments.
Wash hands during breaks and at the end of the work.
Avoid contact with the eyes and skin.*
- **Breathing equipment:** *A2-P3*
- **Hand protection** *Protective gloves.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
After use of gloves apply skin-cleaning agents and skin cosmetics.*
- **Material of gloves** *The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.*
- **Penetration time of glove material** *The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.*
- **Eye/face protection** *Safety glasses
Tightly sealed safety glasses.*
- **Body protection:** *Protective work clothing.*

SECTION 9: Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**
- **General Information**
- **Colour:** *Yellow*
- **Smell:** *Amine-like*
- **Melting point/freezing point:** *Not determined*
- **Boiling point or initial boiling point and boiling range** *205.4 °C (100-51-6 Benzyl alcohol)*
- **Lower and upper explosion limit**
- **Lower:** *1.3 Vol % (100-51-6 Benzyl alcohol)*
- **Upper:** *13 Vol % (100-51-6 Benzyl alcohol)*
- **Flash point:** *101 °C*
- **pH** *Not applicable.
Not determined.*
- **Viscosity:**
- **Kinematic viscosity** *Not determined.*
- **dynamic at 20 °C:** *225 mPas*

(Contd. on page 7)



BE SURE. BUILD SURE.

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 13.05.2023

Version number 26 (replaces version 25)

Revision: 13.05.2023

Trade name MC-DUR 1800 - Komponente B

(Contd. of page 6)

- **Solubility**
- **Water:** Not miscible or difficult to mix
- **Steam pressure at 20 °C:** 0.1 hPa
- **Vapour pressure at 50 °C:** 0.7 hPa
- **Density and/or relative density**
- **Density at 20 °C** 1.03 g/cm³

- **9.2 Other information**
- **Appearance:**
- **Form:** Fluid
- **Important information on protection of health and environment, and on safety.**
- **Self-inflammability:** Product is not selfigniting.
- **Explosive properties:** Product is not explosive.

- **Information with regard to physical hazard classes**
- **Explosives** Void
- **Flammable gases** Void
- **Aerosols** Void
- **Oxidising gases** Void
- **Gases under pressure** Void
- **Flammable liquids** Void
- **Flammable solids** Void
- **Self-reactive substances and mixtures** Void
- **Pyrophoric liquids** Void
- **Pyrophoric solids** Void
- **Self-heating substances and mixtures** Void
- **Substances and mixtures, which emit flammable gases in contact with water** Void
- **Oxidising liquids** Void
- **Oxidising solids** Void
- **Organic peroxides** Void
- **Corrosive to metals** Void
- **Desensitised explosives** Void

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** Reacts with acids and oxidizing agents
- **10.4 Conditions to avoid** No further relevant information available.

(Contd. on page 8)



BE SURE. BUILD SURE.

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 13.05.2023

Version number 26 (replaces version 25)

Revision: 13.05.2023

Trade name MC-DUR 1800 - Komponente B

(Contd. of page 7)

- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** Nitrous vitriol gases
Corrosive gases/vapours

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Harmful if swallowed.

- **LD/LC50 values that are relevant for classification:**

100-51-6 Benzyl alcohol

| | | |
|------------|----------------------|--------------------------------------|
| Oral | LD50 | 1230 mg/kg (rat) |
| | NOAEL 2nd year study | 200 mg/kg (mouse) 200 mg/kg (rat) |
| Dermal | LD50 | 2000 mg/kg (rabbit) |
| Inhalative | LC50/4 h | >4178 mg/l (rat) |

2855-13-2 Isophorone diamine

| | | |
|--------|-------|--|
| Oral | LD50 | 1030 mg/kg (ATE) 1030 mg/kg (rat) |
| | NOAEL | 250 mg/kg (rat) |
| Dermal | LD50 | 1840 mg/kg (rabbit) >2000 mg/kg (rat) |

1477-55-0 m-phenylenebis(methylamine)

| | | |
|--------|------|---------------------------------------|
| Oral | LD50 | 1180 mg/kg (mouse) 930 mg/kg (rat) |
| | LD50 | >3100 mg/kg (rabbit) |
| Dermal | LD50 | >3100 mg/kg (rabbit) |

112-24-3 3,6-diazaoctanethylenediamin

| | | |
|--------|------|--------------------|
| Oral | LD50 | 1716.2 mg/kg (rat) |
| Dermal | LD50 | 1720 mg/kg (rat) |

69-72-7 salicylic acid

| | | |
|--------|------|-------------------|
| Oral | LD50 | 891 mg/kg (rat) |
| Dermal | LD50 | >2000 mg/kg (rat) |

- **Skin corrosion/irritation** Causes severe skin burns and eye damage.
- **Serious eye damage/irritation** Causes serious eye damage.
- **Respiratory or skin sensitisation** May cause an allergic skin reaction.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

(Contd. on page 9)



BE SURE. BUILD SURE.

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 13.05.2023

Version number 26 (replaces version 25)

Revision: 13.05.2023

Trade name MC-DUR 1800 - Komponente B

(Contd. of page 8)

· 11.2 Information on other hazards

· Endocrine disrupting properties

69-72-7 salicylic acid

List II; III

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

100-51-6 Benzyl alcohol

| | |
|----------|---|
| IC50/72h | 700 mg/l (algae) |
| LC50/96h | 460 mg/l (<i>Pimephales promelas</i>) |
| | 10 mg/l (<i>Lepomis macrochirus</i>) |

2855-13-2 Isophorone diamine

| | |
|-----------|---|
| LC50/96h | 110 mg/l (<i>Leucidus idus</i>) |
| EC50 | 1120 mg/l (<i>Pseudomonas putida</i>) |
| EC50/48h | 23 mg/l (<i>Daphnia magna</i>) |
| NOEC | 1.5 mg/l (<i>Desmodesmus subspicatus</i>) |
| | 3 mg/l (<i>Daphnia magna</i>) |
| ErC50/72h | >50 mg/l (<i>Desmodesmus subspicatus</i>) |

1477-55-0 m-phenylenebis(methylamine)

| | |
|----------|--|
| IC50/72h | 12 mg/l (algae) |
| EC50/72h | 12 mg/l (<i>Scenedesmus subspicatus</i>) |
| LC50/96h | >100 mg/l (<i>Oncorhynchus mykiss</i>) |
| | 87.6 mg/l (<i>Ory</i>) |
| EC50/48h | 15.2 mg/l (<i>Daphnia magna</i>) |

· 12.2 Persistence and degradability

No further relevant information available.

· 12.3 Bioaccumulative potential

No further relevant information available.

· 12.4 Mobility in soil

No further relevant information available.

· 12.5 Results of PBT and vPvB assessment

· PBT:

Not applicable.

· vPvB:

Not applicable.

· 12.6 Endocrine disrupting properties

For information on endocrine disrupting properties see section 11.

· 12.7 Other adverse effects

· Additional ecological information:

· General notes:

Do not allow product to reach ground water, water bodies or sewage system.
Danger to drinking water if even small quantities leak into soil.

GB

(Contd. on page 10)



BE SURE. BUILD SURE.

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 13.05.2023

Version number 26 (replaces version 25)

Revision: 13.05.2023

Trade name MC-DUR 1800 - Komponente B

(Contd. of page 9)

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Uncleaned packagings:

Recommendation: Empty contaminated packagings thoroughly. They can be recycled after thorough and proper cleaning.

SECTION 14: Transport information

14.1 UN number or ID number

ADR, IMDG, IATA UN2735

14.2 UN proper shipping name

ADR, IMDG, IATA AMINES, LIQUID, CORROSIVE, N.O.S.
(Isophorone diamine, Tetraethylenepentamine)

14.3 Transport hazard class(es)

ADR
Class 8 (C7) Corrosive substances.
Label 8

IMDG, IATA

Class 8 Corrosive substances.
Label 8

14.4 Packing group

ADR, IMDG, IATA II

14.5 Environmental hazards:

Marine pollutant: No

14.6 Special precautions for user

Warning: Corrosive substances.
Kemler Number: 80
EMS Number: F-A, S-B
Segregation groups (SGG18) Alkalies
Stowage Category A
Segregation Code SG35 Stow "separated from" SGG1-acids

14.7 Maritime transport in bulk according to IMO instruments

Not applicable.

Transport/Additional information:

ADR
Limited quantities (LQ) 1L
Excepted quantities (EQ) Code: E2
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 500 ml

(Contd. on page 11)



BE SURE. BUILD SURE.

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 13.05.2023

Version number 26 (replaces version 25)

Revision: 13.05.2023

Trade name MC-DUR 1800 - Komponente B

(Contd. of page 10)

| | |
|-----------------------------------|---|
| · Transport category | 2 |
| · Tunnel restriction code | E |
| <hr/> | |
| · IMDG | |
| · Limited quantities (LQ) | 1L |
| · Excepted quantities (EQ) | Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml |
| · UN "Model Regulation": | UN 2735 AMINES, LIQUID, CORROSIVE, N.O.S. (ISOPHORONE DIAMINE, TETRAETHYLENEPENTAMINE), 8, II |

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture** No further relevant information available.
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**
 - H302 Harmful if swallowed.
 - H312 Harmful in contact with skin.
 - H314 Causes severe skin burns and eye damage.
 - H315 Causes skin irritation.
 - H317 May cause an allergic skin reaction.
 - H318 Causes serious eye damage.
 - H319 Causes serious eye irritation.
 - H332 Harmful if inhaled.
 - H361d Suspected of damaging the unborn child.
 - H411 Toxic to aquatic life with long lasting effects.
 - H412 Harmful to aquatic life with long lasting effects.
- **Department issuing data specification sheet:** Environment protection department.
- **Abbreviations and acronyms:**
 - RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
 - ICAO: International Civil Aviation Organisation
 - ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
 - IMDG: International Maritime Code for Dangerous Goods
 - IATA: International Air Transport Association
 - GHS: Globally Harmonised System of Classification and Labelling of Chemicals

(Contd. on page 12)



BE SURE. BUILD SURE.

Page 12/12

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 13.05.2023

Version number 26 (replaces version 25)

Revision: 13.05.2023

Trade name MC-DUR 1800 - Komponente B

(Contd. of page 11)

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (UK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Acute Tox. 4: Acute toxicity – Category 4

Skin Corr. 1B: Skin corrosion/irritation – Category 1B

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Skin Sens. 1B: Skin sensitisation – Category 1B

Repr. 2: Reproductive toxicity – Category 2

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

*** Data compared to the
previous version altered.**

GB