



BE SURE. BUILD SURE.

Page 1/13

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 29.12.2022

Version number 21 (replaces version 20)

Revision: 29.12.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name **MC-DUR 1900 Plus - Komponente A**

Article number: 2870

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture

Coating
Epoxy coating

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: MC-Bauchemie Müller GmbH & Co. KG
Am Kruppwald 1-8
D-46238 Bottrop
Tel.: +49(0)2041-101-0
Fax.: +49(0)2041-101-400
E-Mail: info@mc-bauchemie.de

MC-Bauchemie AG
Hagackerstr. 10
CH-8953 Dietikon
Tel.: +44-7400510
Fax : +44-7400533

Informing department: msds@mc-bauchemie.de

1.4 Emergency telephone number:

Tel.: +49 / (0)700 24112112 (MCR)
Tel.: +48612864565

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to

Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms



GHS07 GHS09

(Contd. on page 2)

GB



BE SURE. BUILD SURE.

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 29.12.2022

Version number 21 (replaces version 20)

Revision: 29.12.2022

Trade name MC-DUR 1900 Plus - Komponente A

(Contd. of page 1)

- **Signal word** Warning
- **Hazard-determining components of labelling:** *2,2'-[methylenebis(p-phenyleneoxymethylene)]bisoxirane polymers and homologues, molecular weight < 700
epoxide derivates
Epoxyfunktionelles Polymer
1,6-hexene-diglycidylether
Propyl -2,2-diphenyl-4,4'dipropylloxirane polymers and homologues
molecular weight < 700
Reaktionsprodukt aus polyether-modifiziertem Polysiloxan und 6-Hexandiglycidylether*
- **Hazard statements** *H315 Causes skin irritation.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
H411 Toxic to aquatic life with long lasting effects.*
- **Precautionary statements** *P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P273 Avoid release to the environment.
P280 Wear protective gloves / eye protection / face protection.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 If eye irritation persists: Get medical advice/attention.*
- **Additional information:** *Contains epoxy constituents. May produce an allergic reaction.
Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.*
- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**

· PBT:	
541-02-6	2,2,4,4,6,6,8,8,10,10-decamethylcyclopentasiloxane
· vPvB:	
541-02-6	2,2,4,4,6,6,8,8,10,10-decamethylcyclopentasiloxane

SECTION 3: Composition/information on ingredients

- **3.2 Mixtures**
- **Description:** *Resin mixture with colouring agents.
Mixture consisting of the following components.*

(Contd. on page 3)



BE SURE. BUILD SURE.

Page 3/13

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 29.12.2022

Version number 21 (replaces version 20)

Revision: 29.12.2022

Trade name **MC-DUR 1900 Plus - Komponente A**

(Contd. of page 2)

· Dangerous components:

CAS: 9003-36-5 NLP: 500-006-8	2,2'-[methylenebis(p-phenyleneoxymethylene)] bisoxirane polymers and homologues, molecular weight < 700 Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317, EUH205	25-50%
CAS: 1675-54-3 EINECS: 216-823-5	epoxide derivates Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	≥10-<25%
EC number: 953-811-5	Epoxyfunktionelles Polymer Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; Aquatic Chronic 3, H412	≥10-<25%
CAS: 16096-31-4 EINECS: 240-260-4	1,6-hexene-diglycidylether Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; Aquatic Chronic 3, H412, EUH205	≥2.5-<10%
CAS: 25068-38-6 NLP: 500-033-5 Reg.nr.: 01-2119456619-26-0002	Propyl -2,2-diphenyl-4,4'dipropyloxirane polymers and homologues molecular weight < 700 Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317, EUH205 Specific concentration limits: Eye Irrit. 2; H319: C ≥ 5% Skin Irrit. 2; H315: C ≥ 5 %	≥5-<10%
CAS: 13463-67-7 EINECS: 236-675-5	titanium dioxide Carc. 2, H351	≥0.1-<5%
CAS: 100-51-6 EINECS: 202-859-9 Reg.nr.: 01-2119492630-38	Benzyl alcohol Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332	<3%
CAS: 2530-83-8 EINECS: 219-784-2	[3-(2,3-epoxypropoxy)propyl]trimethoxysilane Eye Dam. 1, H318	≥1-<1.5%
CAS: 869858-05-9	Reaktionsprodukt aus polyether-modifiziertem Polysiloxan und 6-Hexandiglycidylether Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	≥0.1-<1%
CAS: 541-02-6	2,2,4,4,6,6,8,8,10,10-decamethylcyclopentasiloxane Non-classified vPvB substance. Non-classified PBT substance. Substance identified as having endocrine disrupting properties (II).	<0.5%

· SVHC

541-02-6 | 2,2,4,4,6,6,8,8,10,10-decamethylcyclopentasiloxane

· Additional information

For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures**· 4.1 Description of first aid measures****· After inhalation** Supply fresh air.

(Contd. on page 4)

GB



BE SURE. BUILD SURE.

Page 4/13

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 29.12.2022

Version number 21 (replaces version 20)

Revision: 29.12.2022

Trade name **MC-DUR 1900 Plus - Komponente A**

(Contd. of page 3)

- **After skin contact** Instantly wash with water and soap and rinse thoroughly.
- **After eye contact** Rinse opened eye for several minutes under running water.
Seek medical treatment.
- **After swallowing** Rinse out mouth and then drink plenty of water.
Seek medical treatment.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents** Use fire fighting measures that suit the environment.
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** No special measures required.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures** Not required.
- **6.2 Environmental precautions:** Prevent material from reaching sewage system, holes and cellars.
- **6.3 Methods and material for containment and cleaning up:** Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
- **6.4 Reference to other sections** See Section 7 for information on safe handling
See Section 8 for information on personal protection equipment.
See Section 13 for information on disposal.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Store in cool, dry place in tightly closed containers.
Open and handle container with care.
- **Information about protection against explosions and fires:** No special measures required.

(Contd. on page 5)

GB



BE SURE. BUILD SURE.

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 29.12.2022

Version number 21 (replaces version 20)

Revision: 29.12.2022

Trade name MC-DUR 1900 Plus - Komponente A

(Contd. of page 4)

- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage**
- **Requirements to be met by storerooms and containers:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep container tightly sealed.
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **8.1 Control parameters**
- **Components with critical values that require monitoring at the workplace:** The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

· **DNELs**

16096-31-4 1,6-hexene-diglycidylether

Dermal	DNEL	2.8 mg/kg bw/day (ArL)
Inhalative	DNEL	4.9 mg/m ³ (ArL)

25068-38-6 Propyl -2,2-diphenyl-4,4'dipropylloxirane polymers and homologues molecular weight < 700

Oral	DNEL	0.75 mg/kg bw/Tag (General) (Kurzfristig und Langfristig Systemisch)
Dermal	DNEL	3.6 mg/kg bw/day (General) (Kurzfristig und Langfristig Systemisch) 8.3 mg/kg bw/day (Workers) (Kurzfristig und Langfristig Systemisch)
Inhalative	DNEL	0.75 mg/m ³ (General) (Kurzfristig und Langfristig Systemisch) 12.3 mg/m ³ (Workers) (Kurzfristig und Langfristig Systemisch)

100-51-6 Benzyl alcohol

Oral	DNEL	4 mg/kg bw/Tag (ArL) 20 mg/kg bw/Tag (Ark)
Dermal	DNEL	8 mg/kg bw/day (ArL) 40 mg/kg bw/day (Ark)
Inhalative	DNEL	22 mg/m ³ (ArL) 110 mg/m ³ (Ark)

· **PNECs**

16096-31-4 1,6-hexene-diglycidylether

PNEC	0.0115 mg/l (Fresh water) 0.00115 mg/l (Mew)
PNEC	0.223 mg/kg dwt (Bod) 0.0283 mg/kg dwt (Sediment)

(Contd. on page 6)



BE SURE. BUILD SURE.

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 29.12.2022

Version number 21 (replaces version 20)

Revision: 29.12.2022

Trade name MC-DUR 1900 Plus - Komponente A

(Contd. of page 5)

	0.283 mg/kg dwt (Fresh water sediment)
25068-38-6 Propyl -2,2-diphenyl-4,4'dipropylloxirane polymers and homologues molecular weight < 700	
PNEC	3 µg/l (Fresh water) 0.3 µg/l (Marine)
PNEC	10 mg/l (Sewage Treatment Plant)
PNEC	0.5 mg/kg dwt (Marine water sediment) 0.05 mg/kg dwt (Sediment) 0.5 mg/kg dwt (Fresh water sediment)
100-51-6 Benzyl alcohol	
PNEC	0.527 mg/l (Marine water sediment) 0.1 mg/l (Mew) 1 mg/l (Fresh water sediment)
PNEC	0.456 mg/kg dwt (Bod) 5.27 mg/kg dwt (Fresh water sediment)

- **Additional information:** The lists that were valid during the compilation were used as basis.
- **8.2 Exposure controls**
- **Appropriate engineering controls** No further data; see item 7.
- **Individual protection measures, such as personal protective equipment**
- **General protective and hygienic measures** Keep away from foodstuffs, beverages and food.
Instantly remove any soiled and impregnated garments.
Wash hands during breaks and at the end of the work.
Avoid contact with the eyes and skin.
- **Hand protection** Protective gloves.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
After use of gloves apply skin-cleaning agents and skin cosmetics.
- **Material of gloves** The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material** The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye/face protection** Safety glasses
Tightly sealed safety glasses.
- **Body protection:** Protective work clothing.

GB

(Contd. on page 7)



BE SURE. BUILD SURE.

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 29.12.2022

Version number 21 (replaces version 20)

Revision: 29.12.2022

Trade name MC-DUR 1900 Plus - Komponente A

(Contd. of page 6)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

· Colour:	Various colours
· Smell:	Fruit-like
· Melting point/freezing point:	Not determined
· Boiling point or initial boiling point and boiling range	>200 °C (9003-36-5 2,2'-[methylenebis(p-phenyleneoxymethylene)]bisoxirane polymers and homologues, molecular weight < 700)
· Flash point:	Not applicable
· pH	7
	Not applicable.
· Viscosity:	
· dynamic at 20 °C:	11400 mPas
· Solubility	
· Water:	Not miscible or difficult to mix
· Steam pressure at 20 °C:	0.1 hPa
· Density and/or relative density	
· Density at 20 °C	1.33 g/cm ³

9.2 Other information

· Appearance:	
· Form:	Fluid
· Important information on protection of health and environment, and on safety.	
· Self-inflammability:	Product is not selfigniting.
· Explosive properties:	Product is not explosive.

Information with regard to physical hazard classes

· Explosives	Void
· Flammable gases	Void
· Aerosols	Void
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Void
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void

(Contd. on page 8)



BE SURE. BUILD SURE.

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 29.12.2022

Version number 21 (replaces version 20)

Revision: 29.12.2022

Trade name MC-DUR 1900 Plus - Komponente A

(Contd. of page 7)

- **Organic peroxides** Void
- **Corrosive to metals** Void
- **Desensitised explosives** Void

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

LD/LC50 values that are relevant for classification:

9003-36-5 2,2'-[methylenebis(p-phenyleneoxymethylene)]bisoxirane polymers and homologues, molecular weight < 700

Oral	LD50	>2000 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rabbit)

1675-54-3 epoxide derivates

Dermal	LD50	23000 mg/kg (rabbit)
--------	------	----------------------

16096-31-4 1,6-hexene-diglycidylether

Oral	LD50	>8500 mg/kg (rat)
Dermal	LD50	>4900 mg/kg (rat)

25068-38-6 Propyl -2,2-diphenyl-4,4'dipropyloxirane polymers and homologues molecular weight < 700

Oral	LD50	30000 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rabbit)

13463-67-7 titanium dioxide

Oral	LD50	>10000 mg/kg (rat)
Dermal	LD50	>10000 mg/kg (rabbit)
Inhalative	LC50/4 h	>6.8 mg/l (rat)

100-51-6 Benzyl alcohol

Oral	LD50	1230 mg/kg (rat)
------	------	------------------

(Contd. on page 9)



BE SURE. BUILD SURE.

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 29.12.2022

Version number 21 (replaces version 20)

Revision: 29.12.2022

Trade name MC-DUR 1900 Plus - Komponente A

(Contd. of page 8)

	NOAEL 2nd year study	200 mg/kg (mouse) 200 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rabbit)
Inhalative	LC50/4 h	>4178 mg/l (rat)
2530-83-8 [3-(2,3-epoxypropoxy)propyl]trimethoxysilane		
Oral	LD50	8030 mg/kg (rat)
Dermal	LD50	4248 mg/kg (rabbit)

- **Skin corrosion/irritation** Causes skin irritation.
- **Serious eye damage/irritation** Causes serious eye irritation.
- **Respiratory or skin sensitisation** May cause an allergic skin reaction.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

· **11.2 Information on other hazards**

· **Endocrine disrupting properties**

541-02-6	2,2,4,4,6,6,8,8,10,10-decamethylcyclopentasiloxane	List II
540-97-6	Dodecamethylcyclohexasiloxane (D6)	List II
556-67-2	octamethylcyclotetrasiloxane	List II, III
128-37-0	Butylated hydroxytoluene	List II

SECTION 12: Ecological information

· **12.1 Toxicity**

· **Aquatic toxicity:**

9003-36-5 2,2'-[methylenebis(p-phenyleneoxymethylene)]bisoxirane polymers and homologues, molecular weight < 700	
LC50/96h	>100 mg/l (Daphnia magna)
EC50/96h	>100 mg/l (Leucidus idus)
1675-54-3 epoxide derivates	
IC50	>42.6 mg/l (Bak)
LC50/96h	2 mg/l (Oncorhynchus mykiss)
EC50/48h	1.8 mg/l (Daphnia magna)
ErC50/72h	11 mg/l (Selenastrum capricornutum)
16096-31-4 1,6-hexene-diglycidylether	
LC50/96h	30 mg/l (Leucidus idus)
EC50/48h	47 mg/l (Daphnia magna)

(Contd. on page 10)



BE SURE. BUILD SURE.

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 29.12.2022

Version number 21 (replaces version 20)

Revision: 29.12.2022

Trade name MC-DUR 1900 Plus - Komponente A

(Contd. of page 9)

100-51-6 Benzyl alcohol

IC50/72h	700 mg/l (algae)
LC50/96h	460 mg/l (Pimephales promelas)
	10 mg/l (Lepomis macrochirus)

2530-83-8 [3-(2,3-epoxypropoxy)propyl]trimethoxysilane

LC50/96h	55 mg/l (Cyp)
EC50/48h	473 mg/l (Daphnia magna)
ErC50/72h	255 mg/l (Scenedesmus subspicatus)

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**

· **PBT:**

541-02-6	2,2,4,4,6,6,8,8,10,10-decamethylcyclopentasiloxane
----------	--

· **vPvB:**

541-02-6	2,2,4,4,6,6,8,8,10,10-decamethylcyclopentasiloxane
----------	--

- **12.6 Endocrine disrupting properties** For information on endocrine disrupting properties see section 11.
- **12.7 Other adverse effects**
- **Additional ecological information:**
- **General notes:** Do not allow product to reach ground water, water bodies or sewage system.
Danger to drinking water if even small quantities leak into soil.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation** Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Empty contaminated packagings thoroughly. They can be recycled after thorough and proper cleaning.

SECTION 14: Transport information

- **14.1 UN number or ID number**
- **ADR, IMDG, IATA** UN3082

(Contd. on page 11)



BE SURE. BUILD SURE.

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 29.12.2022

Version number 21 (replaces version 20)

Revision: 29.12.2022

Trade name MC-DUR 1900 Plus - Komponente A

(Contd. of page 10)

<ul style="list-style-type: none"> · 14.2 UN proper shipping name · ADR, IATA · IMDG 	<p><i>ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (epoxide derivates)</i></p> <p><i>ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (epoxide derivates), MARINE POLLUTANT</i></p>
--	---

<ul style="list-style-type: none"> · 14.3 Transport hazard class(es) · ADR · Class · Label 	<p><i>9 (M6) Miscellaneous dangerous substances and articles.</i></p> <p><i>9</i></p>
--	---

<ul style="list-style-type: none"> · IMDG, IATA · Class · Label 	<p><i>9 Miscellaneous dangerous substances and articles.</i></p> <p><i>9</i></p>
---	--

<ul style="list-style-type: none"> · 14.4 Packing group · ADR, IMDG, IATA 	<p><i>III</i></p>
---	-------------------

<ul style="list-style-type: none"> · 14.5 Environmental hazards: · Marine pollutant: · Special marking (ADR): · Special marking (IATA): 	<p><i>Product contains environmentally hazardous substances: epoxide derivates</i></p> <p><i>Yes</i></p> <p><i>Symbol (fish and tree)</i></p> <p><i>Symbol (fish and tree)</i></p> <p><i>Symbol (fish and tree)</i></p>
---	---

<ul style="list-style-type: none"> · 14.6 Special precautions for user · Kemler Number: · EMS Number: · Stowage Category 	<p><i>Warning: Miscellaneous dangerous substances and articles.</i></p> <p><i>90</i></p> <p><i>F-A, S-F</i></p> <p><i>A</i></p>
--	---

<ul style="list-style-type: none"> · 14.7 Maritime transport in bulk according to IMO instruments 	<p><i>Not applicable.</i></p>
---	-------------------------------

<ul style="list-style-type: none"> · Transport/Additional information: 	
<ul style="list-style-type: none"> · ADR · Limited quantities (LQ) · Excepted quantities (EQ) · Transport category · Tunnel restriction code 	<p><i>5L</i></p> <p><i>Code: E1</i></p> <p><i>Maximum net quantity per inner packaging: 30 ml</i></p> <p><i>Maximum net quantity per outer packaging: 1000 ml</i></p> <p><i>3</i></p> <p><i>(-)</i></p>

<ul style="list-style-type: none"> · IMDG · Limited quantities (LQ) · Excepted quantities (EQ) 	<p><i>5L</i></p> <p><i>Code: E1</i></p> <p><i>Maximum net quantity per inner packaging: 30 ml</i></p>
--	---

(Contd. on page 12)



BE SURE. BUILD SURE.

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 29.12.2022

Version number 21 (replaces version 20)

Revision: 29.12.2022

Trade name MC-DUR 1900 Plus - Komponente A

(Contd. of page 11)

·	Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXIDE DERIVATES), 9, III

SECTION 15: Regulatory information

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

· Directive 2012/18/EU

· **Qualifying quantity (tonnes) for the application of lower-tier requirements** 200 t

· **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t

· National regulations

· **Substances of very high concern (SVHC) according to UK REACH**

541-02-6 | 2,2,4,4,6,6,8,8,10,10-decamethylcyclopentasiloxane

· **15.2 Chemical safety assessment:**

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H351	Suspected of causing cancer.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH205	Contains epoxy constituents. May produce an allergic reaction.

· **Department issuing data specification sheet:**

Environment protection department.

· **Abbreviations and acronyms:** RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

(Contd. on page 13)



BE SURE. BUILD SURE.

Page 13/13

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 29.12.2022

Version number 21 (replaces version 20)

Revision: 29.12.2022

Trade name MC-DUR 1900 Plus - Komponente A

(Contd. of page 12)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (UK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Carc. 2: Carcinogenicity – Category 2

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

*** Data compared to the
previous version altered.**

GB