



BE SURE. BUILD SURE.

Page 1/11

## Safety data sheet according to UK REACH

Printing date 14.04.2025

Version number 36 (replaces version 35)

Revision: 14.04.2025

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### · 1.1 Product identifier

· Trade name **MC-DUR 2095 ESD - Komponente B**

· Article number: 2388

#### · 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

#### · Application of the substance / the mixture

Coating compound/ Surface coating/ paint  
Hardening agent/ Curing agent

#### · 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier: MC-Bauchemie Müller GmbH & Co. KG  
Am Kruppwald 1-8  
D-46238 Bottrop  
Tel.: +49(0)2041-101-0  
Fax.: +49(0)2041-101-400  
E-Mail: info@mc-bauchemie.de

MC-Bauchemie AG  
Hagackerstr. 10  
CH-8953 Dietikon  
Tel.: +44-7400510  
Fax : +44-7400533

· Informing department: msds@mc-bauchemie.de

#### · 1.4 Emergency telephone number:

Tel.: +49 / (0)700 24112112 (MCR)  
Tel.: +1 872 5888271 (MCR)

### SECTION 2: Hazards identification

#### · 2.1 Classification of the substance or mixture

##### · Classification according to Regulation (EC) No 1272/2008

Acute Tox. 4 H332 Harmful if inhaled.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Dam. 1 H318 Causes serious eye damage.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

#### · 2.2 Label elements

##### · Labelling according to

**Regulation (EC) No 1272/2008** The product is classified and labelled according to the GB CLP regulation.

##### · Hazard pictograms



GHS05 GHS07

(Contd. on page 2)

GB



BE SURE. BUILD SURE.

## Safety data sheet according to UK REACH

Printing date 14.04.2025

Version number 36 (replaces version 35)

Revision: 14.04.2025

**Trade name MC-DUR 2095 ESD - Komponente B**

(Contd. of page 1)

- **Signal word** Danger
- **Hazard-determining components of labelling:** Aliphatisches Polyisocyanat  
Poly(oxy-1,2-ethanediyl), .alpha.-  
Ethyldiisopropylamine  
Phosphoric acid, butyl ester  
hexamethylene diisocyanate
- **Hazard statements** H332 Harmful if inhaled.  
H315 Causes skin irritation.  
H318 Causes serious eye damage.  
H317 May cause an allergic skin reaction.  
H335 May cause respiratory irritation.
- **Precautionary statements** P261 Avoid breathing dust/fume/gas/mist/vapours/  
spray.  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for  
several minutes. Remove contact lenses, if  
present and easy to do. Continue rinsing.  
P310 Immediately call a POISON CENTER/doctor.  
P321 Specific treatment (see on this label).  
P362+P364 Take off contaminated clothing and wash it  
before reuse.  
P403+P233 Store in a well-ventilated place. Keep container  
tightly closed.
- **Additional information:** EUH204 Contains isocyanates. May produce an allergic reaction.  
As from 24 August 2023 adequate training is required before  
industrial or professional use.
- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

### SECTION 3: Composition/information on ingredients

- **3.2 Mixtures**
- **Description:** Mixture consisting of the following components.

· **Dangerous components:**

CAS: 28182-81-2	Aliphatisches Polyisocyanat Acute Tox. 4, H332; Skin Sens. 1, H317; STOT SE 3, H335, EUH204	80-100%
CAS: 9046-01-9 EINECS: 232-911-6	Poly(oxy-1,2-ethanediyl), .alpha.- Eye Dam. 1, H318; Skin Irrit. 2, H315; Aquatic Chronic 3, H412	≥3-<10%
CAS: 7087-68-5 EINECS: 230-392-0	Ethyldiisopropylamine Flam. Liq. 2, H225; Acute Tox. 3, H331; Eye Dam. 1, H318; Acute Tox. 4, H302; STOT SE 3, H335	≥1-<2.5%

(Contd. on page 3)



BE SURE. BUILD SURE.

## Safety data sheet according to UK REACH

Printing date 14.04.2025

Version number 36 (replaces version 35)

Revision: 14.04.2025

**Trade name MC-DUR 2095 ESD - Komponente B**

(Contd. of page 2)

CAS: 12788-93-1 EINECS: 235-826-2	Phosphoric acid, butyl ester Skin Corr. 1B, H314	≥1-<2.5%
CAS: 822-06-0 EINECS: 212-485-8 Reg.nr.: 01-2119457571-37-0000	hexamethylene diisocyanate Acute Tox. 1, H330; Resp. Sens. 1, H334; Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335, EUH204 Specific concentration limits: Resp. Sens. 1; H334: C ≥ 0.5 % Skin Sens. 1; H317: C ≥ 0.5 %	≥0.1-<0.5%

· **Additional information**

For the wording of the listed hazard phrases refer to section 16.

### SECTION 4: First aid measures

· **4.1 Description of first aid measures**

· **General information**

Remove soiled, soaked clothing immediately.

· **After inhalation**

Remove person to fresh air, keep warm, allow to rest; if breathing is difficult, seek medical attention.

· **After skin contact**

In case of contact with skin, wash carefully with plenty of soap and water. Consult a doctor in case of skin reactions.

· **After eye contact**

Rinse the eyes with open eyelids for a sufficiently long time (at least 10 minutes) with water that is as lukewarm as possible. Consult an ophthalmologist.

· **After swallowing**

Do NOT induce vomiting. Rinse mouth with water. Medical attention required.

· **4.2 Most important symptoms and effects, both acute and delayed**

Advice for the doctor: Elementary aid, decontamination, symptomatic treatment.

· **4.3 Indication of any immediate medical attention and special treatment needed**

Therapeutic measures: No information available.

### SECTION 5: Firefighting measures

· **5.1 Extinguishing media**

· **Suitable extinguishing agents** CO<sub>2</sub>, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam.

· **5.2 Special hazards arising from the substance or mixture**

No further relevant information available.

· **5.3 Advice for firefighters**

· **Protective equipment:**

No special measures required.

GB

(Contd. on page 4)



BE SURE. BUILD SURE.

Page 4/11

## Safety data sheet according to UK REACH

Printing date 14.04.2025

Version number 36 (replaces version 35)

Revision: 14.04.2025

Trade name **MC-DUR 2095 ESD - Komponente B**

(Contd. of page 3)

### SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures** *Not required.*
- **6.2 Environmental precautions:** *Inform respective authorities in case product reaches water or sewage system.*
- **6.3 Methods and material for containment and cleaning up:** *Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Ensure adequate ventilation.*
- **6.4 Reference to other sections** *See Section 7 for information on safe handling  
See Section 8 for information on personal protection equipment.  
See Section 13 for information on disposal.*

### SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** *Ensure sufficient air exchange and/or extraction in the work areas. Air extraction is required for spray application.  
For solid products: Avoid dust formation and dust deposits. Air limit values mentioned in section 8 must be monitored.  
At workplaces where isocyanate aerosols and/or vapours can occur in higher concentrations, targeted air extraction must be used to prevent the occupational hygiene limit value from being exceeded. The air must be moved away from people.  
For products containing solvents: Explosion protection required.  
The personal protective measures described in section 8 must be observed. The protective measures required when handling isocyanates must be observed. Avoid contact with skin and eyes and inhalation of vapours.  
Keep away from food and beverages. Wash hands before breaks and at the end of work and apply skin protection ointment. Store work clothes separately. Remove soiled, soaked clothing immediately.*
- **Information about protection against explosions and fires:** *Keep ignition sources away - do not smoke.  
Protect from heat.  
Do not store near heat sources.*
- **7.2 Conditions for safe storage, including any incompatibilities** *Keep container dry and tightly closed. Further information on the storage conditions that must be observed for quality assurance reasons can be found in our technical data sheet.*

(Contd. on page 5)

GB



BE SURE. BUILD SURE.

## Safety data sheet according to UK REACH

Printing date 14.04.2025

Version number 36 (replaces version 35)

Revision: 14.04.2025

**Trade name MC-DUR 2095 ESD - Komponente B**

(Contd. of page 4)

- **Storage**
- **Requirements to be met by storerooms and containers:** *Keep tightly closed in original packaging. Ventilate storage rooms well. Carefully close opened containers and store upright to prevent any leakage.*
- Storage temperature >5°C and <30°C*
- **Information about storage in one common storage facility:** *May be stored together with hazardous substances of other classes up to 200 kg.*
- **Further information about storage conditions:** *None.*
- **Storage class** *10*
- **7.3 Specific end use(s)** *No further relevant information available.*

### SECTION 8: Exposure controls/personal protection

· **8.1 Control parameters**

· **Components with critical values that require monitoring at the workplace:**

**CAS: 822-06-0 hexamethylene diisocyanate**

WEL	Short-term value: 0.07 mg/m <sup>3</sup> Long-term value: 0.02 mg/m <sup>3</sup> Sen; as -NCO
-----	---

· **DNELs**

**CAS: 28182-81-2 Aliphatisches Polyisocyanat**

Inhalative	DNEL	0.5 mg/m <sup>3</sup> (Workers) (long term local) 1 mg/m <sup>3</sup> (kei) (acute local eff)
------------	------	--

**CAS: 822-06-0 hexamethylene diisocyanate**

Inhalative	DNEL	0.5 mg/m <sup>3</sup> (ArL)
------------	------	-----------------------------

· **PNECs**

**CAS: 28182-81-2 Aliphatisches Polyisocyanat**

PNEC aqua	12.7 µg/l (Daphnia magna) (marine)
PNEC	38.28 mg/l (kei) (STP)

**CAS: 822-06-0 hexamethylene diisocyanate**

PNEC	100 mg/l (Sewage Treatment Plant) 0.0199 mg/l (Mew) 0.199 mg/l (Freshwater)
PNEC	8884 mg/kg dwt (Bod) 4455 mg/kg dwt (Marine water sediment) 44551 mg/kg dwt (Fresh water sediment)

(Contd. on page 6)



BE SURE. BUILD SURE.

### Safety data sheet according to UK REACH

Printing date 14.04.2025

Version number 36 (replaces version 35)

Revision: 14.04.2025

**Trade name MC-DUR 2095 ESD - Komponente B**

(Contd. of page 5)

**· Ingredients with biological limit values:**

**CAS: 822-06-0 hexamethylene diisocyanate**

BMGV 1 µmol creatinine/mol

Medium: urine

Sampling time: At the end of the period of exposure

Parameter: isocyanate-derived diamine

**· Additional information:** The lists that were valid during the compilation were used as basis.

**· 8.2 Exposure controls**

**· Appropriate engineering controls**

No further data; see section 7.

**· Individual protection measures, such as personal protective equipment**

**· General protective and hygienic measures**

Do not smoke, eat or drink while working. Have eye wash equipment ready.

Do not inhale gases/vapours/aerosols. Avoid contact with eyes and skin.

Do not store food in the work area. Wash hands before breaks and at the end of work.

**· Breathing equipment:**

Respiratory protection required at insufficiently ventilated workplaces and when working with splashes. Fresh air masks or combination filters A2-P2 (EN529) are recommended for short-term work.

If applicable, further recommendations for respiratory protection can be found in the appendix.

In case of hypersensitivity of the respiratory tract (asthma, chronic bronchitis), handling of the product is not recommended.

**· Hand protection**

Suitable materials for protective gloves; EN 374:

Butyl rubber - IIR: thickness  $\geq 0.5\text{mm}$ ; breakthrough time  $\geq 480\text{min}$ .

Fluororubber - FKM: thickness  $\geq 0.4\text{mm}$ ; breakthrough time  $\geq 480\text{min}$ .

Multi-layer glove - PE/EVAL/PE ; Breakthrough time  $\geq 480\text{min}$ .

Recommendation: Dispose of contaminated gloves.

**· Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

**· Penetration time of glove material**

Butyl rubber - IIR: thickness  $\geq 0.5\text{mm}$ ; breakthrough time  $\geq 480\text{min}$ .

Fluoro rubber - FKM: thickness  $\geq 0.4\text{mm}$ ; breakthrough time  $\geq 480\text{min}$ .

Multi-layer glove - PE/EVAL/PE ; Breakthrough time  $\geq 480\text{min}$ .

**· Eye/face protection**

Wear safety goggles/face protection.

**· Body protection:**

Wear suitable protective clothing when working.

In case of hypersensitivity of the skin, handling of the product is not recommended.

GB

(Contd. on page 7)



BE SURE. BUILD SURE.

### Safety data sheet according to UK REACH

Printing date 14.04.2025

Version number 36 (replaces version 35)

Revision: 14.04.2025

Trade name MC-DUR 2095 ESD - Komponente B

(Contd. of page 6)

#### SECTION 9: Physical and chemical properties

##### · 9.1 Information on basic physical and chemical properties

###### · General Information

· Colour:	Colourless
· Smell:	Characteristic
· Melting point/freezing point:	Not determined
· Boiling point or initial boiling point and boiling range	Not determined
· Flash point:	180 °C
· pH at 20 °C	7
· Viscosity:	
· Kinematic viscosity	Not determined.
· dynamic at 20 °C:	2000 mPas
· Solubility	
· Water:	Not miscible or difficult to mix
· Steam pressure:	Not determined.
· Density and/or relative density	
· Density at 20 °C	1.1 g/cm <sup>3</sup>

##### · 9.2 Other information

· Appearance:	
· Form:	Fluid
· Important information on protection of health and environment, and on safety.	
· Self-inflammability:	Product is not selfigniting.
· Explosive properties:	Product is not explosive.

##### · Information with regard to physical hazard classes

· Explosives	Void
· Flammable gases	Void
· Aerosols	Void
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Void
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void

(Contd. on page 8)





BE SURE. BUILD SURE.

### Safety data sheet according to UK REACH

Printing date 14.04.2025

Version number 36 (replaces version 35)

Revision: 14.04.2025

Trade name MC-DUR 2095 ESD - Komponente B

(Contd. of page 7)

· **Desensitised explosives**

Void

#### SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** Reacts with amines
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known

#### SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Harmful if inhaled.

· **LD/LC50 values that are relevant for classification:**

**CAS: 28182-81-2 Aliphatisches Polyisocyanat**

Oral	LD50	>2500 mg/kg (rat) (OECD 423)
Dermal	LD50	>2000 mg/kg (rat) (OECD 402)
Inhalative	LC50/4 h	1.5 mg/l (rat)

**CAS: 822-06-0 hexamethylene diisocyanate**

Oral	LD50	738 mg/kg (rat)
Inhalative	LC50/4 h	0.39 mg/l (rat)

- **Primary irritant effect:**
- **Skin corrosion/irritation** Causes skin irritation.
- **Serious eye damage/irritation** Causes serious eye damage.
- **Respiratory or skin sensitisation** May cause an allergic skin reaction.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** May cause respiratory irritation.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.
- **11.2 Information on other hazards**

· **Endocrine disrupting properties**

None of the ingredients is listed.

GB

(Contd. on page 9)





BE SURE. BUILD SURE.

### Safety data sheet according to UK REACH

Printing date 14.04.2025

Version number 36 (replaces version 35)

Revision: 14.04.2025

Trade name MC-DUR 2095 ESD - Komponente B

(Contd. of page 8)

#### SECTION 12: Ecological information

· **12.1 Toxicity**

· **Aquatic toxicity:**

**CAS: 28182-81-2 Aliphatisches Polyisocyanat**

ErC10/72h 370 mg/l (Desmodesmus subspicatus) (EU C.3)

ErC50/72h >1000 mg/l (Desmodesmus subspicatus) (EU C.3)

· **12.2 Persistence and degradability**

No further relevant information available.

· **12.3 Bioaccumulative potential**

No further relevant information available.

· **12.4 Mobility in soil**

No further relevant information available.

· **12.5 Results of PBT and vPvB assessment**

· **PBT:**

Not applicable.

· **vPvB:**

Not applicable.

· **12.6 Endocrine disrupting properties**

The product does not contain substances with endocrine disrupting properties.

· **12.7 Other adverse effects**

· **Remark:**

Harmful to fish

· **Additional ecological information:**

· **General notes:**

Harmful to aquatic organisms  
Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system.

#### SECTION 13: Disposal considerations

· **13.1 Waste treatment methods**

· **Recommendation**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· **Uncleaned packagings:**

· **Recommendation:**

Empty contaminated packagings thoroughly. They can be recycled after thorough and proper cleaning.

#### SECTION 14: Transport information

· **14.1 UN number or ID number**

· **ADR, ADN, IMDG, IATA**

Void

· **14.2 UN proper shipping name**

· **ADR, ADN, IMDG, IATA**

Void

(Contd. on page 10)



BE SURE. BUILD SURE.

### Safety data sheet according to UK REACH

Printing date 14.04.2025

Version number 36 (replaces version 35)

Revision: 14.04.2025

Trade name MC-DUR 2095 ESD - Komponente B

(Contd. of page 9)

· <b>14.3 Transport hazard class(es)</b>	
· <b>ADR, ADN, IMDG, IATA</b>	
· <b>Class</b>	Void
· <b>14.4 Packing group</b>	
· <b>ADR, IMDG, IATA</b>	Void
· <b>14.5 Environmental hazards:</b>	
· <b>Marine pollutant:</b>	No
· <b>14.6 Special precautions for user</b>	Not applicable.
· <b>14.7 Maritime transport in bulk according to IMO instruments</b>	Not applicable.
· <b>UN "Model Regulation":</b>	Void

### SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/ legislation specific for the substance or mixture** No further relevant information available.
- **Poisons Act**

· **Regulated explosives precursors**

None of the ingredients is listed.

· **Regulated poisons**

None of the ingredients is listed.

· **Reportable explosives precursors**

None of the ingredients is listed.

· **Reportable poisons**

None of the ingredients is listed.

· **15.2 Chemical safety assessment:**

A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**
  - H225 Highly flammable liquid and vapour.
  - H302 Harmful if swallowed.
  - H314 Causes severe skin burns and eye damage.
  - H315 Causes skin irritation.
  - H317 May cause an allergic skin reaction.
  - H318 Causes serious eye damage.

(Contd. on page 11)



BE SURE. BUILD SURE.

### Safety data sheet according to UK REACH

Printing date 14.04.2025

Version number 36 (replaces version 35)

Revision: 14.04.2025

**Trade name MC-DUR 2095 ESD - Komponente B**

(Contd. of page 10)

- H319 Causes serious eye irritation.
- H330 Fatal if inhaled.
- H331 Toxic if inhaled.
- H332 Harmful if inhaled.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H335 May cause respiratory irritation.
- H412 Harmful to aquatic life with long lasting effects.
- EUH204 Contains isocyanates. May produce an allergic reaction.

· **Department issuing data specification sheet:**

Environment protection department.

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (UK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Acute Tox. 1: Acute toxicity – Category 1

Acute Tox. 3: Acute toxicity – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Corr. 1B: Skin corrosion/irritation – Category 1B

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Resp. Sens. 1: Respiratory sensitisation – Category 1

Skin Sens. 1: Skin sensitisation – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

· **\* Data compared to the previous version altered.**