

Page 1/11

Safety data sheet according to UK REACH

Printing date 29.06.2024 Version number 26 (replaces version 25) Revision: 29.06.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name MC-DUR 2496 CTP Tunnel - Komponente A

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance

/ the mixture Polyurethane lacquer

· 1.3 Details of the supplier of the safety data sheet

· Manufacturor/Supplier: MC Rauchemie Müller GmbH & Co.

· Manufacturer/Supplier: MC-Bauchemie Müller GmbH & Co. KG

Am Kruppwald 1-8 D-46238 Bottrop Tel.: +49(0)2041-101-0 Fax.: +49(0)2041-101-400

Fax.: +49(0)2041-101-400 E-Mail: info@mc-bauchemie.de

MC-Bauchemie AG Hagackerstr. 10 CH-8953 Dietikon Tel.: +44-7400510 Fax: +44-7400533

· Informing department:

msds@mc-bauchemie.de

· 1.4 Emergency telephone

number:

Tel.: +49 / (0)700 24112112 (MCR)

Tel.: +1 872 5888271 (MCR)

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

· 2.2 Label elements

Labelling according to

Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms



GHS07

· Signal word Warning

· Hazard-determining

components of labelling: tetraethyl-N,N'-(methylenedicyclohexane-4,1-diyl)bis-DL-aspartate

Reaction mass of Decanedioic acid, bis(1,2,2,6,6-pentamethyl-4-piperidinyl) ester and decanedioic acid,(1,2,2,6,6-pentamethyl-4-

piperidinyl) methyl ester

(Contd. on page 2)



Page 2/11

Safety data sheet according to UK REACH

Revision: 29.06.2024 Printing date 29.06.2024 Version number 26 (replaces version 25)

Trade name MC-DUR 2496 CTP Tunnel - Komponente A

(Contd. of page 1)

· Hazard statements H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P273 Avoid release to the environment.

P280 Wear protective gloves.

P333+P313 If skin irritation or rash occurs: Get medical advice/

attention.

P321 Specific treatment (see on this label).

P501 Dispose of contents/container in accordance with

local/regional/national/international regulations.

· Additional information: EUH211 Warning! Hazardous respirable droplets may be formed

when sprayed. Do not breathe spray or mist.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· PBT: Not applicable. · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

Description: Resin mixture.

Mixture consisting of the following components.

· Dangerous components:		
CAS: 136210-30-5 ELINCS: 429-270-1 Reg.nr.: 01-0000017556-64-	tetraethyl-N,N'-(methylenedicyclohexane-4,1-diyl) bis-DL-aspartate Skin Sens. 1, H317; Aquatic Chronic 3, H412	30-60%
xxxx	, , , , , , , , , , , , , , , , , , , ,	
CAS: 13463-67-7 EINECS: 236-675-5	titanium dioxide	10-30%
	Carc. 2, H351	
CAS: 64742-95-6	Solvent naphtha (petroleum), light arom.	≥0.25-<1.5%
	Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H335-H336, EUH066	
CAS: 222417-26-7	Polyacrylate	≥0.25-<1%
	Eye Dam. 1, H318; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Irrit. 2, H315	
EC number: 915-687-0 Reg.nr.: 01-2119491304-40- XXXX	Reaction mass of Decanedioic acid, bis(1,2,2,6,6-pentamethyl-4-piperidinyl) ester and decanedioic acid,(1,2,2,6,6-pentamethyl-4-piperidinyl) methyl ester	≥0.1-<0.25%
	Repr. 2, H361; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Sens. 1A, H317	



Page 3/11

Safety data sheet according to UK REACH

Printing date 29.06.2024 Version number 26 (replaces version 25) Revision: 29.06.2024

Trade name MC-DUR 2496 CTP Tunnel - Komponente A

(Contd. of page 2)

SECTION 4: First aid measures

· 4.1 Description of first aid measures

General information Remove soiled, soaked clothing immediately.

· After inhalation Remove person to fresh air, keep warm, allow to rest; if breathing

is difficult, seek medical attention.

· After skin contact In case of contact with skin, wash carefully with plenty of soap and

water. Consult a doctor in case of skin reactions.

· After eye contact Rinse the eyes with open eyelids for a sufficiently long time (at

least 10 minutes) with water that is as lukewarm as possible.

Consult an ophthalmologist.

· After swallowing Do NOT induce vomiting. Rinse mouth with water. Medical

attention required.

· 4.2 Most important symptoms and effects, both acute and

delayed Advice for the doctor: Elementary aid, decontamination,

symptomatic treatment.

· 4.3 Indication of any

immediate medical attention

and special treatment needed Therapeutic measures: No information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents Use fire fighting measures that suit the environment.

 5.2 Special hazards arising from the substance or

mixture No further relevant information available.

· 5.3 Advice for firefighters

· **Protective equipment:** No special measures required.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and

emergency procedures Not required.

· 6.2 Environmental

precautions: No special measures required.

· 6.3 Methods and material for

containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders,

universal binders, sawdust).

· 6.4 Reference to other

sections No dangerous materials are released.

GB



Page 4/11

Safety data sheet according to UK REACH

Printing date 29.06.2024 Version number 26 (replaces version 25) Revision: 29.06.2024

Trade name MC-DUR 2496 CTP Tunnel - Komponente A

(Contd. of page 3)

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure sufficient air exchange and/or extraction in the work areas.

Air extraction is required for spray application.

For solid products: Avoid dust formation and dust deposits. Air limit values mentioned in section 8 must be monitored.

At workplaces where isocyanate aerosols and/or vapours can occur in higher concentrations, targeted air extraction must be used to prevent the occupational hygiene limit value from being

exceeded. The air must be moved away from people.

For products containing solvents: Explosion protection required. The personal protective measures described in section 8 must be observed. The protective measures required when handling isocyanates must be observed. Avoid contact with skin and eyes

and inhalation of vapours.

Keen away from food and be

Keep away from food and beverages. Wash hands before breaks and at the end of work and apply skin protection ointment. Store work clothes separately. Remove soiled, soaked clothing

immediately.

· Information about protection

against explosions and fires: Keep ignition sources away - do not smoke.

Protect from heat.

Do not store near heat sources.

· 7.2 Conditions for safe storage, including any incompatibilities

Keep container dry and tightly closed. Further information on the storage conditions that must be observed for quality assurance

reasons can be found in our technical data sheet.

· Storage

Requirements to be met by

storerooms and containers: Keep tightly closed in original packaging. Ventilate storage rooms

well. Carefully close opened containers and store upright to

prevent any leakage.

Storage temperature >5°C and <30°C

· Information about storage in

one common storage facility: May be stored together with hazardous substances of other

classes up to 200 kg.

· Further information about

storage conditions:
Storage class

None. 12

· 7.3 Specific end use(s)

No further relevant information available.

GB



Page 5/11

Safety data sheet according to UK REACH

Printing date 29.06.2024 Version number 26 (replaces version 25) Revision: 29.06.2024

Trade name MC-DUR 2496 CTP Tunnel - Komponente A

(Contd. of page 4)

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

Components with critical values that require

monitoring at the workplace: The product does not contain any relevant quantities of materials

with critical values that have to be monitored at the workplace.

· DNELs

CAS: 136210-30-5 tetraethyl-N,N'-(methylenedicyclohexane-4,1-diyl)bis-DL-aspartate

Dermal DNEL 4 mg/kg bw/day (ArL)
Inhalative DNEL 28 mg/m³ (ArL)
112 mg/m³ (Ark)

PNECs

CAS: 136210-30-5 tetraethyl-N,N'-(methylenedicyclohexane-4,1-diyl)bis-DL-aspartate

PNEC 31.1 mg/l (Kla)

0.000013 mg/l (Mew)

0.00013 mg/l (Freshwater)

PNEC 0.1 mg/kg dwt (Bod)

0.02 mg/kg dwt (Marine water sediment)

0.21 mg/kg dwt (Fresh water sediment)

· Additional information: The lists that were valid during the compilation were used as basis.

· 8.2 Exposure controls · Appropriate engineering

controls No further data; see section 7.

· Individual protection measures, such as personal protective equipment

· General protective and

hygienic measures Do not smoke, eat or drink while working. Have eye wash

equipment ready.

Do not inhale gases/vapours/aerosols. Avoid contact with eyes and

skin.

Do not store food in the work area. Wash hands before breaks and

at the end of work.

· Breathing equipment: Respiratory protection required at insufficiently ventilated

workplaces and when working with splashes. Fresh air masks or combination filters A2-P2 (EN529) are recommended for short-

term work.

If applicable, further recommendations for respiratory protection

can be found in the appendix.

In case of hypersensitivity of the respiratory tract (asthma, chronic

bronchitis), handling of the product is not recommended.

• Hand protection Suitable materials for protective gloves; EN 374:

Butyl rubber - IIR: thickness ≥ 0.5 mm; breakthrough time ≥ 480 min. Fluororubber - FKM: thickness ≥ 0.4 mm; breakthrough time

*≥*480min.

Multi-layer glove - PE/EVAL/PE; Breakthrough time ≥480 min.

Recommendation: Dispose of contaminated gloves.

(Contd. on page 6)



Page 6/11

Safety data sheet according to UK REACH

Revision: 29.06.2024 Printing date 29.06.2024 Version number 26 (replaces version 25)

Trade name MC-DUR 2496 CTP Tunnel - Komponente A

(Contd. of page 5)

The selection of the suitable gloves does not only depend on the · Material of gloves

material, but also on further marks of quality and varies from

manufacturer to manufacturer.

· Penetration time of glove

material

Butyl rubber - IIR: thickness ≥0.5mm; breakthrough time ≥480min. Fluoro rubber - FKM: thickness ≥0.4mm; breakthrough time

≥480min.

Multi-layer glove - PE/EVAL/PE; Breakthrough time ≥480 min.

· Eye/face protection

Wear safety goggles/face protection.

· Body protection: Wear suitable protective clothing when working.

In case of hypersensitivity of the skin, handling of the product is not

recommended.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

· General Information

· Colour: According to product specification

· Smell: Characteristic · Melting point/freezing point: Not determined

· Boiling point or initial boiling point and

boiling range 185 °C (CAS: 136210-30-5 tetraethyl-N,N'-

(methylenedicyclohexane-4,1-diyl)bis-DL-

aspartate)

· Flash point: Not applicable

Auto-ignition temperature: 375 °C (CAS: 136210-30-5 tetraethyl-N,N'-

(methylenedicyclohexane-4,1-diyl)bis-DL-

aspartate)

Not applicable.

Not determined.

· Viscosity:

· pH

· Kinematic viscosity Not determined. · dynamic: Not determined.

· Solubility

· Water: Not miscible or difficult to mix

· Steam pressure at 20 °C: 0 hPa (CAS: 7727-43-7 barium sulphate, natural)

· Density and/or relative density

· Density at 20 °C 1.55 g/cm³

· 9.2 Other information

· Appearance:

Fluid

· Important information on protection of health

and environment, and on safety.

· Self-inflammability: Product is not selfigniting. Explosive properties: Product is not explosive.

(Contd. on page 7)



Page 7/11

Safety data sheet according to UK REACH

Printing date 29.06.2024 Version number 26 (replaces version 25) Revision: 29.06.2024

Trade name MC-DUR 2496 CTP Tunnel - Komponente A

· Information with regard to physical hazard

(Contd. of page 6)

classes	ıu
· Explosives	Void
· Flammable gases	Void
· Aerosols	Void
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Void
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit	
flammable gases in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void
Corrosive to metals	Void
Desensitised explosives	Void

SECTION 10: Stability and reactivity

• 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability · Thermal decomposition /

conditions to be avoided: No decomposition if used according to specifications.

· 10.3 Possibility of hazardous

reactions No dangerous reactions known

10.4 Conditions to avoid
 10.5 Incompatible materials:
 No further relevant information available.

· 10.6 Hazardous

decomposition products: No dangerous decomposition products known

SECTION 11: Toxicological information

· 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

· Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values that are relevant for classification:

CAS: 136210-30-5 tetraethyl-N,N'-(methylenedicyclohexane-4,1-diyl)bis-DL-aspartate

Oral LD50 >2000 mg/kg (rat) (67/548/EWG, Annex V, B.1)
Dermal LD50 >2000 mg/kg (rat) (67/548/EWG, Annex V, B.3)

(Contd. on page 8)



Page 8/11

Safety data sheet according to UK REACH

Printing date 29.06.2024 Version number 26 (replaces version 25) Revision: 29.06.2024

Trade name MC-DUR 2496 CTP Tunnel - Komponente A

(Contd. of page 7)

 Oral
 LD50
 >5000 mg/kg (rat)

 Dermal
 LD50
 >10000 mg/kg (rabbit)

 Inhalative
 LC50/4 h
 >6.8 mg/l (rat)

CAS: 13463-67-7 titanium dioxide

• Skin corrosion/irritation Based on available data, the classification criteria are not met.

· Respiratory or skin

sensitisation May cause an allergic skin reaction.

Germ cell mutagenicity
 Carcinogenicity
 Reproductive toxicity
 STOT-single exposure
 STOT-repeated exposure
 Aspiration hazard
 Based on available data, the classification criteria are not met.
 Based on available data, the classification criteria are not met.
 Based on available data, the classification criteria are not met.
 Based on available data, the classification criteria are not met.
 Based on available data, the classification criteria are not met.
 Based on available data, the classification criteria are not met.

· 11.2 Information on other hazards

Endocrine disrupting properties

CAS: 128-37-0 2,6-Di-tert-butyl-p-cresol

List II

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

CAS: 136210-30-5 tetraethyl-N,N'-(methylenedicyclohexane-4,1-diyl)bis-DL-aspartate

LC50/96h | 66 mg/l (Danio rerio) (OECD 203)

EC50 3110 mg/l (BEL)

EC50/48h 88.6 mg/l (Daphnia magna) NOEC 0.01 mg/l (Daphnia magna)

ErC50/72h 113 mg/l (Scenedesmus subspicatus)

12.2 Persistence and

degradability No further relevant information available.

· 12.3 Bioaccumulative

potential No further relevant information available.

12.4 Mobility in soil No further relevant information available.

· 12.5 Results of PBT and vPvB assessment
· PBT: Not applicable.
· vPvB: Not applicable.

· 12.6 Endocrine disrupting

properties For information on endocrine disrupting properties see section 11.

· 12.7 Other adverse effects

· Additional ecological information:

• General notes: Do not allow product to reach ground water, water bodies or

sewage system.

Danger to drinking water if even small quantities leak into soil.

GB



Page 9/11

Safety data sheet according to UK REACH

Revision: 29.06.2024 Printing date 29.06.2024 Version number 26 (replaces version 25)

Trade name MC-DUR 2496 CTP Tunnel - Komponente A

(Contd. of page 8)

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

Recommendation Must not be disposed of together with household garbage. Do not

allow product to reach sewage system.

· Uncleaned packagings:

· Recommendation: Empty contaminated packagings thoroughly. They can be recycled

after thorough and proper cleaning.

SECTION 14: Transport information

SECTION 14: Transport informat	ion
· 14.1 UN number or ID number · ADR, ADN, IMDG, IATA	Void
· 14.2 UN proper shipping name · ADR, ADN, IMDG, IATA	Void
· 14.3 Transport hazard class(es)	
· ADR, ADN, IMDG, IATA · Class	Void
· 14.4 Packing group · ADR, IMDG, IATA	Void
· 14.5 Environmental hazards: · Marine pollutant:	No
· 14.6 Special precautions for user	Not applicable.
· 14.7 Maritime transport in bulk accordi IMO instruments	ng to Not applicable.
· UN "Model Regulation":	Void

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/ legislation specific for the

substance or mixture No further relevant information available.

· Poisons Act

· Regulated explosives precursors

None of the ingredients is listed.

Regulated poisons

None of the ingredients is listed.

(Contd. on page 10)



Page 10/11

Safety data sheet according to UK REACH

Printing date 29.06.2024 Version number 26 (replaces version 25) Revision: 29.06.2024

Trade name MC-DUR 2496 CTP Tunnel - Komponente A

(Contd. of page 9)

· Reportable explosives precursors

None of the ingredients is listed.

· Reportable poisons

None of the ingredients is listed.

· 15.2 Chemical safety

assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

arry specific product realth	es and snan n	ot establish a legally valid contractual relationship.	
· Relevant phrases	H226	Flammable liquid and vapour.	
•	H304	May be fatal if swallowed and enters airways.	
	H315	Causes skin irritation.	
	H317	May cause an allergic skin reaction.	
	H318	Causes serious eye damage.	
	H335	May cause respiratory irritation	

H318 Causes serious eye damage.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H351 Suspected of causing cancer.

H361 Suspected of damaging fertility or the unborn child.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.
 H411 Toxic to aquatic life with long lasting effects.
 H412 Harmful to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

Department issuing data specification sheet:

Environment protection department.

· Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International

Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous

Goods by Road)

IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (UK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 3: Flammable liquids – Category 3 Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Skin Sens. 1: Skin sensitisation – Category 1

Skin Sens. 1A: Skin sensitisation – Category 1A

(Contd. on page 11)



Page 11/11

Safety data sheet according to UK REACH

Printing date 29.06.2024

Version number 26 (replaces version 25)

Trade name MC-DUR 2496 CTP Tunnel - Komponente A

(Contd. of page 10)

Revision: 29.06.2024

Carc. 2: Carcinogenicity - Category 2

Repr. 2: Reproductive toxicity - Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard -

Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic

hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic

hazard - Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic

hazard – Category 3

* * Data compared to the previous version altered.