



BE SURE. BUILD SURE.

Page 1/11

## Safety data sheet according to UK REACH

Printing date 09.12.2024

Version number 38 (replaces version 37)

Revision: 08.12.2024

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

· **1.1 Product identifier**

· **Trade name**

**MC-DUR 3500 FA - Komponente B**

· **1.2 Relevant identified uses of the substance or mixture and uses advised against**

No further relevant information available.

· **Application of the substance / the mixture**

Mineral coating

Hardening agent/ Curing agent

· **1.3 Details of the supplier of the safety data sheet**

· **Manufacturer/Supplier:**

MC-Bauchemie Müller GmbH & Co. KG

Am Kruppwald 1-8

D-46238 Bottrop

Tel.: +49(0)2041-101-0

Fax.: +49(0)2041-101-400

E-Mail: [info@mc-bauchemie.de](mailto:info@mc-bauchemie.de)

MC-Bauchemie AG

Hagackerstr. 10

CH-8953 Dietikon

Tel.: +44-7400510

Fax : +44-7400533

· **Informing department:**

[msds@mc-bauchemie.de](mailto:msds@mc-bauchemie.de)

· **1.4 Emergency telephone number:**

Tel.: +49 / (0)700 24112112 (MCR)

Tel.: +1 872 5888271 (MCR)

### SECTION 2: Hazards identification

· **2.1 Classification of the substance or mixture**

· **Classification according to Regulation (EC) No 1272/2008**

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

· **2.2 Label elements**

· **Labelling according to**

**Regulation (EC) No 1272/2008** The product is classified and labelled according to the GB CLP regulation.

· **Hazard pictograms**



GHS02 GHS07

(Contd. on page 2)

GB

## Safety data sheet according to UK REACH

Printing date 09.12.2024

Version number 38 (replaces version 37)

Revision: 08.12.2024

**Trade name MC-DUR 3500 FA - Komponente B**

(Contd. of page 1)

- **Signal word** Danger
- **Hazard-determining components of labelling:** methyl methacrylate  
butyl acrylate  
N-Hydroxyethyl-N-methyl-p-toluidine
- **Hazard statements** H225 Highly flammable liquid and vapour.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H317 May cause an allergic skin reaction.  
H335 May cause respiratory irritation.
- **Precautionary statements** P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P241 Use explosion-proof [electrical/ventilating/lighting] equipment.  
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.  
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P403+P233 Store in a well-ventilated place. Keep container tightly closed.
- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

### SECTION 3: Composition/information on ingredients

- **3.2 Mixtures**
- **Description:** Mixture consisting of the following components.

· **Dangerous components:**

CAS: 80-62-6 EINECS: 201-297-1 Reg.nr.: 01-2119452498-28	methyl methacrylate Flam. Liq. 2, H225; Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	60-80%
CAS: 141-32-2 EINECS: 205-480-7	butyl acrylate Flam. Liq. 3, H226; Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335	≥20-≤30%
CAS: 2082-81-7 EINECS: 218-218-1	tetramethylene dimethacrylate Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	<2.5%

(Contd. on page 3)

## Safety data sheet according to UK REACH

Printing date 09.12.2024

Version number 38 (replaces version 37)

Revision: 08.12.2024

**Trade name MC-DUR 3500 FA - Komponente B**

(Contd. of page 2)

CAS: 2842-44-6 EINECS: 220-638-5	N-Hydroxyethyl-N-methyl-p-toluidine Eye Irrit. 2, H319; Skin Sens. 1, H317	≥1-<2.5%
CAS: 128-37-0 EINECS: 204-881-4	Butylated hydroxytoluene Skin Irrit. 2, H315; Eye Irrit. 2, H319	<0.5%

· **Additional information** For the wording of the listed hazard phrases refer to section 16.

### SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **General information** Immediately remove any clothing contaminated with the product.
- **After inhalation** Supply fresh air and call for doctor for safety reasons.
- **After skin contact** Instantly wash with water and soap and rinse thoroughly.
- **After eye contact** Rinse opened eye for several minutes under running water.  
Seek medical treatment.
- **After swallowing** Do not induce vomiting; instantly call for medical help.

### SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents** CO<sub>2</sub>, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam.
- **For safety reasons unsuitable extinguishing agents** Water with a full water jet.
- **5.2 Special hazards arising from the substance or mixture**  
Can be released in case of fire  
Carbon monoxide (CO)
- **5.3 Advice for firefighters**
- **Protective equipment:** Put on breathing apparatus.

### SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures** Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:** Prevent material from reaching sewage system, holes and cellars.  
Inform respective authorities in case product reaches water or sewage system.
- **6.3 Methods and material for containment and cleaning up:** Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Ensure adequate ventilation.
- **6.4 Reference to other sections** See Section 7 for information on safe handling

(Contd. on page 4)

## Safety data sheet according to UK REACH

Printing date 09.12.2024

Version number 38 (replaces version 37)

Revision: 08.12.2024

**Trade name MC-DUR 3500 FA - Komponente B**

(Contd. of page 3)

See Section 8 for information on personal protection equipment.  
See Section 13 for information on disposal.

### SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**  
Ensure good ventilation/exhaustion at the workplace.  
Prevent formation of aerosols.
- **Information about protection against explosions and fires:** The product is not flammable  
Fumes can combine with air to form an explosive mixture.  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage**
- **Requirements to be met by storerooms and containers:** Store only in the original container.  
Store in cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep container tightly sealed.  
Store in cool, dry conditions in well sealed containers.  
Protect from heat and direct sunlight.
- **Storage class** 3

### SECTION 8: Exposure controls/personal protection

#### · 8.1 Control parameters

#### · Components with critical values that require monitoring at the workplace:

**CAS: 80-62-6 methyl methacrylate**

WEL Short-term value: 416 mg/m<sup>3</sup>, 100 ppm  
Long-term value: 208 mg/m<sup>3</sup>, 50 ppm

**CAS: 141-32-2 butyl acrylate**

WEL Short-term value: 26 mg/m<sup>3</sup>, 5 ppm  
Long-term value: 5 mg/m<sup>3</sup>, 1 ppm

#### · DNELs

**CAS: 128-37-0 Butylated hydroxytoluene**

Dermal	DNEL	8.3 mg/kg bw/day (ArL)
Inhalative	DNEL	5.8 mg/m <sup>3</sup> (ArL)

#### · PNECs

**CAS: 128-37-0 Butylated hydroxytoluene**

PNEC aqua	0.4 µg/l (Mew)
-----------	----------------

(Contd. on page 5)

## Safety data sheet according to UK REACH

Printing date 09.12.2024

Version number 38 (replaces version 37)

Revision: 08.12.2024

**Trade name MC-DUR 3500 FA - Komponente B**

(Contd. of page 4)

<p><b>PNEC</b></p> <p><b>PNEC</b></p>	<p>4 µg/l (Freshwater)</p> <p>100 mg/l (Sewage Treatment Plant)</p> <p>1.04 mg/kg dwt (Bod)</p> <p>1.29 mg/kg dwt (Sediment)</p>
<p>· <b>Additional information:</b></p> <p>· <b>8.2 Exposure controls</b></p> <p>· <b>Appropriate engineering controls</b></p> <p>· <b>Individual protection measures, such as personal protective equipment</b></p> <p>· <b>General protective and hygienic measures</b></p> <p>· <b>Breathing equipment:</b></p> <p>· <b>Hand protection</b></p> <p>· <b>Material of gloves</b></p> <p>· <b>Penetration time of glove material</b></p> <p>· <b>Eye/face protection</b></p> <p>· <b>Body protection:</b></p>	<p>The lists that were valid during the compilation were used as basis.</p> <p>No further data; see section 7.</p> <p>Keep away from foodstuffs, beverages and food. Instantly remove any soiled and impregnated garments. Wash hands during breaks and at the end of the work. Avoid contact with the eyes and skin.</p> <p>Use breathing protection in case of insufficient ventilation. Self-contained breathing apparatus. Filter AX.</p> <p>Protective gloves. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation After use of gloves apply skin-cleaning agents and skin cosmetics.</p> <p>Nitrile rubber, NBR Butyl rubber, BR</p> <p>The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.</p> <p>The exact breakthrough time must be obtained from the protective glove manufacturer and must be observed.</p> <p>Not required.</p> <p>Protective work clothing.</p>

### SECTION 9: Physical and chemical properties

<p>· <b>9.1 Information on basic physical and chemical properties</b></p> <p>· <b>General Information</b></p>	
· <b>Colour:</b>	Transparent
· <b>Smell:</b>	Unpleasant
· <b>Melting point/freezing point:</b>	Not determined
· <b>Boiling point or initial boiling point and boiling range</b>	101 °C

(Contd. on page 6)



BE SURE. BUILD SURE.

Page 6/11

## Safety data sheet according to UK REACH

Printing date 09.12.2024

Version number 38 (replaces version 37)

Revision: 08.12.2024

Trade name MC-DUR 3500 FA - Komponente B

(Contd. of page 5)

<b>Lower and upper explosion limit</b>	
· Lower:	1.2 Vol %
· Upper:	12.5 Vol %
· Flash point:	10 °C
· Auto-ignition temperature:	275 °C
· pH	Not determined.
· Viscosity:	
· Kinematic viscosity at 20 °C	21 s (ISO 3 mm)
· dynamic:	Not determined.
· Solubility	
· Water:	Not miscible or difficult to mix
· Steam pressure at 20 °C:	47 hPa
· Density and/or relative density	
· Density at 20 °C	0.93 g/cm <sup>3</sup>
<b>9.2 Other information</b>	
· Appearance:	SAPT > 55°C
· Form:	Fluid
<b>Important information on protection of health and environment, and on safety.</b>	
· Self-inflammability:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosive air/steam mixtures is possible.
<b>Information with regard to physical hazard classes</b>	
· Explosives	Void
· Flammable gases	Void
· Aerosols	Void
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Highly flammable liquid and vapour.
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

### SECTION 10: Stability and reactivity

- |                   |  |
|-------------------|--|
| · 10.1 Reactivity | No further relevant information available. |
|-------------------|--|

(Contd. on page 7)

GB

## Safety data sheet according to UK REACH

Printing date 09.12.2024

Version number 38 (replaces version 37)

Revision: 08.12.2024

**Trade name MC-DUR 3500 FA - Komponente B**

(Contd. of page 6)

- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known
- **10.4 Conditions to avoid** self-accelerating polymerization temperature => 100°C
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known

### SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

- **LD/LC50 values that are relevant for classification:**

**CAS: 80-62-6 methyl methacrylate**

Oral	LD50	>6000 mg/kg (Rat)
Dermal	LD50	>7550 mg/kg (rabbit)

**CAS: 141-32-2 butyl acrylate**

Oral	LD50	900 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rabbit)

**CAS: 128-37-0 Butylated hydroxytoluene**

Oral	LD50	>2930 mg/kg (rat)
	NOAEL	100 mg/kg (rat)
Dermal	LD50	>5000 mg/kg (rabbit)
		>2000 mg/kg (rat)

- **Primary irritant effect:**
- **Skin corrosion/irritation** Causes skin irritation.
- **Serious eye damage/irritation** Causes serious eye irritation.
- **Respiratory or skin sensitisation** May cause an allergic skin reaction.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** May cause respiratory irritation.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.
- **11.2 Information on other hazards**

- **Endocrine disrupting properties**

CAS: 128-37-0 Butylated hydroxytoluene

List II

GB

(Contd. on page 8)



## Safety data sheet according to UK REACH

Printing date 09.12.2024

Version number 38 (replaces version 37)

Revision: 08.12.2024

Trade name MC-DUR 3500 FA - Komponente B

(Contd. of page 7)

### SECTION 12: Ecological information

#### 12.1 Toxicity

##### Aquatic toxicity:

##### CAS: 80-62-6 methyl methacrylate

EC50/24h	502 mg/l (Daphnia magna)
LC50/96h	130 mg/l (Pimephales promelas)
	191 mg/l (Lepomis macrochirus)
EC50/48h	69 mg/l (Daphnia magna)

##### CAS: 128-37-0 Butylated hydroxytoluene

EC50/72h	0.5 mg/l (Desmodesmus subspicatus)
EC50	>10000 mg/l (BEL)
LC50/48h	0.61 mg/l (Daphnia magna)
NOEC	0.07 mg/l (Daphnia magna)

#### 12.2 Persistence and degradability

No further relevant information available.

#### 12.3 Bioaccumulative potential

No further relevant information available.

#### 12.4 Mobility in soil

No further relevant information available.

#### 12.5 Results of PBT and vPvB assessment

##### PBT:

Not applicable.

##### vPvB:

Not applicable.

#### 12.6 Endocrine disrupting properties

For information on endocrine disrupting properties see section 11.

#### 12.7 Other adverse effects

##### Additional ecological information:

##### General notes:

Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system.

### SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

##### Recommendation

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

##### Uncleaned packagings:

##### Recommendation:

Empty contaminated packagings thoroughly. They can be recycled after thorough and proper cleaning.

### SECTION 14: Transport information

#### 14.1 UN number or ID number

##### ADR, IMDG, IATA

UN1247

(Contd. on page 9)



## Safety data sheet according to UK REACH

Printing date 09.12.2024

Version number 38 (replaces version 37)

Revision: 08.12.2024

**Trade name MC-DUR 3500 FA - Komponente B**

(Contd. of page 8)

· <b>14.2 UN proper shipping name</b> · <b>ADR, IMDG, IATA</b>	METHYL METHACRYLATE MONOMER, STABILIZED solution
· <b>14.3 Transport hazard class(es)</b> · <b>ADR</b> · <b>Class</b> · <b>Label</b>	3 (F1) Flammable liquids. 3
· <b>IMDG, IATA</b> · <b>Class</b> · <b>Label</b>	3 Flammable liquids. 3
· <b>14.4 Packing group</b> · <b>ADR, IMDG, IATA</b>	II
· <b>14.5 Environmental hazards:</b> · <b>Marine pollutant:</b>	No
· <b>14.6 Special precautions for user</b> · <b>Kemler Number:</b> · <b>EMS Number:</b> · <b>Stowage Category</b> · <b>Stowage Code</b>	Warning: Flammable liquids. 33 F-E, S-D C SW1 Protected from sources of heat. SW2 Clear of living quarters.
· <b>14.7 Maritime transport in bulk according to IMO instruments</b>	Not applicable.
· <b>Transport/Additional information:</b>	
· <b>ADR</b> · <b>Limited quantities (LQ)</b> · <b>Excepted quantities (EQ)</b>	1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· <b>Transport category</b> · <b>Tunnel restriction code</b>	2 D/E
· <b>IMDG</b> · <b>Limited quantities (LQ)</b> · <b>Excepted quantities (EQ)</b>	1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· <b>UN "Model Regulation":</b>	UN 1247 METHYL METHACRYLATE MONOMER, STABILIZED SOLUTION, 3, II

GB

(Contd. on page 10)



BE SURE. BUILD SURE.

Page 10/11

## Safety data sheet according to UK REACH

Printing date 09.12.2024

Version number 38 (replaces version 37)

Revision: 08.12.2024

Trade name MC-DUR 3500 FA - Komponente B

(Contd. of page 9)

### SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Poisons Act

· Regulated explosives precursors
-----------------------------------

None of the ingredients is listed.
------------------------------------

· Regulated poisons
---------------------

None of the ingredients is listed.
------------------------------------

· Reportable explosives precursors
------------------------------------

None of the ingredients is listed.
------------------------------------

· Reportable poisons
----------------------

None of the ingredients is listed.
------------------------------------

- Directive 2012/18/EU

- Qualifying quantity (tonnes)  
for the application of lower-  
tier requirements 5000 t

- Qualifying quantity (tonnes)  
for the application of upper-  
tier requirements 50000 t

- 15.2 Chemical safety  
assessment: A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Relevant phrases H225 Highly flammable liquid and vapour.  
H226 Flammable liquid and vapour.  
H302 Harmful if swallowed.  
H312 Harmful in contact with skin.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.  
H335 May cause respiratory irritation.

- Department issuing data  
specification sheet:

Environment protection department.

- Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)  
ICAO: International Civil Aviation Organisation  
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)  
IMDG: International Maritime Code for Dangerous Goods  
IATA: International Air Transport Association

(Contd. on page 11)

GB



BE SURE. BUILD SURE.

Page 11/11

## **Safety data sheet according to UK REACH**

Printing date 09.12.2024

Version number 38 (replaces version 37)

Revision: 08.12.2024

**Trade name MC-DUR 3500 FA - Komponente B**

(Contd. of page 10)

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (UK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

· \* Data compared to the  
previous version altered.

GB