



BE SURE. BUILD SURE.

Page 1/11

Safety data sheet according to UK REACH

Printing date 29.06.2024

Version number 44 (replaces version 43)

Revision: 29.06.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name **MC-DUR TopSpeed flex - Komponente A**

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

· Sector of Use SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

· Product category PC9a Coatings and paints, thinners, paint removers

· Process category PROC10 Roller application or brushing

· Environmental release category

ERC8f Widespread use leading to inclusion into/onto article (outdoor)

ERC11a Widespread use of articles with low release (indoor)

· Article category AC13 Plastic articles

· Application of the substance / the mixture

Polyurethane lacquer

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier: MC-Bauchemie Müller GmbH & Co. KG
Am Kruppwald 1-8
D-46238 Bottrop
Tel.: +49(0)2041-101-0
Fax.: +49(0)2041-101-400
E-Mail: info@mc-bauchemie.de

MC-Bauchemie AG
Hagackerstr. 10
CH-8953 Dietikon
Tel.: +44-7400510
Fax : +44-7400533

· Informing department: msds@mc-bauchemie.de

· 1.4 Emergency telephone number:

Tel.: +49 / (0)700 24112112 (MCR)
Tel.: +1 872 5888271 (MCR)

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

· 2.2 Label elements

· Labelling according to

Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms



GHS07

(Contd. on page 2)

GB



BE SURE. BUILD SURE.

Safety data sheet according to UK REACH

Printing date 29.06.2024

Version number 44 (replaces version 43)

Revision: 29.06.2024

Trade name MC-DUR TopSpeed flex - Komponente A

(Contd. of page 1)

- **Signal word** Warning
- **Hazard-determining components of labelling:** *tetraethyl-N,N'-(methylenedicyclohexane-4,1-diyl)bis-DL-aspartate Reaction mass of Decanedioic acid, bis(1,2,2,6,6-pentamethyl-4-piperidiny) ester and decanedioic acid, (1,2,2,6,6-pentamethyl-4-piperidiny) methyl ester*
- **Hazard statements** *H317 May cause an allergic skin reaction.
H412 Harmful to aquatic life with long lasting effects.*
- **Precautionary statements** *P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P273 Avoid release to the environment.
P280 Wear protective gloves.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P321 Specific treatment (see on this label).
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.*
- **Additional information:** *EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.*
- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** *Not applicable.*
- **vPvB:** *Not applicable.*

SECTION 3: Composition/information on ingredients

- **3.2 Mixtures**
- **Description:** *Resin mixture.
Mixture consisting of the following components.*

· Dangerous components:		
CAS: 136210-30-5 ELINCS: 429-270-1 Reg.nr.: 01-0000017556-64-xxxx	<i>tetraethyl-N,N'-(methylenedicyclohexane-4,1-diyl) bis-DL-aspartate Skin Sens. 1, H317; Aquatic Chronic 3, H412</i>	<i>30-60%</i>
CAS: 13463-67-7 EINECS: 236-675-5	<i>titanium dioxide Carc. 2, H351</i>	<i>10-30%</i>
CAS: 64742-95-6	<i>Solvent naphtha (petroleum), light arom. Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H335-H336, EUH066</i>	<i>≥0.25-<1.5%</i>

(Contd. on page 3)



BE SURE. BUILD SURE.

Safety data sheet according to UK REACH

Printing date 29.06.2024

Version number 44 (replaces version 43)

Revision: 29.06.2024

Trade name MC-DUR TopSpeed flex - Komponente A

CAS: 222417-26-7	Polyacrylate Eye Dam. 1, H318; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Irrit. 2, H315	(Contd. of page 2) ≥0.25-<0.5%
EC number: 915-687-0 Reg.nr.: 01-2119491304-40-XXXX	Reaction mass of Decanedioic acid, bis(1,2,2,6,6-pentamethyl-4-piperidiny) ester and decanedioic acid,(1,2,2,6,6-pentamethyl-4-piperidiny) methyl ester Repr. 2, H361; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Sens. 1A, H317	≥0.1-<0.25%

SECTION 4: First aid measures

· **4.1 Description of first aid measures**

- **General information** Remove soiled, soaked clothing immediately.
- **After inhalation** Remove person to fresh air, keep warm, allow to rest; if breathing is difficult, seek medical attention.
- **After skin contact** In case of contact with skin, wash carefully with plenty of soap and water. Consult a doctor in case of skin reactions.
- **After eye contact** Rinse the eyes with open eyelids for a sufficiently long time (at least 10 minutes) with water that is as lukewarm as possible. Consult an ophthalmologist.
- **After swallowing** Do NOT induce vomiting. Rinse mouth with water. Medical attention required.

· **4.2 Most important symptoms and effects, both acute and delayed**

Advice for the doctor: Elementary aid, decontamination, symptomatic treatment.

· **4.3 Indication of any immediate medical attention and special treatment needed**

Therapeutic measures: No information available.

SECTION 5: Firefighting measures

· **5.1 Extinguishing media**

· **Suitable extinguishing agents** Use fire fighting measures that suit the environment.

· **5.2 Special hazards arising from the substance or mixture**

No further relevant information available.

· **5.3 Advice for firefighters**

· **Protective equipment:**

No special measures required.

GB

(Contd. on page 4)



BE SURE. BUILD SURE.

Page 4/11

Safety data sheet according to UK REACH

Printing date 29.06.2024

Version number 44 (replaces version 43)

Revision: 29.06.2024

Trade name MC-DUR TopSpeed flex - Komponente A

(Contd. of page 3)

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures** *Not required.*
- **6.2 Environmental precautions:** *No special measures required.*
- **6.3 Methods and material for containment and cleaning up:** *Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).*
- **6.4 Reference to other sections** *No dangerous materials are released.*

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**

Ensure sufficient air exchange and/or extraction in the work areas. Air extraction is required for spray application. For solid products: Avoid dust formation and dust deposits. Air limit values mentioned in section 8 must be monitored. At workplaces where isocyanate aerosols and/or vapours can occur in higher concentrations, targeted air extraction must be used to prevent the occupational hygiene limit value from being exceeded. The air must be moved away from people. For products containing solvents: Explosion protection required. The personal protective measures described in section 8 must be observed. The protective measures required when handling isocyanates must be observed. Avoid contact with skin and eyes and inhalation of vapours. Keep away from food and beverages. Wash hands before breaks and at the end of work and apply skin protection ointment. Store work clothes separately. Remove soiled, soaked clothing immediately.
- **Information about protection against explosions and fires:** *Keep ignition sources away - do not smoke. Protect from heat. Do not store near heat sources.*
- **7.2 Conditions for safe storage, including any incompatibilities**

Keep container dry and tightly closed. Further information on the storage conditions that must be observed for quality assurance reasons can be found in our technical data sheet.
- **Storage**
- **Requirements to be met by storerooms and containers:** *Keep tightly closed in original packaging. Ventilate storage rooms well. Carefully close opened containers and store upright to prevent any leakage.*

(Contd. on page 5)

GB



BE SURE. BUILD SURE.

Safety data sheet according to UK REACH

Printing date 29.06.2024

Version number 44 (replaces version 43)

Revision: 29.06.2024

Trade name MC-DUR TopSpeed flex - Komponente A

(Contd. of page 4)

Storage temperature >5°C and <30°C

- **Information about storage in one common storage facility:** May be stored together with hazardous substances of other classes up to 200 kg.
- **Further information about storage conditions:** Keep container tightly closed in a well-ventilated place.
- **Storage class** 10
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **8.1 Control parameters**
- **Components with critical values that require monitoring at the workplace:** The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

· DNELs

CAS: 136210-30-5 tetraethyl-N,N'-(methylenedicyclohexane-4,1-diyl)bis-DL-aspartate

Dermal	DNEL	4 mg/kg bw/day (ArL)
Inhalative	DNEL	28 mg/m ³ (ArL)
		112 mg/m ³ (Ark)

· PNECs

CAS: 136210-30-5 tetraethyl-N,N'-(methylenedicyclohexane-4,1-diyl)bis-DL-aspartate

PNEC	31.1 mg/l (Kla)
	0.000013 mg/l (Mew)
	0.00013 mg/l (Freshwater)
PNEC	0.1 mg/kg dwt (Bod)
	0.02 mg/kg dwt (Marine water sediment)
	0.21 mg/kg dwt (Fresh water sediment)

- **Additional information:** The lists that were valid during the compilation were used as basis.

· 8.2 Exposure controls

· **Appropriate engineering controls**

No further data; see section 7.

· **Individual protection measures, such as personal protective equipment**

· **General protective and hygienic measures**

Do not smoke, eat or drink while working. Have eye wash equipment ready.

Do not inhale gases/vapours/aerosols. Avoid contact with eyes and skin.

Do not store food in the work area. Wash hands before breaks and at the end of work.

· **Breathing equipment:**

Respiratory protection required at insufficiently ventilated workplaces and when working with splashes. Fresh air masks or combination filters A2-P2 (EN529) are recommended for short-term work.

(Contd. on page 6)



BE SURE. BUILD SURE.

Safety data sheet according to UK REACH

Printing date 29.06.2024

Version number 44 (replaces version 43)

Revision: 29.06.2024

Trade name MC-DUR TopSpeed flex - Komponente A

(Contd. of page 5)

· Hand protection

If applicable, further recommendations for respiratory protection can be found in the appendix.

In case of hypersensitivity of the respiratory tract (asthma, chronic bronchitis), handling of the product is not recommended.

Suitable materials for protective gloves; EN 374:

Butyl rubber - IIR: thickness $\geq 0.5\text{mm}$; breakthrough time $\geq 480\text{min}$.

Fluororubber - FKM: thickness $\geq 0.4\text{mm}$; breakthrough time $\geq 480\text{min}$.

Multi-layer glove - PE/EVAL/PE ; Breakthrough time $\geq 480\text{ min}$.

Recommendation: Dispose of contaminated gloves.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· Penetration time of glove material

Butyl rubber - IIR: thickness $\geq 0.5\text{mm}$; breakthrough time $\geq 480\text{min}$.

Fluoro rubber - FKM: thickness $\geq 0.4\text{mm}$; breakthrough time $\geq 480\text{min}$.

Multi-layer glove - PE/EVAL/PE ; Breakthrough time $\geq 480\text{ min}$.

· Eye/face protection

Wear safety goggles/face protection.

· Body protection:

Wear suitable protective clothing when working.

In case of hypersensitivity of the skin, handling of the product is not recommended.

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Colour:

According to product specification

· Smell:

Characteristic

· Melting point/freezing point:

Not determined

· Boiling point or initial boiling point and boiling range

185 °C (CAS: 136210-30-5 tetraethyl-N,N'-(methylenedicyclohexane-4,1-diyl)bis-DL-aspartate)

· Flash point:

93 °C

· Auto-ignition temperature:

375 °C (CAS: 136210-30-5 tetraethyl-N,N'-(methylenedicyclohexane-4,1-diyl)bis-DL-aspartate)

· Decomposition temperature:

Not determined.

· pH

Not applicable.

Not determined.

· Viscosity:

· Kinematic viscosity

Not determined.

· dynamic:

Not determined.

· Solubility

· Water:

Not miscible or difficult to mix

· Steam pressure at 20 °C:

0 hPa (CAS: 7727-43-7 barium sulphate, natural)

(Contd. on page 7)



BE SURE. BUILD SURE.

Safety data sheet according to UK REACH

Printing date 29.06.2024

Version number 44 (replaces version 43)

Revision: 29.06.2024

Trade name MC-DUR TopSpeed flex - Komponente A

(Contd. of page 6)

- Vapour pressure at 50 °C: 8 hPa
- Density and/or relative density
- Density at 20 °C 1.59 g/cm³

· **9.2 Other information**

- Appearance:
- Form: Fluid
- Important information on protection of health and environment, and on safety.
- Self-inflammability: Product is not selfigniting.
- Explosive properties: Product is not explosive.

· **Information with regard to physical hazard classes**

- Explosives Void
- Flammable gases Void
- Aerosols Void
- Oxidising gases Void
- Gases under pressure Void
- Flammable liquids Void
- Flammable solids Void
- Self-reactive substances and mixtures Void
- Pyrophoric liquids Void
- Pyrophoric solids Void
- Self-heating substances and mixtures Void
- Substances and mixtures, which emit flammable gases in contact with water Void
- Oxidising liquids Void
- Oxidising solids Void
- Organic peroxides Void
- Corrosive to metals Void
- Desensitised explosives Void

SECTION 10: Stability and reactivity

- 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known

GB

(Contd. on page 8)



BE SURE. BUILD SURE.

Safety data sheet according to UK REACH

Printing date 29.06.2024

Version number 44 (replaces version 43)

Revision: 29.06.2024

Trade name MC-DUR TopSpeed flex - Komponente A

(Contd. of page 7)

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

- **LD/LC50 values that are relevant for classification:**

CAS: 136210-30-5 tetraethyl-N,N'-(methylenedicyclohexane-4,1-diyl)bis-DL-aspartate

Oral	LD50	>2000 mg/kg (rat) (67/548/EWG, Annex V, B.1)
Dermal	LD50	>2000 mg/kg (rat) (67/548/EWG, Annex V, B.3)

CAS: 13463-67-7 titanium dioxide

Oral	LD50	>5000 mg/kg (rat)
Dermal	LD50	>10000 mg/kg (rabbit)
Inhalative	LC50/4 h	>6.8 mg/l (rat)

- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation** May cause an allergic skin reaction.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.
- **11.2 Information on other hazards**

- **Endocrine disrupting properties**

CAS: 128-37-0 2,6-Di-tert-butyl-p-cresol

List II

SECTION 12: Ecological information

- **12.1 Toxicity**

- **Aquatic toxicity:**

CAS: 136210-30-5 tetraethyl-N,N'-(methylenedicyclohexane-4,1-diyl)bis-DL-aspartate

LC50/96h	66 mg/l (Danio rerio) (OECD 203)
EC50	3110 mg/l (BEL)
EC50/48h	88.6 mg/l (Daphnia magna)
NOEC	0.01 mg/l (Daphnia magna)
ErC50/72h	113 mg/l (Scenedesmus subspicatus)

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

(Contd. on page 9)



BE SURE. BUILD SURE.

Safety data sheet according to UK REACH

Printing date 29.06.2024

Version number 44 (replaces version 43)

Revision: 29.06.2024

Trade name MC-DUR TopSpeed flex - Komponente A

(Contd. of page 8)

- **12.6 Endocrine disrupting properties** For information on endocrine disrupting properties see section 11.
- **12.7 Other adverse effects**
- **Additional ecological information:**
- **General notes:** Do not allow product to reach ground water, water bodies or sewage system.
Danger to drinking water if even small quantities leak into soil.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation** Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Empty contaminated packagings thoroughly. They can be recycled after thorough and proper cleaning.

SECTION 14: Transport information

- | | |
|---|-----------------|
| · 14.1 UN number or ID number
· ADR, ADN, IMDG, IATA | Void |
| · 14.2 UN proper shipping name
· ADR, ADN, IMDG, IATA | Void |
| · 14.3 Transport hazard class(es)
· ADR, ADN, IMDG, IATA
· Class | Void |
| · 14.4 Packing group
· ADR, IMDG, IATA | Void |
| · 14.5 Environmental hazards:
· Marine pollutant: | No |
| · 14.6 Special precautions for user | Not applicable. |
| · 14.7 Maritime transport in bulk according to IMO instruments | Not applicable. |
| · UN "Model Regulation": | Void |

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture** No further relevant information available.

(Contd. on page 10)



BE SURE. BUILD SURE.

Safety data sheet according to UK REACH

Printing date 29.06.2024

Version number 44 (replaces version 43)

Revision: 29.06.2024

Trade name MC-DUR TopSpeed flex - Komponente A

(Contd. of page 9)

· **Poisons Act**

· **Regulated explosives precursors**

CAS: 7664-38-2 phosphoric acid	30%
--------------------------------	-----

· **Regulated poisons**

None of the ingredients is listed.

· **Reportable explosives precursors**

None of the ingredients is listed.

· **Reportable poisons**

None of the ingredients is listed.

· **15.2 Chemical safety assessment:**

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

- H226 Flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H351 Suspected of causing cancer.
- H361 Suspected of damaging fertility or the unborn child.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.
- EUH066 Repeated exposure may cause skin dryness or cracking.

· **Department issuing data specification sheet:**

Environment protection department.

· **Abbreviations and acronyms:**

- RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
- ICAO: International Civil Aviation Organisation
- ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- DNEL: Derived No-Effect Level (UK REACH)
- PNEC: Predicted No-Effect Concentration (UK REACH)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent

(Contd. on page 11)



BE SURE. BUILD SURE.

Page 11/11

Safety data sheet according to UK REACH

Printing date 29.06.2024

Version number 44 (replaces version 43)

Revision: 29.06.2024

Trade name MC-DUR TopSpeed flex - Komponente A

(Contd. of page 10)

PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 3: Flammable liquids – Category 3
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Skin Sens. 1: Skin sensitisation – Category 1
Skin Sens. 1A: Skin sensitisation – Category 1A
Carc. 2: Carcinogenicity – Category 2
Repr. 2: Reproductive toxicity – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

*** Data compared to the
previous version altered.**

GB