Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 12.04.2024 Version number 35 (replaces version 34) Revision: 12.04.2024

*
SECTION 1: Identification of the substance/mixture and of the company/undertaking

· **1.1 Product identifier**

· **Trade name** **MC-DUR TopSpeed flex - Komponente B**

· **1.2 Relevant identified uses of the substance or mixture and uses advised against**

· **Sector of Use** SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

· **Product category** PC9a Coatings and paints, thinners, paint removers

· **Process category** PROC10 Roller application or brushing

· **Environmental release category** ERC8f Widespread use leading to inclusion into/onto article (outdoor)
ERC11a Widespread use of articles with low release (indoor)

· **Article category** AC13 Plastic articles

· **Application of the substance / the mixture** Polyurethane lacquer
Hardening agent/ Curing agent

· **1.3 Details of the supplier of the safety data sheet**

· **Manufacturer/Supplier:** MC-Bauchemie Müller GmbH & Co. KG
Am Kruppwald 1-8
D-46238 Bottrop
Tel.: +49(0)2041-101-0
Fax.: +49(0)2041-101-400
E-Mail: info@mc-bauchemie.de

MC-Bauchemie AG
Hagackerstr. 10
CH-8953 Dietikon
Tel.: +44-7400510
Fax : +44-7400533

· **Informing department:** msds@mc-bauchemie.de

· **1.4 Emergency telephone number:** Tel.: +49 / (0)700 24112112 (MCR)
Tel.: +1 872 5888271 (MCR)

*
SECTION 2: Hazards identification

· **2.1 Classification of the substance or mixture**

· **Classification according to Regulation (EC) No 1272/2008**

Acute Tox. 4	H332 Harmful if inhaled.
Skin Sens. 1	H317 May cause an allergic skin reaction.
STOT SE 3	H335 May cause respiratory irritation.
Aquatic Chronic 2	H411 Toxic to aquatic life with long lasting effects.

· **2.2 Label elements**

· **Labelling according to Regulation (EC) No 1272/2008** The product is classified and labelled according to the GB CLP regulation.

(Contd. on page 2)

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 12.04.2024 Version number 35 (replaces version 34) Revision: 12.04.2024

Trade name MC-DUR TopSpeed flex - Komponente B

(Contd. of page 1)

· **Hazard pictograms**

GHS07 GHS09

· **Signal word** Warning

· **Hazard-determining components of labelling:**
aliphatic polyisocyanate 1
aliphatic polyisocyanate 2
Aliphatisches Polyisocyanat
Hexamethylendiisocyanat, Oligomerisationsprodukt (Uretdion Typ)
Aliphatisches Polyisocyanat 3
hexamethylene diisocyanate

· **Hazard statements**
H332 Harmful if inhaled.
H317 May cause an allergic skin reaction.
H335 May cause respiratory irritation.
H411 Toxic to aquatic life with long lasting effects.

· **Precautionary statements**
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P280 Wear protective gloves.
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P312 Call a POISON CENTER/doctor if you feel unwell.
P403+P233 Store in a well-ventilated place. Keep container tightly closed.
P405 Store locked up.

· **Additional information:** EUH204 Contains isocyanates. May produce an allergic reaction.
As from 24 August 2023 adequate training is required before industrial or professional use.

· **2.3 Other hazards**
· **Results of PBT and vPvB assessment**
· **PBT:** Not applicable.
· **vPvB:** Not applicable.

*
SECTION 3: Composition/information on ingredients

· **3.2 Mixtures**
· **Description:** Active substance with propellant.
Mixture consisting of the following components.

· **Dangerous components:**		
CAS: 164250-92-4	aliphatic polyisocyanate 1 Aquatic Chronic 2, H411; Acute Tox. 4, H332; Skin Sens. 1B, H317; STOT SE 3, H335	30-60%
CAS: 29891-05-2	aliphatic polyisocyanate 2 Aquatic Chronic 2, H411; Acute Tox. 4, H332; Skin Sens. 1B, H317; STOT SE 3, H335	≥10-<20%

(Contd. on page 3)

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 12.04.2024 Version number 35 (replaces version 34) Revision: 12.04.2024

Trade name MC-DUR TopSpeed flex - Komponente B

(Contd. of page 2)

CAS: 28182-81-2	Aliphatisches Polyisocyanat Acute Tox. 4, H332; Skin Sens. 1, H317; STOT SE 3, H335, EUH204	≥10-<20%
CAS: 28182-81-2 EC number: 931-297-3 Reg.nr.: :01-2119488934-20-0000	Hexamethylendiisocyanat, Oligomerisationsprodukt (Uretdion Typ) Acute Tox. 4, H332; Skin Sens. 1, H317; STOT SE 3, H335	≥10-<20%
CAS: 108-32-7 EINECS: 203-572-1	Propylene carbonate Eye Irrit. 2, H319	<2.5%
CAS: 1809331-98-3	Aliphatisches Polyisocyanat 3 Aquatic Chronic 2, H411; Acute Tox. 4, H332; Skin Sens. 1B, H317; STOT SE 3, H335	≥1-<1.5%
CAS: 822-06-0 EINECS: 212-485-8 Reg.nr.: 01-2119457571-37-0000	hexamethylene diisocyanate Acute Tox. 3, H331; Resp. Sens. 1, H334; Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335, EUH204 Specific concentration limits: Resp. Sens. 1; H334: C≥ 0.5 % Skin Sens. 1; H317: C ≥ 0.5 %	≥0.1-<0.5%

· **Additional information** For the wording of the listed hazard phrases refer to section 16.

*

SECTION 4: First aid measures

· **4.1 Description of first aid measures**

· **General information** Remove soiled, soaked clothing immediately.

· **After inhalation** Remove person to fresh air, keep warm, allow to rest; if breathing is difficult, seek medical attention.

· **After skin contact** In case of contact with skin, wash carefully with plenty of soap and water. Consult a doctor in case of skin reactions.

· **After eye contact** Rinse the eyes with open eyelids for a sufficiently long time (at least 10 minutes) with water that is as lukewarm as possible. Consult an ophthalmologist.

· **After swallowing** Do NOT induce vomiting. Rinse mouth with water. Medical attention required.

· **4.2 Most important symptoms and effects, both acute and delayed** Advice for the doctor: Elementary aid, decontamination, symptomatic treatment.

· **4.3 Indication of any immediate medical attention and special treatment needed** Therapeutic measures: No information available.

SECTION 5: Firefighting measures

· **5.1 Extinguishing media**

· **Suitable extinguishing agents** CO2, sand, extinguishing powder. Do not use water.

(Contd. on page 4)

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

(Contd. of page 3)

· **For safety reasons unsuitable extinguishing agents** Water.

· **5.2 Special hazards arising from the substance or mixture** Can be released in case of fire
Carbon monoxide (CO)
Nitrogen oxides (NOx)
Under certain fire conditions, traces of other toxic gases cannot be excluded, e.g.:
Hydrogen cyanide (HCN)

· **5.3 Advice for firefighters**

· **Protective equipment:** Wear self-contained breathing apparatus.
Put on breathing apparatus.

SECTION 6: Accidental release measures

· **6.1 Personal precautions, protective equipment and emergency procedures** Ensure adequate ventilation
Use breathing protection against the effects of fumes/dust/aerosol.
Wear protective equipment. Keep unprotected persons away.

· **6.2 Environmental precautions:** Inform respective authorities in case product reaches water or sewage system.
Dilute with much water.

· **6.3 Methods and material for containment and cleaning up:** Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose of contaminated material as waste according to item 13.
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents

· **6.4 Reference to other sections** See Section 7 for information on safe handling
See Section 8 for information on personal protection equipment.
See Section 13 for information on disposal.

*
SECTION 7: Handling and storage

· **7.1 Precautions for safe handling** Ensure sufficient air exchange and/or extraction in the work areas.
Air extraction is required for spray application.
For solid products: Avoid dust formation and dust deposits.
Air limit values mentioned in section 8 must be monitored.
At workplaces where isocyanate aerosols and/or vapours can occur in higher concentrations, targeted air extraction must be used to prevent the occupational hygiene limit value from being exceeded. The air must be moved away from people.
For products containing solvents: Explosion protection required.

(Contd. on page 5)

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 12.04.2024 Version number 35 (replaces version 34) Revision: 12.04.2024

Trade name MC-DUR TopSpeed flex - Komponente B

(Contd. of page 4)

The personal protective measures described in section 8 must be observed. The protective measures required when handling isocyanates must be observed. Avoid contact with skin and eyes and inhalation of vapours.
Keep away from food and beverages. Wash hands before breaks and at the end of work and apply skin protection ointment. Store work clothes separately. Remove soiled, soaked clothing immediately.

· **Information about protection against explosions and fires:** Keep ignition sources away - do not smoke.
Protect from heat.
Do not store near heat sources.

· **7.2 Conditions for safe storage, including any incompatibilities** Keep container dry and tightly closed. Further information on the storage conditions that must be observed for quality assurance reasons can be found in our technical data sheet.

· **Storage**
· **Requirements to be met by storerooms and containers:** Keep tightly closed in original packaging. Ventilate storage rooms well. Carefully close opened containers and store upright to prevent any leakage.

Storage temperature >5°C and <30°C

· **Information about storage in one common storage facility:** May be stored together with hazardous substances of other classes up to 200 kg.

· **Further information about storage conditions:** Keep container tightly closed in a well-ventilated place.
· **Storage class** 10
· **7.3 Specific end use(s)** No further relevant information available.

*
SECTION 8: Exposure controls/personal protection

· **8.1 Control parameters**

· **Components with critical values that require monitoring at the workplace:**	
CAS: 822-06-0 hexamethylene diisocyanate	
WEL	Short-term value: 0.07 mg/m³ Long-term value: 0.02 mg/m³ Sen; as -NCO

· **DNELs**		
CAS: 28182-81-2 Aliphatisches Polyisocyanat		
Inhalative	DNEL	0.5 mg/m³ (Workers) (long term local) 1 mg/m³ (kei) (acute local eff)

(Contd. on page 6)

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 12.04.2024 Version number 35 (replaces version 34) Revision: 12.04.2024

Trade name MC-DUR TopSpeed flex - Komponente B

(Contd. of page 5)

CAS: 28182-81-2 Hexamethylendiisocyanat, Oligomerisationsprodukt (Uretdion Typ)		
Inhalative	DNEL	0.5 mg/m³ (Workers) (long term local) 1 mg/m³ (kei) (acute local eff)
CAS: 822-06-0 hexamethylene diisocyanate		
Inhalative	DNEL	0.5 mg/m³ (ArL)

· **PNECs**	
CAS: 28182-81-2 Aliphatisches Polyisocyanat	
PNEC aqua	12.7 µg/l (Daphnia magna) (marine)
PNEC	38.28 mg/l (kei) (STP)
CAS: 28182-81-2 Hexamethylendiisocyanat, Oligomerisationsprodukt (Uretdion Typ)	
PNEC aqua	12.7 µg/l (Daphnia magna) (marine)
PNEC	38.28 mg/l (kei) (STP)
CAS: 822-06-0 hexamethylene diisocyanate	
PNEC	100 mg/l (Sewage Treatment Plant) 0.0199 mg/l (Mew) 0.199 mg/l (Freshwater)
PNEC	8884 mg/kg dwt (Bod) 4455 mg/kg dwt (Marine water sediment) 44551 mg/kg dwt (Fresh water sediment)

· **Ingredients with biological limit values:**	
CAS: 822-06-0 hexamethylene diisocyanate	
BMGV	1 µmol creatinine/mol Medium: urine Sampling time: At the end of the period od exposure Parameter: isocyanate-derived diamine

· **Additional information:** The lists that were valid during the compilation were used as basis.

· **8.2 Exposure controls**

· **Appropriate engineering controls** No further data; see section 7.

· **Individual protection measures, such as personal protective equipment**

· **General protective and hygienic measures** Do not smoke, eat or drink while working. Have eye wash equipment ready.
Do not inhale gases/vapours/aerosols. Avoid contact with eyes and skin.
Do not store food in the work area. Wash hands before breaks and at the end of work.

· **Breathing equipment:** Respiratory protection required at insufficiently ventilated workplaces and when working with splashes. Fresh air masks or combination filters A2-P2 (EN529) are recommended for short-term work.
If applicable, further recommendations for respiratory protection can be found in the appendix.
In case of hypersensitivity of the respiratory tract (asthma, chronic

(Contd. on page 7)

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 12.04.2024 Version number 35 (replaces version 34) Revision: 12.04.2024

Trade name MC-DUR TopSpeed flex - Komponente B

(Contd. of page 6)

bronchitis), handling of the product is not recommended.
An nicht ausreichend entlüfteten Arbeitsplätzen und bei Spritzverarbeitung Atemschutz erforderlich. Empfohlen werden Frischluftmaske oder für kurzzeitige Arbeiten Kombinationsfilter A2-P2.

Bei Überempfindlichkeit der Atemwege und der Haut (Asthma, chronische Bronchitis, chronische Hautleiden) wird der Umgang mit dem Produkt abgeraten.

· **Hand protection** Suitable materials for protective gloves; EN 374:
Butyl rubber - IIR: thickness ≥0.5mm; breakthrough time ≥480min.
Fluororubber - FKM: thickness ≥0.4mm; breakthrough time ≥480min.
Multi-layer glove - PE/EVAL/PE ; Breakthrough time ≥480 min.
Recommendation: Dispose of contaminated gloves.

· **Material of gloves** The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· **Penetration time of glove material** Butyl rubber - IIR: thickness ≥0.5mm; breakthrough time ≥480min.
Fluoro rubber - FKM: thickness ≥0.4mm; breakthrough time ≥480min.
Multi-layer glove - PE/EVAL/PE ; Breakthrough time ≥480 min.

· **Eye/face protection** Wear safety goggles/face protection.

· **Body protection:** Wear suitable protective clothing when working.
In case of hypersensitivity of the skin, handling of the product is not recommended.

*
SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**	
· **Physical state**	Fluid
· **Colour:**	Dark brown
· **Smell:**	Characteristic
· **Odour threshold:**	Not determined.
· **Melting point/freezing point:**	Not determined
· **Boiling point or initial boiling point and boiling range**	190 °C (CAS: 623-84-7 propane-1,2-diyl diacetate)
· **Flammability**	Not applicable.
· **Lower and upper explosion limit**	
· **Lower:**	2.8 Vol % (CAS: 623-84-7 propane-1,2-diyl diacetate)
· **Upper:**	12.7 Vol % (CAS: 623-84-7 propane-1,2-diyl diacetate)

(Contd. on page 8)

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

(Contd. of page 7)

· **Flash point:**	86-95 °C
· **Auto-ignition temperature:**	431 °C (CAS: 623-84-7 propane-1,2-diyl diacetate)
· **Decomposition temperature:**	Not determined.
· **pH**	Not applicable. Not determined.
· **Viscosity:**	
· **Kinematic viscosity**	Not determined.
· **dynamic:**	Not determined.
· **Solubility**	
· **Water:**	Hydrolized
· **Partition coefficient n-octanol/water (log value)**	Not determined.
· **Steam pressure at 20 °C:**	<3 hPa (CAS: 623-84-7 propane-1,2-diyl diacetate)
· **Density and/or relative density**	
· **Density at 20 °C**	1.12 g/cm³
· **Relative density**	Not determined.
· **Vapour density**	Not determined.

· **9.2 Other information**	
· **Appearance:**	
· **Form:**	Fluid
· **Important information on protection of health and environment, and on safety.**	
· **Self-inflammability:**	Product is not selfigniting.
· **Explosive properties:**	Product is not explosive.
· **Change in condition**	
· **Evaporation rate**	Not determined.

· **Information with regard to physical hazard classes**	
· **Explosives**	Void
· **Flammable gases**	Void
· **Aerosols**	Void
· **Oxidising gases**	Void
· **Gases under pressure**	Void
· **Flammable liquids**	Void
· **Flammable solids**	Void
· **Self-reactive substances and mixtures**	Void
· **Pyrophoric liquids**	Void
· **Pyrophoric solids**	Void
· **Self-heating substances and mixtures**	Void
· **Substances and mixtures, which emit flammable gases in contact with water**	Void
· **Oxidising liquids**	Void
· **Oxidising solids**	Void
· **Organic peroxides**	Void
· **Corrosive to metals**	Void

(Contd. on page 9)

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 12.04.2024 Version number 35 (replaces version 34) Revision: 12.04.2024

Trade name MC-DUR TopSpeed flex - Komponente B

(Contd. of page 8)

· **Desensitised explosives** Void

SECTION 10: Stability and reactivity

· **10.1 Reactivity** No further relevant information available.
· **10.2 Chemical stability**
· **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
· **10.3 Possibility of hazardous reactions** Reacts with amines
· **10.4 Conditions to avoid** No further relevant information available.
· **10.5 Incompatible materials:** No further relevant information available.
· **10.6 Hazardous decomposition products:** No dangerous decomposition products known

*
SECTION 11: Toxicological information

· **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
· **Acute toxicity** Harmful if inhaled.

· **LD/LC50 values that are relevant for classification:**		
CAS: 164250-92-4 aliphatic polyisocyanate 1		
Oral	LD50	>5000 mg/kg (rat)
CAS: 29891-05-2 aliphatic polyisocyanate 2		
Oral	LD50	>5000 mg/kg (rat)
CAS: 28182-81-2 Aliphatisches Polyisocyanat		
Oral	LD50	>2500 mg/kg (rat) (OECD 423)
Dermal	LD50	>2000 mg/kg (rat) (OECD 402)
Inhalative	LC50/4 h	1.5 mg/l (rat)
CAS: 28182-81-2 Hexamethylendiisocyanat, Oligomerisationsprodukt (Uretdion Typ)		
Oral	LD50	>2500 mg/kg (rat) (OECD 423)
Dermal	LD50	>2000 mg/kg (rat) (OECD 402)
Inhalative	LC50/4 h	1.5 mg/l (rat)
CAS: 108-32-7 Propylene carbonate		
Oral	LD50	>5000 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rabbit)
CAS: 822-06-0 hexamethylene diisocyanate		
Oral	LD50	738 mg/kg (rat)
Inhalative	LC50/4 h	0.39 mg/l (rat)

· **Respiratory or skin sensitisation** May cause an allergic skin reaction.
· **STOT-single exposure** May cause respiratory irritation.

(Contd. on page 10)

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 12.04.2024 Version number 35 (replaces version 34) Revision: 12.04.2024

Trade name MC-DUR TopSpeed flex - Komponente B

(Contd. of page 9)

· **11.2 Information on other hazards**

· **Endocrine disrupting properties**
None of the ingredients is listed.

*
SECTION 12: Ecological information

· **12.1 Toxicity**

· **Aquatic toxicity:**	
CAS: 28182-81-2 Aliphatisches Polyisocyanat	
ErC10/72h	370 mg/l (Desmodesmus subspicatus) (EU C.3)
ErC50/72h	>1000 mg/l (Desmodesmus subspicatus) (EU C.3)
CAS: 28182-81-2 Hexamethylendiisocyanat, Oligomerisationsprodukt (Uretdion Typ)	
ErC10/72h	370 mg/l (Desmodesmus subspicatus) (EU C.3)
ErC50/72h	>1000 mg/l (Desmodesmus subspicatus) (EU C.3)

· **12.2 Persistence and degradability** No further relevant information available.
· **12.3 Bioaccumulative potential** No further relevant information available.
· **12.4 Mobility in soil** No further relevant information available.
· **12.5 Results of PBT and vPvB assessment**
· **PBT:** Not applicable.
· **vPvB:** Not applicable.
· **12.6 Endocrine disrupting properties** The product does not contain substances with endocrine disrupting properties.
· **12.7 Other adverse effects**
· **Remark:** Toxic for fish
· **Additional ecological information:**
· **General notes:** Toxic for aquatic organisms
Also poisonous for fish and plankton in water bodies.
Do not allow product to reach ground water, water bodies or sewage system.
Danger to drinking water if even small quantities leak into soil.

SECTION 13: Disposal considerations

· **13.1 Waste treatment methods**
· **Recommendation** Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· **Uncleaned packagings:**
· **Recommendation:** Empty contaminated packagings thoroughly. They can be recycled after thorough and proper cleaning.

(Contd. on page 11)

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 12.04.2024 Version number 35 (replaces version 34) Revision: 12.04.2024

Trade name MC-DUR TopSpeed flex - Komponente B

(Contd. of page 10)

· **Recommended cleaning agent:** Water, if necessary with cleaning agent.

*

SECTION 14: Transport information

· **14.1 UN number or ID number**	
· **ADR, IMDG, IATA**	UN3082
· **14.2 UN proper shipping name**	
· **ADR, IATA**	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (aliphatic polyisocyanate 1, aliphatic polyisocyanate 2)
· **IMDG**	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (aliphatic polyisocyanate 1, aliphatic polyisocyanate 2), MARINE POLLUTANT
· **14.3 Transport hazard class(es)**	
· **ADR**	
· **Class**	9 (M6) Miscellaneous dangerous substances and articles.
· **Label**	9
· **IMDG, IATA**	
· **Class**	9 Miscellaneous dangerous substances and articles.
· **Label**	9
· **14.4 Packing group**	
· **ADR, IMDG, IATA**	III
· **14.5 Environmental hazards:**	
· **Marine pollutant:**	Yes Symbol (fish and tree)
· **Special marking (ADR):**	Symbol (fish and tree)
· **Special marking (IATA):**	Symbol (fish and tree)
· **14.6 Special precautions for user**	Warning: Miscellaneous dangerous substances and articles.
· **Kemler Number:**	90
· **EMS Number:**	F-A,S-F
· **Stowage Category**	A
· **14.7 Maritime transport in bulk according to IMO instruments**	Not applicable.
· **Transport/Additional information:**	
· **ADR**	
· **Limited quantities (LQ)**	5L
· **Excepted quantities (EQ)**	Code: E1 Maximum net quantity per inner packaging: 30 ml

(Contd. on page 12)

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 12.04.2024 Version number 35 (replaces version 34) Revision: 12.04.2024

Trade name MC-DUR TopSpeed flex - Komponente B

(Contd. of page 11)

·	Maximum net quantity per outer packaging: 1000 ml
· **Transport category**	3
· **Tunnel restriction code**	(-)
· **IMDG**	
· **Limited quantities (LQ)**	5L
· **Excepted quantities (EQ)**	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· **UN "Model Regulation":**	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (ALIPHATIC POLYISOCYANATE 1, ALIPHATIC POLYISOCYANATE 2), 9, III

SECTION 15: Regulatory information

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
· **Poisons Act**

· **Regulated explosives precursors**
None of the ingredients is listed.

· **Regulated poisons**
None of the ingredients is listed.

· **Reportable explosives precursors**
None of the ingredients is listed.

· **Reportable poisons**
None of the ingredients is listed.

· **Directive 2012/18/EU**	
· **Named dangerous substances - ANNEX I**	None of the ingredients is listed.
· **Seveso category**	E2 Hazardous to the Aquatic Environment
· **Qualifying quantity (tonnes) for the application of lower-tier requirements**	200 t
· **Qualifying quantity (tonnes) for the application of upper-tier requirements**	500 t
· **15.2 Chemical safety assessment:**	A Chemical Safety Assessment has not been carried out.

(Contd. on page 13)

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 12.04.2024 Version number 35 (replaces version 34) Revision: 12.04.2024

Trade name MC-DUR TopSpeed flex - Komponente B

(Contd. of page 12)

*
SECTION 16: Other information

· **Relevant phrases**

H302 Harmful if swallowed.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H331 Toxic if inhaled.
H332 Harmful if inhaled.
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335 May cause respiratory irritation.
H411 Toxic to aquatic life with long lasting effects.
EUH204 Contains isocyanates. May produce an allergic reaction.

· **Department issuing data specification sheet:** Environment protection department.

· **Abbreviations and acronyms:**
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
ICAO: International Civil Aviation Organisation
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
DNEL: Derived No-Effect Level (UK REACH)
PNEC: Predicted No-Effect Concentration (UK REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Acute Tox. 3: Acute toxicity – Category 3
Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Resp. Sens. 1: Respiratory sensitisation – Category 1
Skin Sens. 1: Skin sensitisation – Category 1
Skin Sens. 1B: Skin sensitisation – Category 1B
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

· *** Data compared to the previous version altered.**